

How to Design Programs Languages

Version 5.0.1

August 3, 2010

The languages documented in this manual are provided by DrRacket to be used with the *How to Design Programs* book.

When programs in these languages are run in DrRacket, any part of the program that was not run is highlighted in orange and black. These colors are intended to give the programmer feedback about the parts of the program that have not been tested. To avoid seeing these colors, use `check-expect` to test your program. Of course, just because you see no colors, does not mean that your program has been fully tested; it simply means that each part of the program has been run (at least once).

Contents

1	Beginning Student	7
1.1	define	13
1.2	define-struct	14
1.3	Function Calls	14
1.4	Primitive Calls	14
1.5	cond	15
1.6	if	15
1.7	and	16
1.8	or	16
1.9	Test Cases	16
1.10	empty	17
1.11	Identifiers	17
1.12	Symbols	17
1.13	true and false	18
1.14	require	18
1.15	Primitive Operations	19
1.15.1	Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . .	19
1.15.2	Booleans	25
1.15.3	Symbols	26
1.15.4	Lists	26
1.15.5	Posns	31
1.15.6	Characters	32
1.15.7	Strings	34
1.15.8	Images	38

1.15.9 Misc	38
2 Beginning Student with List Abbreviations	40
2.1 Quote	46
2.2 Quasiquote	47
2.3 Primitive Operations	47
2.3.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . .	47
2.3.2 Booleans	54
2.3.3 Symbols	55
2.3.4 Lists	55
2.3.5 Posns	60
2.3.6 Characters	61
2.3.7 Strings	63
2.3.8 Images	66
2.3.9 Misc	67
2.4 Unchanged Forms	68
3 Intermediate Student	70
3.1 define	77
3.2 define-struct	77
3.3 local	78
3.4 letrec, let, and let*	78
3.5 Function Calls	78
3.6 time	79
3.7 Identifiers	79
3.8 Primitive Operations	79

3.8.1	Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . .	79
3.8.2	Booleans	86
3.8.3	Symbols	86
3.8.4	Lists	87
3.8.5	Posns	92
3.8.6	Characters	92
3.8.7	Strings	94
3.8.8	Images	98
3.8.9	Misc	98
3.8.10	Numbers (relaxed conditions)	99
3.8.11	Higher-Order Functions	100
3.9	Unchanged Forms	102
4	Intermediate Student with Lambda	104
4.1	define	111
4.2	lambda	111
4.3	Function Calls	112
4.4	Primitive Operation Names	112
4.4.1	Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . .	112
4.4.2	Booleans	118
4.4.3	Symbols	119
4.4.4	Lists	119
4.4.5	Posns	124
4.4.6	Characters	125
4.4.7	Strings	127
4.4.8	Images	130

4.4.9	Misc	131
4.4.10	Numbers (relaxed conditions)	132
4.4.11	Higher-Order Functions	133
4.5	Unchanged Forms	135
5	Advanced Student	137
5.1	define	146
5.2	define-struct	146
5.3	lambda	146
5.4	Function Calls	146
5.5	begin	147
5.6	begin0	147
5.7	set!	147
5.8	delay	147
5.9	shared	148
5.10	let	148
5.11	recur	148
5.12	case	149
5.13	when and unless	149
5.14	Primitive Operations	149
5.14.1	Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . .	149
5.14.2	Booleans	156
5.14.3	Symbols	156
5.14.4	Lists	157
5.14.5	Posns	162
5.14.6	Characters	163

5.14.7 Strings	165
5.14.8 Images	168
5.14.9 Misc	168
5.14.10 Numbers (relaxed conditions)	171
5.14.11 Higher-Order Functions	171
5.14.12 Reading and Printing	173
5.14.13 Vectors	174
5.14.14 Boxes	175
5.14.15 Hash Tables	176
5.15 Unchanged Forms	178

Index	180
--------------	------------

1 Beginning Student

```
program = def-or-expr ...

def-or-expr = definition
            | expr
            | test-case
            | library-require

definition = (define (id id id ...) expr)
            | (define id expr)
            | (define id (lambda (id id ...) expr))
            | (define-struct id (id ...))

expr = (id expr expr ...) ; function call
      | (prim-op expr ...) ; primitive operation call
      | (cond [expr expr] ... [expr expr])
      | (cond [expr expr] ... [else expr])
      | (if expr expr expr)
      | (and expr expr expr ...)
      | (or expr expr expr ...)
      | empty
      | id
      | id ; identifier
      | 'id ; symbol
      | number
      | true
      | false
      | string
      | character

test-case = (check-expect expr expr)
            | (check-within expr expr expr)
            | (check-member-of expr expr ...)
            | (check-range expr expr expr)
            | (check-error expr expr)

library-require = (require string)
                 | (require (lib string string ...))
                 | (require (planet string package))

package = (string string number number)
```

An *id* is a sequence of characters not including a space or one of the following:

`" , ' () [] { } ; #`

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of `"`. Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, "abcdef", "This is a string", and "This is a string with \" inside" are all strings.

A *character* begins with `#\` and has the name of the character. For example, `#\a`, `#\b`, and `#\space` are characters.

A *prim-op* is one of:

Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```
* : (number number number ... -> number)
+ : (number number number ... -> number)
- : (number number ... -> number)
/ : (number number number ... -> number)
< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)
>= : (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)
angle : (number -> real)
asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
```



```

integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (integer -> integer)
rational? : (any -> boolean)
real-part : (number -> real)
real? : (any -> boolean)
remainder : (integer integer -> integer)
round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)

```

Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

Lists

```

append : ((listof any)
          (listof any)
          (listof any)
          ...
          ->
          (listof any))
assq : (X
        (listof (cons X Y))
        ->
        (union false (cons X Y)))
caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
          ->
          W)
caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
          ->
          (listof Z))
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
          ->
          Z)
caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)
cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
          ->
          (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
          ->
          (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
          ->
          (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
          ->
          (listof Y))
cddr : ((cons W (cons Z (cons Y (listof X))))
          ->
          (listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))

```

```

cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

Posns

```

make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)

```

Characters

```

char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)

```

```

char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)

```

Strings

```

explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)
string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)

```

Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

Misc

```
=~ : (real real non-negative-real -> boolean)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
identity : (any -> any)
struct? : (any -> boolean)
```

1.1 define

```
(define (id id id ...) expr)
```

Defines a function. The first *id* inside the parentheses is the name of the function. All remaining *ids* are the names of the function's arguments. The *expr* is the body of the function, evaluated whenever the function is called. The name of the function cannot be that of a primitive or another definition.

```
(define id expr)
```

Defines a constant *id* as a synonym for the value produced by *expr*. The defined name cannot be that of a primitive or another definition, and *id* itself must not appear in *expr*.

```
(define id (lambda (id id ...) expr))
```

An alternate form for defining functions. The first *id* is the name of the function. The *ids* in parentheses are the names of the function's arguments, and the *expr* is the body of the function, which evaluated whenever the function is called. The name of the function cannot be that of a primitive or another definition.

lambda

The lambda keyword can only be used with define in the alternative function-definition syntax.

1.2 define-struct

```
(define-struct structid (fieldid ...))
```

Define a new type of structure. The structure's fields are named by the *fieldids* in parentheses. After evaluation of a define-struct form, a set of new primitives is available for creation, extraction, and type-like queries:

- *make-structid* : takes a number of arguments equal to the number of fields in the structure type, and creates a new instance of the structure type.
- *structid-fieldid* : takes an instance of the structure and returns the field named by *structid*.
- *structid?* : takes any value, and returns *true* if the value is an instance of the structure type.
- *structid* : an identifier representing the structure type, but never used directly.

The created names must not be the same as a primitive or another defined name.

1.3 Function Calls

```
(id expr expr ...)
```

Calls a function. The *id* must refer to a defined function, and the *exprs* are evaluated from left to right to produce the values that are passed as arguments to the function. The result of the function call is the result of evaluating the function's body with every instance of an argument name replaced by the value passed for that argument. The number of argument *exprs* must be the same as the number of arguments expected by the function.

```
(#%app id expr expr ...)
```

A function call can be written with *%app*, though it's practically never written that way.

1.4 Primitive Calls

```
(prim-op expr ...)
```

Like a function call, but for a primitive operation. The *expr*s are evaluated from left to right, and passed as arguments to the primitive operation named by *prim-op*. A *define-struct* form creates new primitives.

1.5 cond

```
(cond [expr expr] ... [expr expr])
```

A *cond* form contains one or more “lines” that are surrounded by parentheses or square brackets. Each line contains two *expr*s: a question *expr* and an answer *expr*.

The lines are considered in order. To evaluate a line, first evaluate the question *expr*. If the result is *true*, then the result of the whole *cond* expression is the result of evaluating the answer *expr* of the same line. If the result of evaluating the question *expr* is *false*, the line is discarded and evaluation proceeds with the next line.

If the result of a question *expr* is neither *true* nor *false*, it is an error. If none of the question *expr*s evaluates to *true*, it is also an error.

```
(cond [expr expr] ... [else expr])
```

This form of *cond* is similar to the prior one, except that the final *else* clause is always taken if no prior line’s test expression evaluates to *true*. In other words, *else* acts like *true*, so there is no possibility to “fall off the end” of the *cond* form.

else

The *else* keyword can be used only with *cond*.

1.6 if

```
(if expr expr expr)
```

The first *expr* (known as the “test” *expr*) is evaluated. If it evaluates to *true*, the result of the *if* expression is the result of evaluating the second *expr* (often called the “then” *expr*). If the test *expr* evaluates to *false*, the result of the *if* expression is the result of evaluating the third *expr* (known as the “else” *expr*). If the result of evaluating the test *expr* is neither *true* nor *false*, it is an error.

1.7 and

`(and expr expr expr ...)`

The *exprs* are evaluated from left to right. If the first *expr* evaluates to `false`, the and expression immediately evaluates to `false`. If the first *expr* evaluates to `true`, the next expression is considered. If all *exprs* evaluate to `true`, the and expression evaluates to `true`. If any of the expressions evaluate to a value other than `true` or `false`, it is an error.

1.8 or

`(or expr expr expr ...)`

The *exprs* are evaluated from left to right. If the first *expr* evaluates to `true`, the or expression immediately evaluates to `true`. If the first *expr* evaluates to `false`, the next expression is considered. If all *exprs* evaluate to `false`, the or expression evaluates to `false`. If any of the expressions evaluate to a value other than `true` or `false`, it is an error.

1.9 Test Cases

`(check-expect expr expr)`

A test case to check that the first *expr* produces the same value as the second *expr*, where the latter is normally an immediate value.

`(check-within expr expr expr)`

Like `check-expect`, but with an extra expression that produces a number *delta*. The test case checks that each number in the result of the first *expr* is within *delta* of each corresponding number from the second *expr*.

`(check-error expr expr)`

A test case to check that the first *expr* signals an error, where the error messages matches the string produced by the second *expr*.

`(check-member-of expr expr expr ...)`

A test case to check that the first *expr* produces an element that is equivalent to one of the

following *exprs*.

```
(check-range expr expr expr)
```

A test case to check that the first *expr* produces a number inbetween the numbers produced by the second and third *exprs*, inclusive.

1.10 *empty*

```
empty : empty?
```

The empty list.

1.11 Identifiers

id

An *id* refers to a defined constant or argument within a function body. If no definition or argument matches the *id* name, an error is reported. Similarly, if *id* matches the name of a defined function or primitive operation, an error is reported.

1.12 Symbols

```
'id  
(quote id)
```

A quoted *id* is a symbol. A symbol is a constant, like 0 and *empty*.

Normally, a symbol is written with a `'`, like `'apple`, but it can also be written with quote, like `(quote apple)`.

The *id* for a symbol is a sequence of characters not including a space or one of the following:

```
" , ' ' ( ) [ ] { } | ; #
```

1.13 true and false

```
true : boolean?
```

The true value.

```
false : boolean?
```

The false value.

1.14 require

```
(require string)
```

Makes the definitions of the module specified by *string* available in the current module (i.e., current file), where *string* refers to a file relative to the enclosing file.

The *string* is constrained in several ways to avoid problems with different path conventions on different platforms: a */* is a directory separator, *.* always means the current directory, *..* always means the parent directory, path elements can use only *a* through *z* (uppercase or lowercase), *0* through *9*, *=*, *_*, and *.*, and the string cannot be empty or contain a leading or trailing */*.

```
(require module-id)
```

Accesses a file in an installed library. The library name is an identifier with the same constraints as for a relative-path string, with the additional constraint that it must not contain a *..*.

```
(require (lib string string ...))
```

Accesses a file in an installed library, making its definitions available in the current module (i.e., current file). The first *string* names the library file, and the remaining *strings* name the collection (and sub-collection, and so on) where the file is installed. Each string is constrained in the same way as for the `(require string)` form.

```
(require (planet string (string string number number)))
```

Accesses a library that is distributed on the internet via the PLaneT server, making its definitions available in the current module (i.e., current file).

1.15 Primitive Operations

1.15.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```
* : (number number number ... -> number)
```

Purpose: to compute the product of all of the input numbers

```
+ : (number number number ... -> number)
```

Purpose: to compute the sum of the input numbers

```
- : (number number ... -> number)
```

Purpose: to subtract the second (and following) number(s) from the first; negate the number if there is only one argument

```
/ : (number number number ... -> number)
```

Purpose: to divide the first by the second (and all following) number(s); try (/ 3 4) and (/ 3 2 2) only the first number can be zero.

```
< : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than

```
<= : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than or equality

```
= : (number number number ... -> boolean)
```

Purpose: to compare numbers for equality

```
> : (real real real ... -> boolean)
```

Purpose: to compare real numbers for greater-than

```
>= : (real real ... -> boolean)
```

Purpose: to compare real numbers for greater-than or equality

`abs : (real -> real)`

Purpose: to compute the absolute value of a real number

`acos : (number -> number)`

Purpose: to compute the arccosine (inverse of cos) of a number

`add1 : (number -> number)`

Purpose: to compute a number one larger than a given number

`angle : (number -> real)`

Purpose: to extract the angle from a complex number

`asin : (number -> number)`

Purpose: to compute the arcsine (inverse of sin) of a number

`atan : (number -> number)`

Purpose: to compute the arctan (inverse of tan) of a number

`ceiling : (real -> integer)`

Purpose: to determine the closest integer (exact or inexact) above a real number

`complex? : (any -> boolean)`

Purpose: to determine whether some value is complex

`conjugate : (number -> number)`

Purpose: to compute the conjugate of a complex number

`cos : (number -> number)`

Purpose: to compute the cosine of a number (radians)

`cosh` : (number -> number)

Purpose: to compute the hyperbolic cosine of a number

`current-seconds` : (-> integer)

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

`denominator` : (rat -> integer)

Purpose: to compute the denominator of a rational

`e` : real

Purpose: Euler's number

`even?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is even or not

`exact->inexact` : (number -> number)

Purpose: to convert an exact number to an inexact one

`exact?` : (number -> boolean)

Purpose: to determine whether some number is exact

`exp` : (number -> number)

Purpose: to compute e raised to a number

`expt` : (number number -> number)

Purpose: to compute the power of the first to the second number

`floor` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) below a real number

```
gcd : (integer integer ... -> integer)
```

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

```
imag-part : (number -> real)
```

Purpose: to extract the imaginary part from a complex number

```
inexact->exact : (number -> number)
```

Purpose: to approximate an inexact number by an exact one

```
inexact? : (number -> boolean)
```

Purpose: to determine whether some number is inexact

```
integer->char : (integer -> char)
```

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

```
integer-sqrt : (number -> integer)
```

Purpose: to compute the integer (exact or inexact) square root of a number

```
integer? : (any -> boolean)
```

Purpose: to determine whether some value is an integer (exact or inexact)

```
lcm : (integer integer ... -> integer)
```

Purpose: to compute the least common multiple of two integers (exact or inexact)

```
log : (number -> number)
```

Purpose: to compute the base-e logarithm of a number

```
magnitude : (number -> real)
```

Purpose: to determine the magnitude of a complex number

```
make-polar : (real real -> number)
```

Purpose: to create a complex from a magnitude and angle

```
make-rectangular : (real real -> number)
```

Purpose: to create a complex from a real and an imaginary part

```
max : (real real ... -> real)
```

Purpose: to determine the largest number

```
min : (real real ... -> real)
```

Purpose: to determine the smallest number

```
modulo : (integer integer -> integer)
```

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

```
negative? : (number -> boolean)
```

Purpose: to determine if some value is strictly smaller than zero

```
number->string : (number -> string)
```

Purpose: to convert a number to a string

```
number? : (any -> boolean)
```

Purpose: to determine whether some value is a number

```
numerator : (rat -> integer)
```

Purpose: to compute the numerator of a rational

```
odd? : (integer -> boolean)
```

Purpose: to determine if some integer (exact or inexact) is odd or not

`pi : real`

Purpose: the ratio of a circle's circumference to its diameter

`positive? : (number -> boolean)`

Purpose: to determine if some value is strictly larger than zero

`quotient : (integer integer -> integer)`

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

`random : (integer -> integer)`

Purpose: to generate a random natural number less than some given integer (exact only!)

`rational? : (any -> boolean)`

Purpose: to determine whether some value is a rational number

`real-part : (number -> real)`

Purpose: to extract the real part from a complex number

`real? : (any -> boolean)`

Purpose: to determine whether some value is a real number

`remainder : (integer integer -> integer)`

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

`round : (real -> integer)`

Purpose: to round a real number to an integer (rounds to even to break ties)

```
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
```

Purpose: to compute the sign of a real number

```
sin : (number -> number)
```

Purpose: to compute the sine of a number (radians)

```
sinh : (number -> number)
```

Purpose: to compute the hyperbolic sine of a number

```
sqr : (number -> number)
```

Purpose: to compute the square of a number

```
sqrt : (number -> number)
```

Purpose: to compute the square root of a number

```
sub1 : (number -> number)
```

Purpose: to compute a number one smaller than a given number

```
tan : (number -> number)
```

Purpose: to compute the tangent of a number (radians)

```
zero? : (number -> boolean)
```

Purpose: to determine if some value is zero or not

1.15.2 Booleans

```
boolean=? : (boolean boolean -> boolean)
```

Purpose: to determine whether two booleans are equal

```
boolean? : (any -> boolean)
```

Purpose: to determine whether some value is a boolean

```
false? : (any -> boolean)
```

Purpose: to determine whether a value is false

```
not : (boolean -> boolean)
```

Purpose: to compute the negation of a boolean value

1.15.3 Symbols

```
symbol->string : (symbol -> string)
```

Purpose: to convert a symbol to a string

```
symbol=? : (symbol symbol -> boolean)
```

Purpose: to determine whether two symbols are equal

```
symbol? : (any -> boolean)
```

Purpose: to determine whether some value is a symbol

1.15.4 Lists

```
append : ((listof any)  
          (listof any)  
          (listof any)  
          ...  
          ->  
          (listof any))
```

Purpose: to create a single list from several, by juxtaposition of the items

```
assq : (X
      (listof (cons X Y))
      ->
      (union false (cons X Y)))
```

Purpose: to determine whether some item is the first item of a pair in a list of pairs

```
caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        W)
```

Purpose: to select the first item of the first list in the first list of a list

```
caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
```

Purpose: to select the first item of the first list in a list

```
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
```

Purpose: to select the second item of the first list of a list

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
cdaar : ((cons
  (cons (cons W (listof Z)) (listof Y))
  (listof X))
  ->
  (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
  ->
  (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

```
cdar : ((cons (cons Z (listof Y)) (listof X))
  ->
  (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
  ->
  (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list

```
cdddr : ((cons W (cons Z (cons Y (listof X))))
  ->
  (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
memq : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

```
memv : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

```
null : empty
```

Purpose: the empty list

```
null? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

`pair? : (any -> boolean)`

Purpose: to determine whether some value is a constructed list

`remove : (any (listof any) -> (listof any))`

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

`rest : ((cons Y (listof X)) -> (listof X))`

Purpose: to select the rest of a non-empty list

`reverse : ((listof any) -> list)`

Purpose: to create a reversed version of a list

`second : ((cons Z (cons Y (listof X))) -> Y)`

Purpose: to select the second item of a non-empty list

`seventh : ((listof Y) -> Y)`

Purpose: to select the seventh item of a non-empty list

`sixth : ((listof Y) -> Y)`

Purpose: to select the sixth item of a non-empty list

`third : ((cons W (cons Z (cons Y (listof X)))) -> Y)`

Purpose: to select the third item of a non-empty list

1.15.5 Posns

`make-posn : (number number -> posn)`

Purpose: to construct a posn

`posn : signature`

Purpose: signature for posns

`posn-x : (posn -> number)`

Purpose: to extract the x component of a posn

`posn-y : (posn -> number)`

Purpose: to extract the y component of a posn

`posn? : (anything -> boolean)`

Purpose: to determine if its input is a posn

1.15.6 Characters

`char->integer : (char -> integer)`

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

`char-alphabetic? : (char -> boolean)`

Purpose: to determine whether a character represents an alphabetic character

`char-ci<=? : (char char char ... -> boolean)`

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

`char-ci<? : (char char char ... -> boolean)`

Purpose: to determine whether a character precedes another in a case-insensitive manner

`char-ci=? : (char char char ... -> boolean)`

Purpose: to determine whether two characters are equal in a case-insensitive manner

`char-ci>=? : (char char char ... -> boolean)`

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

`char-ci>? : (char char char ... -> boolean)`

Purpose: to determine whether a character succeeds another in a case-insensitive manner

`char-downcase : (char -> char)`

Purpose: to determine the equivalent lower-case character

`char-lower-case? : (char -> boolean)`

Purpose: to determine whether a character is a lower-case character

`char-numeric? : (char -> boolean)`

Purpose: to determine whether a character represents a digit

`char-upcase : (char -> char)`

Purpose: to determine the equivalent upper-case character

`char-upper-case? : (char -> boolean)`

Purpose: to determine whether a character is an upper-case character

`char-whitespace? : (char -> boolean)`

Purpose: to determine whether a character represents space

`char<=? : (char char char ... -> boolean)`

Purpose: to determine whether a character precedes another (or is equal to it)

`char<? : (char char char ... -> boolean)`

Purpose: to determine whether a character precedes another

`char=? : (char char char ... -> boolean)`

Purpose: to determine whether two characters are equal

`char>=? : (char char char ... -> boolean)`

Purpose: to determine whether a character succeeds another (or is equal to it)

`char>? : (char char char ... -> boolean)`

Purpose: to determine whether a character succeeds another

`char? : (any -> boolean)`

Purpose: to determine whether a value is a character

1.15.7 Strings

`explode : (string -> (listof string))`

Purpose: to translate a string into a list of 1-letter strings

`format : (string any ... -> string)`

Purpose: to format a string, possibly embedding values

`implode : ((listof string) -> string)`

Purpose: to concatenate the list of 1-letter strings into one string

`int->string : (integer -> string)`

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

`list->string : ((listof char) -> string)`

Purpose: to convert a s list of characters into a string

`make-string : (nat char -> string)`

Purpose: to produce a string of given length from a single given character

`replicate : (nat string -> string)`

Purpose: to replicate the given string

`string : (char ... -> string)`

Purpose: (string c1 c2 ...) builds a string

`string->int : (string -> integer)`

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

`string->list : (string -> (listof char))`

Purpose: to convert a string into a list of characters

`string->number : (string -> (union number false))`

Purpose: to convert a string into a number, produce false if impossible

`string->symbol : (string -> symbol)`

Purpose: to convert a string into a symbol

`string-alphabetic? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are alphabetic

`string-append : (string ... -> string)`

Purpose: to juxtapose the characters of several strings

`string-ci<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

`string-ci<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

`string-ci=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise in a case-insensitive manner

`string-ci>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

`string-ci>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

`string-copy : (string -> string)`

Purpose: to copy a string

`string-ith : (string nat -> string)`

Purpose: to extract the *i*th 1-letter substring from the given one

`string-length : (string -> nat)`

Purpose: to determine the length of a string

`string-lower-case? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are lower case

`string-numeric? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are numeric

`string-ref : (string nat -> char)`

Purpose: to extract the i-th character from a string

`string-upper-case? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are upper case

`string-whitespace? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are white space

`string<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

`string<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another

`string=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise

`string>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

`string>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another

`string? : (any -> boolean)`

Purpose: to determine whether a value is a string

`substring : (string nat nat -> string)`

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

1.15.8 Images

`image=? : (image image -> boolean)`

Purpose: to determine whether two images are equal

`image? : (any -> boolean)`

Purpose: to determine whether a value is an image

1.15.9 Misc

`=~ : (real real non-negative-real -> boolean)`

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

`eof : eof`

Purpose: the end-of-file value

`eof-object? : (any -> boolean)`

Purpose: to determine whether some value is the end-of-file value

`eq? : (any any -> boolean)`

Purpose: to determine whether two values are equivalent from the computer's perspective (intensional)

`equal? : (any any -> boolean)`

Purpose: to determine whether two values are structurally equal where basic values are compared with the `eqv?` predicate

`equal~? : (any any non-negative-real -> boolean)`

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

`eqv? : (any any -> boolean)`

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

`error : (any ... -> void)`

Purpose: to signal an error, combining the given values into an error message.

If any of the values' printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

`exit : (-> void)`

Purpose: to exit the running program

`identity : (any -> any)`

Purpose: to return the argument unchanged

`struct? : (any -> boolean)`

Purpose: to determine whether some value is a structure

2 Beginning Student with List Abbreviations

```
program = def-or-expr ...

def-or-expr = definition
            | expr
            | test-case
            | library-require

definition = (define (id id id ...) expr)
            | (define id expr)
            | (define id (lambda (id id ...) expr))
            | (define-struct id (id ...))

expr = (id expr expr ...) ; function call
      | (prim-op expr ...) ; primitive operation call
      | (cond [expr expr] ... [expr expr])
      | (cond [expr expr] ... [else expr])
      | (if expr expr expr)
      | (and expr expr expr ...)
      | (or expr expr expr ...)
      | empty
      | id
      | 'quoted ; quoted value
      | 'quasiquoted ; quasiquote
      | number
      | true
      | false
      | string
      | character

quoted = id
        | number
        | string
        | character
        | (quoted ...)
        | 'quoted
        | 'quoted
        | ,quoted
        | ,@quoted

quasiquoted = id
             | number
             | string
             | character
```



```

| (quasiquoted ...)
| 'quasiquoted
| `quasiquoted
| ,expr
| ,@expr

test-case = (check-expect expr expr)
| (check-within expr expr expr)
| (check-member-of expr expr ...)
| (check-range expr expr expr)
| (check-error expr expr)

library-require = (require string)
| (require (lib string string ...))
| (require (planet string package))

package = (string string number number)

```

An *id* is a sequence of characters not including a space or one of the following:

```
" , ' ( ) [ ] { } | ; #
```

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of ". Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, "abcdef", "This is a string", and "This is a string with \" inside" are all strings.

A *character* begins with #\ and has the name of the character. For example, #\a, #\b, and #\space are characters.

A *prim-op* is one of:

Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```

* : (number number number ... -> number)
+ : (number number number ... -> number)
- : (number number ... -> number)
/ : (number number number ... -> number)
< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)
>= : (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)
angle : (number -> real)
asin : (number -> number)

```

```

atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (integer -> integer)
rational? : (any -> boolean)
real-part : (number -> real)
real? : (any -> boolean)
remainder : (integer integer -> integer)
round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)

```

```

sinh : (number -> number)
sqr  : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan  : (number -> number)
zero? : (number -> boolean)

```

Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

Lists

```

append : ((listof any)
           (listof any)
           (listof any)
           ...
           ->
           (listof any))

assq : (X
        (listof (cons X Y))
        ->
        (union false (cons X Y)))

caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
          ->
          W)

caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
          ->
          (listof Z))

caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
          ->
          Z)

caddadr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)

```

```

cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
cdddr : ((cons W (cons Z (cons Y (listof X))))
         ->
         (listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

Posns

```

make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)

```

Characters

```

char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)
char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)

```

Strings

```

explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)

```

```

string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)

```

Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

Misc

```

=~ : (real real non-negative-real -> boolean)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
identity : (any -> any)
struct? : (any -> boolean)

```

2.1 Quote

```

'quoted


```

Creates symbols and abbreviates nested lists.

Normally, this form is written with a [quote](#) symbol, like `'(apple banana)`, but it can also be written with `quote`, like `(quote (apple banana))`.

2.2 Quasiquote

```
'quasiquoted  
(quasiquote quasiquoted)
```

Creates symbols and abbreviates nested lists, but also allows escaping to expression “un-quotes.”

Normally, this form is written with a backquote, ```, like `'(apple ,(+ 1 2))`, but it can also be written with `quasiquote`, like `(quasiquote (apple ,(+ 1 2)))`.

```
,quasiquoted  
(unquote expr)
```

Under a single quasiquote, `,expr` escapes from the quote to include an evaluated expression whose result is inserted into the abbreviated list.

Under multiple quasiquotes, `,expr` is really `,quasiquoted`, decrementing the quasiquote count by one for `quasiquoted`.

Normally, an unquote is written with `,`, but it can also be written with `unquote`.

```
,@quasiquoted  
(unquote-splicing expr)
```

Under a single quasiquote, `,@expr` escapes from the quote to include an evaluated expression whose result is a list to splice into the abbreviated list.

Under multiple quasiquotes, a splicing unquote is like an unquote; that is, it decrements the quasiquote count by one.

Normally, a splicing unquote is written with `,@`, but it can also be written with `unquote-splicing`.

2.3 Primitive Operations

2.3.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```
* : (number number number ... -> number)
```

Purpose: to compute the product of all of the input numbers

`+` : (number number number ... -> number)

Purpose: to compute the sum of the input numbers

`-` : (number number ... -> number)

Purpose: to subtract the second (and following) number(s) from the first; negate the number if there is only one argument

`/` : (number number number ... -> number)

Purpose: to divide the first by the second (and all following) number(s); try (/ 3 4) and (/ 3 2 2) only the first number can be zero.

`<` : (real real real ... -> boolean)

Purpose: to compare real numbers for less-than

`<=` : (real real real ... -> boolean)

Purpose: to compare real numbers for less-than or equality

`=` : (number number number ... -> boolean)

Purpose: to compare numbers for equality

`>` : (real real real ... -> boolean)

Purpose: to compare real numbers for greater-than

`>=` : (real real ... -> boolean)

Purpose: to compare real numbers for greater-than or equality

`abs` : (real -> real)

Purpose: to compute the absolute value of a real number

`acos` : (number -> number)

Purpose: to compute the arccosine (inverse of cos) of a number

`add1 : (number -> number)`

Purpose: to compute a number one larger than a given number

`angle : (number -> real)`

Purpose: to extract the angle from a complex number

`asin : (number -> number)`

Purpose: to compute the arcsine (inverse of sin) of a number

`atan : (number -> number)`

Purpose: to compute the arctan (inverse of tan) of a number

`ceiling : (real -> integer)`

Purpose: to determine the closest integer (exact or inexact) above a real number

`complex? : (any -> boolean)`

Purpose: to determine whether some value is complex

`conjugate : (number -> number)`

Purpose: to compute the conjugate of a complex number

`cos : (number -> number)`

Purpose: to compute the cosine of a number (radians)

`cosh : (number -> number)`

Purpose: to compute the hyperbolic cosine of a number

`current-seconds : (-> integer)`

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

`denominator : (rat -> integer)`

Purpose: to compute the denominator of a rational

`e : real`

Purpose: Euler's number

`even? : (integer -> boolean)`

Purpose: to determine if some integer (exact or inexact) is even or not

`exact->inexact : (number -> number)`

Purpose: to convert an exact number to an inexact one

`exact? : (number -> boolean)`

Purpose: to determine whether some number is exact

`exp : (number -> number)`

Purpose: to compute e raised to a number

`expt : (number number -> number)`

Purpose: to compute the power of the first to the second number

`floor : (real -> integer)`

Purpose: to determine the closest integer (exact or inexact) below a real number

`gcd : (integer integer ... -> integer)`

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

`imag-part : (number -> real)`

Purpose: to extract the imaginary part from a complex number

```
inexact->exact : (number -> number)
```

Purpose: to approximate an inexact number by an exact one

```
inexact? : (number -> boolean)
```

Purpose: to determine whether some number is inexact

```
integer->char : (integer -> char)
```

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

```
integer-sqrt : (number -> integer)
```

Purpose: to compute the integer (exact or inexact) square root of a number

```
integer? : (any -> boolean)
```

Purpose: to determine whether some value is an integer (exact or inexact)

```
lcm : (integer integer ... -> integer)
```

Purpose: to compute the least common multiple of two integers (exact or inexact)

```
log : (number -> number)
```

Purpose: to compute the base-e logarithm of a number

```
magnitude : (number -> real)
```

Purpose: to determine the magnitude of a complex number

```
make-polar : (real real -> number)
```

Purpose: to create a complex from a magnitude and angle

```
make-rectangular : (real real -> number)
```

Purpose: to create a complex from a real and an imaginary part

```
max : (real real ... -> real)
```

Purpose: to determine the largest number

```
min : (real real ... -> real)
```

Purpose: to determine the smallest number

```
modulo : (integer integer -> integer)
```

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

```
negative? : (number -> boolean)
```

Purpose: to determine if some value is strictly smaller than zero

```
number->string : (number -> string)
```

Purpose: to convert a number to a string

```
number? : (any -> boolean)
```

Purpose: to determine whether some value is a number

```
numerator : (rat -> integer)
```

Purpose: to compute the numerator of a rational

```
odd? : (integer -> boolean)
```

Purpose: to determine if some integer (exact or inexact) is odd or not

```
pi : real
```

Purpose: the ratio of a circle's circumference to its diameter

```
positive? : (number -> boolean)
```

Purpose: to determine if some value is strictly larger than zero

```
quotient : (integer integer -> integer)
```

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

```
random : (integer -> integer)
```

Purpose: to generate a random natural number less than some given integer (exact only!)

```
rational? : (any -> boolean)
```

Purpose: to determine whether some value is a rational number

```
real-part : (number -> real)
```

Purpose: to extract the real part from a complex number

```
real? : (any -> boolean)
```

Purpose: to determine whether some value is a real number

```
remainder : (integer integer -> integer)
```

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

```
round : (real -> integer)
```

Purpose: to round a real number to an integer (rounds to even to break ties)

```
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
```

Purpose: to compute the sign of a real number

```
sin : (number -> number)
```

Purpose: to compute the sine of a number (radians)

```
sinh : (number -> number)
```

Purpose: to compute the hyperbolic sine of a number

```
sqr : (number -> number)
```

Purpose: to compute the square of a number

```
sqrt : (number -> number)
```

Purpose: to compute the square root of a number

```
sub1 : (number -> number)
```

Purpose: to compute a number one smaller than a given number

```
tan : (number -> number)
```

Purpose: to compute the tangent of a number (radians)

```
zero? : (number -> boolean)
```

Purpose: to determine if some value is zero or not

2.3.2 Booleans

```
boolean=? : (boolean boolean -> boolean)
```

Purpose: to determine whether two booleans are equal

```
boolean? : (any -> boolean)
```

Purpose: to determine whether some value is a boolean

```
false? : (any -> boolean)
```

Purpose: to determine whether a value is false

```
not : (boolean -> boolean)
```

Purpose: to compute the negation of a boolean value

2.3.3 Symbols

```
symbol->string : (symbol -> string)
```

Purpose: to convert a symbol to a string

```
symbol=? : (symbol symbol -> boolean)
```

Purpose: to determine whether two symbols are equal

```
symbol? : (any -> boolean)
```

Purpose: to determine whether some value is a symbol

2.3.4 Lists

```
append : ((listof any)
           (listof any)
           (listof any)
           ...
           ->
           (listof any))
```

Purpose: to create a single list from several, by juxtaposition of the items

```
assq : (X
        (listof (cons X Y))
        ->
        (union false (cons X Y)))
```

Purpose: to determine whether some item is the first item of a pair in a list of pairs

```
caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        W)
```

Purpose: to select the first item of the first list in the first list of a list

```
caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
```

Purpose: to select the first item of the first list in a list

```
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
```

Purpose: to select the second item of the first list of a list

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
        ->
        (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

```
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list

```
cdadr : ((cons W (cons Z (cons Y (listof X))))
        ->
        (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
memq : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

```
memv : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

```
null : empty
```

Purpose: the empty list

```
null? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

```
pair? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

```
remove : (any (listof any) -> (listof any))
```

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

```
rest : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

```
reverse : ((listof any) -> list)
```

Purpose: to create a reversed version of a list

```
second : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

```
seventh : ((listof Y) -> Y)
```

Purpose: to select the seventh item of a non-empty list

```
sixth : ((listof Y) -> Y)
```

Purpose: to select the sixth item of a non-empty list

```
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

2.3.5 Posns

```
make-posn : (number number -> posn)
```

Purpose: to construct a posn

```
posn : signature
```

Purpose: signature for posns

```
posn-x : (posn -> number)
```

Purpose: to extract the x component of a posn

`posn-y` : (posn -> number)

Purpose: to extract the y component of a posn

`posn?` : (anything -> boolean)

Purpose: to determine if its input is a posn

2.3.6 Characters

`char->integer` : (char -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

`char-alphabetic?` : (char -> boolean)

Purpose: to determine whether a character represents an alphabetic character

`char-ci<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

`char-ci<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

`char-ci=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal in a case-insensitive manner

`char-ci>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

`char-ci>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another in a case-insensitive manner

`char-downcase` : (char -> char)

Purpose: to determine the equivalent lower-case character

`char-lower-case?` : (char -> boolean)

Purpose: to determine whether a character is a lower-case character

`char-numeric?` : (char -> boolean)

Purpose: to determine whether a character represents a digit

`char-upcase` : (char -> char)

Purpose: to determine the equivalent upper-case character

`char-upper-case?` : (char -> boolean)

Purpose: to determine whether a character is an upper-case character

`char-whitespace?` : (char -> boolean)

Purpose: to determine whether a character represents space

`char<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it)

`char<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another

`char=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal

`char>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it)

```
char>? : (char char char ... -> boolean)
```

Purpose: to determine whether a character succeeds another

```
char? : (any -> boolean)
```

Purpose: to determine whether a value is a character

2.3.7 Strings

```
explode : (string -> (listof string))
```

Purpose: to translate a string into a list of 1-letter strings

```
format : (string any ... -> string)
```

Purpose: to format a string, possibly embedding values

```
implode : ((listof string) -> string)
```

Purpose: to concatenate the list of 1-letter strings into one string

```
int->string : (integer -> string)
```

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

```
list->string : ((listof char) -> string)
```

Purpose: to convert a s list of characters into a string

```
make-string : (nat char -> string)
```

Purpose: to produce a string of given length from a single given character

```
replicate : (nat string -> string)
```

Purpose: to replicate the given string

`string : (char ... -> string)`

Purpose: (string c1 c2 ...) builds a string

`string->int : (string -> integer)`

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

`string->list : (string -> (listof char))`

Purpose: to convert a string into a list of characters

`string->number : (string -> (union number false))`

Purpose: to convert a string into a number, produce false if impossible

`string->symbol : (string -> symbol)`

Purpose: to convert a string into a symbol

`string-alphabetic? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are alphabetic

`string-append : (string ... -> string)`

Purpose: to juxtapose the characters of several strings

`string-ci<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

`string-ci<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

`string-ci=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise in a case-insensitive manner

```
string-ci>=? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

```
string-ci>? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

```
string-copy : (string -> string)
```

Purpose: to copy a string

```
string-ith : (string nat -> string)
```

Purpose: to extract the *i*th 1-letter substring from the given one

```
string-length : (string -> nat)
```

Purpose: to determine the length of a string

```
string-lower-case? : (string -> boolean)
```

Purpose: to determine whether all 'letters' in the string are lower case

```
string-numeric? : (string -> boolean)
```

Purpose: to determine whether all 'letters' in the string are numeric

```
string-ref : (string nat -> char)
```

Purpose: to extract the *i*-th character from a string

```
string-upper-case? : (string -> boolean)
```

Purpose: to determine whether all 'letters' in the string are upper case

`string-whitespace? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are white space

`string<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

`string<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another

`string=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise

`string>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

`string>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another

`string? : (any -> boolean)`

Purpose: to determine whether a value is a string

`substring : (string nat nat -> string)`

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

2.3.8 Images

`image=? : (image image -> boolean)`

Purpose: to determine whether two images are equal

`image? : (any -> boolean)`

Purpose: to determine whether a value is an image

2.3.9 Misc

`=~ : (real real non-negative-real -> boolean)`

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

`eof : eof`

Purpose: the end-of-file value

`eof-object? : (any -> boolean)`

Purpose: to determine whether some value is the end-of-file value

`eq? : (any any -> boolean)`

Purpose: to determine whether two values are equivalent from the computer's perspective (intensional)

`equal? : (any any -> boolean)`

Purpose: to determine whether two values are structurally equal where basic values are compared with the `eqv?` predicate

`equal~? : (any any non-negative-real -> boolean)`

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

`eqv? : (any any -> boolean)`

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

```
error : (any ... -> void)
```

Purpose: to signal an error, combining the given values into an error message.

If any of the values' printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

```
exit : (-> void)
```

Purpose: to exit the running program

```
identity : (any -> any)
```

Purpose: to return the argument unchanged

```
struct? : (any -> boolean)
```

Purpose: to determine whether some value is a structure

2.4 Unchanged Forms

```
(define (id id id ...) expr)
(define id expr)
(define id (lambda (id id ...) expr))
lambda
```

The same as Beginning's define.

```
(define-struct structid (fieldid ...))
```

The same as Beginning's define-struct.

```
(cond [expr expr] ... [expr expr])
else
```

The same as Beginning's cond.

```
(if expr expr expr)
```

The same as Beginning's if.

```
(and expr expr expr ...)  
(or expr expr expr ...)
```

The same as Beginning's and and or.

```
(check-expect expr expr)  
(check-within expr expr expr)  
(check-error expr expr)  
(check-member-of expr expr expr ...)  
(check-range expr expr expr)
```

The same as Beginning's check-expect, etc.

```
empty : empty?  
true : boolean?  
false : boolean?
```

Constants for the empty list, true, and false.

```
(require module-path)
```

The same as Beginning's require.

3 Intermediate Student

```
program = def-or-expr ...

def-or-expr = definition
            | expr
            | test-case
            | library-require

definition = (define (id id id ...) expr)
            | (define id expr)
            | (define id (lambda (id id ...) expr))
            | (define-struct id (id ...))

expr = (local [definition ...] expr)
      | (letrec ([id expr-for-let] ...) expr)
      | (let ([id expr-for-let] ...) expr)
      | (let* ([id expr-for-let] ...) expr)
      | (id expr expr ...) ; function call
      | (prim-op expr ...) ; primitive operation call
      | (cond [expr expr] ... [expr expr])
      | (cond [expr expr] ... [else expr])
      | (if expr expr expr)
      | (and expr expr expr ...)
      | (or expr expr expr ...)
      | (time expr)
      | empty
      | id ; identifier
      | prim-op ; primitive operation
      | 'quoted ; quoted value
      | 'quasiquoted ; quasiquote
      | number
      | true
      | false
      | string
      | character

expr-for-let = (lambda (id id ...) expr)
              | expr

quoted = id
        | number
        | string
        | character
        | (quoted ...)
```

```

| 'quoted
| 'quoted
| ,quoted
| ,@quoted

quasiquoted = id
| number
| string
| character
| (quasiquoted ...)
| 'quasiquoted
| 'quasiquoted
| ,expr
| ,@expr

test-case = (check-expect expr expr)
| (check-within expr expr expr)
| (check-member-of expr expr ...)
| (check-range expr expr expr)
| (check-error expr expr)

library-require = (require string)
| (require (lib string string ...))
| (require (planet string package))

package = (string string number number)

```

An *id* is a sequence of characters not including a space or one of the following:

```
" , ' ' ( ) [ ] { } | ; #
```

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of ". Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, "abcdef", "This is a string", and "This is a string with \" inside" are all strings.

A *character* begins with #\ and has the name of the character. For example, #\a, #\b, and #\space are characters.

A *prim-op* is one of:

Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```

< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)
>= : (real real ... -> boolean)

```

```

abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)
angle : (number -> real)
asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (integer -> integer)
rational? : (any -> boolean)
real-part : (number -> real)

```



```

real? : (any -> boolean)
remainder : (integer integer -> integer)
round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)

```

Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

Lists

```

append : ((listof any) ... -> (listof any))
assq : (X
        (listof (cons X Y))
        ->
        (union false (cons X Y)))
caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        W)
caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        (listof Z))
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)

```

```

cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
cdddr : ((cons W (cons Z (cons Y (listof X))))
         ->
         (listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

Posns

```

make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)

```

Characters

```

char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)
char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)

```

Strings

```

explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)

```

```

string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)

```

Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

Misc

```

=∼ : (real real non-negative-real -> boolean)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal∼? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
identity : (any -> any)
struct? : (any -> boolean)

```

Numbers (relaxed conditions)

```

* : (number ... -> number)
+ : (number ... -> number)
- : (number ... -> number)
/ : (number ... -> number)

```

Higher-Order Functions

```

andmap : ((X -> boolean) (listof X) -> boolean)
apply : ((X-1 ... X-N -> Y)
         X-1
         ...
         X-i
         (list X-i+1 ... X-N)
         ->
         Y)
argmax : ((X -> real) (listof X) -> X)
argmin : ((X -> real) (listof X) -> X)
build-list : (nat (nat -> X) -> (listof X))

```

```

build-string : (nat (nat -> char) -> string)
compose : ((Y-1 -> Z)
           ...
           (Y-N -> Y-N-1)
           (X-1 ... X-N -> Y-N)
           ->
           (X-1 ... X-N -> Z))
filter : ((X -> boolean) (listof X) -> (listof X))
foldl : ((X Y -> Y) Y (listof X) -> Y)
foldr : ((X Y -> Y) Y (listof X) -> Y)
for-each : ((any ... -> any) (listof any) ... -> void)
map : ((X ... -> Z) (listof X) ... -> (listof Z))
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
ormap : ((X -> boolean) (listof X) -> boolean)
procedure? : (any -> boolean)
quicksort : ((listof X) (X X -> boolean) -> (listof X))
sort : ((listof X) (X X -> boolean) -> (listof X))

```

3.1 define

```

(define (id id id ...) expr)
(define id expr)
(define id (lambda (id id ...) expr))

```

Besides working in `local`, definition forms are the same as Beginning's `define`.

`lambda`

As in Beginning, `lambda` keyword can only be used with `define` in the alternative function-definition syntax.

3.2 define-struct

```

(define-struct structid (fieldid ...))

```

Besides working in `local`, this form is the same as Beginning's `define-struct`.

3.3 local

```
(local [definition ...] expr)
```

Groups related definitions for use in *expr*. Each *definition* is evaluated in order, and finally the body *expr* is evaluated. Only the expressions within the `local` form (including the right-hand-sides of the *definitions* and the *expr*) may refer to the names defined by the *definitions*. If a name defined in the `local` form is the same as a top-level binding, the inner one “shadows” the outer one. That is, inside the `local` form, any references to that name refer to the inner one.

Since `local` is an expression and may occur anywhere an expression may occur, it introduces the notion of lexical scope. Expressions within the `local` may “escape” the scope of the `local`, but these expressions may still refer to the bindings established by the `local`.

3.4 letrec, let, and let*

```
(letrec ([id expr-for-let] ...) expr)
```

Similar to `local`, but essentially omitting the `define` for each definition.

A *expr-for-let* can be either an expression for a constant definition or a lambda form for a function definition.

```
(let ([id expr-for-let] ...) expr)
```

Like `letrec`, but the defined *ids* can be used only in the last *expr*, not the *expr-for-lets* next to the *ids*.

```
(let* ([id expr-for-let] ...) expr)
```

Like `let`, but each *id* can be used in any subsequent *expr-for-let*, in addition to *expr*.

3.5 Function Calls

```
(id expr expr ...)
```

A function call in Intermediate is the same as a Beginning function call, except that it can also call locally defined functions or functions passed as arguments. That is, *id* can be a function defined in `local` or an argument name while in a function.

```
(#%app id expr expr ...)
```

A function call can be written with `%app`, though it's practically never written that way.

3.6 time

```
(time expr)
```

This form is used to measure the time taken to evaluate `expr`. After evaluating `expr`, Scheme prints out the time taken by the evaluation (including real time, time taken by the cpu, and the time spent collecting free memory) and returns the result of the expression.

(The reported time is measured as the number of milliseconds of CPU time required to obtain this result, the number of “real” milliseconds required for the result, and the number of milliseconds of CPU time (included in the first result) spent on garbage collection. The reliability of the timing numbers depends on the platform.)

3.7 Identifiers

`id`

An `id` refers to a defined constant (possibly local), defined function (possibly local), or argument within a function body. If no definition or argument matches the `id` name, an error is reported.

3.8 Primitive Operations

`prim-op`

The name of a primitive operation can be used as an expression. If it is passed to a function, then it can be used in a function call within the function's body.

3.8.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```
< : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than

```
<= : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than or equality

```
= : (number number number ... -> boolean)
```

Purpose: to compare numbers for equality

```
> : (real real real ... -> boolean)
```

Purpose: to compare real numbers for greater-than

```
>= : (real real ... -> boolean)
```

Purpose: to compare real numbers for greater-than or equality

```
abs : (real -> real)
```

Purpose: to compute the absolute value of a real number

```
acos : (number -> number)
```

Purpose: to compute the arccosine (inverse of cos) of a number

```
add1 : (number -> number)
```

Purpose: to compute a number one larger than a given number

```
angle : (number -> real)
```

Purpose: to extract the angle from a complex number

```
asin : (number -> number)
```

Purpose: to compute the arcsine (inverse of sin) of a number

```
atan : (number -> number)
```


Purpose: to compute the arctan (inverse of tan) of a number

`ceiling : (real -> integer)`

Purpose: to determine the closest integer (exact or inexact) above a real number

`complex? : (any -> boolean)`

Purpose: to determine whether some value is complex

`conjugate : (number -> number)`

Purpose: to compute the conjugate of a complex number

`cos : (number -> number)`

Purpose: to compute the cosine of a number (radians)

`cosh : (number -> number)`

Purpose: to compute the hyperbolic cosine of a number

`current-seconds : (-> integer)`

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

`denominator : (rat -> integer)`

Purpose: to compute the denominator of a rational

`e : real`

Purpose: Euler's number

`even? : (integer -> boolean)`

Purpose: to determine if some integer (exact or inexact) is even or not

`exact->inexact : (number -> number)`

Purpose: to convert an exact number to an inexact one

```
exact? : (number -> boolean)
```

Purpose: to determine whether some number is exact

```
exp : (number -> number)
```

Purpose: to compute e raised to a number

```
expt : (number number -> number)
```

Purpose: to compute the power of the first to the second number

```
floor : (real -> integer)
```

Purpose: to determine the closest integer (exact or inexact) below a real number

```
gcd : (integer integer ... -> integer)
```

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

```
imag-part : (number -> real)
```

Purpose: to extract the imaginary part from a complex number

```
inexact->exact : (number -> number)
```

Purpose: to approximate an inexact number by an exact one

```
inexact? : (number -> boolean)
```

Purpose: to determine whether some number is inexact

```
integer->char : (integer -> char)
```

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

```
integer-sqrt : (number -> integer)
```

Purpose: to compute the integer (exact or inexact) square root of a number

```
integer? : (any -> boolean)
```

Purpose: to determine whether some value is an integer (exact or inexact)

```
lcm : (integer integer ... -> integer)
```

Purpose: to compute the least common multiple of two integers (exact or inexact)

```
log : (number -> number)
```

Purpose: to compute the base-e logarithm of a number

```
magnitude : (number -> real)
```

Purpose: to determine the magnitude of a complex number

```
make-polar : (real real -> number)
```

Purpose: to create a complex from a magnitude and angle

```
make-rectangular : (real real -> number)
```

Purpose: to create a complex from a real and an imaginary part

```
max : (real real ... -> real)
```

Purpose: to determine the largest number

```
min : (real real ... -> real)
```

Purpose: to determine the smallest number

```
modulo : (integer integer -> integer)
```

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

```
negative? : (number -> boolean)
```

Purpose: to determine if some value is strictly smaller than zero

```
number->string : (number -> string)
```

Purpose: to convert a number to a string

```
number? : (any -> boolean)
```

Purpose: to determine whether some value is a number

```
numerator : (rat -> integer)
```

Purpose: to compute the numerator of a rational

```
odd? : (integer -> boolean)
```

Purpose: to determine if some integer (exact or inexact) is odd or not

```
pi : real
```

Purpose: the ratio of a circle's circumference to its diameter

```
positive? : (number -> boolean)
```

Purpose: to determine if some value is strictly larger than zero

```
quotient : (integer integer -> integer)
```

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

```
random : (integer -> integer)
```

Purpose: to generate a random natural number less than some given integer (exact only!)

```
rational? : (any -> boolean)
```

Purpose: to determine whether some value is a rational number

```
real-part : (number -> real)
```

Purpose: to extract the real part from a complex number

```
real? : (any -> boolean)
```

Purpose: to determine whether some value is a real number

```
remainder : (integer integer -> integer)
```

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

```
round : (real -> integer)
```

Purpose: to round a real number to an integer (rounds to even to break ties)

```
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
```

Purpose: to compute the sign of a real number

```
sin : (number -> number)
```

Purpose: to compute the sine of a number (radians)

```
sinh : (number -> number)
```

Purpose: to compute the hyperbolic sine of a number

```
sqr : (number -> number)
```

Purpose: to compute the square of a number

```
sqrt : (number -> number)
```

Purpose: to compute the square root of a number

```
sub1 : (number -> number)
```

Purpose: to compute a number one smaller than a given number

```
tan : (number -> number)
```

Purpose: to compute the tangent of a number (radians)

```
zero? : (number -> boolean)
```

Purpose: to determine if some value is zero or not

3.8.2 Booleans

```
boolean=? : (boolean boolean -> boolean)
```

Purpose: to determine whether two booleans are equal

```
boolean? : (any -> boolean)
```

Purpose: to determine whether some value is a boolean

```
false? : (any -> boolean)
```

Purpose: to determine whether a value is false

```
not : (boolean -> boolean)
```

Purpose: to compute the negation of a boolean value

3.8.3 Symbols

```
symbol->string : (symbol -> string)
```

Purpose: to convert a symbol to a string

```
symbol=? : (symbol symbol -> boolean)
```

Purpose: to determine whether two symbols are equal

```
symbol? : (any -> boolean)
```

Purpose: to determine whether some value is a symbol

3.8.4 Lists

`append` : ((listof any) ... -> (listof any))

Purpose: to create a single list from several, by juxtaposition of the items

`assq` : (X
 (listof (cons X Y))
 ->
 (union false (cons X Y)))

Purpose: to determine whether some item is the first item of a pair in a list of pairs

`caaar` : ((cons
 (cons (cons W (listof Z)) (listof Y))
 (listof X))
 ->
 W)

Purpose: to select the first item of the first list in the first list of a list

`caadr` : ((cons
 (cons (cons W (listof Z)) (listof Y))
 (listof X))
 ->
 (listof Z))

Purpose: to select the rest of the first list in the first list of a list

`caar` : ((cons (cons Z (listof Y)) (listof X)) -> Z)

Purpose: to select the first item of the first list in a list

`cadar` : ((cons (cons W (cons Z (listof Y))) (listof X))
 ->
 Z)

Purpose: to select the second item of the first list of a list

`caddr` : ((listof Y) -> Y)

Purpose: to select the fourth item of a non-empty list

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
cdaar : ((cons  
          (cons (cons W (listof Z)) (listof Y))  
          (listof X))  
          ->  
          (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))  
          ->  
          (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

```
cdar : ((cons (cons Z (listof Y)) (listof X))  
        ->  
        (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))  
          ->  
          (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list

```
cdddr : ((cons W (cons Z (cons Y (listof X))))  
        ->  
        (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
memq : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

```
memv : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

`null` : empty

Purpose: the empty list

`null?` : (any -> boolean)

Purpose: to determine whether some value is the empty list

`pair?` : (any -> boolean)

Purpose: to determine whether some value is a constructed list

`remove` : (any (listof any) -> (listof any))

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

`rest` : ((cons Y (listof X)) -> (listof X))

Purpose: to select the rest of a non-empty list

`reverse` : ((listof any) -> list)

Purpose: to create a reversed version of a list

`second` : ((cons Z (cons Y (listof X))) -> Y)

Purpose: to select the second item of a non-empty list

`seventh` : ((listof Y) -> Y)

Purpose: to select the seventh item of a non-empty list

`sixth` : ((listof Y) -> Y)

Purpose: to select the sixth item of a non-empty list

`third` : ((cons W (cons Z (cons Y (listof X)))) -> Y)

Purpose: to select the third item of a non-empty list

3.8.5 Posns

`make-posn` : (number number -> posn)

Purpose: to construct a posn

`posn` : signature

Purpose: signature for posns

`posn-x` : (posn -> number)

Purpose: to extract the x component of a posn

`posn-y` : (posn -> number)

Purpose: to extract the y component of a posn

`posn?` : (anything -> boolean)

Purpose: to determine if its input is a posn

3.8.6 Characters

`char->integer` : (char -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

`char-alphabetic?` : (char -> boolean)

Purpose: to determine whether a character represents an alphabetic character

`char-ci<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

`char-ci<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

```
char-ci=? : (char char char ... -> boolean)
```

Purpose: to determine whether two characters are equal in a case-insensitive manner

```
char-ci>=? : (char char char ... -> boolean)
```

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

```
char-ci>? : (char char char ... -> boolean)
```

Purpose: to determine whether a character succeeds another in a case-insensitive manner

```
char-downcase : (char -> char)
```

Purpose: to determine the equivalent lower-case character

```
char-lower-case? : (char -> boolean)
```

Purpose: to determine whether a character is a lower-case character

```
char-numeric? : (char -> boolean)
```

Purpose: to determine whether a character represents a digit

```
char-upcase : (char -> char)
```

Purpose: to determine the equivalent upper-case character

```
char-upper-case? : (char -> boolean)
```

Purpose: to determine whether a character is an upper-case character

```
char-whitespace? : (char -> boolean)
```

Purpose: to determine whether a character represents space

```
char<=? : (char char char ... -> boolean)
```

Purpose: to determine whether a character precedes another (or is equal to it)

```
char<? : (char char char ... -> boolean)
```

Purpose: to determine whether a character precedes another

```
char=? : (char char char ... -> boolean)
```

Purpose: to determine whether two characters are equal

```
char>=? : (char char char ... -> boolean)
```

Purpose: to determine whether a character succeeds another (or is equal to it)

```
char>? : (char char char ... -> boolean)
```

Purpose: to determine whether a character succeeds another

```
char? : (any -> boolean)
```

Purpose: to determine whether a value is a character

3.8.7 Strings

```
explode : (string -> (listof string))
```

Purpose: to translate a string into a list of 1-letter strings

```
format : (string any ... -> string)
```

Purpose: to format a string, possibly embedding values

```
implode : ((listof string) -> string)
```

Purpose: to concatenate the list of 1-letter strings into one string

```
int->string : (integer -> string)
```

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

`list->string : ((listof char) -> string)`

Purpose: to convert a s list of characters into a string

`make-string : (nat char -> string)`

Purpose: to produce a string of given length from a single given character

`replicate : (nat string -> string)`

Purpose: to replicate the given string

`string : (char ... -> string)`

Purpose: (string c1 c2 ...) builds a string

`string->int : (string -> integer)`

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

`string->list : (string -> (listof char))`

Purpose: to convert a string into a list of characters

`string->number : (string -> (union number false))`

Purpose: to convert a string into a number, produce false if impossible

`string->symbol : (string -> symbol)`

Purpose: to convert a string into a symbol

`string-alphabetic? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are alphabetic

`string-append : (string ... -> string)`

Purpose: to juxtapose the characters of several strings

`string-ci<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

`string-ci<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

`string-ci=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise in a case-insensitive manner

`string-ci>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

`string-ci>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

`string-copy : (string -> string)`

Purpose: to copy a string

`string-ith : (string nat -> string)`

Purpose: to extract the *ith* 1-letter substring from the given one

`string-length : (string -> nat)`

Purpose: to determine the length of a string

`string-lower-case? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are lower case

`string-numeric? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are numeric

`string-ref : (string nat -> char)`

Purpose: to extract the i-th character from a string

`string-upper-case? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are upper case

`string-whitespace? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are white space

`string<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

`string<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another

`string=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise

`string>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

`string>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another

`string? : (any -> boolean)`

Purpose: to determine whether a value is a string

`substring` : (string nat nat -> string)

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

3.8.8 Images

`image=?` : (image image -> boolean)

Purpose: to determine whether two images are equal

`image?` : (any -> boolean)

Purpose: to determine whether a value is an image

3.8.9 Misc

`=~` : (real real non-negative-real -> boolean)

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

`eof` : eof

Purpose: the end-of-file value

`eof-object?` : (any -> boolean)

Purpose: to determine whether some value is the end-of-file value

`eq?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the computer's perspective (intensional)

`equal?` : (any any -> boolean)

Purpose: to determine whether two values are structurally equal where basic values are

compared with the `eqv?` predicate

```
equal~? : (any any non-negative-real -> boolean)
```

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

```
eqv? : (any any -> boolean)
```

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

```
error : (any ... -> void)
```

Purpose: to signal an error, combining the given values into an error message.

If any of the values' printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

```
exit : (-> void)
```

Purpose: to exit the running program

```
identity : (any -> any)
```

Purpose: to return the argument unchanged

```
struct? : (any -> boolean)
```

Purpose: to determine whether some value is a structure

3.8.10 Numbers (relaxed conditions)

```
* : (number ... -> number)
```

Purpose: to multiply all given numbers

```
+ : (number ... -> number)
```

Purpose: to add all given numbers

```
- : (number ... -> number)
```

Purpose: to subtract from the first all remaining numbers

```
/ : (number ... -> number)
```

Purpose: to divide the first by all remaining numbers

3.8.11 Higher-Order Functions

```
andmap : ((X -> boolean) (listof X) -> boolean)
```

Purpose: $(\text{andmap } p \text{ (list } x-1 \dots x-n)) = (\text{and } (p \text{ } x-1) \dots (p \text{ } x-n))$

```
apply : ((X-1 ... X-N -> Y)
         X-1
         ...
         X-i
         (list X-i+1 ... X-N)
         ->
         Y)
```

Purpose: to apply a function using items from a list as the arguments

```
argmax : ((X -> real) (listof X) -> X)
```

Purpose: to find the (first) element of the list that maximizes the output of the function

```
argmin : ((X -> real) (listof X) -> X)
```

Purpose: to find the (first) element of the list that minimizes the output of the function

```
build-list : (nat (nat -> X) -> (listof X))
```

Purpose: $(\text{build-list } n \text{ } f) = (\text{list } (f \text{ } 0) \dots (f \text{ } (- \text{ } n \text{ } 1)))$

```
build-string : (nat (nat -> char) -> string)
```

Purpose: (build-string n f) = (string (f 0) ... (f (- n 1)))

```
compose : ((Y-1 -> Z)
           ...
           (Y-N -> Y-N-1)
           (X-1 ... X-N -> Y-N)
           ->
           (X-1 ... X-N -> Z))
```

Purpose: to compose a sequence of procedures into a single procedure

```
filter : ((X -> boolean) (listof X) -> (listof X))
```

Purpose: to construct a list from all those items on a list for which the predicate holds

```
foldl : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldl f base (list x-1 ... x-n)) = (f x-n ... (f x-1 base))

```
foldr : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldr f base (list x-1 ... x-n)) = (f x-1 ... (f x-n base))

```
for-each : ((any ... -> any) (listof any) ... -> void)
```

Purpose: to apply a function to each item on one or more lists for effect only

```
map : ((X ... -> Z) (listof X) ... -> (listof Z))
```

Purpose: to construct a new list by applying a function to each item on one or more existing lists

```
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
```

Purpose: to determine whether the first argument produces true for some value in the second argument

```
ormap : ((X -> boolean) (listof X) -> boolean)
```

Purpose: $(\text{ormap } p \text{ (list } x-1 \dots x-n)) = (\text{or } (p \ x-1) \dots (p \ x-n))$

`procedure? : (any -> boolean)`

Purpose: to determine if a value is a procedure

`quicksort : ((listof X) (X X -> boolean) -> (listof X))`

Purpose: to construct a list from all items on a list in an order according to a predicate

`sort : ((listof X) (X X -> boolean) -> (listof X))`

Purpose: to construct a list from all items on a list in an order according to a predicate

3.9 Unchanged Forms

`(cond [expr expr] ... [expr expr])`
`else`

The same as Beginning's cond.

`(if expr expr expr)`

The same as Beginning's if.

`(and expr expr expr ...)`
`(or expr expr expr ...)`

The same as Beginning's and and or.

`(check-expect expr expr)`
`(check-within expr expr expr)`
`(check-error expr expr)`
`(check-member-of expr expr expr ...)`
`(check-range expr expr expr)`

The same as Beginning's check-expect, etc.

`empty : empty?`

```
true : boolean?  
false : boolean?
```

Constants for the empty list, true, and false.

```
(require module-path)
```

The same as Beginning's require.

4 Intermediate Student with Lambda

```
program = def-or-expr ...

def-or-expr = definition
            | expr
            | test-case
            | library-require

definition = (define (id id id ...) expr)
            | (define id expr)
            | (define-struct id (id ...))

expr = (lambda (id id ...) expr)
      | (λ (id id ...) expr)
      | (local [definition ...] expr)
      | (letrec ([id expr] ...) expr)
      | (let ([id expr] ...) expr)
      | (let* ([id expr] ...) expr)
      | (expr expr expr ...) ; function call
      | (cond [expr expr] ... [expr expr])
      | (cond [expr expr] ... [else expr])
      | (if expr expr expr)
      | (and expr expr expr ...)
      | (or expr expr expr ...)
      | (time expr)
      | empty
      | id ; identifier
      | prim-op ; primitive operation
      | 'quoted ; quoted value
      | 'quasiquoted ; quasiquote
      | number
      | true
      | false
      | string
      | character

quoted = id
        | number
        | string
        | character
        | (quoted ...)
        | 'quoted
        | 'quoted
        | ,quoted
```



```

| ,@quoted

quasiquoted = id
| number
| string
| character
| (quasiquoted ...)
| 'quasiquoted
| 'quasiquoted
| ,expr
| ,@expr

test-case = (check-expect expr expr)
| (check-within expr expr expr)
| (check-member-of expr expr ...)
| (check-range expr expr expr)
| (check-error expr expr)

library-require = (require string)
| (require (lib string string ...))
| (require (planet string package))

package = (string string number number)

```

An *id* is a sequence of characters not including a space or one of the following:

```
" , ' ' ( ) [ ] { } | ; #
```

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of ". Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, "abcdef", "This is a string", and "This is a string with \" inside" are all strings.

A *character* begins with #\ and has the name of the character. For example, #\a, #\b, and #\space are characters.

A *prim-op* is one of:

Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```

< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)
>= : (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)

```

```

angle : (number -> real)
asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (integer -> integer)
rational? : (any -> boolean)
real-part : (number -> real)
real? : (any -> boolean)
remainder : (integer integer -> integer)
round : (real -> integer)

```

```

sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)

```

Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

Lists

```

append : ((listof any) ... -> (listof any))
assq : (X
      (listof (cons X Y))
      ->
      (union false (cons X Y)))
caaar : ((cons
      (cons (cons W (listof Z)) (listof Y))
      (listof X))
      ->
      W)
caadr : ((cons
      (cons (cons W (listof Z)) (listof Y))
      (listof X))
      ->
      (listof Z))
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
      ->
      Z)
caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)
cdaar : ((cons
      (cons (cons W (listof Z)) (listof Y))
      (listof X))
      ->
      (listof Z))

```

```

cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
->
(listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
->
(listof Y))
cddr : ((cons (cons W (cons Z (listof Y))) (listof X))
->
(listof Y))
cdddr : ((cons W (cons Z (cons Y (listof X))))
->
(listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

Posns

```

make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)

```

Characters

```
char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)
char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)
```

Strings

```
explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)
string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
```

```

string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)

```

Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

Misc

```

=~ : (real real non-negative-real -> boolean)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
identity : (any -> any)
struct? : (any -> boolean)

```

Numbers (relaxed conditions)

```

* : (number ... -> number)
+ : (number ... -> number)
- : (number ... -> number)
/ : (number ... -> number)

```

Higher-Order Functions

```

andmap : ((X -> boolean) (listof X) -> boolean)
apply : ((X-1 ... X-N -> Y)
         X-1
         ...
         X-i
         (list X-i+1 ... X-N)
         ->
         Y)
argmax : ((X -> real) (listof X) -> X)
argmin : ((X -> real) (listof X) -> X)
build-list : (nat (nat -> X) -> (listof X))
build-string : (nat (nat -> char) -> string)

```

```

compose : ((Y-1 -> Z)
           ...
           (Y-N -> Y-N-1)
           (X-1 ... X-N -> Y-N)
           ->
           (X-1 ... X-N -> Z))
filter : ((X -> boolean) (listof X) -> (listof X))
foldl : ((X Y -> Y) Y (listof X) -> Y)
foldr : ((X Y -> Y) Y (listof X) -> Y)
for-each : ((any ... -> any) (listof any) ... -> void)
map : ((X ... -> Z) (listof X) ... -> (listof Z))
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
ormap : ((X -> boolean) (listof X) -> boolean)
procedure? : (any -> boolean)
quicksort : ((listof X) (X X -> boolean) -> (listof X))
sort : ((listof X) (X X -> boolean) -> (listof X))

```

4.1 define

```

(define (id id id ...) expr)
(define id expr)

```

The same as Intermediate's define. No special case is needed for lambda, since a lambda form is an expression.

4.2 lambda

```

(lambda (id id ...) expr)

```

Creates a function that takes as many arguments as given *ids*, and whose body is *expr*.

```

(λ (id id ...) expr)

```

The Greek letter λ is a synonym for lambda.

4.3 Function Calls

```
(expr expr expr ...)
```

Like a Beginning function call, except that the function position can be an arbitrary expression—perhaps a lambda expression or a *prim-op*.

```
(#%app expr expr expr ...)
```

A function call can be written with `%app`, though it's practically never written that way.

4.4 Primitive Operation Names

prim-op

The name of a primitive operation can be used as an expression. It produces a function version of the operation.

4.4.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```
< : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than

```
<= : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than or equality

```
= : (number number number ... -> boolean)
```

Purpose: to compare numbers for equality

```
> : (real real real ... -> boolean)
```

Purpose: to compare real numbers for greater-than

```
>= : (real real ... -> boolean)
```


Purpose: to compare real numbers for greater-than or equality

```
abs : (real -> real)
```

Purpose: to compute the absolute value of a real number

```
acos : (number -> number)
```

Purpose: to compute the arccosine (inverse of cos) of a number

```
add1 : (number -> number)
```

Purpose: to compute a number one larger than a given number

```
angle : (number -> real)
```

Purpose: to extract the angle from a complex number

```
asin : (number -> number)
```

Purpose: to compute the arcsine (inverse of sin) of a number

```
atan : (number -> number)
```

Purpose: to compute the arctan (inverse of tan) of a number

```
ceiling : (real -> integer)
```

Purpose: to determine the closest integer (exact or inexact) above a real number

```
complex? : (any -> boolean)
```

Purpose: to determine whether some value is complex

```
conjugate : (number -> number)
```

Purpose: to compute the conjugate of a complex number

```
cos : (number -> number)
```

Purpose: to compute the cosine of a number (radians)

`cosh` : (number -> number)

Purpose: to compute the hyperbolic cosine of a number

`current-seconds` : (-> integer)

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

`denominator` : (rat -> integer)

Purpose: to compute the denominator of a rational

`e` : real

Purpose: Euler's number

`even?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is even or not

`exact->inexact` : (number -> number)

Purpose: to convert an exact number to an inexact one

`exact?` : (number -> boolean)

Purpose: to determine whether some number is exact

`exp` : (number -> number)

Purpose: to compute e raised to a number

`expt` : (number number -> number)

Purpose: to compute the power of the first to the second number

`floor` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) below a real number

```
gcd : (integer integer ... -> integer)
```

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

```
imag-part : (number -> real)
```

Purpose: to extract the imaginary part from a complex number

```
inexact->exact : (number -> number)
```

Purpose: to approximate an inexact number by an exact one

```
inexact? : (number -> boolean)
```

Purpose: to determine whether some number is inexact

```
integer->char : (integer -> char)
```

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

```
integer-sqrt : (number -> integer)
```

Purpose: to compute the integer (exact or inexact) square root of a number

```
integer? : (any -> boolean)
```

Purpose: to determine whether some value is an integer (exact or inexact)

```
lcm : (integer integer ... -> integer)
```

Purpose: to compute the least common multiple of two integers (exact or inexact)

```
log : (number -> number)
```

Purpose: to compute the base-e logarithm of a number

```
magnitude : (number -> real)
```

Purpose: to determine the magnitude of a complex number

```
make-polar : (real real -> number)
```

Purpose: to create a complex from a magnitude and angle

```
make-rectangular : (real real -> number)
```

Purpose: to create a complex from a real and an imaginary part

```
max : (real real ... -> real)
```

Purpose: to determine the largest number

```
min : (real real ... -> real)
```

Purpose: to determine the smallest number

```
modulo : (integer integer -> integer)
```

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

```
negative? : (number -> boolean)
```

Purpose: to determine if some value is strictly smaller than zero

```
number->string : (number -> string)
```

Purpose: to convert a number to a string

```
number? : (any -> boolean)
```

Purpose: to determine whether some value is a number

```
numerator : (rat -> integer)
```

Purpose: to compute the numerator of a rational

```
odd? : (integer -> boolean)
```

Purpose: to determine if some integer (exact or inexact) is odd or not

`pi : real`

Purpose: the ratio of a circle's circumference to its diameter

`positive? : (number -> boolean)`

Purpose: to determine if some value is strictly larger than zero

`quotient : (integer integer -> integer)`

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

`random : (integer -> integer)`

Purpose: to generate a random natural number less than some given integer (exact only!)

`rational? : (any -> boolean)`

Purpose: to determine whether some value is a rational number

`real-part : (number -> real)`

Purpose: to extract the real part from a complex number

`real? : (any -> boolean)`

Purpose: to determine whether some value is a real number

`remainder : (integer integer -> integer)`

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

`round : (real -> integer)`

Purpose: to round a real number to an integer (rounds to even to break ties)

```
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
```

Purpose: to compute the sign of a real number

```
sin : (number -> number)
```

Purpose: to compute the sine of a number (radians)

```
sinh : (number -> number)
```

Purpose: to compute the hyperbolic sine of a number

```
sqr : (number -> number)
```

Purpose: to compute the square of a number

```
sqrt : (number -> number)
```

Purpose: to compute the square root of a number

```
sub1 : (number -> number)
```

Purpose: to compute a number one smaller than a given number

```
tan : (number -> number)
```

Purpose: to compute the tangent of a number (radians)

```
zero? : (number -> boolean)
```

Purpose: to determine if some value is zero or not

4.4.2 Booleans

```
boolean=? : (boolean boolean -> boolean)
```

Purpose: to determine whether two booleans are equal

```
boolean? : (any -> boolean)
```

Purpose: to determine whether some value is a boolean

```
false? : (any -> boolean)
```

Purpose: to determine whether a value is false

```
not : (boolean -> boolean)
```

Purpose: to compute the negation of a boolean value

4.4.3 Symbols

```
symbol->string : (symbol -> string)
```

Purpose: to convert a symbol to a string

```
symbol=? : (symbol symbol -> boolean)
```

Purpose: to determine whether two symbols are equal

```
symbol? : (any -> boolean)
```

Purpose: to determine whether some value is a symbol

4.4.4 Lists

```
append : ((listof any) ... -> (listof any))
```

Purpose: to create a single list from several, by juxtaposition of the items

```
assq : (X  
      (listof (cons X Y))  
      ->  
      (union false (cons X Y)))
```

Purpose: to determine whether some item is the first item of a pair in a list of pairs

```
caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        W)
```

Purpose: to select the first item of the first list in the first list of a list

```
caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
```

Purpose: to select the first item of the first list in a list

```
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
```

Purpose: to select the second item of the first list of a list

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
          (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
        ->
          (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

```
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
          (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
          (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list

```
cdadr : ((cons W (cons Z (cons Y (listof X))))
        ->
          (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
memq : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

```
memv : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

```
null : empty
```

Purpose: the empty list

```
null? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

```
pair? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

```
remove : (any (listof any) -> (listof any))
```

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

```
rest : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

```
reverse : ((listof any) -> list)
```

Purpose: to create a reversed version of a list

```
second : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

```
seventh : ((listof Y) -> Y)
```

Purpose: to select the seventh item of a non-empty list

```
sixth : ((listof Y) -> Y)
```

Purpose: to select the sixth item of a non-empty list

```
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

4.4.5 Posns

```
make-posn : (number number -> posn)
```

Purpose: to construct a posn

```
posn : signature
```

Purpose: signature for posns

```
posn-x : (posn -> number)
```

Purpose: to extract the x component of a posn

`posn-y` : (posn -> number)

Purpose: to extract the y component of a posn

`posn?` : (anything -> boolean)

Purpose: to determine if its input is a posn

4.4.6 Characters

`char->integer` : (char -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

`char-alphabetic?` : (char -> boolean)

Purpose: to determine whether a character represents an alphabetic character

`char-ci<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

`char-ci<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

`char-ci=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal in a case-insensitive manner

`char-ci>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

`char-ci>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another in a case-insensitive manner

`char-downcase` : (char -> char)

Purpose: to determine the equivalent lower-case character

`char-lower-case?` : (char -> boolean)

Purpose: to determine whether a character is a lower-case character

`char-numeric?` : (char -> boolean)

Purpose: to determine whether a character represents a digit

`char-upcase` : (char -> char)

Purpose: to determine the equivalent upper-case character

`char-upper-case?` : (char -> boolean)

Purpose: to determine whether a character is an upper-case character

`char-whitespace?` : (char -> boolean)

Purpose: to determine whether a character represents space

`char<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it)

`char<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another

`char=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal

`char>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it)

`char>? : (char char char ... -> boolean)`

Purpose: to determine whether a character succeeds another

`char? : (any -> boolean)`

Purpose: to determine whether a value is a character

4.4.7 Strings

`explode : (string -> (listof string))`

Purpose: to translate a string into a list of 1-letter strings

`format : (string any ... -> string)`

Purpose: to format a string, possibly embedding values

`implode : ((listof string) -> string)`

Purpose: to concatenate the list of 1-letter strings into one string

`int->string : (integer -> string)`

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

`list->string : ((listof char) -> string)`

Purpose: to convert a s list of characters into a string

`make-string : (nat char -> string)`

Purpose: to produce a string of given length from a single given character

`replicate : (nat string -> string)`

Purpose: to replicate the given string

`string : (char ... -> string)`

Purpose: (string c1 c2 ...) builds a string

`string->int : (string -> integer)`

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

`string->list : (string -> (listof char))`

Purpose: to convert a string into a list of characters

`string->number : (string -> (union number false))`

Purpose: to convert a string into a number, produce false if impossible

`string->symbol : (string -> symbol)`

Purpose: to convert a string into a symbol

`string-alphabetic? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are alphabetic

`string-append : (string ... -> string)`

Purpose: to juxtapose the characters of several strings

`string-ci<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

`string-ci<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

`string-ci=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise in a case-insensitive manner

`string-ci>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

`string-ci>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

`string-copy : (string -> string)`

Purpose: to copy a string

`string-ith : (string nat -> string)`

Purpose: to extract the ith 1-letter substring from the given one

`string-length : (string -> nat)`

Purpose: to determine the length of a string

`string-lower-case? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are lower case

`string-numeric? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are numeric

`string-ref : (string nat -> char)`

Purpose: to extract the i-the character from a string

`string-upper-case? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are upper case

`string-whitespace? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are white space

`string<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

`string<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another

`string=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise

`string>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

`string>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another

`string? : (any -> boolean)`

Purpose: to determine whether a value is a string

`substring : (string nat nat -> string)`

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

4.4.8 Images

`image=? : (image image -> boolean)`

Purpose: to determine whether two images are equal

`image? : (any -> boolean)`

Purpose: to determine whether a value is an image

4.4.9 Misc

`=~ : (real real non-negative-real -> boolean)`

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

`eof : eof`

Purpose: the end-of-file value

`eof-object? : (any -> boolean)`

Purpose: to determine whether some value is the end-of-file value

`eq? : (any any -> boolean)`

Purpose: to determine whether two values are equivalent from the computer's perspective (intensional)

`equal? : (any any -> boolean)`

Purpose: to determine whether two values are structurally equal where basic values are compared with the `eqv?` predicate

`equal~? : (any any non-negative-real -> boolean)`

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

`eqv? : (any any -> boolean)`

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

`error` : (any ... -> void)

Purpose: to signal an error, combining the given values into an error message.

If any of the values' printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

`exit` : (-> void)

Purpose: to exit the running program

`identity` : (any -> any)

Purpose: to return the argument unchanged

`struct?` : (any -> boolean)

Purpose: to determine whether some value is a structure

4.4.10 Numbers (relaxed conditions)

`*` : (number ... -> number)

Purpose: to multiply all given numbers

`+` : (number ... -> number)

Purpose: to add all given numbers

`-` : (number ... -> number)

Purpose: to subtract from the first all remaining numbers

`/` : (number ... -> number)

Purpose: to divide the first by all remaining numbers

4.4.11 Higher-Order Functions

`andmap` : ((X -> boolean) (listof X) -> boolean)

Purpose: (andmap p (list x-1 ... x-n)) = (and (p x-1) ... (p x-n))

`apply` : ((X-1 ... X-N -> Y)
 X-1
 ...
 X-i
 (list X-i+1 ... X-N)
 ->
 Y)

Purpose: to apply a function using items from a list as the arguments

`argmax` : ((X -> real) (listof X) -> X)

Purpose: to find the (first) element of the list that maximizes the output of the function

`argmin` : ((X -> real) (listof X) -> X)

Purpose: to find the (first) element of the list that minimizes the output of the function

`build-list` : (nat (nat -> X) -> (listof X))

Purpose: (build-list n f) = (list (f 0) ... (f (- n 1)))

`build-string` : (nat (nat -> char) -> string)

Purpose: (build-string n f) = (string (f 0) ... (f (- n 1)))

`compose` : ((Y-1 -> Z)
 ...
 (Y-N -> Y-N-1)
 (X-1 ... X-N -> Y-N)
 ->
 (X-1 ... X-N -> Z))

Purpose: to compose a sequence of procedures into a single procedure

```
filter : ((X -> boolean) (listof X) -> (listof X))
```

Purpose: to construct a list from all those items on a list for which the predicate holds

```
foldl : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldl f base (list x-1 ... x-n)) = (f x-n ... (f x-1 base))

```
foldr : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldr f base (list x-1 ... x-n)) = (f x-1 ... (f x-n base))

```
for-each : ((any ... -> any) (listof any) ... -> void)
```

Purpose: to apply a function to each item on one or more lists for effect only

```
map : ((X ... -> Z) (listof X) ... -> (listof Z))
```

Purpose: to construct a new list by applying a function to each item on one or more existing lists

```
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
```

Purpose: to determine whether the first argument produces true for some value in the second argument

```
ormap : ((X -> boolean) (listof X) -> boolean)
```

Purpose: (ormap p (list x-1 ... x-n)) = (or (p x-1) ... (p x-n))

```
procedure? : (any -> boolean)
```

Purpose: to determine if a value is a procedure

```
quicksort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

```
sort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

4.5 Unchanged Forms

```
(define-struct structid (fieldid ...))
```

The same as Intermediate's define-struct.

```
(local [definition ...] expr)  
(letrec ([id expr-for-let] ...) expr)  
(let ([id expr-for-let] ...) expr)  
(let* ([id expr-for-let] ...) expr)
```

The same as Intermediate's local, letrec, let, and let*.

```
(cond [expr expr] ... [expr expr])  
else
```

The same as Beginning's cond.

```
(if expr expr expr)
```

The same as Beginning's if.

```
(and expr expr expr ...)  
(or expr expr expr ...)
```

The same as Beginning's and and or.

```
(time expr)
```

The same as Intermediate's time.

```
(check-expect expr expr)  
(check-within expr expr expr)  
(check-error expr expr)  
(check-member-of expr expr expr ...)
```

`(check-range expr expr expr)`

The same as Beginning's `check-expect`, etc.

`empty : empty?`
`true : boolean?`
`false : boolean?`

Constants for the empty list, true, and false.

`(require module-path)`

The same as Beginning's `require`.

5 Advanced Student

```
program = def-or-expr ...

def-or-expr = definition
            | expr
            | test-case
            | library-require

definition = (define (id id id ...) expr)
            | (define id expr)
            | (define-struct id (id ...))

expr = (begin expr expr ...)
      | (begin0 expr expr ...)
      | (set! id expr)
      | (delay expr)
      | (lambda (id ...) expr)
      | (λ (id ...) expr)
      | (local [definition ...] expr)
      | (letrec ([id expr] ...) expr)
      | (shared ([id expr] ...) expr)
      | (let ([id expr] ...) expr)
      | (let id ([id expr] ...) expr)
      | (let* ([id expr] ...) expr)
      | (recur id ([id expr] ...) expr)
      | (expr expr ...) ; function call
      | (cond [expr expr] ... [expr expr])
      | (cond [expr expr] ... [else expr])
      | (case expr [(choice choice ...) expr] ...
           [(choice choice ...) expr])
      | (case expr [(choice choice ...) expr] ...
           [else expr])
      | (if expr expr expr)
      | (when expr expr)
      | (unless expr expr)
      | (and expr expr expr ...)
      | (or expr expr expr ...)
      | (time expr)
      | empty
      | id ; identifier
      | prim-op ; primitive operation
      | 'quoted ; quoted value
      | 'quasiquoted ; quasiquote
      | number
```

```

| true
| false
| string
| character

choice = id ; treated as a symbol
| number

quoted = id
| number
| string
| character
| (quoted ...)
| 'quoted
| 'quoted
| ,quoted
| ,@quoted

quasiquoted = id
| number
| string
| character
| (quasiquoted ...)
| 'quasiquoted
| 'quasiquoted
| ,expr
| ,@expr

test-case = (check-expect expr expr)
| (check-within expr expr expr)
| (check-member-of expr expr ...)
| (check-range expr expr expr)
| (check-error expr expr)

library-require = (require string)
| (require (lib string string ...))
| (require (planet string package))

package = (string string number number)

```

An *id* is a sequence of characters not including a space or one of the following:

```
" , ' ( ) [ ] { } | ; #
```

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of `"`. Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, `"abcdef"`, `"This is a string"`, and `"This is a string with \" inside"` are all strings.

A *character* begins with `#\` and has the name of the character. For example, `#\a`, `#\b`, and `#\space` are characters.

A *prim-op* is one of:

Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```
< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)
>= : (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)
angle : (number -> real)
asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
```

```

max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (case->
    (integer -> integer)
    (-> (and/c real inexact? (>/c 0) (</c 1))))
rational? : (any -> boolean)
real-part : (number -> real)
real? : (any -> boolean)
remainder : (integer integer -> integer)
round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)

```

Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

Lists

```

append : ((listof any) ... -> (listof any))
assoc : (any (listof any) -> (listof any) or false)
assq : (X
    (listof (cons X Y))
    ->
    (union false (cons X Y)))

```

```

caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         W)
caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         Z)
caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)
cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        (listof Y))
cddr : ((cons W (cons Z (cons Y (listof X))))
        ->
        (listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))

```

```

list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
list? : (any -> boolean)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

Posns

```

make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)
set-posn-x! : (posn number -> void)
set-posn-y! : (posn number -> void)

```

Characters

```

char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)
char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)

```

Strings

```
explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)
string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)
```

Images

```
image=? : (image image -> boolean)
image? : (any -> boolean)
```

Misc

```
=~ : (real real non-negative-real -> boolean)
current-milliseconds : (-> exact-integer)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
```

```

eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
force : (delay -> any)
gensym : (-> symbol?)
identity : (any -> any)
promise? : (any -> boolean)
sleep : (-> positive-number void)
struct? : (any -> boolean)
void : (-> void)
void? : (any -> boolean)
Numbers (relaxed conditions)
* : (number ... -> number)
+ : (number ... -> number)
- : (number ... -> number)
/ : (number ... -> number)
Higher-Order Functions
andmap : ((X -> boolean) (listof X) -> boolean)
apply : ((X-1 ... X-N -> Y)
         X-1
         ...
         X-i
         (list X-i+1 ... X-N)
         ->
         Y)
argmax : ((X -> real) (listof X) -> X)
argmin : ((X -> real) (listof X) -> X)
build-list : (nat (nat -> X) -> (listof X))
build-string : (nat (nat -> char) -> string)
compose : ((Y-1 -> Z)
           ...
           (Y-N -> Y-N-1)
           (X-1 ... X-N -> Y-N)
           ->
           (X-1 ... X-N -> Z))
filter : ((X -> boolean) (listof X) -> (listof X))
foldl : ((X Y -> Y) Y (listof X) -> Y)
foldr : ((X Y -> Y) Y (listof X) -> Y)
for-each : ((any ... -> any) (listof any) ... -> void)
map : ((X ... -> Z) (listof X) ... -> (listof Z))
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
ormap : ((X -> boolean) (listof X) -> boolean)
procedure? : (any -> boolean)

```



```
quicksort : ((listof X) (X X -> boolean) -> (listof X))
sort : ((listof X) (X X -> boolean) -> (listof X))
```

Reading and Printing

```
display : (any -> void)
newline : (-> void)
pretty-print : (any -> void)
print : (any -> void)
printf : (string any ... -> void)
read : (-> sexp)
with-input-from-file : (string (-> any) -> any)
with-input-from-string : (string (-> any) -> any)
with-output-to-file : (string (-> any) -> any)
with-output-to-string : (string (-> any) -> any)
write : (any -> void)
```

Vectors

```
build-vector : (nat (nat -> X) -> (vectorof X))
make-vector : (number X -> (vectorof X))
vector : (X ... -> (vector X ...))
vector-length : ((vector X) -> nat)
vector-ref : ((vector X) nat -> X)
vector-set! : ((vectorof X) nat X -> void)
vector? : (any -> boolean)
```

Boxes

```
box : (any -> box)
box? : (any -> boolean)
set-box! : (box any -> void)
unbox : (box -> any)
```

Hash Tables

```
hash-copy : (hash -> hash)
hash-count : (hash -> integer)
hash-eq? : (hash -> boolean)
hash-equal? : (hash -> boolean)
hash-eqv? : (hash -> boolean)
hash-for-each : ((hash X Y) (X Y -> any) -> void)
hash-has-key? : ((hash X Y) X -> boolean)
hash-map : ((hash X Y) (X Y -> A) -> (listof A))
hash-ref : (case->
  ((hash X Y) X -> Y)
  ((hash X Y) X Y -> Y)
  ((hash X Y) X (-> Y) -> Y))
hash-ref! : (case->
  ((hash X Y) X Y -> Y)
  ((hash X Y) X (-> Y) -> Y))
hash-remove! : ((hash X Y) X -> void)
hash-set! : ((hash X Y) X Y -> void)
```

```

hash-update! : (case->
  ((hash X Y) X (Y -> Y) -> void)
  ((hash X Y) X (Y -> Y) Y -> void)
  ((hash X Y) X (Y -> Y) (-> Y) -> void))
hash? : (any -> boolean)
make-hash : ((listof (list X Y)) -> (hash X Y))
make-hasheq : ((listof (list X Y)) -> (hash X Y))
make-hasheqv : ((listof (list X Y)) -> (hash X Y))

```

5.1 define

```

(define (id id ...) expr)
(define id expr)

```

The same as Intermediate with Lambda's `define`, except that a function is allowed to accept zero arguments.

5.2 define-struct

```

(define-struct structid (fieldid ...))

```

The same as Intermediate's `define-struct`, but defines an additional set of operations:

- `set-structid-fieldid!` : takes an instance of the structure and a value, and changes the instance's field to the given value.

5.3 lambda

```

(lambda (id ...) expr)
(λ (id ...) expr)

```

The same as Intermediate with Lambda's `lambda`, except that a function is allowed to accept zero arguments.

5.4 Function Calls

```

(expr expr ...)

```

A function call in Advanced is the same as an Intermediate with Lambda function call, except that zero arguments are allowed.

```
(#%app expr expr ...)
```

A function call can be written with `%app`, though it's practically never written that way.

5.5 begin

```
(begin expr expr ...)
```

Evaluates the *exprs* in order from left to right. The value of the `begin` expression is the value of the last *expr*.

5.6 begin0

```
(begin0 expr expr ...)
```

Evaluates the *exprs* in order from left to right. The value of the `begin` expression is the value of the first *expr*.

5.7 set!

```
(set! id expr)
```

Evaluates *expr*, and then changes the definition *id* to have *expr*'s value. The *id* must be defined or bound by `letrec`, `let`, or `let*`.

5.8 delay

```
(delay expr)
```

Produces a “promise” to evaluate *expr*. The *expr* is not evaluated until the promise is forced through the `force` operator; when the promise is forced, the result is recorded, so that any further `force` of the promise always produces the remembered value.

5.9 shared

```
(shared ([id expr] ...) expr)
```

Like `letrec`, but when an `expr` next to an `id` is a `cons`, `list`, `vector`, quasiquoted expression, or `make-structid` from a `define-struct`, the `expr` can refer directly to any `id`, not just `ids` defined earlier. Thus, `shared` can be used to create cyclic data structures.

5.10 let

```
(let ([id expr] ...) expr)
(let id ([id expr] ...) expr)
```

The first form of `let` is the same as Intermediate's `let`.

The second form is equivalent to a `recur` form.

5.11 recur

```
(recur id ([id expr] ...) expr)
```

A short-hand recursion construct. The first `id` corresponds to the name of the recursive function. The parenthesized `ids` are the function's arguments, and each corresponding `expr` is a value supplied for that argument in an initial starting call of the function. The last `expr` is the body of the function.

More precisely, a `recur` form

```
(recur func-id ([arg-id arg-expr] ...)
  body-expr)
```

is equivalent to

```
((local [(define (func-id arg-id ...)
  body-expr)]
  func-id)
  arg-expr ...)
```

5.12 case

```
(case expr [(choice ...) expr] ... [(choice ...) expr])
```

A case form contains one or more “lines” that are surrounded by parentheses or square brackets. Each line contains a sequence of choices—numbers and names for symbols—and an answer *expr*. The initial *expr* is evaluated, and the resulting value is compared to the choices in each line, where the lines are considered in order. The first line that contains a matching choice provides an answer *expr* whose value is the result of the whole case expression. If none of the lines contains a matching choice, it is an error.

```
(case expr [(choice ...) expr] ... [else expr])
```

This form of case is similar to the prior one, except that the final `else` clause is always taken if no prior line contains a choice matching the value of the initial *expr*. In other words, so there is no possibility to “fall off the end” of the case form.

5.13 when and unless

```
(when expr expr)
```

The first *expr* (known as the “test” expression) is evaluated. If it evaluates to `true`, the result of the when expression is the result of evaluating the second *expr*, otherwise the result is `(void)` and the second *expr* is not evaluated. If the result of evaluating the test *expr* is neither `true` nor `false`, it is an error.

```
(unless expr expr)
```

Like when, but the second *expr* is evaluated when the first *expr* produces `false` instead of `true`.

5.14 Primitive Operations

5.14.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

```
< : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than

`<= : (real real real ... -> boolean)`

Purpose: to compare real numbers for less-than or equality

`= : (number number number ... -> boolean)`

Purpose: to compare numbers for equality

`> : (real real real ... -> boolean)`

Purpose: to compare real numbers for greater-than

`>= : (real real ... -> boolean)`

Purpose: to compare real numbers for greater-than or equality

`abs : (real -> real)`

Purpose: to compute the absolute value of a real number

`acos : (number -> number)`

Purpose: to compute the arccosine (inverse of cos) of a number

`add1 : (number -> number)`

Purpose: to compute a number one larger than a given number

`angle : (number -> real)`

Purpose: to extract the angle from a complex number

`asin : (number -> number)`

Purpose: to compute the arcsine (inverse of sin) of a number

`atan : (number -> number)`

Purpose: to compute the arctan (inverse of tan) of a number

`ceiling` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) above a real number

`complex?` : (any -> boolean)

Purpose: to determine whether some value is complex

`conjugate` : (number -> number)

Purpose: to compute the conjugate of a complex number

`cos` : (number -> number)

Purpose: to compute the cosine of a number (radians)

`cosh` : (number -> number)

Purpose: to compute the hyperbolic cosine of a number

`current-seconds` : (-> integer)

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

`denominator` : (rat -> integer)

Purpose: to compute the denominator of a rational

`e` : real

Purpose: Euler's number

`even?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is even or not

`exact->inexact` : (number -> number)

Purpose: to convert an exact number to an inexact one

`exact? : (number -> boolean)`

Purpose: to determine whether some number is exact

`exp : (number -> number)`

Purpose: to compute e raised to a number

`expt : (number number -> number)`

Purpose: to compute the power of the first to the second number

`floor : (real -> integer)`

Purpose: to determine the closest integer (exact or inexact) below a real number

`gcd : (integer integer ... -> integer)`

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

`imag-part : (number -> real)`

Purpose: to extract the imaginary part from a complex number

`inexact->exact : (number -> number)`

Purpose: to approximate an inexact number by an exact one

`inexact? : (number -> boolean)`

Purpose: to determine whether some number is inexact

`integer->char : (integer -> char)`

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

`integer-sqrt : (number -> integer)`

Purpose: to compute the integer (exact or inexact) square root of a number

`integer? : (any -> boolean)`

Purpose: to determine whether some value is an integer (exact or inexact)

`lcm : (integer integer ... -> integer)`

Purpose: to compute the least common multiple of two integers (exact or inexact)

`log : (number -> number)`

Purpose: to compute the base-e logarithm of a number

`magnitude : (number -> real)`

Purpose: to determine the magnitude of a complex number

`make-polar : (real real -> number)`

Purpose: to create a complex from a magnitude and angle

`make-rectangular : (real real -> number)`

Purpose: to create a complex from a real and an imaginary part

`max : (real real ... -> real)`

Purpose: to determine the largest number

`min : (real real ... -> real)`

Purpose: to determine the smallest number

`modulo : (integer integer -> integer)`

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

`negative? : (number -> boolean)`

Purpose: to determine if some value is strictly smaller than zero

```
number->string : (number -> string)
```

Purpose: to convert a number to a string

```
number? : (any -> boolean)
```

Purpose: to determine whether some value is a number

```
numerator : (rat -> integer)
```

Purpose: to compute the numerator of a rational

```
odd? : (integer -> boolean)
```

Purpose: to determine if some integer (exact or inexact) is odd or not

```
pi : real
```

Purpose: the ratio of a circle's circumference to its diameter

```
positive? : (number -> boolean)
```

Purpose: to determine if some value is strictly larger than zero

```
quotient : (integer integer -> integer)
```

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

```
random : (case->
  (integer -> integer)
  (-> (and/c real inexact? (>/c 0) (</c 1))))
```

Purpose: to generate a random natural number less than some given integer, or to generate a random inexact number between 0.0 and 1.0 exclusive

```
rational? : (any -> boolean)
```

Purpose: to determine whether some value is a rational number

`real-part` : (number -> real)

Purpose: to extract the real part from a complex number

`real?` : (any -> boolean)

Purpose: to determine whether some value is a real number

`remainder` : (integer integer -> integer)

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

`round` : (real -> integer)

Purpose: to round a real number to an integer (rounds to even to break ties)

`sgn` : (real -> (union 1 1.0 0 0.0 -1 -1.0))

Purpose: to compute the sign of a real number

`sin` : (number -> number)

Purpose: to compute the sine of a number (radians)

`sinh` : (number -> number)

Purpose: to compute the hyperbolic sine of a number

`sqr` : (number -> number)

Purpose: to compute the square of a number

`sqrt` : (number -> number)

Purpose: to compute the square root of a number

`sub1` : (number -> number)

Purpose: to compute a number one smaller than a given number

```
tan : (number -> number)
```

Purpose: to compute the tangent of a number (radians)

```
zero? : (number -> boolean)
```

Purpose: to determine if some value is zero or not

5.14.2 Booleans

```
boolean=? : (boolean boolean -> boolean)
```

Purpose: to determine whether two booleans are equal

```
boolean? : (any -> boolean)
```

Purpose: to determine whether some value is a boolean

```
false? : (any -> boolean)
```

Purpose: to determine whether a value is false

```
not : (boolean -> boolean)
```

Purpose: to compute the negation of a boolean value

5.14.3 Symbols

```
symbol->string : (symbol -> string)
```

Purpose: to convert a symbol to a string

```
symbol=? : (symbol symbol -> boolean)
```

Purpose: to determine whether two symbols are equal

```
symbol? : (any -> boolean)
```

Purpose: to determine whether some value is a symbol

5.14.4 Lists

```
append : ((listof any) ... -> (listof any))
```

Purpose: to create a single list from several

```
assoc : (any (listof any) -> (listof any) or false)
```

Purpose: to produce the first element on the list whose first is equal? to v; otherwise it produces false

```
assq : (X
      (listof (cons X Y))
      ->
      (union false (cons X Y)))
```

Purpose: to determine whether some item is the first item of a pair in a list of pairs

```
caaar : ((cons
      (cons (cons W (listof Z)) (listof Y))
      (listof X))
      ->
      W)
```

Purpose: to select the first item of the first list in the first list of a list

```
caadr : ((cons
      (cons (cons W (listof Z)) (listof Y))
      (listof X))
      ->
      (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
```

Purpose: to select the first item of the first list in a list

```
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))  
        ->  
        Z)
```

Purpose: to select the second item of the first list of a list

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
cdaar : ((cons  
          (cons (cons W (listof Z)) (listof Y))  
          (listof X))  
        ->  
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))  
        ->  
        (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

```
cdr : ((cons (cons Z (listof Y)) (listof X))  
      ->  
      (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

```
cdddr : ((cons (cons W (cons Z (listof Y))) (listof X))  
        ->  
        (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list

```
cdddr : ((cons W (cons Z (cons Y (listof X))))  
        ->  
        (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

```
list? : (any -> boolean)
```

Purpose: to determine whether some value is a list

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

`memq` : (any (listof any) -> (union false list))

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

`memv` : (any (listof any) -> (union false list))

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

`null` : empty

Purpose: the empty list

`null?` : (any -> boolean)

Purpose: to determine whether some value is the empty list

`pair?` : (any -> boolean)

Purpose: to determine whether some value is a constructed list

`remove` : (any (listof any) -> (listof any))

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

`rest` : ((cons Y (listof X)) -> (listof X))

Purpose: to select the rest of a non-empty list

`reverse` : ((listof any) -> list)

Purpose: to create a reversed version of a list

`second` : ((cons Z (cons Y (listof X))) -> Y)

Purpose: to select the second item of a non-empty list

`seventh` : ((listof Y) -> Y)

Purpose: to select the seventh item of a non-empty list

```
sixth : ((listof Y) -> Y)
```

Purpose: to select the sixth item of a non-empty list

```
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

5.14.5 Posns

```
make-posn : (number number -> posn)
```

Purpose: to construct a posn

```
posn : signature
```

Purpose: signature for posns

```
posn-x : (posn -> number)
```

Purpose: to extract the x component of a posn

```
posn-y : (posn -> number)
```

Purpose: to extract the y component of a posn

```
posn? : (anything -> boolean)
```

Purpose: to determine if its input is a posn

```
set-posn-x! : (posn number -> void)
```

Purpose: to update the x component of a posn

```
set-posn-y! : (posn number -> void)
```

Purpose: to update the y component of a posn

5.14.6 Characters

`char->integer` : (char -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

`char-alphabetic?` : (char -> boolean)

Purpose: to determine whether a character represents an alphabetic character

`char-ci<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

`char-ci<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

`char-ci=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal in a case-insensitive manner

`char-ci>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

`char-ci>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another in a case-insensitive manner

`char-downcase` : (char -> char)

Purpose: to determine the equivalent lower-case character

`char-lower-case?` : (char -> boolean)

Purpose: to determine whether a character is a lower-case character

`char-numeric?` : (char -> boolean)

Purpose: to determine whether a character represents a digit

`char-upcase` : (char -> char)

Purpose: to determine the equivalent upper-case character

`char-upper-case?` : (char -> boolean)

Purpose: to determine whether a character is an upper-case character

`char-whitespace?` : (char -> boolean)

Purpose: to determine whether a character represents space

`char<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it)

`char<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another

`char=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal

`char>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it)

`char>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another

`char?` : (any -> boolean)

Purpose: to determine whether a value is a character

5.14.7 Strings

`explode : (string -> (listof string))`

Purpose: to translate a string into a list of 1-letter strings

`format : (string any ... -> string)`

Purpose: to format a string, possibly embedding values

`implode : ((listof string) -> string)`

Purpose: to concatenate the list of 1-letter strings into one string

`int->string : (integer -> string)`

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

`list->string : ((listof char) -> string)`

Purpose: to convert a s list of characters into a string

`make-string : (nat char -> string)`

Purpose: to produce a string of given length from a single given character

`replicate : (nat string -> string)`

Purpose: to replicate the given string

`string : (char ... -> string)`

Purpose: (string c1 c2 ...) builds a string

`string->int : (string -> integer)`

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

`string->list : (string -> (listof char))`

Purpose: to convert a string into a list of characters

```
string->number : (string -> (union number false))
```

Purpose: to convert a string into a number, produce false if impossible

```
string->symbol : (string -> symbol)
```

Purpose: to convert a string into a symbol

```
string-alphabetic? : (string -> boolean)
```

Purpose: to determine whether all 'letters' in the string are alphabetic

```
string-append : (string ... -> string)
```

Purpose: to juxtapose the characters of several strings

```
string-ci<=? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

```
string-ci<? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

```
string-ci=? : (string string string ... -> boolean)
```

Purpose: to compare two strings character-wise in a case-insensitive manner

```
string-ci>=? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

```
string-ci>? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

`string-copy` : (string -> string)

Purpose: to copy a string

`string-ith` : (string nat -> string)

Purpose: to extract the ith 1-letter substring from the given one

`string-length` : (string -> nat)

Purpose: to determine the length of a string

`string-lower-case?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are lower case

`string-numeric?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are numeric

`string-ref` : (string nat -> char)

Purpose: to extract the i-the character from a string

`string-upper-case?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are upper case

`string-whitespace?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are white space

`string<=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

`string<?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another

`string=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise

`string>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

`string>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another

`string? : (any -> boolean)`

Purpose: to determine whether a value is a string

`substring : (string nat nat -> string)`

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

5.14.8 Images

`image=? : (image image -> boolean)`

Purpose: to determine whether two images are equal

`image? : (any -> boolean)`

Purpose: to determine whether a value is an image

5.14.9 Misc

`=~ : (real real non-negative-real -> boolean)`

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

`current-milliseconds` : (`-> exact-integer`)

Purpose: to return the current “time” in fixnum milliseconds (possibly negative)

`eof` : `eof`

Purpose: the end-of-file value

`eof-object?` : (`any -> boolean`)

Purpose: to determine whether some value is the end-of-file value

`eq?` : (`any any -> boolean`)

Purpose: to determine whether two values are equivalent from the computer’s perspective (intensional)

`equal?` : (`any any -> boolean`)

Purpose: to determine whether two values are structurally equal where basic values are compared with the `eqv?` predicate

`equal~?` : (`any any non-negative-real -> boolean`)

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

`eqv?` : (`any any -> boolean`)

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

`error` : (`any ... -> void`)

Purpose: to signal an error, combining the given values into an error message.

If any of the values’ printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

`exit` : (`-> void`)

Purpose: to exit the running program

`force` : (`delay -> any`)

Purpose: to find the delayed value; see also `delay`

`gensym` : (`-> symbol?`)

Purpose: to generate a new symbol, different from all symbols in the program

`identity` : (`any -> any`)

Purpose: to return the argument unchanged

`promise?` : (`any -> boolean`)

Purpose: to determine if a value is delayed

`sleep` : (`-> positive-number void`)

Purpose: to cause the program to sleep for the given number of seconds

`struct?` : (`any -> boolean`)

Purpose: to determine whether some value is a structure

`void` : (`-> void`)

Purpose: produces a void value

`void?` : (`any -> boolean`)

Purpose: to determine if a value is void

5.14.10 Numbers (relaxed conditions)

`* : (number ... -> number)`

Purpose: to multiply all given numbers

`+ : (number ... -> number)`

Purpose: to add all given numbers

`- : (number ... -> number)`

Purpose: to subtract from the first all remaining numbers

`/ : (number ... -> number)`

Purpose: to divide the first by all remaining numbers

5.14.11 Higher-Order Functions

`andmap : ((X -> boolean) (listof X) -> boolean)`

Purpose: $(\text{andmap } p \text{ (list } x-1 \dots x-n)) = (\text{and } (p \text{ } x-1) \dots (p \text{ } x-n))$

`apply : ((X-1 ... X-N -> Y)
 X-1
 ...
 X-i
 (list X-i+1 ... X-N)
 ->
 Y)`

Purpose: to apply a function using items from a list as the arguments

`argmax : ((X -> real) (listof X) -> X)`

Purpose: to find the (first) element of the list that maximizes the output of the function

`argmin : ((X -> real) (listof X) -> X)`

Purpose: to find the (first) element of the list that minimizes the output of the function

```
build-list : (nat (nat -> X) -> (listof X))
```

Purpose: (build-list n f) = (list (f 0) ... (f (- n 1)))

```
build-string : (nat (nat -> char) -> string)
```

Purpose: (build-string n f) = (string (f 0) ... (f (- n 1)))

```
compose : ((Y-1 -> Z)
           ...
           (Y-N -> Y-N-1)
           (X-1 ... X-N -> Y-N)
           ->
           (X-1 ... X-N -> Z))
```

Purpose: to compose a sequence of procedures into a single procedure

```
filter : ((X -> boolean) (listof X) -> (listof X))
```

Purpose: to construct a list from all those items on a list for which the predicate holds

```
foldl : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldl f base (list x-1 ... x-n)) = (f x-n ... (f x-1 base))

```
foldr : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldr f base (list x-1 ... x-n)) = (f x-1 ... (f x-n base))

```
for-each : ((any ... -> any) (listof any) ... -> void)
```

Purpose: to apply a function to each item on one or more lists for effect only

```
map : ((X ... -> Z) (listof X) ... -> (listof Z))
```

Purpose: to construct a new list by applying a function to each item on one or more existing lists

```
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
```

Purpose: to determine whether the first argument produces true for some value in the second argument

```
ormap : ((X -> boolean) (listof X) -> boolean)
```

Purpose: $(\text{ormap } p \text{ (list } x-1 \dots x-n)) = (\text{or } (p \ x-1) \dots (p \ x-n))$

```
procedure? : (any -> boolean)
```

Purpose: to determine if a value is a procedure

```
quicksort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

```
sort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

5.14.12 Reading and Printing

```
display : (any -> void)
```

Purpose: to print the argument to stdout (without quotes on symbols and strings, etc.)

```
newline : (-> void)
```

Purpose: to print a newline to stdout

```
pretty-print : (any -> void)
```

Purpose: like write, but with standard newlines and indentation

```
print : (any -> void)
```

Purpose: to print the argument as a value to stdout

```
printf : (string any ... -> void)
```

Purpose: to format the rest of the arguments according to the first argument and print it to stdout

```
read : (-> sexp)
```

Purpose: to read input from the user

```
with-input-from-file : (string (-> any) -> any)
```

Purpose: to open the named input file and to extract all input from there

```
with-input-from-string : (string (-> any) -> any)
```

Purpose: to turn the given string into input for read* operations

```
with-output-to-file : (string (-> any) -> any)
```

Purpose: to open the named output file and to put all output there

```
with-output-to-string : (string (-> any) -> any)
```

Purpose: to produce a string from all write/display/print operations

```
write : (any -> void)
```

Purpose: to print the argument to stdout (in a traditional style that is somewhere between print and display)

5.14.13 Vectors

```
build-vector : (nat (nat -> X) -> (vectorof X))
```

Purpose: to construct a vector

```
make-vector : (number X -> (vectorof X))
```

Purpose: to construct a vector

```
vector : (X ... -> (vector X ...))
```

Purpose: to construct a vector

```
vector-length : ((vector X) -> nat)
```

Purpose: to determine the length of a vector

```
vector-ref : ((vector X) nat -> X)
```

Purpose: to extract an element from a vector

```
vector-set! : ((vectorof X) nat X -> void)
```

Purpose: to update a vector

```
vector? : (any -> boolean)
```

Purpose: to determine if a value is a vector

5.14.14 Boxes

```
box : (any -> box)
```

Purpose: to construct a box

```
box? : (any -> boolean)
```

Purpose: to determine if a value is a box

```
set-box! : (box any -> void)
```

Purpose: to update a box

```
unbox : (box -> any)
```

Purpose: to extract the boxed value

5.14.15 Hash Tables

`hash-copy` : (hash -> hash)

Purpose: to copy a hash table

`hash-count` : (hash -> integer)

Purpose: to determine the number of keys mapped by a hash table

`hash-eq?` : (hash -> boolean)

Purpose: to determine if a hash table uses eq? for comparisons

`hash-equal?` : (hash -> boolean)

Purpose: to determine if a hash table uses equal? for comparisons

`hash-eqv?` : (hash -> boolean)

Purpose: to determine if a hash table uses eqv? for comparisons

`hash-for-each` : ((hash X Y) (X Y -> any) -> void)

Purpose: to apply a function to each mapping of a hash table for effect only

`hash-has-key?` : ((hash X Y) X -> boolean)

Purpose: to determine if a key is associated with a value in a hash table

`hash-map` : ((hash X Y) (X Y -> A) -> (listof A))

Purpose: to construct a new list by applying a function to each mapping of a hash table

`hash-ref` : (case->
 ((hash X Y) X -> Y)
 ((hash X Y) X Y -> Y)
 ((hash X Y) X (-> Y) -> Y))

Purpose: to extract the value associated with a key from a hash table; the three argument

case allows a default value or default value computation

```
hash-ref! : (case->
              ((hash X Y) X Y -> Y)
              ((hash X Y) X (-> Y) -> Y))
```

Purpose: to extract the value associated with a key from a hash table; if the key does not have an mapping, the third argument is used as the value (or used to compute the value) and is added to the hash table associated with the key

```
hash-remove! : ((hash X Y) X -> void)
```

Purpose: to remove an mapping from a hash table

```
hash-set! : ((hash X Y) X Y -> void)
```

Purpose: to update a hash table with a new mapping

```
hash-update! : (case->
                 ((hash X Y) X (Y -> Y) -> void)
                 ((hash X Y) X (Y -> Y) Y -> void)
                 ((hash X Y) X (Y -> Y) (-> Y) -> void))
```

Purpose: to compose hash-ref and hash-set! to update an existing mapping; the third argument is used to compute the new mapping value; the fourth argument is used as the third argument to hash-ref

```
hash? : (any -> boolean)
```

Purpose: to determine if a value is a hash table

```
make-hash : ((listof (list X Y)) -> (hash X Y))
```

Purpose: to construct a hash table from a list of mappings that uses equal? for comparisons

```
make-hasheq : ((listof (list X Y)) -> (hash X Y))
```

Purpose: to construct a hash table from a list of mappings that uses eq? for comparisons

```
make-hasheqv : ((listof (list X Y)) -> (hash X Y))
```

Purpose: to construct a hash table from a list of mappings that uses `eqv?` for comparisons

5.15 Unchanged Forms

```
(local [definition ...] expr)
(letrec ([id expr-for-let] ...) expr)
(let* ([id expr-for-let] ...) expr)
```

The same as Intermediate's `local`, `letrec`, and `let*`.

```
(cond [expr expr] ... [expr expr])
else
```

The same as Beginning's `cond`, except that `else` can be used with `case`.

```
(if expr expr expr)
```

The same as Beginning's `if`.

```
(and expr expr expr ...)
(or expr expr expr ...)
```

The same as Beginning's `and` and `or`.

```
(time expr)
```

The same as Intermediate's `time`.

```
(check-expect expr expr)
(check-within expr expr expr)
(check-error expr expr)
(check-member-of expr expr expr ...)
(check-range expr expr expr)
```

The same as Beginning's `check-expect`, etc.

```
empty : empty?
true : boolean?
false : boolean?
```

Constants for the empty list, true, and false.

```
(require module-path)
```

The same as Beginning's require.

Index

#%app, 79
#%app, 112
#%app, 14
#%app, 147
*, 19
*, 132
*, 47
*, 99
*, 171
+, 48
+, 99
+, 132
+, 171
+, 19
-, 48
-, 19
-, 100
-, 132
-, 171
/, 19
/, 132
/, 48
/, 100
/, 171
<, 79
<, 48
<, 112
<, 19
<, 149
<=, 80
<=, 112
<=, 19
<=, 48
<=, 150
=, 48
=, 112
=, 19
=, 150
=, 80
=~, 98
=~, 131
=~, 168
=~, 67
=~, 38
>, 80
>, 48
>, 112
>, 150
>, 19
>=, 19
>=, 150
>=, 112
>=, 80
>=, 48
abs, 150
abs, 48
abs, 113
abs, 80
abs, 20
acos, 113
acos, 150
acos, 80
acos, 20
acos, 48
add1, 20
add1, 49
add1, 150
add1, 80
add1, 113
Advanced Student, 137
and, 16
and, 69
and, 135
and, 102
and, 16
and, 178
andmap, 171
andmap, 133
andmap, 100
angle, 150
angle, 113
angle, 49

[angle](#), 80
[angle](#), 20
[append](#), 157
[append](#), 87
[append](#), 55
[append](#), 26
[append](#), 119
[apply](#), 133
[apply](#), 100
[apply](#), 171
[argmax](#), 100
[argmax](#), 171
[argmax](#), 133
[argmin](#), 171
[argmin](#), 133
[argmin](#), 100
[asin](#), 49
[asin](#), 150
[asin](#), 113
[asin](#), 80
[asin](#), 20
[assoc](#), 157
[assq](#), 157
[assq](#), 27
[assq](#), 55
[assq](#), 119
[assq](#), 87
[atan](#), 80
[atan](#), 49
[atan](#), 150
[atan](#), 20
[atan](#), 113
[begin](#), 147
[begin](#), 147
[begin0](#), 147
[begin0](#), 147
[Beginning Student](#), 7
[Beginning Student with List Abbreviations](#), 40
[boolean=?](#), 156
[boolean=?](#), 118
[boolean=?](#), 54
[boolean=?](#), 86
[boolean=?](#), 25
[boolean?](#), 86
[boolean?](#), 119
[boolean?](#), 156
[boolean?](#), 26
[boolean?](#), 54
[Booleans](#), 156
[Booleans](#), 54
[Booleans](#), 25
[Booleans](#), 118
[Booleans](#), 86
[box](#), 175
[box?](#), 175
[Boxes](#), 175
[build-list](#), 172
[build-list](#), 133
[build-list](#), 100
[build-string](#), 172
[build-string](#), 100
[build-string](#), 133
[build-vector](#), 174
[caaar](#), 157
[caaar](#), 27
[caaar](#), 87
[caaar](#), 56
[caaar](#), 120
[caadr](#), 27
[caadr](#), 87
[caadr](#), 120
[caadr](#), 56
[caadr](#), 157
[caar](#), 157
[caar](#), 27
[caar](#), 87
[caar](#), 120
[caar](#), 56
[cadar](#), 120
[cadar](#), 27
[cadar](#), 56
[cadar](#), 158
[cadar](#), 87

<code>caddr</code> , 27	<code>cdddr</code> , 121
<code>caddr</code> , 158	<code>cdddr</code> , 28
<code>caddr</code> , 87	<code>cdddr</code> , 159
<code>caddr</code> , 120	<code>cdddr</code> , 57
<code>caddr</code> , 56	<code>cdddr</code> , 89
<code>caddr</code> , 56	<code>cddr</code> , 89
<code>caddr</code> , 120	<code>cddr</code> , 121
<code>caddr</code> , 158	<code>cddr</code> , 159
<code>caddr</code> , 88	<code>cddr</code> , 28
<code>caddr</code> , 27	<code>cddr</code> , 57
<code>cadr</code> , 158	<code>cdr</code> , 159
<code>cadr</code> , 56	<code>cdr</code> , 29
<code>cadr</code> , 88	<code>cdr</code> , 89
<code>cadr</code> , 28	<code>cdr</code> , 121
<code>cadr</code> , 120	<code>cdr</code> , 57
<code>car</code> , 88	<code>ceiling</code> , 151
<code>car</code> , 120	<code>ceiling</code> , 81
<code>car</code> , 56	<code>ceiling</code> , 20
<code>car</code> , 28	<code>ceiling</code> , 49
<code>car</code> , 158	<code>ceiling</code> , 113
<code>case</code> , 149	<code>char->integer</code> , 125
<code>case</code> , 149	<code>char->integer</code> , 61
<code>cdaar</code> , 57	<code>char->integer</code> , 32
<code>cdaar</code> , 158	<code>char->integer</code> , 163
<code>cdaar</code> , 28	<code>char->integer</code> , 92
<code>cdaar</code> , 121	<code>char-alphabetic?</code> , 163
<code>cdaar</code> , 88	<code>char-alphabetic?</code> , 92
<code>cdadr</code> , 121	<code>char-alphabetic?</code> , 32
<code>cdadr</code> , 88	<code>char-alphabetic?</code> , 125
<code>cdadr</code> , 28	<code>char-alphabetic?</code> , 61
<code>cdadr</code> , 57	<code>char-ci<=?</code> , 61
<code>cdadr</code> , 158	<code>char-ci<=?</code> , 92
<code>cdar</code> , 28	<code>char-ci<=?</code> , 32
<code>cdar</code> , 57	<code>char-ci<=?</code> , 163
<code>cdar</code> , 121	<code>char-ci<=?</code> , 125
<code>cdar</code> , 88	<code>char-ci<?</code> , 125
<code>cdar</code> , 158	<code>char-ci<?</code> , 163
<code>cddar</code> , 121	<code>char-ci<?</code> , 92
<code>cddar</code> , 88	<code>char-ci<?</code> , 32
<code>cddar</code> , 28	<code>char-ci<?</code> , 61
<code>cddar</code> , 57	<code>char-ci=?</code> , 32
<code>cddar</code> , 159	<code>char-ci=?</code> , 125

char-ci=?, 93	char-whitespace?, 33
char-ci=?, 163	char<=?, 33
char-ci=?, 61	char<=?, 93
char-ci>=?, 61	char<=?, 62
char-ci>=?, 163	char<=?, 126
char-ci>=?, 93	char<=?, 164
char-ci>=?, 125	char<?, 94
char-ci>=?, 33	char<?, 126
char-ci>?, 33	char<?, 164
char-ci>?, 125	char<?, 33
char-ci>?, 61	char<?, 62
char-ci>?, 163	char=?, 62
char-ci>?, 93	char=?, 164
char-downcase, 33	char=?, 34
char-downcase, 62	char=?, 126
char-downcase, 93	char=?, 94
char-downcase, 126	char>=?, 62
char-downcase, 163	char>=?, 126
char-lower-case?, 62	char>=?, 164
char-lower-case?, 93	char>=?, 94
char-lower-case?, 33	char>=?, 34
char-lower-case?, 126	char>?, 34
char-lower-case?, 163	char>?, 63
char-numeric?, 126	char>?, 164
char-numeric?, 93	char>?, 127
char-numeric?, 62	char>?, 94
char-numeric?, 33	char?, 127
char-numeric?, 164	char?, 94
char-upcase, 62	char?, 63
char-upcase, 126	char?, 164
char-upcase, 33	char?, 34
char-upcase, 164	Characters, 163
char-upcase, 93	Characters, 61
char-upper-case?, 93	Characters, 32
char-upper-case?, 126	Characters, 125
char-upper-case?, 33	Characters, 92
char-upper-case?, 62	check-error, 102
char-upper-case?, 164	check-error, 135
char-whitespace?, 164	check-error, 69
char-whitespace?, 126	check-error, 16
char-whitespace?, 62	check-error, 178
char-whitespace?, 93	check-expect, 135

check-expect, 102
 check-expect, 178
 check-expect, 16
 check-expect, 69
 check-member-of, 135
 check-member-of, 178
 check-member-of, 69
 check-member-of, 16
 check-member-of, 102
 check-range, 69
 check-range, 178
 check-range, 136
 check-range, 102
 check-range, 17
 check-within, 16
 check-within, 135
 check-within, 69
 check-within, 178
 check-within, 102
 complex?, 113
 complex?, 151
 complex?, 20
 complex?, 49
 complex?, 81
 compose, 172
 compose, 101
 compose, 133
 cond, 15
 cond, 68
 cond, 135
 cond, 15
 cond, 102
 cond, 178
 conjugate, 81
 conjugate, 151
 conjugate, 20
 conjugate, 49
 conjugate, 113
 cons, 57
 cons, 159
 cons, 89
 cons, 29
 cons, 121
 cons?, 29
 cons?, 122
 cons?, 89
 cons?, 159
 cons?, 58
 cos, 49
 cos, 20
 cos, 81
 cos, 151
 cos, 113
 cosh, 49
 cosh, 114
 cosh, 21
 cosh, 81
 cosh, 151
 current-milliseconds, 169
 current-seconds, 49
 current-seconds, 151
 current-seconds, 114
 current-seconds, 81
 current-seconds, 21
 define, 146
 define, 13
 define, 77
 define, 111
 define, 77
 define, 146
 define, 13
 define, 111
 define, 68
 define-struct, 146
 define-struct, 14
 define-struct, 77
 define-struct, 146
 define-struct, 68
 define-struct, 135
 define-struct, 77
 define-struct, 14
 delay, 147
 delay, 147
 denominator, 114

denominator, 81	eq?, 98
denominator, 151	eq?, 169
denominator, 21	eq?, 131
denominator, 50	eq?, 38
display, 173	equal?, 169
e, 114	equal?, 131
e, 21	equal?, 38
e, 81	equal?, 98
e, 151	equal?, 67
e, 50	equal~?, 38
eighth, 159	equal~?, 169
eighth, 89	equal~?, 131
eighth, 122	equal~?, 99
eighth, 58	equal~?, 67
eighth, 29	eqv?, 67
else, 68	eqv?, 169
else, 15	eqv?, 39
else, 135	eqv?, 131
else, 102	eqv?, 99
else, 178	error, 39
empty, 17	error, 132
empty, 69	error, 169
empty, 136	error, 99
empty, 17	error, 68
empty, 178	even?, 50
empty, 102	even?, 151
empty?, 122	even?, 114
empty?, 159	even?, 81
empty?, 89	even?, 21
empty?, 58	exact->inexact, 21
empty?, 29	exact->inexact, 114
eof, 98	exact->inexact, 151
eof, 131	exact->inexact, 50
eof, 67	exact->inexact, 81
eof, 38	exact?, 50
eof, 169	exact?, 152
eof-object?, 98	exact?, 82
eof-object?, 131	exact?, 21
eof-object?, 67	exact?, 114
eof-object?, 169	exit, 170
eof-object?, 38	exit, 68
eq?, 67	exit, 132

[exit](#), 99
[exit](#), 39
[exp](#), 82
[exp](#), 50
[exp](#), 114
[exp](#), 21
[exp](#), 152
[explode](#), 34
[explode](#), 63
[explode](#), 165
[explode](#), 94
[explode](#), 127
[expt](#), 21
[expt](#), 82
[expt](#), 50
[expt](#), 152
[expt](#), 114
[false](#), 18
[false](#), 178
[false](#), 103
[false](#), 69
[false](#), 136
[false?](#), 86
[false?](#), 54
[false?](#), 156
[false?](#), 26
[false?](#), 119
[fifth](#), 58
[fifth](#), 29
[fifth](#), 122
[fifth](#), 89
[fifth](#), 159
[filter](#), 101
[filter](#), 172
[filter](#), 134
[first](#), 160
[first](#), 122
[first](#), 29
[first](#), 89
[first](#), 58
[floor](#), 21
[floor](#), 114
[floor](#), 50
[floor](#), 82
[floor](#), 152
[foldl](#), 172
[foldl](#), 101
[foldl](#), 134
[foldr](#), 172
[foldr](#), 101
[foldr](#), 134
[for-each](#), 134
[for-each](#), 172
[for-each](#), 101
[force](#), 170
[format](#), 63
[format](#), 34
[format](#), 94
[format](#), 165
[format](#), 127
[fourth](#), 89
[fourth](#), 58
[fourth](#), 160
[fourth](#), 122
[fourth](#), 29
Function Calls, 146
Function Calls, 14
Function Calls, 78
Function Calls, 112
[gcd](#), 152
[gcd](#), 50
[gcd](#), 22
[gcd](#), 82
[gcd](#), 115
[gensym](#), 170
Hash Tables, 176
[hash-copy](#), 176
[hash-count](#), 176
[hash-eq?](#), 176
[hash-equal?](#), 176
[hash-eqv?](#), 176
[hash-for-each](#), 176
[hash-has-key?](#), 176
[hash-map](#), 176

- [hash-ref](#), 176
- [hash-ref!](#), 177
- [hash-remove!](#), 177
- [hash-set!](#), 177
- [hash-update!](#), 177
- [hash?](#), 177
- Higher-Order Functions, 171
- Higher-Order Functions, 133
- Higher-Order Functions, 100
- How to Design Programs Languages*, 1
- Identifiers, 17
- Identifiers, 79
- [identity](#), 99
- [identity](#), 132
- [identity](#), 68
- [identity](#), 39
- [identity](#), 170
- [if](#), 15
- [if](#), 15
- [if](#), 102
- [if](#), 68
- [if](#), 178
- [if](#), 135
- [imag-part](#), 50
- [imag-part](#), 22
- [imag-part](#), 115
- [imag-part](#), 82
- [imag-part](#), 152
- [image=?](#), 38
- [image=?](#), 168
- [image=?](#), 66
- [image=?](#), 98
- [image=?](#), 130
- [image?](#), 131
- [image?](#), 38
- [image?](#), 168
- [image?](#), 98
- [image?](#), 67
- Images, 168
- Images, 66
- Images, 38
- Images, 130
- Images, 98
- [implode](#), 34
- [implode](#), 94
- [implode](#), 165
- [implode](#), 63
- [implode](#), 127
- [inexact->exact](#), 82
- [inexact->exact](#), 115
- [inexact->exact](#), 51
- [inexact->exact](#), 22
- [inexact->exact](#), 152
- [inexact?](#), 152
- [inexact?](#), 22
- [inexact?](#), 51
- [inexact?](#), 82
- [inexact?](#), 115
- [int->string](#), 94
- [int->string](#), 34
- [int->string](#), 63
- [int->string](#), 165
- [int->string](#), 127
- [integer->char](#), 152
- [integer->char](#), 82
- [integer->char](#), 115
- [integer->char](#), 22
- [integer->char](#), 51
- [integer-sqrt](#), 22
- [integer-sqrt](#), 51
- [integer-sqrt](#), 82
- [integer-sqrt](#), 115
- [integer-sqrt](#), 152
- [integer?](#), 153
- [integer?](#), 51
- [integer?](#), 22
- [integer?](#), 83
- [integer?](#), 115
- Intermediate Student, 70
- Intermediate Student with Lambda, 104
- [lambda](#), 146
- [lambda](#), 111
- [lambda](#), 77
- [lambda](#), 111

lambda, 13	list-ref, 58
lambda, 146	list-ref, 30
lambda, 68	list?, 160
lcm, 153	Lists, 157
lcm, 83	Lists, 55
lcm, 22	Lists, 26
lcm, 115	Lists, 119
lcm, 51	Lists, 87
length, 58	local, 78
length, 122	local, 135
length, 160	local, 178
length, 90	local, 78
length, 29	log, 115
let, 148	log, 22
let, 148	log, 51
let, 78	log, 153
let, 135	log, 83
let*, 78	magnitude, 83
let*, 135	magnitude, 22
let*, 178	magnitude, 115
letrec, 178	magnitude, 153
letrec, 78	magnitude, 51
letrec, 135	make-hash, 177
letrec, let, and let*, 78	make-hasheq, 177
list, 58	make-hasheqv, 177
list, 90	make-list, 30
list, 29	make-list, 59
list, 160	make-list, 90
list, 122	make-list, 123
list*, 160	make-list, 160
list*, 122	make-polar, 51
list*, 58	make-polar, 116
list*, 30	make-polar, 153
list*, 90	make-polar, 83
list->string, 127	make-polar, 23
list->string, 95	make-posn, 31
list->string, 63	make-posn, 92
list->string, 34	make-posn, 162
list->string, 165	make-posn, 124
list-ref, 122	make-posn, 60
list-ref, 160	make-rectangular, 153
list-ref, 90	make-rectangular, 83

make-rectangular , 116	min , 52
make-rectangular , 51	min , 83
make-rectangular , 23	min , 116
make-string , 127	Misc, 168
make-string , 95	Misc, 67
make-string , 35	Misc, 38
make-string , 63	Misc, 131
make-string , 165	Misc, 98
make-vector , 174	modulo , 116
map , 101	modulo , 153
map , 134	modulo , 52
map , 172	modulo , 83
max , 52	modulo , 23
max , 23	negative? , 83
max , 83	negative? , 116
max , 153	negative? , 52
max , 116	negative? , 153
member , 30	negative? , 23
member , 123	newline , 173
member , 160	not , 26
member , 90	not , 156
member , 59	not , 119
member? , 59	not , 55
member? , 160	not , 86
member? , 90	null , 30
member? , 123	null , 161
member? , 30	null , 123
memf , 101	null , 59
memf , 134	null , 91
memf , 173	null? , 161
memq , 123	null? , 91
memq , 161	null? , 123
memq , 59	null? , 59
memq , 30	null? , 30
memq , 90	number->string , 52
memv , 59	number->string , 116
memv , 30	number->string , 154
memv , 90	number->string , 23
memv , 123	number->string , 84
memv , 161	number? , 23
min , 23	number? , 154
min , 153	number? , 52

- [number?](#), 116
- [number?](#), 84
- Numbers (relaxed conditions), 171
- Numbers (relaxed conditions), 132
- Numbers (relaxed conditions), 99
- Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 149
- Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 47
- Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 19
- Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 112
- Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 79
- [numerator](#), 52
- [numerator](#), 154
- [numerator](#), 23
- [numerator](#), 84
- [numerator](#), 116
- [odd?](#), 84
- [odd?](#), 52
- [odd?](#), 116
- [odd?](#), 23
- [odd?](#), 154
- or, 16
- or, 69
- or, 135
- or, 16
- or, 102
- or, 178
- [ormap](#), 101
- [ormap](#), 134
- [ormap](#), 173
- [pair?](#), 59
- [pair?](#), 91
- [pair?](#), 31
- [pair?](#), 161
- [pair?](#), 123
- [pi](#), 84
- [pi](#), 52
- [pi](#), 154
- [pi](#), 24
- [pi](#), 117
- [positive?](#), 24
- [positive?](#), 154
- [positive?](#), 84
- [positive?](#), 52
- [positive?](#), 117
- [posn](#), 162
- [posn](#), 124
- [posn](#), 92
- [posn](#), 32
- [posn](#), 60
- [posn-x](#), 60
- [posn-x](#), 124
- [posn-x](#), 32
- [posn-x](#), 92
- [posn-x](#), 162
- [posn-y](#), 92
- [posn-y](#), 162
- [posn-y](#), 125
- [posn-y](#), 61
- [posn-y](#), 32
- [posn?](#), 61
- [posn?](#), 162
- [posn?](#), 125
- [posn?](#), 32
- [posn?](#), 92
- Posns, 162
- Posns, 60
- Posns, 31
- Posns, 124
- Posns, 92
- [pretty-print](#), 173
- Primitive Calls, 14
- Primitive Operation Names, 112
- Primitive Operations, 149
- Primitive Operations, 47
- Primitive Operations, 19
- Primitive Operations, 79
- [print](#), 173
- [printf](#), 174
- [procedure?](#), 102

[procedure?](#), 134
[procedure?](#), 173
[promise?](#), 170
[Quasiquote](#), 47
[quasiquote](#), 47
[quicksort](#), 173
[quicksort](#), 134
[quicksort](#), 102
[Quote](#), 46
[quote](#), 17
[quote](#), 46
[quotient](#), 117
[quotient](#), 84
[quotient](#), 154
[quotient](#), 24
[quotient](#), 53
[random](#), 24
[random](#), 53
[random](#), 117
[random](#), 84
[random](#), 154
[rational?](#), 84
[rational?](#), 154
[rational?](#), 24
[rational?](#), 117
[rational?](#), 53
[read](#), 174
[Reading and Printing](#), 173
[real-part](#), 155
[real-part](#), 53
[real-part](#), 84
[real-part](#), 117
[real-part](#), 24
[real?](#), 155
[real?](#), 85
[real?](#), 24
[real?](#), 117
[real?](#), 53
[recur](#), 148
[recur](#), 148
[remainder](#), 85
[remainder](#), 24
[remainder](#), 53
[remainder](#), 117
[remainder](#), 155
[remove](#), 91
[remove](#), 31
[remove](#), 59
[remove](#), 161
[remove](#), 123
[replicate](#), 95
[replicate](#), 63
[replicate](#), 165
[replicate](#), 127
[replicate](#), 35
[require](#), 18
[require](#), 18
[require](#), 136
[require](#), 103
[require](#), 69
[require](#), 179
[rest](#), 31
[rest](#), 91
[rest](#), 124
[rest](#), 60
[rest](#), 161
[reverse](#), 91
[reverse](#), 31
[reverse](#), 161
[reverse](#), 124
[reverse](#), 60
[round](#), 53
[round](#), 85
[round](#), 155
[round](#), 24
[round](#), 117
[second](#), 60
[second](#), 91
[second](#), 31
[second](#), 124
[second](#), 161
[set!](#), 147
[set!](#), 147
[set-box!](#), 175

- set-posn-x!, 162
- set-posn-y!, 162
- seventh, 31
- seventh, 124
- seventh, 161
- seventh, 91
- seventh, 60
- sgn, 118
- sgn, 25
- sgn, 155
- sgn, 85
- sgn, 53
- shared, 148
- shared, 148
- sin, 85
- sin, 25
- sin, 53
- sin, 118
- sin, 155
- sinh, 155
- sinh, 54
- sinh, 85
- sinh, 25
- sinh, 118
- sixth, 91
- sixth, 124
- sixth, 31
- sixth, 60
- sixth, 162
- sleep, 170
- sort, 173
- sort, 135
- sort, 102
- sqr, 155
- sqr, 54
- sqr, 25
- sqr, 118
- sqr, 85
- sqrt, 85
- sqrt, 54
- sqrt, 118
- sqrt, 25

- sqrt, 155
- string, 64
- string, 35
- string, 165
- string, 95
- string, 128
- string->int, 64
- string->int, 128
- string->int, 95
- string->int, 35
- string->int, 165
- string->list, 35
- string->list, 95
- string->list, 128
- string->list, 165
- string->list, 64
- string->number, 64
- string->number, 95
- string->number, 166
- string->number, 128
- string->number, 35
- string->symbol, 166
- string->symbol, 35
- string->symbol, 95
- string->symbol, 128
- string->symbol, 64
- string-alphabetic?, 35
- string-alphabetic?, 95
- string-alphabetic?, 64
- string-alphabetic?, 166
- string-alphabetic?, 128
- string-append, 95
- string-append, 166
- string-append, 64
- string-append, 35
- string-append, 128
- string-ci<=?, 35
- string-ci<=?, 128
- string-ci<=?, 166
- string-ci<=?, 64
- string-ci<=?, 96
- string-ci<?, 166

string-ci<?, 128	string-numeric?, 36
string-ci<?, 64	string-numeric?, 167
string-ci<?, 36	string-ref, 65
string-ci<?, 96	string-ref, 167
string-ci=?, 36	string-ref, 129
string-ci=?, 96	string-ref, 97
string-ci=?, 166	string-ref, 36
string-ci=?, 128	string-upper-case?, 97
string-ci=?, 64	string-upper-case?, 65
string-ci>=?, 166	string-upper-case?, 129
string-ci>=?, 96	string-upper-case?, 37
string-ci>=?, 36	string-upper-case?, 167
string-ci>=?, 65	string-whitespace?, 37
string-ci>=?, 129	string-whitespace?, 130
string-ci>?, 65	string-whitespace?, 66
string-ci>?, 96	string-whitespace?, 97
string-ci>?, 129	string-whitespace?, 167
string-ci>?, 166	string<=?, 130
string-ci>?, 36	string<=?, 167
string-copy, 65	string<=?, 37
string-copy, 129	string<=?, 97
string-copy, 36	string<=?, 66
string-copy, 96	string<?, 167
string-copy, 167	string<?, 66
string-ith, 167	string<?, 130
string-ith, 36	string<?, 97
string-ith, 129	string<?, 37
string-ith, 96	string=?, 66
string-ith, 65	string=?, 37
string-length, 167	string=?, 130
string-length, 96	string=?, 168
string-length, 65	string=?, 97
string-length, 129	string>=?, 97
string-length, 36	string>=?, 168
string-lower-case?, 167	string>=?, 66
string-lower-case?, 65	string>=?, 130
string-lower-case?, 96	string>=?, 37
string-lower-case?, 36	string>?, 97
string-lower-case?, 129	string>?, 66
string-numeric?, 97	string>?, 168
string-numeric?, 65	string>?, 130
string-numeric?, 129	string>?, 37

- [string?](#), 97
- [string?](#), 130
- [string?](#), 37
- [string?](#), 66
- [string?](#), 168
- Strings, 165
- Strings, 63
- Strings, 34
- Strings, 127
- Strings, 94
- [struct?](#), 170
- [struct?](#), 68
- [struct?](#), 132
- [struct?](#), 99
- [struct?](#), 39
- [sub1](#), 155
- [sub1](#), 54
- [sub1](#), 85
- [sub1](#), 25
- [sub1](#), 118
- [substring](#), 130
- [substring](#), 66
- [substring](#), 98
- [substring](#), 37
- [substring](#), 168
- [symbol->string](#), 86
- [symbol->string](#), 55
- [symbol->string](#), 119
- [symbol->string](#), 26
- [symbol->string](#), 156
- [symbol=?](#), 156
- [symbol=?](#), 86
- [symbol=?](#), 119
- [symbol=?](#), 55
- [symbol=?](#), 26
- [symbol?](#), 55
- [symbol?](#), 26
- [symbol?](#), 86
- [symbol?](#), 119
- [symbol?](#), 156
- Symbols, 156
- Symbols, 55
- Symbols, 26
- Symbols, 119
- Symbols, 86
- Symbols, 17
- [tan](#), 85
- [tan](#), 54
- [tan](#), 118
- [tan](#), 156
- [tan](#), 25
- Test Cases, 16
- [third](#), 91
- [third](#), 60
- [third](#), 162
- [third](#), 124
- [third](#), 31
- time, 79
- time, 135
- time, 79
- time, 178
- [true](#), 136
- [true](#), 178
- [true](#), 18
- [true](#), 69
- [true](#), 103
- [true](#) and [false](#), 18
- [unbox](#), 175
- Unchanged Forms, 68
- Unchanged Forms, 178
- Unchanged Forms, 135
- Unchanged Forms, 102
- unless, 149
- unquote, 47
- unquote-splicing, 47
- [vector](#), 175
- [vector-length](#), 175
- [vector-ref](#), 175
- [vector-set!](#), 175
- [vector?](#), 175
- Vectors, 174
- [void](#), 170
- [void?](#), 170
- when, 149

- when and unless, 149
- with-input-from-file, 174
- with-input-from-string, 174
- with-output-to-file, 174
- with-output-to-string, 174
- write, 174
- zero?, 86
- zero?, 54
- zero?, 25
- zero?, 118
- zero?, 156
- λ , 146
- λ , 111