

FFI: Racket Foreign Interface

Version 5.1

Eli Barzilay

February 14, 2011

`(require ffi/unsafe)`

The `ffi/unsafe` library enables the direct use of C-based APIs within Racket programs—without writing any new C code. From the Racket perspective, functions and data with a C-based API are *foreign*, hence the term *foreign interface*. Furthermore, since most APIs consist mostly of functions, the foreign interface is sometimes called a *foreign function interface*, abbreviated *FFI*.

Contents

1 Overview	4
2 Loading Foreign Libraries	5
3 C Types	8
3.1 Type Constructors	8
3.2 Numeric Types	9
3.3 Other Atomic Types	10
3.4 String Types	11
3.4.1 Primitive String Types	11
3.4.2 Fixed Auto-Converting String Types	12
3.4.3 Variable Auto-Converting String Type	12
3.4.4 Other String Types	13
3.5 Pointer Types	13
3.6 Function Types	15
3.6.1 Custom Function Types	19
3.7 C Struct Types	22
3.8 Enumerations and Masks	26
4 Pointer Functions	27
4.1 Pointer Dereferencing	28
4.2 Memory Management	31
5 Derived Utilities	35
5.1 Safe Homogenous Vectors	35
5.2 Safe C Vectors	42

5.3	Tagged C Pointer Types	44
5.4	Defining Bindings	45
5.5	Allocation and Finalization	47
5.6	Atomic Execution	48
5.7	Speculatively Atomic Execution	49
5.8	Objective-C FFI	50
5.8.1	FFI Types and Constants	51
5.8.2	Syntactic Forms and Procedures	52
5.8.3	Raw Runtime Functions	55
5.8.4	Legacy Library	59
6	Miscellaneous Support	60
7	Unexported Primitive Functions	63
	Index	65

1 Overview

Although using the FFI requires writing no new C code, it provides very little insulation against the issues that C programmers face related to safety and memory management. An FFI programmer must be particularly aware of memory management issues for data that spans the Racket–C divide. Thus, this manual relies in many ways on the information in *Inside: Racket C API*, which defines how Racket interacts with C APIs in general.

Since using the FFI entails many safety concerns that Racket programmers can normally ignore, the library name includes `unsafe`. Importing the library macro should be considered as a declaration that your code is itself unsafe, therefore can lead to serious problems in case of bugs: it is your responsibility to provide a safe interface. If your library provides an unsafe interface, then it should have `unsafe` in its name, too.

For examples of common FFI usage patterns, see the defined interfaces in the "ffi" collection.

2 Loading Foreign Libraries

The FFI is normally used by extracting functions and other objects from shared objects (a.k.a. *shared libraries* or *dynamically loaded libraries*). The `ffi-lib` function loads a shared object.

```
(ffi-lib? v) → boolean?  
  v : any/c
```

Returns `#t` if `v` is the result of `ffi-lib`, `#f` otherwise.

```
(ffi-lib path [version]) → any  
  path : (or/c path-string? #f)  
  version : (or/c string? (listof (or/c string? #f)) #f) = #f
```

Returns a foreign-library value. If `path` is a path, the result represents the foreign library, which is opened in an OS-specific way (using `LoadLibrary` under Windows, and `dlopen` under Unix and Mac OS X).

The path is not expected to contain the library suffix, which is added according to the current platform. If adding the suffix fails, several other filename variations are tried: retrying without an automatically added suffix, and using a full path of a file if it exists relative to the current directory (since the OS-level library function usually searches, unless the library name is an absolute path). An optional `version` string can be supplied, which is appended to the name before or after the suffix, depending on platform conventions, unless it is `#f` or `""`. If `version` is a list, `ffi-lib` will try each of them in order.

If `path` is `#f`, then the resulting foreign-library value represents all libraries loaded in the current process, including libraries previously opened with `ffi-lib`. In particular, use `#f` to access C-level functionality exported by the run-time system (as described in *Inside: Racket C API*).

Note: `ffi-lib` tries to look for the library file in a few places, including the Racket libraries path (see `get-lib-search-dirs`), a relative path, or a system search. When `version` is a list, different versions are tried through each route before continuing the search with other routes. However, if `dlopen` cannot open a library, there is no reliable way to know why it failed, so if all path combinations fail, it will raise an error with the result of `dlopen` on the unmodified argument name. For example, if you have a local `"foo.so"` library that cannot be loaded because of a missing symbol, using `(ffi-lib "foo.so")` will fail with all its search options, most because the library is not found, and once because of the missing symbol, and eventually produce an error message that comes from `dlopen("foo.so")` which will look like the file is not found. In such cases try to specify a full or relative path (containing slashes, e.g., `"/foo.so"`).

Note! Because of the way the operating system performs dynamic binding, loaded libraries are associated with Racket or DrRacket for the duration of the process; re-evaluating `ffi-lib` and/or hitting the "Run" button will not force a re-load of the corresponding library.

```
(get-ffi-obj objname lib type [failure-thunk]) → any
  objname : (or/c string? bytes? symbol?)
  lib : (or/c ffi-lib? path-string? #f)
  type : ctype?
  failure-thunk : (or/c (-> any) #f) = #f
```

Looks for the given object name `objname` in the given `lib` library. If `lib` is not a foreign-library value produced by `ffi-lib`, it is converted to one by calling `ffi-lib`. If `objname` is found in `lib`, it is converted to Racket using the given `type`. Types are described in §3 “C Types”; in particular the `get-ffi-obj` procedure is most often used with function types created with `_fun`.

Keep in mind that `get-ffi-obj` is an unsafe procedure; see §1 “Overview” for details.

If the object is not found, and `failure-thunk` is provided, it is used to produce a return value. For example, a failure thunk can be provided to report a specific error if an object is not found:

```
(define foo
  (get-ffi-obj "foo" foolib (_fun _int -> _int)
    (lambda ()
      (error 'foolib
        "installed foolib does not provide \"foo\"")))))
```

The default (also when `failure-thunk` is provided as `#f`) is to raise an exception.

```
(set-ffi-obj! objname lib type new) → void?
  objname : (or/c string? bytes? symbol?)
  lib : (or/c ffi-lib? path-string? #f)
  type : ctype?
  new : any/c
```

Looks for `objname` in `lib` similarly to `get-ffi-obj`, but then it stores the given `new` value into the library, converting it to a C value. This can be used for setting library customization variables that are part of its interface, including Racket callbacks.

```
(make-c-parameter objname lib type) → (and/c (-> any)
                                             (any/c -> void?))
  objname : (or/c string? bytes? symbol?)
  lib : (or/c ffi-lib? path-string? #f)
```

`type : ctype?`

Returns a parameter-like procedure that can either references the specified foreign value, or set it. The arguments are handled as in `get-ffi-obj`.

A parameter-like function is useful in case Racket code and library code interact through a library value. Although `make-c-parameter` can be used with any time, it is not recommended to use this for foreign functions, since each reference through the parameter will construct the low-level interface before the actual call.

```
(define-c id lib-expr type-expr)
```

Defines `id` behave like a Racket binding, but `id` is actually redirected through a parameter-like procedure created by `make-c-parameter`. The `id` is used both for the Racket binding and for the foreign object's name.

```
(ffi-obj-ref objname lib [failure-thunk]) → any  
  objname : (or/c string? bytes? symbol?)  
  lib : (or/c ffi-lib? path-string? #f)  
  failure-thunk : (or/c (-> any) #f) = #f
```

Returns a pointer object for the specified foreign object. This procedure is for rare cases where `make-c-parameter` is insufficient, because there is no type to cast the foreign object to (e.g., a vector of numbers).

3 C Types

C *types* are the main concept of the FFI, either primitive types or user-defined types. The FFI deals with primitive types internally, converting them to and from C types. A user type is defined in terms of existing primitive and user types, along with conversion functions to and from the existing types.

3.1 Type Constructors

```
(make-ctype type scheme-to-c c-to-scheme) → ctype?  
  type : ctype?  
  scheme-to-c : (or/c #f (any/c . -> . any))  
  c-to-scheme : (or/c #f (any/c . -> . any))
```

Creates a new C type value whose representation for foreign code is the same as *type*'s. The given conversions functions convert to and from the Racket representation of *type*. Either conversion function can be *#f*, meaning that the conversion for the corresponding direction is the identity function. If both functions are *#f*, *type* is returned.

```
(ctype? v) → boolean?  
  v : any/c
```

Returns *#t* if *v* is a C type, *#f* otherwise.

```
(ctype-sizeof type) → exact-nonnegative-integer?  
  type : ctype?  
(ctype-alignof type) → exact-nonnegative-integer?  
  type : ctype?
```

Returns the size or alignment of a given *type* for the current platform.

```
(ctype->layout type)  
→ (flat-rec-contract rep symbol? (listof rep))  
  type : ctype?
```

Returns a value to describe the eventual C representation of the type. It can be any of the following symbols:

```
'int8 'uint8 'int16 'uint16 'int32 'uint32 'int64 'uint64  
'float 'double 'bool 'void 'pointer 'fpointer  
'bytes 'string/ucs-4 'string/utf-16
```


The result can also be a list, which describes a C struct whose element representations are provided in order within the list.

```
(compiler-sizeof sym) → exact-nonnegative-integer?  
  sym : symbol?
```

Possible values for `symbol` are `'int`, `'char`, `'short`, `'long`, `'*`, `'void`, `'float`, `'double`. The result is the size of the correspond type according to the C `sizeof` operator for the current platform. The `compiler-sizeof` operation should be used to gather information about the current platform, such as defining alias type like `_int` to a known type like `_int32`.

3.2 Numeric Types

```
_int8 : ctype?  
_sint8 : ctype?  
_uint8 : ctype?  
_int16 : ctype?  
_sint16 : ctype?  
_uint16 : ctype?  
_int32 : ctype?  
_sint32 : ctype?  
_uint32 : ctype?  
_int64 : ctype?  
_sint64 : ctype?  
_uint64 : ctype?
```

The basic integer types at various sizes. The `s` or `u` prefix specifies a signed or an unsigned integer, respectively; the ones with no prefix are signed.

```
_byte : ctype?  
_sbyte : ctype?  
_ubyte : ctype?  
_short : ctype?  
_sshort : ctype?  
_ushort : ctype?  
_int : ctype?  
_sint : ctype?  
_uint : ctype?  
_word : ctype?  
_sword : ctype?  
_uword : ctype?
```

```
_long : ctype?  
_slong : ctype?  
_ulong : ctype?  
_llong : ctype?  
_sllong : ctype?  
_ullong : ctype?  
_intptr : ctype?  
_sintptr : ctype?  
_uintptr : ctype?
```

Aliases for basic integer types. The `_byte` aliases correspond to `_int8`. The `_short` and `_word` aliases correspond to `_int16`. The `_int` aliases correspond to `_int32`. The `_long` aliases correspond to either `_int32` or `_int64`, depending on the platform. Similarly, the `_intptr` aliases correspond to either `_int32` or `_int64`, depending on the platform.

```
_fixnum : ctype?  
_ufixnum : ctype?
```

For cases where speed matters and where you know that the integer is small enough, the types `_fixnum` and `_ufixnum` are similar to `_intptr` and `_uintptr` but assume that the quantities fit in Racket's immediate integers (i.e., not bignums).

```
_fixint : ctype?  
_ufixint : ctype?
```

Similar to `_fixnum/_ufixnum`, but based on `_int/_uint` instead of `_intptr/_uintptr`, and coercions from C are checked to be in range.

```
_float : ctype?  
_double : ctype?  
_double* : ctype?
```

The `_float` and `_double` types represent the corresponding C types. The type `_double*` that implicitly coerces any real number to a C double.

3.3 Other Atomic Types

```
_bool : ctype?
```

Translates `#f` to a 0 `_int`, and any other value to 1.

`_void` : `ctype?`

Indicates a Racket #<void> return value, and it cannot be used to translate values to C. This type cannot be used for function inputs.

3.4 String Types

3.4.1 Primitive String Types

The five primitive string types correspond to cases where a C representation matches Racket's representation without encodings.

The form `_bytes` form can be used type for Racket byte strings, which corresponds to C's `char*` type. In addition to translating byte strings, `#f` corresponds to the NULL pointer.

`_string/ucs-4` : `ctype?`

A type for Racket's native Unicode strings, which are in UCS-4 format. These correspond to the C `mzchar*` type used by Racket. As usual, the types treat `#f` as NULL and vice versa.

`_string/utf-16` : `ctype?`

Unicode strings in UTF-16 format. As usual, the types treat `#f` as NULL and vice versa.

`_path` : `ctype?`

Simple `char*` strings, corresponding to Racket's paths. As usual, the types treat `#f` as NULL and vice versa.

Beware that changing the current directory via `current-directory` does not change the OS-level current directory as seen by foreign library functions. Paths normally should be converted to absolute form using `path->complete-path` (which uses the `current-directory` parameter) before passing them to a foreign function.

`_symbol` : `ctype?`

Simple `char*` strings as Racket symbols (encoded in UTF-8). Return values using this type are interned as symbols.

3.4.2 Fixed Auto-Converting String Types

```
_string/utf-8 : ctype?  
_string/latin-1 : ctype?  
_string/locale : ctype?
```

Types that correspond to (character) strings on the Racket side and `char*` strings on the C side. The bridge between the two requires a transformation on the content of the string. As usual, the types treat `#f` as NULL and vice versa.

```
_string*/utf-8 : ctype?  
_string*/latin-1 : ctype?  
_string*/locale : ctype?
```

Similar to `_string/utf-8`, etc., but accepting a wider range of values: Racket byte strings are allowed and passed as is, and Racket paths are converted using `path->bytes`.

3.4.3 Variable Auto-Converting String Type

The `_string/ucs-4` type is rarely useful when interacting with foreign code, while using `_bytes` is somewhat unnatural, since it forces Racket programmers to use byte strings. Using `_string/utf-8`, etc., meanwhile, may prematurely commit to a particular encoding of strings as bytes. The `_string` type supports conversion between Racket strings and `char*` strings using a parameter-determined conversion.

```
_string : ctype?
```

Expands to a use of the `default-_string-type` parameter. The parameter's value is consulted when `_string` is evaluated, so the parameter should be set before any interface definition that uses `_string`.

```
(default-_string-type) → ctype?  
(default-_string-type type) → void?  
  type : ctype?
```

A parameter that determines the current meaning of `_string`. It is initially set to `_string*/utf-8`. If you change it, do so *before* interfaces are defined.

3.4.4 Other String Types

`_file` : `ctype?`

Like `_path`, but when values go from Racket to C, `cleanse-path` is used on the given value. As an output value, it is identical to `_path`.

`_bytes/eof` : `ctype?`

Similar to the `_bytes` type, except that a foreign return value of NULL is translated to a Racket `eof` value.

`_string/eof` : `ctype?`

Similar to the `_string` type, except that a foreign return value of NULL is translated to a Racket `eof` value.

3.5 Pointer Types

`_pointer` : `ctype?`

Corresponds to Racket “C pointer” objects. These pointers can have an arbitrary Racket object attached as a type tag. The tag is ignored by built-in functionality; it is intended to be used by interfaces. See §5.3 “Tagged C Pointer Types” for creating pointer types that use these tags for safety. A `#f` value is converted to NULL and vice versa.

The address referenced by a `_pointer` value must not refer to memory managed by the garbage collector (unless the address corresponds to a value that supports interior pointers and that is otherwise referenced to preserve the value from garbage collection). The reference is not traced or updated by the garbage collector.

The `equal?` predicate equates C pointers (including pointers for `_gcpointer` and possibly containing an offset) when they refer to the same address.

`_gcpointer` : `ctype?`

Like `_pointer`, but for a value that can refer to memory managed by the garbage collector.

Although a `_gcpointer` can reference to memory that is not managed by the garbage collector, beware of using an address that might eventually become managed by the garbage collector. For example, if a reference is created by `malloc` with `'raw` and released by `free`,

then the `free` may allow the memory formerly occupied by the reference to be used later by the garbage collector.

```
_racket : ctype?  
_scheme : ctype?
```

A type that can be used with any Racket object; it corresponds to the `Scheme_Object*` type of Racket's C API (see *Inside: Racket C API*). It is useful only for libraries that are aware of Racket's C API.

```
_fpointer : ctype?
```

Similar to `_pointer`, except that when an `_fpointer` is extracted from a pointer produced by `ffi-obj-ref`, then a level of indirection is skipped. A level of indirection is similarly skipped when extracting a pointer via `get-ffi-obj`. Like `_pointer`, `_fpointer` treats `#f` as `NULL` and vice versa.

A type generated by `_cprocedure` builds on `_fpointer`, and normally `_cprocedure` should be used instead of `_fpointer`.

```
(_or-null ctype) → ctype?  
  ctype : ctype?
```

Creates a type that is like `ctype`, but `#f` is converted to `NULL` and vice versa. The given `ctype` must have the same C representation as `_pointer`, `_gcpointer`, or `_fpointer`.

```
(_gcable ctype) → ctype?  
  ctype : ctype?
```

Creates a type that is like `ctype`, but whose base representation is like `_gcpointer` instead of `_pointer`. The given `ctype` must have a base representation like `_pointer` or `_gcpointer` (and in the later case, the result is the `ctype`).

3.6 Function Types

```
(_cprocedure input-types
             output-type
             [#:abi abi
             #:atomic? atomic?
             #:async-apply async-apply
             #:save-errno save-errno
             #:wrapper wrapper
             #:keep keep])          → any
input-types : (list ctype?)
output-type : ctype?
abi : (or/c #f 'default 'stdcall 'sysv) = #f
atomic? : any/c = #f
async-apply : (or/c #f ((-> any) . -> . any)) = #f
save-errno : (or/c #f 'posix 'windows) = #f
wrapper : (or/c #f (procedure? . -> . procedure?)) = #f
keep : (or/c boolean? box? (any/c . -> . any/c)) = #t
```

A type constructor that creates a new function type, which is specified by the given *input-types* list and *output-type*. Usually, the `_fun` syntax (described below) should be used instead, since it manages a wide range of complicated cases.

The resulting type can be used to reference foreign functions (usually *ffi-objs*, but any pointer object can be referenced with this type), generating a matching foreign callout object. Such objects are new primitive procedure objects that can be used like any other Racket procedure. As with other pointer types, `#f` is treated as a NULL function pointer and vice versa.

A type created with `_cprocedure` can also be used for passing Racket procedures to foreign functions, which will generate a foreign function pointer that calls the given Racket procedure when it is used. There are no restrictions on the Racket procedure; in particular, its lexical context is properly preserved.

The optional *abi* keyword argument determines the foreign ABI that is used. Supplying `#f` or `'default` indicates the platform-dependent default. The other possible values—`'stdcall` and `'sysv` (i.e., “cdecl”)—are currently supported only for 32-bit Windows; using them on other platforms raises an exception.

If *atomic?* is true, then when a Racket procedure is given this procedure type and called from foreign code, then the Racket process is put into atomic mode while evaluating the Racket procedure body. In atomic mode, other Racket threads do not run, so the Racket code must not call any function that potentially blocks on synchronization with other threads, or else it may lead to deadlock. In addition, the Racket code must not perform any potentially blocking operation (such as I/O), it must not raise an uncaught exception, it must not perform

any escaping continuation jumps, and its non-tail recursion must be minimal to avoid C-level stack overflow; otherwise, the process may crash or misbehave.

If an *async-apply* procedure is provided, then a Racket procedure with the generated procedure type can be applied in a foreign thread (i.e., an OS-level thread other than the one used to run Racket). The call in the foreign thread is transferred to the OS-level thread that runs Racket, but the Racket-level thread (in the sense of *thread*) is unspecified; the job of the provided *async-apply* procedure is to arrange for the callback procedure to be run in a suitable Racket thread. The given *async-apply* procedure is applied to a thunk that encapsulates the specific callback invocation, and the foreign OS-level thread blocks until the thunk is called and completes; the thunk must be called exactly once, and the callback invocation must return normally. The given *async-apply* procedure itself is called in atomic mode (see *atomic?* above). If the callback is known to complete quickly, requires no synchronization, and works independent of the Racket thread in which it runs, then it is safe for the given *async-apply* procedure to apply the thunk directly. Otherwise, the given *async-apply* procedure must arrange for the thunk to be applied in a suitable Racket thread sometime after the given *async-apply* procedure itself returns; if the thunk raises an exception or synchronizes within an unsuitable Racket-level thread, it can deadlock or otherwise damage the Racket process. Foreign-thread detection to trigger *async-apply* works only when Racket is compiled with OS-level thread support, which is the default for many platforms. If a callback with an *async-apply* is called from foreign code in the same OS-level thread that runs Racket, then the *async-apply* wrapper is not used.

If *save-errno* is *'posix*, then the value of *errno* is saved (specific to the current thread) immediately after a foreign function returns. The saved value is accessible through *saved-errno*. If *save-errno* is *'windows*, then the value of *GetLastError()* is saved for later use via *saved-errno*; the *'windows* option is available only under Windows (on other platforms *saved-errno* will return 0). If *save-errno* is *#f*, no error value is saved automatically. The error-recording support provided by *save-errno* is needed because the Racket runtime system may otherwise preempt the current Racket thread and itself call functions that set error values.

The optional *wrapper*, if provided, is expected to be a function that can change a callout procedure: when a callout is generated, the wrapper is applied on the newly created primitive procedure, and its result is used as the new function. Thus, *wrapper* is a hook that can perform various argument manipulations before the foreign function is invoked, and return different results (for example, grabbing a value stored in an “output” pointer and returning multiple values). It can also be used for callbacks, as an additional layer that tweaks arguments from the foreign code before they reach the Racket procedure, and possibly changes the result values too.

Sending Racket functions as callbacks to foreign code is achieved by translating them to a foreign “closure,” which foreign code can call as plain C functions. Additional care must be taken in case the foreign code might hold on to the callback function. In these cases you must arrange for the callback value to not be garbage-collected, or the held callback will become invalid. The optional *keep* keyword argument is used to achieve this. It can have

the following values:

- `#t` makes the callback value stay in memory as long as the converted function is. In order to use this, you need to hold on to the original function, for example, have a binding for it. Note that each function can hold onto one callback value (it is stored in a weak hash table), so if you need to use a function in multiple callbacks you will need to use one of the last two options below. (This is the default, as it is fine in most cases.)
- `#f` means that the callback value is not held. This may be useful for a callback that is only used for the duration of the foreign call — for example, the comparison function argument to the standard C library `qsort` function is only used while `qsort` is working, and no additional references to the comparison function are kept. Use this option only in such cases, when no holding is necessary and you want to avoid the extra cost.
- A box holding `#f` (or a callback value) — in this case the callback value will be stored in the box, overriding any value that was in the box (making it useful for holding a single callback value). When you know that it is no longer needed, you can “release” the callback value by changing the box contents, or by allowing the box itself to be garbage-collected. This is can be useful if the box is held for a dynamic extent that corresponds to when the callback is needed; for example, you might encapsulate some foreign functionality in a Racket class or a unit, and keep the callback box as a field in new instances or instantiations of the unit.
- A box holding `null` (or any list) – this is similar to the previous case, except that new callback values are consed onto the contents of the box. It is therefore useful in (rare) cases when a Racket function is used in multiple callbacks (that is, sent to foreign code to hold onto multiple times).
- Finally, if a one-argument function is provided as `keep`, it will be invoked with the callback value when it is generated. This allows you to grab the value directly and use it in any way.

```
(_fun fun-option ... maybe-args type-spec ... -> type-spec  
  maybe-wrapper)
```

```

fun-option = #:abi abi-expr
             | #:save-errno save-errno-expr
             | #:keep keep-expr
             | #:atomic? atomic?-expr
             | #:async-apply async-apply-expr

maybe-args =
             | (id ...) ::
             | id ::
             | (id ... . id) ::

type-spec = type-expr
             | (id : type-expr)
             | (type-expr = value-expr)
             | (id : type-expr = value-expr)

maybe-wrapper =
             | -> output-expr

```

Creates a new function type. The `_fun` form is a convenient syntax for the `_cprocedure` type constructor. In its simplest form, only the input *type-exprs* and the output *type-expr* are specified, and each types is a simple expression, which creates a straightforward function type.

For instance,

```
(_fun _int _string -> _int)
```

specifies a function that receives an integer and a string, and returns an integer.

In its full form, the `_fun` syntax provides an IDL-like language that can be used to create a wrapper function around the primitive foreign function. These wrappers can implement complex foreign interfaces given simple specifications. The full form of each of the type specifications can include an optional label and an expression. If a `= value-expr` is provided, then the resulting function will be a wrapper that calculates the argument for that position itself, meaning that it does not expect an argument for that position. The expression can use previous arguments if they were labeled with `id` `:`. In addition, the result of a function call need not be the value returned from the foreign call: if the optional *output-expr* is specified, or if an expression is provided for the output type, then this specifies an expression that will be used as a return value. This expression can use any of the previous labels, including a label given for the output which can be used to access the actual foreign return value.

In rare cases where complete control over the input arguments is needed, the wrapper's argument list can be specified as *args*, in any form (including a "rest" argument). Identifiers in this place are related to type labels, so if an argument is there is no need to use an expression.

For example,

```
(_fun (n s) :: (s : _string) (n : _int) -> _int)
```

specifies a function that receives an integer and a string, but the foreign function receives the string first.

```
(function-ptr ptr-or-proc fun-type) → cpointer?  
ptr-or-proc : (or cpointer? procedure?)  
fun-type : ctype?
```

Casts *ptr-or-proc* to a function pointer of type *fun-type*.

3.6.1 Custom Function Types

The behavior of the `_fun` type can be customized via *custom function types*, which are pieces of syntax that can behave as C types and C type constructors, but they can interact with function calls in several ways that are not possible otherwise. When the `_fun` form is expanded, it tries to expand each of the given type expressions, and ones that expand to certain keyword-value lists interact with the generation of the foreign function wrapper. This expansion makes it possible to construct a single wrapper function, avoiding the costs involved in compositions of higher-order functions.

Custom function types are macros that expand to a sequence (`key: val ...`), where each `key`: is from a short list of known keys. Each key interacts with generated wrapper functions in a different way, which affects how its corresponding argument is treated:

- `type`: specifies the foreign type that should be used, if it is `#f` then this argument does not participate in the foreign call.
- `expr`: specifies an expression to be used for arguments of this type, removing it from wrapper arguments.
- `bind`: specifies a name that is bound to the original argument if it is required later (e.g., `_box` converts its associated value to a C pointer, and later needs to refer back to the original box).
- `1st-arg`: specifies a name that can be used to refer to the first argument of the foreign call (good for common cases where the first argument has a special meaning, e.g., for method calls).
- `prev-arg`: similar to `1st-arg`:, but refers to the previous argument.
- `pre`: a pre-foreign code chunk that is used to change the argument's value.
- `post`: a similar post-foreign code chunk.

- `keywords`: specifies keyword/value expressions that will be used with the surrounding `_fun` form. (Note: the keyword/value sequence follows `keywords:`, not parenthesized.)

The `pre:` and `post:` bindings can be of the form `(id => expr)` to use the existing value. Note that if the `pre:` expression is not `(id => expr)`, then it means that there is no input for this argument to the `_fun`-generated procedure. Also note that if a custom type is used as an output type of a function, then only the `post:` code is used.

Most custom types are meaningful only in a `_fun` context, and will raise a syntax error if used elsewhere. A few such types can be used in non-`_fun` contexts: types which use only `type:`, `pre:`, `post:`, and no others. Such custom types can be used outside a `_fun` by expanding them into a usage of `make-ctype`, using other keywords makes this impossible, because it means that the type has specific interaction with a function call.

```
(define-fun-syntax id transformer-expr)
```

Binds `id` as a custom function type. The type is expanded by applying the procedure produced by `transformer-expr` to a use of the custom function type.

```
_?
```

A custom function type that is a marker for expressions that should not be sent to the foreign function. Use this to bind local values in a computation that is part of an ffi wrapper interface, or to specify wrapper arguments that are not sent to the foreign function (e.g., an argument that is used for processing the foreign output).

```
(_ptr mode type-expr)
```

```
mode = i
      | o
      | io
```

Creates a C pointer type, where `mode` indicates input or output pointers (or both). The `mode` can be one of the following:

- `i` — indicates an *input* pointer argument: the wrapper arranges for the function call to receive a value that can be used with the `type` and to send a pointer to this value to the foreign function. After the call, the value is discarded.
- `o` — indicates an *output* pointer argument: the foreign function expects a pointer to a place where it will save some value, and this value is accessible after the call, to be used by an extra return expression. If `_ptr` is used in this mode, then the generated wrapper does not expect an argument since one will be freshly allocated before the

call.

- `io` — combines the above into an *input/output* pointer argument: the wrapper gets the Racket value, allocates and set a pointer using this value, and then references the value after the call. The “`_ptr`” name can be confusing here: it means that the foreign function expects a pointer, but the generated wrapper uses an actual value. (Note that if this is used with structs, a struct is created when calling the function, and a copy of the return value is made too—which is inefficient, but ensures that structs are not modified by C code.)

For example, the `_ptr` type can be used in output mode to create a foreign function wrapper that returns more than a single argument. The following type:

```
(_fun (i : (_ptr o _int))
      -> (d : _double)
      -> (values d i))
```

creates a function that calls the foreign function with a fresh integer pointer, and use the value that is placed there as a second return value.

`_box`

A custom function type similar to a `(_ptr io type)` argument, where the input is expected to be a box holding an appropriate value, which is unboxed on entry and modified accordingly on exit.

```
(_list mode type maybe-len)
```

```
mode = i
      | o
      | io
```

```
maybe-len =
            | len-expr
```

A custom function type that is similar to `_ptr`, except that it is used for converting lists to/from C vectors. The optional `maybe-len` argument is needed for output values where it is used in the post code, and in the pre code of an output mode to allocate the block. In either case, it can refer to a previous binding for the length of the list which the C function will most likely require.

```
(_vector mode type maybe-len)
```

A custom function type like `_list`, except that it uses Racket vectors instead of lists.

```
(_bytes o len-expr)
_bytes
```

A custom function type that can be used by itself as a simple type for a byte string as a C pointer. Alternatively, the second form is for a pointer return value, where the size should be explicitly specified.

There is no need for other modes: input or input/output would be just like `_bytes`, since the string carries its size information (there is no real need for the `o` part of the syntax, but it is present for consistency with the above macros).

3.7 C Struct Types

```
(make-cstruct-type types [abi alignment]) → ctype?
  types : (listof ctype?)
  abi : (or/c #f 'default 'stdcall 'sysv) = #f
  alignment : (or/c #f 1 2 4 8 16) = #f
```

The primitive type constructor for creating new C struct types. These types are actually new primitive types; they have no conversion functions associated. The corresponding Racket objects that are used for structs are pointers, but when these types are used, the value that the pointer *refers to* is used, rather than the pointer itself. This value is basically made of a number of bytes that is known according to the given list of `types` list.

If `alignment` is `#f`, then the natural alignment of each type in `types` is used for its alignment within the struct type. Otherwise, `alignment` is used for all struct type members.

```
(_list-struct [#:alignment alignment]
  type ...+) → ctype?
  alignment : (or/c #f 1 2 4 8 16) = #f
  type : ctype?
```

A type constructor that builds a struct type using `make-cstruct-type` function and wraps it in a type that marshals a struct as a list of its components. Note that space for structs must be allocated; the converter for a `_list-struct` type immediately allocates and uses a list from the allocated space, so it is inefficient. Use `define-cstruct` below for a more efficient approach.

```
(define-cstruct id/sup ([field-id type-expr] ...) alignment)
```

```

id/sup = _id
        | (_id super-id)

alignment =
          | #:alignment alignment-expr

```

Defines a new C struct type, but unlike `_list-struct`, the resulting type deals with C structs in binary form, rather than marshaling them to Racket values. The syntax is similar to `define-struct`, providing accessor functions for raw struct values (which are pointer objects). The new type uses pointer tags to guarantee that only proper struct objects are used. The `_id` must start with `_`.

The resulting bindings are as follows:

- `_id` : the new C type for this struct.
- `_id-pointer`: a pointer type that should be used when a pointer to values of this struct are used.
- `id?`: a predicate for the new type.
- `id-tag`: the tag string object that is used with instances.
- `make-id` : a constructor, which expects an argument for each type.
- `id-field-id` : an accessor function for each `field-id`; if the field has a cstruct type, then the result of the accessor is a pointer to the field within the enclosing structure, rather than a copy of the field.
- `set-id-field-id!` : a mutator function for each `field-id`.
- `id`: structure-type information compatible with `struct-out` or `match` (but not `define-struct`); currently, this information is correct only when no `super-id` is specified.

Objects of the new type are actually C pointers, with a type tag that is a list that contains the string form of `id`. Since structs are implemented as pointers, they can be used for a `_pointer` input to a foreign function: their address will be used. To make this a little safer, the corresponding cpointer type is defined as `_id-pointer`. The `_id` type should not be used when a pointer is expected, since it will cause the struct to be copied rather than use the pointer value, leading to memory corruption.

If the first field is itself a cstruct type, its tag will be used in addition to the new tag. This feature supports common cases of object inheritance, where a sub-struct is made by having a first field that is its super-struct. Instances of the sub-struct can be considered as instances of the super-struct, since they share the same initial layout. Using the tag of an initial cstruct field means that the same behavior is implemented in Racket; for example, accessors and mutators of the super-cstruct can be used with the new sub-cstruct. See the example below.

Providing a *super-id* is shorthand for using an initial field named *super-id* and using *_super-id* as its type. Thus, the new struct will use *_super-id*'s tag in addition to its own tag, meaning that instances of *_id* can be used as instances of *_super-id*. Aside from the syntactic sugar, the constructor function is different when this syntax is used: instead of expecting a first argument that is an instance of *_super-id*, the constructor will expect arguments for each of *_super-id*'s fields, in addition for the new fields. This adjustment of the constructor is, again, in analogy to using a supertype with `define-struct`.

Note that structs are allocated as atomic blocks, which means that the garbage collector ignores their content. Thus, struct fields can hold only non-pointer values, pointers to memory outside the GC's control, and otherwise-reachable pointers to immobile GC-managed values (such as those allocated with `malloc` and `'internal` or `'internal-atomic`).

As an example, consider the following C code:

```
typedef struct { int x; char y; } A;
typedef struct { A a; int z; } B;

A* makeA() {
  A *p = malloc(sizeof(A));
  p->x = 1;
  p->y = 2;
  return p;
}

B* makeB() {
  B *p = malloc(sizeof(B));
  p->a.x = 1;
  p->a.y = 2;
  p->z = 3;
  return p;
}

char gety(A* a) {
  return a->y;
}
```

Using the simple `_list-struct`, you might expect this code to work:

```
(define makeB
  (get-ffi-obj 'makeB "foo.so"
    (_fun -> (_list-struct (_list-struct _int _byte) _int))))
(makeB) ; should return '((1 2) 3)
```

The problem here is that `makeB` returns a pointer to the struct rather than the struct itself. The following works as expected:


```
(define makeB
  (get-ffi-obj 'makeB "foo.so" (_fun -> _pointer)))
(ptr-ref (makeB) (_list-struct (_list-struct _int _byte) _int))
```

As described above, `_list-structs` should be used in cases where efficiency is not an issue. We continue using `define-cstruct`, first define a type for A which makes it possible to use `makeA`:

```
(define-cstruct _A ([x _int] [y _byte]))
(define makeA
  (get-ffi-obj 'makeA "foo.so"
    (_fun -> _A-pointer))) ; using _A is a memory-corrupting bug!
(define a (makeA))
(list a (A-x a) (A-y a))
; produces an A containing 1 and 2
```

Using `gety` is also simple:

```
(define gety
  (get-ffi-obj 'gety "foo.so"
    (_fun _A-pointer -> _byte)))
(gety a) ; produces 2
```

We now define another C struct for B, and expose `makeB` using it:

```
(define-cstruct _B ([a _A] [z _int]))
(define makeB
  (get-ffi-obj 'makeB "foo.so"
    (_fun -> _B-pointer)))
(define b (makeB))
```

We can access all values of `b` using a naive approach:

```
(list (A-x (B-a b)) (A-y (B-a b)) (B-z b))
```

but this is inefficient as it allocates and copies an instance of A on every access. Inspecting the tags (`cpointer-tag b`) we can see that A's tag is included, so we can simply use its accessors and mutators, as well as any function that is defined to take an A pointer:

```
(list (A-x b) (A-y b) (B-z b))
(gety b)
```

Constructing a B instance in Racket requires allocating a temporary A struct:

```
(define b (make-B (make-A 1 2) 3))
```

To make this more efficient, we switch to the alternative `define-cstruct` syntax, which creates a constructor that expects arguments for both the super fields and the new ones:

```
(define-cstruct (_B _A) ([z _int]))
(define b (make-B 1 2 3))
```

3.8 Enumerations and Masks

Although the constructors below are described as procedures, they are implemented as syntax, so that error messages can report a type name where the syntactic context implies one.

```
(_enum symbols [basetype #:unknown unknown]) → ctype?
  symbols : list?
  basetype : ctype? = _ufixint
  unknown : any/c = (lambda (x) (error ...))
```

Takes a list of symbols and generates an enumeration type. The enumeration maps between a symbol in the given *symbols* list and corresponding integers, counting from 0.

The list *symbols* can also set the values of symbols by putting '=' and an exact integer after the symbol. For example, the list '(x y = 10 z) maps 'x to 0, 'y to 10, and 'z to 11.

The *basetype* argument specifies the base type to use.

The *unknown* argument specifies the result of converting an unknown integer from the foreign side: it can be a one-argument function to be applied on the integer, or a value to return instead. The default is to throw an exception.

```
(_bitmask symbols [basetype]) → ctype?
  symbols : (or symbol? list?)
  basetype : ctype? = _uint
```

Similar to `_enum`, but the resulting mapping translates a list of symbols to a number and back, using `bitwise-ior`. A single symbol is equivalent to a list containing just the symbol. The default *basetype* is `_uint`, since high bits are often used for flags.

4 Pointer Functions

```
(cpointer? v) → boolean?  
  v : any/c
```

Returns `#t` if `v` is a C pointer or a value that can be used as a pointer: `#f` (used as a NULL pointer), byte strings (used as memory blocks), or some additional internal objects (`ffi-obj`s and callbacks, see §7 “Unexported Primitive Functions”). Returns `#f` for other values.

```
(ptr-equal? cptr1 cptr2) → boolean?  
  cptr1 : cpointer?  
  cptr2 : cpointer?
```

Compares the values of the two pointers. Two different Racket pointer objects can contain the same pointer.

If the values are both C pointers—as opposed to `#f`, a byte string, `ffi-obj`, or callback—this comparison is the same as `equal?`.

```
(ptr-add cptr offset [type]) → cpointer?  
  cptr : cpointer?  
  offset : exact-integer?  
  type : ctype? = _byte
```

Returns a pointer that is like `cptr` offset by `offset` instances of `ctype`.

The resulting cpointer keeps the base pointer and offset separate. The two pieces are combined at the last minute before any operation on the pointer, such as supplying the pointer to a foreign function. In particular, the pointer and offset are not combined until after all allocation leading up to a foreign-function call; if the called function does not itself call anything that can trigger a garbage collection, it can safely use pointers that are offset into the middle of a GCable object.

```
(offset-ptr? cptr) → boolean?  
  cptr : cpointer?
```

A predicate for cpointers that have an offset, such as pointers that were created using `ptr-add`. Returns `#t` even if such an offset happens to be 0. Returns `#f` for other cpointers and non-cpointers.

```
(ptr-offset cptr) → exact-integer?  
  cptr : cpointer?
```

Returns the offset of a pointer that has an offset. The resulting offset is always in bytes.

4.1 Pointer Dereferencing

```
(set-ptr-offset! cptr offset [ctype]) → void?  
  cptr : cpointer?  
  offset : exact-integer?  
  ctype : ctype? = _byte
```

Sets the offset component of an offset pointer. The arguments are used in the same way as `ptr-add`. If `cptr` has no offset, the `exn:fail:contract` exception is raised.

```
(ptr-add! cptr offset [ctype]) → void?  
  cptr : cpointer?  
  offset : exact-integer?  
  ctype : ctype? = _byte
```

Like `ptr-add`, but destructively modifies the offset contained in a pointer. The same operation could be performed using `ptr-offset` and `set-ptr-offset!`.

```
(ptr-ref cptr type [offset]) → any  
  cptr : cpointer?  
  type : ctype?  
  offset : exact-nonnegative-integer? = 0  
(ptr-ref cptr type abs-tag offset) → any  
  cptr : cpointer?  
  type : ctype?  
  abs-tag : (one-of/c 'abs)  
  offset : exact-nonnegative-integer?  
(ptr-set! cptr type val) → void?  
  cptr : cpointer?  
  type : ctype?  
  val : any/c  
(ptr-set! cptr type offset val) → void?  
  cptr : cpointer?  
  type : ctype?  
  offset : exact-nonnegative-integer?  
  val : any/c  
(ptr-set! cptr type abs-tag offset val) → void?  
  cptr : cpointer?  
  type : ctype?  
  abs-tag : (one-of/c 'abs)
```

```
offset : exact-nonnegative-integer?
val : any/c
```

The `ptr-ref` procedure returns the object referenced by `cptr`, using the given `type`. The `ptr-set!` procedure stores the `val` in the memory `cptr` points to, using the given `type` for the conversion.

In each case, `offset` defaults to 0 (which is the only value that should be used with `ffi-obj` objects, see §7 “Unexported Primitive Functions”). If an `offset` index is non-0, the value is read or stored at that location, considering the pointer as a vector of `types` — so the actual address is the pointer plus the size of `type` multiplied by `offset`. In addition, a `'abs` flag can be used to use the `offset` as counting bytes rather than increments of the specified `type`.

Beware that the `ptr-ref` and `ptr-set!` procedure do not keep any meta-information on how pointers are used. It is the programmer’s responsibility to use this facility only when appropriate. For example, on a little-endian machine:

```
> (define block (malloc _int 5))
> (ptr-set! block _int 0 196353)
> (map (lambda (i) (ptr-ref block _byte i)) '(0 1 2 3))
(1 255 2 0)
```

In addition, `ptr-ref` and `ptr-set!` cannot detect when offsets are beyond an object’s memory bounds; out-of-bounds access can easily lead to a segmentation fault or memory corruption.

```
(memmove cptr src-cptr count [type]) → void?
  cptr : cpointer?
  src-cptr : cpointer?
  count : exact-nonnegative-integer?
  type : ctype? = _byte
(memmove cptr offset src-cptr count [type]) → void?
  cptr : cpointer?
  offset : exact-integer?
  src-cptr : cpointer?
  count : exact-nonnegative-integer?
  type : ctype? = _byte
(memmove cptr
  offset
  src-cptr
  src-offset
  count
  [type]) → void?
  cptr : cpointer?
  offset : exact-integer?
```

```
src-cptr : cpointer?  
src-offset : exact-integer?  
count : exact-nonnegative-integer?  
type : ctype? = _byte
```

Copies to *cptr* from *src-cptr*. The destination pointer can be offset by an optional *offset*, which is in *type* instances. The source pointer can be similarly offset by *src-offset*. The number of bytes copied from source to destination is determined by *count*, which is in *type* instances when supplied.

```
(memcpy cptr src-cptr count [type]) → void?  
  cptr : cpointer?  
  src-cptr : cpointer?  
  count : exact-nonnegative-integer?  
  type : ctype? = _byte  
(memcpy cptr offset src-cptr count [type]) → void?  
  cptr : cpointer?  
  offset : exact-integer?  
  src-cptr : cpointer?  
  count : exact-nonnegative-integer?  
  type : ctype? = _byte  
(memcpy cptr  
  offset  
  src-cptr  
  src-offset  
  count  
  [type]) → void?  
  cptr : cpointer?  
  offset : exact-integer?  
  src-cptr : cpointer?  
  src-offset : exact-integer?  
  count : exact-nonnegative-integer?  
  type : ctype? = _byte
```

Like `memmove`, but the result is undefined if the destination and source overlap.

```
(memset cptr byte count [type]) → void?  
  cptr : cpointer?  
  byte : byte?  
  count : exact-nonnegative-integer?  
  type : ctype? = _byte  
(memset cptr offset byte count [type]) → void?  
  cptr : cpointer?  
  offset : exact-integer?
```

```
byte : byte?
count : exact-nonnegative-integer?
type : ctype? = _byte
```

Similar to `memmove`, but the destination is uniformly filled with `byte` (i.e., an exact integer between 0 and 255 inclusive). When a `type` argument is present, the result is that of a call to `memset` with no `type` argument and the `count` multiplied by the size associated with the `type`.

```
(cpointer-tag cptr) → any
  cptr : cpointer?
```

Returns the Racket object that is the tag of the given `cptr` pointer.

```
(set-cpointer-tag! cptr tag) → void?
  cptr : cpointer?
  tag : any/c
```

Sets the tag of the given `cptr`. The `tag` argument can be any arbitrary value; other pointer operations ignore it. When a pointer value is printed, its tag is shown if it is a symbol, a byte string, a string. In addition, if the tag is a pair holding one of these in its `car`, the `car` is shown (so that the tag can contain other information).

4.2 Memory Management

For general information on C-level memory management with Racket, see *Inside: Racket C API*.

```
(malloc bytes-or-type
  [type-or-bytes
   cptr
   mode
   fail-mode]) → cpointer?
bytes-or-type : (or/c exact-nonnegative-integer? ctype?)
type-or-bytes : (or/c exact-nonnegative-integer? ctype?)
               = absent
cptr : cpointer? = absent
mode : (one-of/c 'nonatomic 'stubborn 'uncollectable = absent
           'eternal 'interior 'atomic-interior
           'raw)
fail-mode : (one-of/c 'failok) = absent
```

Allocates a memory block of a specified size using a specified allocation. The result is a

`cpointer` to the allocated memory. Although not reflected above, the four arguments can appear in any order since they are all different types of Racket objects; a size specification is required at minimum:

- If a C type `bytes-or-type` is given, its size is used to the block allocation size.
- If an integer `bytes-or-type` is given, it specifies the required size in bytes.
- If both `bytes-or-type` and `type-or-bytes` are given, then the allocated size is for a vector of values (the multiplication of the size of the C type and the integer).
- If a `cptr` pointer is given, its content is copied to the new block.
- A symbol `mode` argument can be given, which specifies what allocation function to use. It should be one of `'nonatomic` (uses `scheme_malloc` from Racket's C API), `'atomic` (`scheme_malloc_atomic`), `'stubborn` (`scheme_malloc_stubborn`), `'uncollectable` (`scheme_malloc_uncollectable`), `'eternal` (`scheme_malloc_eternal`), `'interior` (`scheme_malloc_allow_interior`), `'atomic-interior` (`scheme_malloc_atomic_allow_interior`), or `'raw` (uses the operating system's `malloc`, creating a GC-invisible block).
- If an additional `'failok` flag is given, then `scheme_malloc_fail_ok` is used to wrap the call.

If no `mode` is specified, then `'nonatomic` allocation is used when the type is a `_gcpointer`- or `_scheme`-based type, and `'atomic` allocation is used otherwise.

```
(free cptr) → void  
cptr : cpointer?
```

Uses the operating system's `free` function for `'raw`-allocated pointers, and for pointers that a foreign library allocated and we should free. Note that this is useful as part of a finalizer (see below) procedure hook (e.g., on the Racket pointer object, freeing the memory when the pointer object is collected, but beware of aliasing).

```
(end-stubborn-change cptr) → void?  
cptr : cpointer?
```

Uses `scheme_end_stubborn_change` on the given stubborn-allocated pointer.

```
(malloc-immobile-cell v) → cpointer?  
v : any/c
```

Allocates memory large enough to hold one arbitrary (collectable) Racket value, but that is not itself collectable or moved by the memory manager. The cell is initialized with `v`; use

the type `_scheme` with `ptr-ref` and `ptr-set!` to get or set the cell's value. The cell must be explicitly freed with `free-immobile-cell`.

```
(free-immobile-cell cptr) → void?  
  cptr : cpointer?
```

Frees an immobile cell created by `malloc-immobile-cell`.

```
(register-finalizer obj finalizer) → void?  
  obj : any/c  
  finalizer : (any/c . -> . any)
```

Registers a finalizer procedure `finalizer-proc` with the given `obj`, which can be any Racket (GC-able) object. The finalizer is registered with a will executor; see `make-will-executor`. The finalizer is invoked when `obj` is about to be collected. (This is done by a thread that is in charge of triggering these will executors.)

Finalizers are mostly intended to be used with `cpointer` objects (for freeing unused memory that is not under GC control), but it can be used with any Racket object—even ones that have nothing to do with foreign code. Note, however, that the finalizer is registered for the *Racket* object. If you intend to free a pointer object, then you must be careful to not register finalizers for two `cpointer`s that point to the same address. Also, be careful to not make the finalizer a closure that holds on to the object.

For example, suppose that you're dealing with a foreign function that returns a C string that you should free. Here is an attempt at creating a suitable type:

```
(define bytes/free  
  (make-ctype _pointer  
    #f ; a Racket bytes can be used as a pointer  
    (lambda (x)  
      (let ([b (make-byte-string x)])  
        (register-finalizer x free)  
        b))))
```

The above code is wrong: the finalizer is registered for `x`, which is no longer needed once the byte string is created. Changing this to register the finalizer for `b` corrects this problem, but then `free` will be invoked on it instead of on `x`. In an attempt to fix this, we will be careful and print out a message for debugging:

```
(define bytes/free  
  (make-ctype _pointer  
    #f ; a Racket bytes can be used as a pointer  
    (lambda (x)  
      (let ([b (make-byte-string x)])
```

```
(register-finalizer b
  (lambda (ignored)
    (printf "Releasing ~s\n" b)
    (free x)))
b))))
```

but we never see any printout. The problem is that the finalizer is a closure that keeps a reference to `b`. To fix this, you should use the input argument to the finalizer. Simply changing `ignored` to `b` will solve this problem. (Removing the debugging message also avoids the problem, since the finalization procedure would then not close over `b`.)

```
(make-sized-byte-string cptr length) → bytes?
  cptr : cpointer?
  length : exact-nonnegative-integer?
```

Returns a byte string made of the given pointer and the given length. No copying is done. This can be used as an alternative to make pointer values accessible in Racket when the size is known.

If `cptr` is an offset pointer created by `ptr-add`, the offset is immediately added to the pointer. Thus, this function cannot be used with `ptr-add` to create a substring of a Racket byte string, because the offset pointer would be to the middle of a collectable object (which is not allowed).

5 Derived Utilities

5.1 Safe Homogenous Vectors

```
(require ffi/vector)
```

Homogenous vectors are similar to C vectors (see §5.2 “Safe C Vectors”), except that they define different types of vectors, each with a hard-wired type. An exception is the `u8` family of bindings, which are just aliases for byte-string bindings; for example, `make-u8vector` is an alias for `make-bytes`.

```
(make-u8vector len) → u8vector?  
  len : exact-nonnegative-integer?  
(u8vector val ...) → u8vector?  
  val : number?  
(u8vector? v) → boolean?  
  v : any/c  
(u8vector-length vec) → exact-nonnegative-integer?  
  vec : u8vector?  
(u8vector-ref vec k) → number?  
  vec : u8vector?  
  k : exact-nonnegative-integer?  
(u8vector-set! vec k val) → void?  
  vec : u8vector?  
  k : exact-nonnegative-integer?  
  val : number?  
(list->u8vector lst) → u8vector?  
  lst : (listof number?)  
(u8vector->list vec) → (listof number?)  
  vec : u8vector?  
(u8vector->cpointer vec) → cpointer?  
  vec : u8vector?
```

Like `_cvector`, but for vectors of `_byte` elements. These are aliases for `byte` operations, where `u8vector->cpointer` is the identity function.

```
(_u8vector mode maybe-len)  
_u8vector
```

Like `_cvector`, but for vectors of `_uint8` elements.

```
(make-s8vector len) → s8vector?  
  len : exact-nonnegative-integer?
```

```

(s8vector val ...) → s8vector?
  val : number?
(s8vector? v) → boolean?
  v : any/c
(s8vector-length vec) → exact-nonnegative-integer?
  vec : s8vector?
(s8vector-ref vec k) → number?
  vec : s8vector?
  k : exact-nonnegative-integer?
(s8vector-set! vec k val) → void?
  vec : s8vector?
  k : exact-nonnegative-integer?
  val : number?
(list->s8vector lst) → s8vector?
  lst : (listof number?)
(s8vector->list vec) → (listof number?)
  vec : s8vector?
(s8vector->cpointer vec) → cpointer?
  vec : s8vector?

```

Like `make-vector`, etc., but for `_int8` elements. The `s8vector->cpointer` function extracts a plain pointer to the underlying array.

```

(_s8vector mode maybe-len)
_s8vector

```

Like `_cvector`, but for vectors of `_int8` elements.

```

(make-s16vector len) → s16vector?
  len : exact-nonnegative-integer?
(s16vector val ...) → s16vector?
  val : number?
(s16vector? v) → boolean?
  v : any/c
(s16vector-length vec) → exact-nonnegative-integer?
  vec : s16vector?
(s16vector-ref vec k) → number?
  vec : s16vector?
  k : exact-nonnegative-integer?
(s16vector-set! vec k val) → void?
  vec : s16vector?
  k : exact-nonnegative-integer?
  val : number?
(list->s16vector lst) → s16vector?

```

```

  lst : (listof number?)
(s16vector->list vec) → (listof number?)
  vec : s16vector?
(s16vector->cpointer vec) → cpointer?
  vec : s16vector?

```

Like `make-vector`, etc., but for `_int16` elements. The `s16vector->cpointer` function extracts a plain pointer to the underlying array.

```

(_s16vector mode maybe-len)
_s16vector

```

Like `_cvector`, but for vectors of `_int16` elements.

```

(make-u16vector len) → u16vector?
  len : exact-nonnegative-integer?
(u16vector val ...) → u16vector?
  val : number?
(u16vector? v) → boolean?
  v : any/c
(u16vector-length vec) → exact-nonnegative-integer?
  vec : u16vector?
(u16vector-ref vec k) → number?
  vec : u16vector?
  k : exact-nonnegative-integer?
(u16vector-set! vec k val) → void?
  vec : u16vector?
  k : exact-nonnegative-integer?
  val : number?
(list->u16vector lst) → u16vector?
  lst : (listof number?)
(u16vector->list vec) → (listof number?)
  vec : u16vector?
(u16vector->cpointer vec) → cpointer?
  vec : u16vector?

```

Like `make-vector`, etc., but for `_uint16` elements. The `u16vector->cpointer` function extracts a plain pointer to the underlying array.

```

(_u16vector mode maybe-len)
_u16vector

```

Like `_cvector`, but for vectors of `_uint16` elements.

```

(make-s32vector len) → s32vector?
  len : exact-nonnegative-integer?
(s32vector val ...) → s32vector?
  val : number?
(s32vector? v) → boolean?
  v : any/c
(s32vector-length vec) → exact-nonnegative-integer?
  vec : s32vector?
(s32vector-ref vec k) → number?
  vec : s32vector?
  k : exact-nonnegative-integer?
(s32vector-set! vec k val) → void?
  vec : s32vector?
  k : exact-nonnegative-integer?
  val : number?
(list->s32vector lst) → s32vector?
  lst : (listof number?)
(s32vector->list vec) → (listof number?)
  vec : s32vector?
(s32vector->cpointer vec) → cpointer?
  vec : s32vector?

```

Like `make-vector`, etc., but for `_int32` elements. The `s32vector->cpointer` function extracts a plain pointer to the underlying array.

```

(_s32vector mode maybe-len)
_s32vector

```

Like `_cvector`, but for vectors of `_int32` elements.

```

(make-u32vector len) → u32vector?
  len : exact-nonnegative-integer?
(u32vector val ...) → u32vector?
  val : number?
(u32vector? v) → boolean?
  v : any/c
(u32vector-length vec) → exact-nonnegative-integer?
  vec : u32vector?
(u32vector-ref vec k) → number?
  vec : u32vector?
  k : exact-nonnegative-integer?
(u32vector-set! vec k val) → void?
  vec : u32vector?

```

```

    k : exact-nonnegative-integer?
    val : number?
(list->u32vector lst) → u32vector?
  lst : (listof number?)
(u32vector->list vec) → (listof number?)
  vec : u32vector?
(u32vector->cpointer vec) → cpointer?
  vec : u32vector?

```

Like `make-vector`, etc., but for `_uint32` elements. The `u32vector->cpointer` function extracts a plain pointer to the underlying array.

```

(_u32vector mode maybe-len)
_u32vector

```

Like `_cvector`, but for vectors of `_uint32` elements.

```

(make-s64vector len) → s64vector?
  len : exact-nonnegative-integer?
(s64vector val ...) → s64vector?
  val : number?
(s64vector? v) → boolean?
  v : any/c
(s64vector-length vec) → exact-nonnegative-integer?
  vec : s64vector?
(s64vector-ref vec k) → number?
  vec : s64vector?
  k : exact-nonnegative-integer?
(s64vector-set! vec k val) → void?
  vec : s64vector?
  k : exact-nonnegative-integer?
  val : number?
(list->s64vector lst) → s64vector?
  lst : (listof number?)
(s64vector->list vec) → (listof number?)
  vec : s64vector?
(s64vector->cpointer vec) → cpointer?
  vec : s64vector?

```

Like `make-vector`, etc., but for `_int64` elements. The `s64vector->cpointer` function extracts a plain pointer to the underlying array.

```

(_s64vector mode maybe-len)
_s64vector

```

Like `_cvector`, but for vectors of `_int64` elements.

```
(make-u64vector len) → u64vector?  
  len : exact-nonnegative-integer?  
(u64vector val ...) → u64vector?  
  val : number?  
(u64vector? v) → boolean?  
  v : any/c  
(u64vector-length vec) → exact-nonnegative-integer?  
  vec : u64vector?  
(u64vector-ref vec k) → number?  
  vec : u64vector?  
  k : exact-nonnegative-integer?  
(u64vector-set! vec k val) → void?  
  vec : u64vector?  
  k : exact-nonnegative-integer?  
  val : number?  
(list->u64vector lst) → u64vector?  
  lst : (listof number?)  
(u64vector->list vec) → (listof number?)  
  vec : u64vector?  
(u64vector->cpointer vec) → cpointer?  
  vec : u64vector?
```

Like `make-vector`, etc., but for `_uint64` elements. The `u64vector->cpointer` function extracts a plain pointer to the underlying array.

```
(_u64vector mode maybe-len)  
_u64vector
```

Like `_cvector`, but for vectors of `_uint64` elements.

```
(make-f32vector len) → f32vector?  
  len : exact-nonnegative-integer?  
(f32vector val ...) → f32vector?  
  val : number?  
(f32vector? v) → boolean?  
  v : any/c  
(f32vector-length vec) → exact-nonnegative-integer?  
  vec : f32vector?  
(f32vector-ref vec k) → number?  
  vec : f32vector?  
  k : exact-nonnegative-integer?  
(f32vector-set! vec k val) → void?
```



```

    vec : f32vector?
    k : exact-nonnegative-integer?
    val : number?
(list->f32vector lst) → f32vector?
  lst : (listof number?)
(f32vector->list vec) → (listof number?)
  vec : f32vector?
(f32vector->cpointer vec) → cpointer?
  vec : f32vector?

```

Like `make-vector`, etc., but for `_float` elements. The `f32vector->cpointer` function extracts a plain pointer to the underlying array.

```

(_f32vector mode maybe-len)
_f32vector

```

Like `_cvector`, but for vectors of `_float` elements.

```

(make-f64vector len) → f64vector?
  len : exact-nonnegative-integer?
(f64vector val ...) → f64vector?
  val : number?
(f64vector? v) → boolean?
  v : any/c
(f64vector-length vec) → exact-nonnegative-integer?
  vec : f64vector?
(f64vector-ref vec k) → number?
  vec : f64vector?
  k : exact-nonnegative-integer?
(f64vector-set! vec k val) → void?
  vec : f64vector?
  k : exact-nonnegative-integer?
  val : number?
(list->f64vector lst) → f64vector?
  lst : (listof number?)
(f64vector->list vec) → (listof number?)
  vec : f64vector?
(f64vector->cpointer vec) → cpointer?
  vec : f64vector?

```

Like `make-vector`, etc., but for `_double*` elements. The `f64vector->cpointer` function extracts a plain pointer to the underlying array.

```

(_f64vector mode maybe-len)

```

`_f64vector`

Like `_cvector`, but for vectors of `_double*` elements.

5.2 Safe C Vectors

```
(require ffi/cvector)
(require ffi/unsafe/cvector)
```

The `ffi/unsafe/cvector` library exports the bindings of this section. The `ffi/cvector` library exports the same bindings, except for the unsafe `make-cvector*` operation.

The `cvector` form can be used as a type C vectors (i.e., a pointer to a memory block).

```
(_cvector mode type maybe-len)
_cvector
```

Like `_bytes`, `_cvector` can be used as a simple type that corresponds to a pointer that is managed as a safe C vector on the Racket side. The longer form behaves similarly to the `_list` and `_vector` custom types, except that `_cvector` is more efficient; no Racket list or vector is needed.

```
(make-cvector type length) → cvector?
  type : ctype?
  length : exact-nonnegative-integer?
```

Allocates a C vector using the given `type` and `length`. The resulting vector is not guaranteed to contain any particular values.

```
(cvector type val ...) → cvector?
  type : ctype?
  val : any/c
```

Creates a C vector of the given `type`, initialized to the given list of `vals`.

```
(cvector? v) → boolean?
  v : any/c
```

Returns `#t` if `v` is a C vector, `#f` otherwise.

```
(cvector-length cvec) → exact-nonnegative-integer?
  cvec : cvector?
```

Returns the length of a C vector.

```
(cvector-type cvec) → ctype?  
  cvec : cvector?
```

Returns the C type object of a C vector.

```
(cvector-ptr cvec) → cpointer?  
  cvec : cvector?
```

Returns the pointer that points at the beginning block of the given C vector.

```
(cvector-ref cvec k) → any  
  cvec : cvector?  
  k : exact-nonnegative-integer?
```

References the *k*th element of the *cvec* C vector. The result has the type that the C vector uses.

```
(cvector-set! cvec k val) → void?  
  cvec : cvector?  
  k : exact-nonnegative-integer?  
  val : any
```

Sets the *k*th element of the *cvec* C vector to *val*. The *val* argument should be a value that can be used with the type that the C vector uses.

```
(cvector->list cvec) → list?  
  cvec : cvector?
```

Converts the *cvec* C vector object to a list of values.

```
(list->cvector lst type) → cvector?  
  lst : list?  
  type : ctype?
```

Converts the list *lst* to a C vector of the given *type*.

```
(make-cvector* cptr type length) → cvector?  
  cptr : any/c  
  type : ctype?  
  length : exact-nonnegative-integer?
```

Constructs a C vector using an existing pointer object. This operation is not safe, so it is intended to be used in specific situations where the *type* and *length* are known.

5.3 Tagged C Pointer Types

The unsafe `cpointer-has-tag?` and `cpointer-push-tag!` operations manage tags to distinguish pointer types.

```
(_cpointer tag
  [ptr-type
   scheme-to-c
   c-to-scheme]) → ctype
tag : any/c
ptr-type : ctype? = xpointer
scheme-to-c : (any/c . -> . any/c) = values
c-to-scheme : (any/c . -> . any/c) = values
(_cpointer/null tag
  [ptr-type
   scheme-to-c
   c-to-scheme]) → ctype
tag : any/c
ptr-type : ctype? = xpointer
scheme-to-c : (any/c . -> . any/c) = values
c-to-scheme : (any/c . -> . any/c) = values
```

Construct a kind of a pointer that gets a specific tag when converted to Racket, and accept only such tagged pointers when going to C. An optional *ptr-type* can be given to be used as the base pointer type, instead of `_pointer`.

Pointer tags are checked with `cpointer-has-tag?` and changed with `cpointer-push-tag!` which means that other tags are preserved. Specifically, if a base *ptr-type* is given and is itself a `_cpointer`, then the new type will handle pointers that have the new tag in addition to *ptr-type*'s tag(s). When the tag is a pair, its first value is used for printing, so the most recently pushed tag which corresponds to the inheriting type will be displayed.

Note that tags are compared with `eq?` (or `memq`), which means an interface can hide its value from users (e.g., not provide the `cpointer-tag` accessor), which makes such pointers un-fake-able.

`_cpointer/null` is similar to `_cpointer` except that it tolerates NULL pointers both going to C and back. Note that NULL pointers are represented as `#f` in Racket, so they are not tagged.

```
(define-cpointer-type _id)
(define-cpointer-type _id scheme-to-c-expr)
(define-cpointer-type _id scheme-to-c-expr c-to-scheme-expr)
```

A macro version of `_cpointer` and `_cpointer/null`, using the defined name for a tag string, and defining a predicate too. The `_id` must start with `_`.

The optional expression produces optional arguments to `_cpointer`.

In addition to defining `_id` to a type generated by `_cpointer`, `_id/null` is bound to a type produced by `_cpointer/null` type. Finally, `id?` is defined as a predicate, and `id-tag` is defined as an accessor to obtain a tag. The tag is the string form of `id`.

```
(cpointer-has-tag? cptr tag) → boolean?
  cptr : any/c
  tag : any/c
(cpointer-push-tag! cptr tag) → void
  cptr : any/c
  tag : any/c
```

These two functions treat pointer tags as lists of tags. As described in §4 “Pointer Functions”, a pointer tag does not have any role, except for Racket code that uses it to distinguish pointers; these functions treat the tag value as a list of tags, which makes it possible to construct pointer types that can be treated as other pointer types, mainly for implementing inheritance via upcasts (when a struct contains a super struct as its first element).

The `cpointer-has-tag?` function checks whether if the given `cptr` has the `tag`. A pointer has a tag `tag` when its tag is either `eq?` to `tag` or a list that contains (in the sense of `memq`) `tag`.

The `cpointer-push-tag!` function pushes the given `tag` value on `cptr`’s tags. The main properties of this operation are: (a) pushing any tag will make later calls to `cpointer-has-tag?` succeed with this tag, and (b) the pushed tag will be used when printing the pointer (until a new value is pushed). Technically, pushing a tag will simply set it if there is no tag set, otherwise push it on an existing list or an existing value (treated as a single-element list).

5.4 Defining Bindings

```
(require ffi/unsafe/define)
```

```
(define-ffi-definer define-id ffi-lib-expr
  option ...)
```

```
option = #:provide provide-id
        | #:define core-define-id
        | #:default-make-fail default-make-fail-expr
```

Binds *define-id* as a definition form to extract bindings from the library produced by *ffi-lib-expr*. The syntax of *define-id* is

```
(define-id id type-expr
  bind-option ...)
```

```
bind-option = #:c-id c-id
              | #:wrap wrap-expr
              | #:make-fail make-fail-expr
              | #:fail fail-expr
```

A *define-id* form binds *id* by extracting a binding with the name *c-id* from the library produced by *ffi-lib-expr*, where *c-id* defaults to *id*. The other options support further wrapping and configuration:

- Before the extracted result is bound as *id*, it is passed to the result of *wrap-expr*, which defaults to *values*. Expressions such as (*allocator delete*) or (*deallocator*) are useful as *wrap-exprs*.
- The *#:make-fail* and *#:fail* options are mutually exclusive; if *make-fail-expr* is provided, it is applied to *id* to obtain the last argument to *get-ffi-obj*; if *fail-expr* is provided, it is supplied directly as the last argument to *get-ffi-obj*. The *make-not-available* function is useful as *make-fail-expr* to cause a use of *id* to report an error when it is applied if *c-id* was not found in the foreign library.

If *provide-id* is provided to *define-ffi-definer*, then *define-id* also provides its binding using *provide-id*. The provide-protected form is usually a good choice for *provide-id*.

If *core-define-id* is provided to *define-ffi-definer*, then *code-define-id* is used in place of *define* in the expansion of *define-id* for each binding.

If *default-make-fail-expr* is provided to *define-ffi-definer*, it serves as the default *#:make-fail* value for *define-id*.

For example,

```
(define-ffi-definer define-gtk gtk-lib)
```

binds *define-gtk* to extract FFI bindings from *gtk-lib*, so that *gtk_rc_parse* could be bound as

```
(define-gtk gtk_rc_parse (_fun _path -> _void))
```

If `gtk_rc_parse` is not found, then `define-gtk` reports an error immediately. If `define-gtk` is instead defined with

```
(define-ffi-definer define-gtk gtk-lib
  #:default-make-fail make-not-available)
```

then if `gtk_rc_parse` is not found in `gtk-lib`, an error is reported only when `gtk_rc_parse` is called.

```
(make-not-available name) → (#:rest list? -> any/c)
  name : symbol?
```

Returns a procedure that takes any number of arguments and reports an error message from `name`. This function is intended for using with `#:make-fail` or `#:default-make-fail` in `define-ffi-definer`

```
(provide-protected provide-spec ...)
```

Equivalent to `(provide (protect-out provide-spec ...))`. The `provide-protected` identifier is useful with `#:provide` in `define-ffi-definer`.

5.5 Allocation and Finalization

```
(require ffi/unsafe/alloc)
```

The `ffi/unsafe/alloc` library provides utilities for ensuring that values allocated through foreign functions are reliably deallocated.

```
((allocator dealloc) alloc) → procedure?
  dealloc : (any/c . -> . any)
  alloc : procedure?
```

Produces a procedure that behaves like `alloc`, but the result of `alloc` is given a finalizer that calls `dealloc` on the result if it is not otherwise freed through a deallocator (as designated with `deallocator`). In addition, `alloc` is called in atomic mode (see `start-atomic`); its result is received and registered in atomic mode, so that the result is reliably freed.

The `dealloc` procedure itself need not be specifically designated a deallocator (via `deallocator`). If a deallocator is called explicitly, it need not be the same as `dealloc`.

```
((deallocator [get-arg]) dealloc) → procedure?  
  get-arg : (list? . -> . any/c) = car  
  dealloc : procedure?  
(releaser [get-arg] dealloc) → procedure?  
  get-arg : (list? . -> . any/c) = car  
  dealloc : procedure?
```

Produces a procedure that behaves like `dealloc`. The `dealloc` procedure is called in atomic mode (see `start-atomic`), and the reference count on one of its arguments is decremented; if the reference count reaches zero, no finalizer associated by an `allocator`- or `referencer`-wrapped procedure is invoked when the value becomes inaccessible.

The optional `get-arg` procedure determines which of `dealloc`'s arguments correspond to the released object; `get-arg` receives a list of arguments passed to `dealloc`, so the default `car` selects the first one.

The `releaser` procedure is a synonym for `deallocator`.

```
((retainer release [get-arg]) retain) → procedure?  
  release : (any/c . -> . any)  
  get-arg : (list? . -> . any/c) = car  
  retain : procedure?
```

Produces a procedure that behaves like `retain`. The procedure is called in atomic mode (see `start-atomic`), and the reference count on one of its arguments is incremented, with `release` recorded as the corresponding release procedure to be called by the finalizer on the retained object (unless some deallocator, as wrapped by `deallocate`, is explicitly called first).

The optional `get-arg` procedure determines which of `retain`'s arguments correspond to the retained object; `get-arg` receives a list of arguments passed to `retain`, so the default `car` selects the first one.

The `release` procedure itself need not be specifically designated a deallocator (via `deallocator`). If a deallocator is called explicitly, it need not be the same as `release`.

5.6 Atomic Execution

```
(require ffi/unsafe/atomic)
```

```
(start-atomic) → void?  
(end-atomic) → void?
```


Disables and enables context switches and delivery of break exceptions at the level of Racket threads. Calls to `start-atomic` and `end-atomic` can be nested.

Using `call-as-atomic` is somewhat safer, in that `call-as-atomic` correctly catches exceptions and re-raises them after exiting atomic mode. For simple uses where exceptions need not be handled, however, `start-atomic` and `end-atomic` are faster.

```
(start-breakable-atomic) → void?  
(end-breakable-atomic) → void?
```

Like `start-atomic` and `end-atomic`, but the delivery of break exceptions is not suspended. To ensure that a call to `start-atomic` is reliably paired with a call to `end-atomic`, use `dynamic-wind` pre- and post thunks or some other context where breaks are disabled. These variants are not faster than plain `start-atomic` and `end-atomic`.

```
(call-as-atomic thunk) → any  
  thunk : (-> any)
```

Calls `thunk` in atomic mode. If `thunk` raises an exception, the exception is caught and re-raised after exiting atomic mode.

When `call-as-atomic` is used in the dynamic extent of `call-as-atomic`, then `thunk` is simply called directly (as a tail call).

```
(call-as-nonatomic thunk) → any  
  thunk : (-> any)
```

Within the dynamic extent of a `call-as-atomic`, calls `thunk` in non-atomic mode. Beware that the current thread may be suspended or terminated by other threads during `thunk`, in which case the call never returns.

When used not in the dynamic extent of `call-as-atomic`, `call-as-nonatomic` raises `exn:fail:contract`.

5.7 Speculatively Atomic Execution

```
(require ffi/unsafe/try-atomic)
```

The `ffi/unsafe/try-atomic` supports atomic execution that can be suspended and resumed in non-atomic mode if it takes too long or if some external event causes the attempt to be abandoned.

```
(call-as-nonatomic-retry-point thunk) → any
```

`thunk` : (-> any)

Calls `thunk` in atomic mode (see `start-atomic` and `end-atomic`) while allowing `thunk` to use `try-atomic`. Any incomplete computations started with `try-atomic` are run non-atomically after `thunk` returns. The result of `thunk` is used as the result of `call-as-nonatomic-retry-point`.

```
(try-atomic thunk
  default-val
  [#:should-give-up? give-up-proc
   #:keep-in-order? keep-in-order?]) → any
thunk : (-> any)
default-val : any/c
give-up-proc : (-> any/c) = run-200-milliseconds
keep-in-order? : any/c = #t
```

Within the dynamic extent of a `call-as-nonatomic-retry-point` call, attempts to run `thunk` in the existing atomic mode. The `give-up-proc` procedure is called periodically to determine whether atomic mode should be abandoned; the default `give-up-proc` returns true after 200 milliseconds. If atomic mode is abandoned, the computation is suspended, and `default-val` is returned, instead. The computation is resumed later by the enclosing `call-as-nonatomic-retry-point` call.

If `keep-in-order?` is true, then if `try-atomic` is called after an earlier computation was suspended for the same `call-as-nonatomic-retry-point` call, then `thunk` is immediately enqueued for completion by `call-as-nonatomic-retry-point` and `default-val` is returned.

The `give-up-proc` callback is polled only at points where the level of atomic-mode nesting (see `start-atomic`, `start-breakable-atomic`, and `call-as-atomic`) is the same as at the point of calling `try-atomic`.

If `thunk` aborts the current continuation using (`default-continuation-prompt-tag`), the abort is suspended the resumed by the enclosing `call-as-nonatomic-retry-point`. Escapes to the context of the call to `thunk` using any other prompt tag or continuation are blocked (using `dynamic-wind`) and simply return (`void`) from `thunk`.

5.8 Objective-C FFI

```
(require ffi/unsafe/objc)
```

The `ffi/unsafe/objc` library builds on `ffi/unsafe` to support interaction with Objective-C.

The library supports Objective-C interaction in two layers. The upper layer provides syntactic forms for sending messages and deriving subclasses. The lower layer is a thin wrapper on the Objective-C runtime library functions. Even the upper layer is unsafe and relatively low-level compared to normal Racket libraries, because argument and result types must be declared in terms of FFI C types (see §3.1 “Type Constructors”).

5.8.1 FFI Types and Constants

`_id` : `ctype?`

The type of an Objective-C object, an opaque pointer.

`_Class` : `ctype?`

The type of an Objective-C class, which is also an `_id`.

`_Protocol` : `ctype?`

The type of an Objective-C protocol, which is also an `_id`.

`_SEL` : `ctype?`

The type of an Objective-C selector, an opaque pointer.

`_BOOL` : `ctype?`

The Objective-C boolean type. Racket values are converted for C in the usual way: `#f` is false and any other value is true. C values are converted to Racket booleans.

`YES` : `boolean?`

Synonym for `#t`

`NO` : `boolean?`

Synonym for `#f`

5.8.2 Syntactic Forms and Procedures

```
(tell result-type obj-expr method-id)
(tell result-type obj-expr arg ...)
```

```
result-type =
  | #:type ctype-expr

  arg = method-id arg-expr
  | method-id #:type ctype-expr arg-expr
```

Sends a message to the Objective-C object produced by *obj-expr*. When a type is omitted for either the result or an argument, the type is assumed to be `_id`, otherwise it must be specified as an FFI C type (see §3.1 “Type Constructors”).

If a single *method-id* is provided with no arguments, then *method-id* must not end with `;`; otherwise, each *method-id* must end with `;`.

Examples:

```
> (tell NSString alloc)
#<cpointer:id>
> (tell (tell NSString alloc)
      initWithUTF8String: #:type _string "Hello")
#<cpointer:id>
```

```
(tellv obj-expr method-id)
(tellv obj-expr arg ...)
```

Like `tell`, but with a result type `_void`.

```
(import-class class-id ...)
```

Defines each *class-id* to the class (a value with FFI type `_Class`) that is registered with the string form of *class-id*. The registered class is obtained via `objc_lookupClass`.

Example:

```
> (import-class NSString)
```

```
(import-protocol protocol-id ...)
```

Defines each *protocol-id* to the protocol (a value with FFI type `_Protocol`) that is registered with the string form of *protocol-id*. The registered class is obtained via `objc_getProtocol`.

Example:

```
> (import-protocol NSCoding)
```

```
(define-objc-class class-id superclass-expr
  maybe-mixins
  maybe-protocols
  [field-id ...]
  method)

  maybe-mixins =
    | #:mixins (mixin-expr ...)

maybe-protocols =
    | #:protocols (protocol-expr ...)

  method = (mode result-ctype-expr (method-id) body ...+)
    | (mode result-ctype-expr (arg ...+) body ...+)

  mode = +
    | -
    | +a
    | -a

  arg = method-id [ctype-expr arg-id]
```

Defines *class-id* as a new, registered Objective-C class (of FFI type `_Class`). The *superclass-expr* should produce an Objective-C class or `#f` for the superclass. An optional `#:mixins` clause can specify mixins defined with `define-objc-mixin`. An optional `#:protocols` clause can specify Objective-C protocols to be implemented by the class.

Each *field-id* is an instance field that holds a Racket value and that is initialized to `#f` when the object is allocated. The *field-ids* can be referenced and `set!` directly when the method *bodys*. Outside the object, they can be referenced and set with `get-ivar` and `set-ivar!`.

Each *method* adds or overrides a method to the class (when *mode* is `-` or `-a`) to be called on instances, or it adds a method to the meta-class (when *mode* is `+` or `+a`) to be called on the class itself. All result and argument types must be declared using FFI C types (see §3.1 “Type Constructors”). When *mode* is `+a` or `-a`, the method is called in atomic mode (see `_cprocedure`).

If a *method* is declared with a single *method-id* and no arguments, then *method-id* must not end with `.`. Otherwise, each *method-id* must end with `.`.

If the special method `dealloc` is declared for mode `-`, it must not call the superclass method, because a `(super-tell dealloc)` is added to the end of the method automatically. In

addition, before `(super-tell dealloc)`, space for each *field-id* within the instance is deallocated.

Example:

```
> (define-objc-class MyView NSView
  [bm] ; <- one field
  (- _racket (swapBitmap: [_racket new-bm])
    (begin0 bm (set! bm new-bm)))
  (- _void (drawRect: [_NSRect exposed-rect])
    (super-tell drawRect: exposed-rect)
    (draw-bitmap-region bm exposed-rect))
  (- _void (dealloc)
    (when bm (done-with-bm bm))))
```

```
(define-objc-mixin (class-id superclass-id)
  maybe-mixins
  maybe-protocols
  [field-id ...]
  method)
```

Like `define-objc-class`, but defines a mixin to be combined with other method definitions through either `define-objc-class` or `define-objc-mixin`. The specified *field-ids* are not added by the mixin, but must be a subset of the *field-ids* declared for the class to which the methods are added.

`self`

When used within the body of a `define-objc-class` or `define-objc-mixin` method, refers to the object whose method was called. This form cannot be used outside of a `define-objc-class` or `define-objc-mixin` method.

```
(super-tell result-type method-id)
(super-tell result-type arg ...)
```

When used within the body of a `define-objc-class` or `define-objc-mixin` method, calls a superclass method. The *result-type* and *arg* sub-forms have the same syntax as in `tell`. This form cannot be used outside of a `define-objc-class` or `define-objc-mixin` method.

```
(get-ivar obj-expr field-id)
```

Extracts the Racket value of a field in a class created with `define-objc-class`.

```
(set-ivar! obj-expr field-id value-expr)
```

Sets the Racket value of a field in a class created with `define-objc-class`.

```
(selector method-id)
```

Returns a selector (of FFI type `_SEL`) for the string form of *method-id*.

Example:

```
> (tellv button setAction: #:type _SEL (selector terminate:))
```

```
(objc-is-a? obj cls) → boolean?  
obj : _id  
cls : _Class
```

Check whether *obj* is an instance of the Objective-C class *cls*.

5.8.3 Raw Runtime Functions

```
(objc_lookUpClass s) → (or/c _Class #f)  
s : string?
```

Finds a registered class by name.

```
(objc_getProtocol s) → (or/c _Protocol #f)  
s : string?
```

Finds a registered protocol by name.

```
(sel_registerName s) → _SEL  
s : string?
```

Interns a selector given its name in string form.

```
(objc_allocateClassPair cls s extra) → _Class  
cls : _Class  
s : string?  
extra : integer?
```

Allocates a new Objective-C class.

```
(objc_registerClassPair cls) → void?  
  cls : _Class
```

Registers an Objective-C class.

```
(object_getClass obj) → _Class  
  obj : _id
```

Returns the class of an object (or the meta-class of a class).

```
(class_addMethod cls  
                sel  
                imp  
                type  
                type-encoding) → boolean?  
  
cls : _Class  
sel : _SEL  
imp : procedure?  
type : ctype?  
type-encoding : string?
```

Adds a method to a class. The *type* argument must be a FFI C type (see §3.1 “Type Constructors”) that matches both *imp* and the not Objective-C type string *type-encoding*.

```
(class_addIvar cls  
              name  
              size  
              log-alignment  
              type-encoding) → boolean?  
  
cls : _Class  
name : string?  
size : exact-nonnegative-integer?  
log-alignment : exact-nonnegative-integer?  
type-encoding : string?
```

Adds an instance variable to an Objective-C class.

```
(object_getInstanceVariable obj name) → _Ivar any/c  
  obj : _id  
  name : string?
```

Gets the value of an instance variable whose type is `_pointer`.

```
(object_setInstanceVariable obj name val) → _Ivar
  obj : _id
  name : string?
  val : any/c
```

Sets the value of an instance variable whose type is `_pointer`.

```
_Ivar : ctype?
```

The type of an Objective-C instance variable, an opaque pointer.

```
((objc_msgSend/typed types) obj sel arg) → any/c
  types : (vector/c result-ctype arg-ctype ...)
  obj : _id
  sel : _SEL
  arg : any/c
```

Calls the Objective-C method on `_id` named by `sel`. The `types` vector must contain one more than the number of supplied `args`; the first FFI C type in `type` is used as the result type.

```
((objc_msgSendSuper/typed types)
  super
  sel
  arg) → any/c
  types : (vector/c result-ctype arg-ctype ...)
  super : _objc_super
  sel : _SEL
  arg : any/c
```

Like `objc_msgSend/typed`, but for a super call.

```
(make_objc_super id super) → _objc_super
  id : _id
  super : _Class
  _objc_super : ctype?
```

Constructor and FFI C type use for super calls.

Contents

5.8.4 Legacy Library

```
(require ffi/objc)
```

The `ffi/objc` library is a deprecated entry point to `ffi/unsafe/objc`. It exports only safe operations directly, and unsafe operations are imported using `objc-unsafe!`.

```
(objc-unsafe!)
```

Analogous to `(unsafe!)`, makes unsafe bindings of `ffi/unsafe/objc` available in the importing module.

6 Miscellaneous Support

```
(regexp-replaces objname substs) → string?  
  objname : (or/c string? bytes? symbol?)  
  substs : (listof (list regexp? string?))
```

A function that is convenient for many interfaces where the foreign library has some naming convention that you want to use in your interface as well. The *objname* argument can be any value that will be used to name the foreign object; it is first converted into a string, and then modified according to the given *subst*s list in sequence, where each element in this list is a list of a regular expression and a substitution string. Usually, **regexp-replace*** is used to perform the substitution, except for cases where the regular expression begins with a `~` or ends with a `$`, in which case **regexp-replace** is used.

For example, the following makes it convenient to define Racket bindings such as `foo-bar` for foreign names like `MyLib_foo_bar`:

```
(define mylib (ffi-lib "mylib"))  
(define-syntax defmyobj  
  (syntax-rules (:)  
    [(_ name : type ...)  
      (define name  
        (get-ffi-obj  
          (regexp-replaces 'name '(#rx"-" "_" )  
                             (#rx"^" "MyLib_")))  
          mylib (_fun type ...)))]))  
(defmyobj foo-bar : _int -> _int)
```

```
(list->cblock lst type) → any  
  lst : list?  
  type : c-type?
```

Allocates a memory block of an appropriate size, and initializes it using values from *lst* and the given *type*. The *lst* must hold values that can all be converted to C values according to the given *type*.

```
(vector->cblock vec type) → any  
  vec : vector?  
  type : type?
```

Like **list->cblock**, but for Racket vectors.

```
(vector->cpointer vec) → cpointer?
```

`vec` : `vector?`

Returns a pointer to an array of `_scheme` values, which is the internal representation of `vec`.

`(flvector->cpointer flvec)` → `cpointer?`
`flvec` : `flvector?`

Returns a pointer to an array of `_double` values, which is the internal representation of `flvec`.

`(saved-errno)` → `exact-integer?`

Returns the value most recently saved (in the current thread) after a foreign call with a non-`#f #:save-errno` option (see `_fun` and `_cprocedure`).

`(lookup-errno sym)` → `exact-integer?`
`sym` : `(or/c 'EINTR 'EEXIST 'EAGAIN)`

Returns a platform-specific value corresponding to a Posix `errno` symbol. The set of supported symbols is likely to expand in the future.

`(cast v from-type to-type)` → `any/c`
`v` : `any/c`
`from-type` : `ctype?`
`to-type` : `ctype?`

Converts `v` from a value matching `from-type` to a value matching `to-type`, where `(ctype-sizeof from-type)` matches `(ctype-sizeof to-type)`.

The conversion is equivalent to

```
(let ([p (malloc from-type)])
  (ptr-set! p from-type v)
  (ptr-ref p to-type))
```

`(cblock->list cblock type length)` → `list?`
`cblock` : `any/c`
`type` : `ctype?`
`length` : `exact-nonnegative-integer?`

Converts C `cblock`, which is a vector of `types`, to a Racket list. The arguments are the same as in the `list->cblock`. The `length` must be specified because there is no way to know where the block ends.

```
(cblock->vector cblock type length) → vector?  
  cblock : any/c  
  type : ctype?  
  length : exact-nonnegative-integer?
```

Like `cblock->vector`, but for Racket vectors.

7 Unexported Primitive Functions

Parts of the `ffi/unsafe` library are implemented by the Racket built-in `'%foreign` module. The `'%foreign` module is not intended for direct use, but it exports the following procedures. If you find any of these useful, please let us know.

```
(ffi-obj objname lib) → any
  objname : (or/c string? bytes? symbol?)
  lib : (or/c ffi-lib? path-string? #f)
```

Pulls out a foreign object from a library, returning a Racket value that can be used as a pointer. If a name is provided instead of a foreign-library value, `ffi-lib` is used to create a library object.

```
(ffi-obj? x) → boolean?
  x : any/c
(ffi-obj-lib obj) → ffi-lib?
  obj : ffi-obj?
(ffi-obj-name obj) → string?
  obj : ffi-obj?
```

A predicate for objects returned by `ffi-obj`, and accessor functions that return its corresponding library object and name. These values can also be used as C pointer objects.

```
(ctype-basetype type) → (or/c ctype? #f)
  type : ctype?
(ctype-scheme->c type) → procedure?
  type : ctype?
(ctype-c->scheme type) → procedure?
  type : ctype?
```

Accessors for the components of a C type object, made by `make-ctype`. The `ctype-basetype` selector returns a symbol for primitive types that names the type, a list of ctypes for cstructs, and another ctype for user-defined ctypes.

```
(ffi-call ptr in-types out-type [abi]) → any
  ptr : any/c
  in-types : (listof ctype?)
  out-type : ctype?
  abi : (or/c symbol/c #f) = #f
```

The primitive mechanism that creates Racket “callout” values. The given `ptr` (any pointer value, including `ffi-obj` values) is wrapped in a Racket-callable primitive function that

uses the types to specify how values are marshaled.

The optional `abi` argument determines the foreign ABI that is used. `#f` or `'default` will use a platform-dependent default; other possible values are `'stdcall` and `'sysv` (the latter corresponds to “cdecl”). This is especially important on Windows, where most system functions are `'stdcall`, which is not the default.

```
(ffi-callback proc
  in-types
  out-type
  [abi
   atomic?]) → ffi-callback?
proc : any/c
in-types : any/c
out-type : any/c
abi : (or/c symbol/c #f) = #f
atomic? : any/c = #f
```

The symmetric counterpart of `ffi-call`. It receives a Racket procedure and creates a callback object, which can also be used as a pointer. This object can be used as a C-callable function, which invokes `proc` using the types to specify how values are marshaled.

```
(ffi-callback? x) → boolean?
x : any/c
```

A predicate for callback values that are created by `ffi-callback`.

Index

[_?](#), 20
[_bitmask](#), 26
[_BOOL](#), 51
[_bool](#), 10
[_box](#), 21
[_byte](#), 9
[_bytes](#), 22
[_bytes/eof](#), 13
[_Class](#), 51
[_cpointer](#), 44
[_cpointer/null](#), 44
[_cprocedure](#), 15
[_cvector](#), 42
[_double](#), 10
[_double*](#), 10
[_enum](#), 26
[_f32vector](#), 41
[_f64vector](#), 41
[_file](#), 13
[_fixint](#), 10
[_fixnum](#), 10
[_float](#), 10
[_fpointer](#), 14
[_fun](#), 17
[_gcable](#), 14
[_gcpointer](#), 13
[_id](#), 51
[_int](#), 9
[_int16](#), 9
[_int32](#), 9
[_int64](#), 9
[_int8](#), 9
[_intptr](#), 10
[_Ivar](#), 57
[_list](#), 21
[_list-struct](#), 22
[_llong](#), 10
[_long](#), 10
[_objc_super](#), 57
[_or-null](#), 14
[_path](#), 11
[_pointer](#), 13
[_Protocol](#), 51
[_ptr](#), 20
[_racket](#), 14
[_s16vector](#), 37
[_s32vector](#), 38
[_s64vector](#), 39
[_s8vector](#), 36
[_sbyte](#), 9
[_scheme](#), 14
[_SEL](#), 51
[_short](#), 9
[_sint](#), 9
[_sint16](#), 9
[_sint32](#), 9
[_sint64](#), 9
[_sint8](#), 9
[_sintptr](#), 10
[_sllong](#), 10
[_slong](#), 10
[_sshort](#), 9
[_string](#), 12
[_string*/latin-1](#), 12
[_string*/locale](#), 12
[_string*/utf-8](#), 12
[_string/eof](#), 13
[_string/latin-1](#), 12
[_string/locale](#), 12
[_string/ucs-4](#), 11
[_string/utf-16](#), 11
[_string/utf-8](#), 12
[_sword](#), 9
[_symbol](#), 11
[_u16vector](#), 37
[_u32vector](#), 39
[_u64vector](#), 40
[_u8vector](#), 35
[_ubyte](#), 9
[_ufixint](#), 10
[_ufixnum](#), 10
[_uint](#), 9

- `_uint16`, 9
- `_uint32`, 9
- `_uint64`, 9
- `_uint8`, 9
- `_uintptr`, 10
- `_ullong`, 10
- `_ulong`, 10
- `_ushort`, 9
- `_uword`, 9
- `_vector`, 21
- `_void`, 11
- `_word`, 9
- Allocation and Finalization, 47
- `allocator`, 47
- `'atomic`, 32
- Atomic Execution, 48
- `'atomic-interior`, 32
- C Struct Types, 22
- C Types, 8
- C types*, 8
- `call-as-atomic`, 49
- `call-as-nonatomic`, 49
- `call-as-nonatomic-retry-point`, 49
- `cast`, 61
- `cblock->list`, 61
- `cblock->vector`, 62
- `class_addIvar`, 56
- `class_addMethod`, 56
- `compiler-sizeof`, 9
- `cpointer-has-tag?`, 45
- `cpointer-push-tag!`, 45
- `cpointer-tag`, 31
- `cpointer?`, 27
- `ctype->layout`, 8
- `ctype-alignof`, 8
- `ctype-basetype`, 63
- `ctype-c->scheme`, 63
- `ctype-scheme->c`, 63
- `ctype-sizeof`, 8
- `ctype?`, 8
- Custom Function Types, 19
- custom function types*, 19
- `cvector`, 42
- `cvector->list`, 43
- `cvector-length`, 42
- `cvector-ptr`, 43
- `cvector-ref`, 43
- `cvector-set!`, 43
- `cvector-type`, 43
- `cvector?`, 42
- `deallocator`, 48
- `default-_string-type`, 12
- `define-c`, 7
- `define-cpointer-type`, 45
- `define-cstruct`, 22
- `define-ffi-definer`, 45
- `define-fun-syntax`, 20
- `define-objc-class`, 53
- `define-objc-mixin`, 54
- Defining Bindings, 45
- Derived Utilities, 35
- dynamically loaded libraries, 5
- `end-atomic`, 48
- `end-breakable-atomic`, 49
- `end-stubborn-change`, 32
- Enumerations and Masks, 26
- `errno`, 16
- `'eternal`, 32
- `f32vector`, 40
- `f32vector->cpointer`, 41
- `f32vector->list`, 41
- `f32vector-length`, 40
- `f32vector-ref`, 40
- `f32vector-set!`, 40
- `f32vector?`, 40
- `f64vector`, 41
- `f64vector->cpointer`, 41
- `f64vector->list`, 41
- `f64vector-length`, 41
- `f64vector-ref`, 41
- `f64vector-set!`, 41
- `f64vector?`, 41
- `'failok`, 32
- FFI*, 1

- FFI Types and Constants, 51
- `ffi-call`, 63
- `ffi-callback`, 64
- `ffi-callback?`, 64
- `ffi-lib`, 5
- `ffi-lib?`, 5
- `ffi-obj`, 63
- `ffi-obj-lib`, 63
- `ffi-obj-name`, 63
- `ffi-obj-ref`, 7
- `ffi-obj?`, 63
- `ffi/cvector`, 42
- `ffi/objc`, 59
- `ffi/unsafe`, 1
- `ffi/unsafe/alloc`, 47
- `ffi/unsafe/atomic`, 48
- `ffi/unsafe/cvector`, 42
- `ffi/unsafe/define`, 45
- `ffi/unsafe/objc`, 50
- `ffi/unsafe/try-atomic`, 49
- `ffi/vector`, 35
- FFI: Racket Foreign Interface**, 1
- Fixed Auto-Converting String Types, 12
- `flvector->cpointer`, 61
- `free`, 32
- `free-immobile-cell`, 33
- Function Types, 15
- `function-ptr`, 19
- `get-ffi-obj`, 6
- `get-ivar`, 54
- `GetLastError`, 16
- `import-class`, 52
- `import-protocol`, 52
- `'interior`, 32
- Legacy Library, 59
- `list->cblock`, 60
- `list->cvector`, 43
- `list->f32vector`, 41
- `list->f64vector`, 41
- `list->s16vector`, 36
- `list->s32vector`, 38
- `list->s64vector`, 39
- `list->s8vector`, 36
- `list->u16vector`, 37
- `list->u32vector`, 39
- `list->u64vector`, 40
- `list->u8vector`, 35
- Loading Foreign Libraries, 5
- `lookup-errno`, 61
- `make-c-parameter`, 6
- `make-cstruct-type`, 22
- `make-ctype`, 8
- `make-cvector`, 42
- `make-cvector*`, 43
- `make-f32vector`, 40
- `make-f64vector`, 41
- `make-not-available`, 47
- `make-objc_super`, 57
- `make-s16vector`, 36
- `make-s32vector`, 38
- `make-s64vector`, 39
- `make-s8vector`, 35
- `make-sized-byte-string`, 34
- `make-u16vector`, 37
- `make-u32vector`, 38
- `make-u64vector`, 40
- `make-u8vector`, 35
- `malloc`, 31
- `malloc-immobile-cell`, 32
- `memcpy`, 30
- `memmove`, 29
- Memory Management, 31
- `memset`, 30
- Miscellaneous Support, 60
- `NO`, 51
- `'nonatomic`, 32
- Numeric Types, 9
- `objc-is-a?`, 55
- `objc-unsafe!`, 59
- `objc_allocateClassPair`, 55
- `objc_getProtocol`, 55
- `objc_lookupClass`, 55
- `objc_msgSend/typed`, 57
- `objc_msgSendSuper/typed`, 57

- [objc_registerClassPair](#), 56
- [object_getClass](#), 56
- [object_getInstanceVariable](#), 56
- [object_setInstanceVariable](#), 57
- Objective-C FFI, 50
- [offset-ptr?](#), 27
- Other Atomic Types, 10
- Other String Types, 13
- Overview, 4
- Pointer Dereferencing, 28
- Pointer Functions, 27
- Pointer Types, 13
- Primitive String Types, 11
- [provide-protected](#), 47
- [ptr-add](#), 27
- [ptr-add!](#), 28
- [ptr-equal?](#), 27
- [ptr-offset](#), 27
- [ptr-ref](#), 28
- [ptr-set!](#), 28
- ['raw](#), 32
- Raw Runtime Functions, 55
- [regexp-replaces](#), 60
- [register-finalizer](#), 33
- [releaser](#), 48
- [retainer](#), 48
- [s16vector](#), 36
- [s16vector->cpointer](#), 37
- [s16vector->list](#), 37
- [s16vector-length](#), 36
- [s16vector-ref](#), 36
- [s16vector-set!](#), 36
- [s16vector?](#), 36
- [s32vector](#), 38
- [s32vector->cpointer](#), 38
- [s32vector->list](#), 38
- [s32vector-length](#), 38
- [s32vector-ref](#), 38
- [s32vector-set!](#), 38
- [s32vector?](#), 38
- [s64vector](#), 39
- [s64vector->cpointer](#), 39
- [s64vector->list](#), 39
- [s64vector-length](#), 39
- [s64vector-ref](#), 39
- [s64vector-set!](#), 39
- [s64vector?](#), 39
- [s8vector](#), 36
- [s8vector->cpointer](#), 36
- [s8vector->list](#), 36
- [s8vector-length](#), 36
- [s8vector-ref](#), 36
- [s8vector-set!](#), 36
- [s8vector?](#), 36
- Safe C Vectors, 42
- Safe Homogenous Vectors, 35
- [saved-errno](#), 61
- [sel_registerName](#), 55
- [selector](#), 55
- [self](#), 54
- [set-cpointer-tag!](#), 31
- [set-ffi-obj!](#), 6
- [set-ivar!](#), 55
- [set-ptr-offset!](#), 28
- shared libraries, 5
- shared objects, 5
- Speculatively Atomic Execution, 49
- [start-atomic](#), 48
- [start-breakable-atomic](#), 49
- String Types, 11
- ['stubborn](#), 32
- [super-tell](#), 54
- Syntactic Forms and Procedures, 52
- Tagged C Pointer Types, 44
- [tell](#), 52
- [tellv](#), 52
- [try-atomic](#), 50
- Type Constructors, 8
- [u16vector](#), 37
- [u16vector->cpointer](#), 37
- [u16vector->list](#), 37
- [u16vector-length](#), 37
- [u16vector-ref](#), 37
- [u16vector-set!](#), 37

u16vector?, 37
u32vector, 38
u32vector->cpointer, 39
u32vector->list, 39
u32vector-length, 38
u32vector-ref, 38
u32vector-set!, 38
u32vector?, 38
u64vector, 40
u64vector->cpointer, 40
u64vector->list, 40
u64vector-length, 40
u64vector-ref, 40
u64vector-set!, 40
u64vector?, 40
u8vector, 35
u8vector->cpointer, 35
u8vector->list, 35
u8vector-length, 35
u8vector-ref, 35
u8vector-set!, 35
u8vector?, 35
'uncollectable', 32
Unexported Primitive Functions, 63
Variable Auto-Converting String Type, 12
vector->cblock, 60
vector->cpointer, 60
YES, 51