

# Framework: Racket GUI Application Framework

Version 5.1

Robert Bruce Findler  
and Matthew Flatt

February 14, 2011

`(require framework)`

The framework provides a number of mixins, classes and functions designed to help you build a complete application program on top of the `racket/gui` library.

- **Entire Framework**

- `(require framework)`

- This library provides all of the definitions and syntax described in this manual.

- `(require framework/framework-sig)`

- This library provides the signature definitions: `framework^`, and `framework-class^`. The `framework^` signature contains all of the names of the procedures described in this manual, except those that begin with `test:` and `gui-utils:`. The `framework-class^` signature contains all of the classes defined in this manual.

- `(require framework/framework-unit)`

- This library provides one `unit/sig`: `framework@`. It exports the signature `framework^`. It imports the `mred^` signature.

- **Test Suite Engine**

- `(require framework/test)`

- This library provides all of the definitions beginning with `test:` described in this manual.

- **GUI Utilities** `(require framework/gui-utils)`

- This libraries provides all of the definitions beginning with `gui-utils:` described in this manual.

- **Preferences** (require `framework/preferences`)

This library provides a subset of the names of the `framework.ss` library, namely those for manipulating preference settings and is designed to be used from `racket`.

The precise set of exported names is: `preferences:snapshot?`, `preferences:restore-prefs-snapshot`, `preferences:get-prefs-snapshot`, `exn:make-unknown-preference`, `exn:unknown-preference?`, `preferences:low-level-put-preferences`, `preferences:get`, `preferences:set`, `preferences:add-callback`, `preferences:set-default`, `preferences:set-un/marshall`, and `preferences:restore-defaults`.

- **Splash Screen** (require `framework/splash`)

This library provides support for a splash screen. See `framework/splash` for more.

- **Decorated Editor Snip** (require `framework/decorated-editor-snip`)

This library is here for backwards compatibility. The functionality in it has moved into the `framework` proper, in the §8 “Editor Snip” section.

## Thanks

Thanks to Shriram Krishnamurthi, Cormac Flanagan, Matthias Felleisen, Ian Barland, Gann Bierner, Richard Cobbe, Dan Grossman, Stephanie Weirich, Paul Steckler, Sebastian Good, Johnathan Franklin, Mark Krentel, Corky Cartwright, Michael Ernst, Kennis Koldewyn, Bruce Duba, and many others for their feedback and help.

# 1 Application

---

```
(application:current-app-name) → string?  
(application:current-app-name name) → void?  
  name : string?
```

This is a parameter specifying the name of the current application. It is used in the help menu (see [frame:standard-menus%](#)) and in frame titles (see [frame:editor%](#)). The first case in the case-lambda returns the current name, and the second case in the case-lambda sets the name of the application to *name*.

## 2 Autosave

---

`autosave:autosavable<%>` : interface?

Classes that implement this interface can be autosaved.

---

`(send an-autosave:autosavable do-autosave)` → void

This method is called when the object is registered to be autosaved (see `autosave:register`).

---

`(autosave:register obj)` → void?

`obj` : (and/c (is-a?/c autosave:autosavable<%>)  
(is-a?/c editor<%>))

Adds `obj` to the list of objects to be autosaved. When it is time to autosave, the `do-autosave` method of the object is called. This method is responsible for performing the autosave.

There is no need to de-register an object because the autosaver keeps a “weak” pointer to the object; i.e., the autosaver does not keep an object from garbage collection.

---

`(autosave:restore-autosave-files/gui)` → void?

Opens a GUI to ask the user about recovering any autosave files left around from crashes and things.

This function doesn’t return until the user has finished restoring the autosave files. (It uses `yield` to handle events however.)

### 3 Canvas

---

```
canvas:basic<%> : interface?  
  implements: editor-canvas%
```

---

```
canvas:basic-mixin : (class? . -> . class?)  
  argument extends/implements: editor-canvas%  
  result implements: canvas:basic<%>
```

---

```
canvas:color<%> : interface?  
  implements: canvas:basic<%>
```

Mixins that implement this interface initialize the background color of the canvas to the value of the `'framework:basic-canvas-background` preference. Adds a callback so that when that preference is modified, the background color changes.

---

```
canvas:color-mixin : (class? . -> . class?)  
  argument extends/implements: canvas:basic<%>  
  result implements: canvas:color<%>
```

---

```
canvas:delegate<%> : interface?  
  implements: canvas:basic<%>
```

This class is part of the delegate window implementation.

---

```
canvas:delegate-mixin : (class? . -> . class?)  
  argument extends/implements: canvas:basic<%>
```

result implements: `canvas:delegate<%>`

Provides an implementation of `canvas:delegate<%>`.

---

```
(send a-canvas:delegate on-superwindow-show shown?) → void  
shown? : boolean?
```

Overrides `on-superwindow-show` in `window<%>`.

Notifies the delegate window when the original window is visible. When invisible, the blue highlighting is erased.

---

```
canvas:info<%> : interface?  
implements: canvas:basic<%>
```

---

```
canvas:info-mixin : (class? . -> . class?)  
argument extends/implements: canvas:basic<%>  
result implements: canvas:info<%>
```

---

```
(send a-canvas:info on-focus) → void
```

Overrides `on-focus` in `editor-canvas%`.

sets the canvas that the frame displays info about.

---

```
(send a-canvas:info set-editor) → void
```

Overrides `set-editor` in `editor-canvas%`.

Calls `update-info` to update the frame's info panel.

---

```
canvas:wide-snip<%> : interface?  
implements: canvas:basic<%>
```

Any `canvas%` that matches this interface will automatically resize selected snips when it's size changes. Use `add-tall-snip` and `add-wide-snip` to specify which snips should be resized.

---

```
(send a-canvas:wide-snip recalc-snips) → void
```

Recalculates the sizes of the wide snips.

---

```
(send a-canvas:wide-snip add-wide-snip snip) → void
  snip : (instance snip%)
```

Snips passed to this method will be resized when the canvas's size changes. Their width will be set so they take up all of the space from their lefts to the right edge of the canvas.

---

```
(send a-canvas:wide-snip add-tall-snip snip) → void
  snip : (instance snip%)
```

Snips passed to this method will be resized when the canvas's size changes. Their height will be set so they take up all of the space from their tops to the bottom of the canvas.

---

```
canvas:wide-snip-mixin : (class? . -> . class?)
  argument extends/implements: canvas:basic<%>
  result implements: canvas:wide-snip<%>
```

This canvas maintains a list of wide and tall snips and adjusts their heights and widths when the canvas's size changes.

The result of this mixin uses the same initialization arguments as the mixin's argument.

---

```
(send a-canvas:wide-snip on-size width
                                     height) → void
  width : (integer-in 0 10000)
  height : (integer-in 0 10000)
```

Overrides `on-size` in `editor-canvas%`.

Adjusts the sizes of the marked snips.

See `add-wide-snip` and `add-tall-snip`.

---

```
canvas:basic% : class?
  superclass: (canvas:basic-mixin editor-canvas%)
```

---

```
canvas:color% : class?
  superclass: (canvas:color-mixin canvas:basic%)
```

---

```
canvas:info% : class?  
  superclass: (canvas:info-mixin canvas:basic%)
```

---

```
canvas:delegate% : class?  
  superclass: (canvas:delegate-mixin canvas:basic%)
```

---

```
canvas:wide-snip% : class?  
  superclass: (canvas:wide-snip-mixin canvas:basic%)
```



## 4 Color Model

---

```
(color-model:rgb->xyz r g b) → color-model:xyz?  
  r : number?  
  g : number?  
  b : number?
```

Converts a color represented as a red-green-blue tuple (each value from 0 to 255) into an XYZ tuple. This describes a point in the CIE XYZ color space.

---

```
(color-model:rgb-color-distance red-a  
                                green-a  
                                blue-a  
                                red-b  
                                green-b  
                                blue-b) → number?  
  
red-a : number?  
green-a : number?  
blue-a : number?  
red-b : number?  
green-b : number?  
blue-b : number?
```

This calculates a distance between two colors. The smaller the distance, the closer the colors should appear to the human eye. A distance of 10 is reasonably close that it could be called the same color.

This function is not symmetric in red, green, and blue, so it is important to pass red, green, and blue components of the colors in the proper order. The first three arguments are red, green and blue for the first color, respectively, and the second three arguments are red green and blue for the second color, respectively.

---

```
(color-model:xyz->rgb x y z) → (list/c number? number? number?)  
  x : number?  
  y : number?  
  z : number?
```

Converts an XYZ-tuple (in the CIE XYZ colorspace) into a list of values representing an RGB-tuple.

---

```
(color-model:xyz? val) → boolean?  
  val : any/c
```

Determines if *val* an xyz color record.

---

```
(color-model:xyz-x xyz) → number?  
xyz : color-model:xyz?
```

Extracts the x component of *xyz*.

---

```
(color-model:xyz-y xyz) → number?  
xyz : color-model:xyz?
```

Extracts the y component of *xyz*.

---

```
(color-model:xyz-z xyz) → number?  
xyz : color-model:xyz?
```

Extracts the z component of *xyz*.

## 5 Color Prefs

---

```
(color-prefs:set-default/color-scheme pref-sym
                                       black-on-white-color
                                       white-on-black-color)

→ void?
pref-sym : symbol?
black-on-white-color : (or/c (is-a?/c color%) string?)
white-on-black-color : (or/c (is-a?/c color%) string?)
```

Registers a preference whose value will be updated when the user clicks on one of the color scheme default settings in the preferences dialog.

Also calls `preferences:set-default` and `preferences:set-un/marshall` with appropriate arguments to register the preference.

---

```
(color-prefs:register-color-preference pref-name
                                       style-name
                                       color/sd
                                       [white-on-black-color])

→ void?
pref-name : symbol?
style-name : string?
color/sd : (or/c (is-a?/c color%) (is-a?/c style-delta%))
white-on-black-color : (or/c string? (is-a?/c color%) false/c)
                        = #f
```

This function registers a color preference and initializes the style list returned from `editor:get-standard-style-list`. In particular, it calls `preferences:set-default` and `preferences:set-un/marshall` to install the pref for *pref-name*, using *color/sd* as the default color. The preference is bound to a `style-delta%`, and initially the `style-delta%` changes the foreground color to *color/sd*, unless *color/sd* is a style delta already, in which case it is just used directly. Then, it calls `editor:set-standard-style-list-delta` passing the *style-name* and the current value of the preference *pref-name*.

Finally, it adds calls `preferences:add-callback` to set a callback for *pref-name* that updates the style list when the preference changes.

If *white-on-black-color* is not `#f`, then the color of the *color/sd* argument is used in combination with *white-on-black-color* to register this preference with `color-prefs:set-default/color-scheme`.

---

```
(color-prefs:add-background-preferences-panel) → void?
```

Adds a preferences panel that configures the background color for `editor:basic-mixin`.

---

```
(color-prefs:add-to-preferences-panel name
                                     func) → void?
  name : string?
  func : ((is-a?/c vertical-panel%) . -> . void?)
```

Calls `func` with the subpanel of the preferences coloring panel that corresponds to `name`.

---

```
(color-prefs:build-color-selection-panel parent
                                         pref-sym
                                         style-name
                                         example-text) → void?
  parent : (is-a?/c area-container<%>)
  pref-sym : symbol?
  style-name : string?
  example-text : string?
```

Builds a panel with a number of controls for configuring a font: the color and check boxes for bold, italic, and underline. The `parent` argument specifies where the panel will be placed. The `pref-sym` should be a preference (suitable for use with `preferences:get` and `preferences:set`). The `style-name` specifies the name of a style in the style list returned from `editor:get-standard-style-list` and `example-text` is shown in the panel so users can see the results of their configuration.

---

```
(color-prefs:marshall-style-delta style-delta) → printable/c
  style-delta : (is-a?/c style-delta%)
```

Builds a printed representation for a style-delta.

---

```
(color-prefs:unmarshall-style-delta marshalled-style-delta)
→ (or/c false/c (is-a?/c style-delta%))
  marshalled-style-delta : printable/c
```

Builds a style delta from its printed representation. Returns `#f` if the printed form cannot be parsed.

---

```
(color-prefs:white-on-black) → any
```

Sets the colors registered by `color-prefs:register-color-preference` to their white-on-black variety.

---

(`color-prefs:black-on-white`) → any

Sets the colors registered by `color-prefs:register-color-preference` to their black-on-white variety.

## 6 Color

---

```
color:text<%> : interface?
  implements: text:basic<%>
```

This interface describes how coloring is stopped and started for text that knows how to color itself. It also describes how to query the lexical and s-expression structure of the text.

---

```
(send a-color:text start-colorer token-sym->style
      get-token
      pairs)          → void
token-sym->style : (-> symbol? string?)
get-token : (or/c (-> input-port?
                  (values any/c
                          symbol?
                          (or/c false? symbol?)
                          exact-nonnegative-integer?
                          exact-nonnegative-integer?))
            (-> input-port?
                exact-nonnegative-integer?
                any/c
                (values any/c
                        symbol?
                        (or/c false? symbol?)
                        exact-nonnegative-integer?
                        exact-nonnegative-integer?
                        exact-nonnegative-integer?
                        any/c)))
pairs : (listof (list/p symbol? symbol?))
```

Starts tokenizing the buffer for coloring and parenthesis matching.

The *token-sym->style* argument will be passed the first return symbol from *get-token*, and it should return the style-name that the token should be colored.

The *get-token* argument takes an input port and optionally an offset and mode value. When it accepts just an input port, *get-token* returns the next token as 5 values:

- An unused value. This value is intended to represent the textual component of the token and may be used as such in the future.
- A symbol describing the type of the token. This symbol is transformed into a style-name via the *token-sym->style* argument. The symbols *'white-space* and *'comment* have special meaning and should always

be returned for white space and comment tokens respectively. The symbol `'no-color` can be used to indicate that although the token is not white space, it should not be colored. The symbol `'eof` must be used to indicate when all the tokens have been consumed.

- A symbol indicating how the token should be treated by the paren matcher or `#f`. This symbol should be in the `pairs` argument.
- The starting position of the token.
- The ending position of the token.

When `get-token` accepts an offset and mode value in addition to an input port, it must also return two extra results, which are a backup distance and new mode. The offset given to `get-token` can be added to the position of the input port to obtain absolute coordinates within a text stream. The mode argument allows `get-token` to communicate information from earlier parsing to later. When `get-token` is called for the beginning on a stream, the mode argument is `#f`; thereafter, the mode returned for the previous token is provided to `get-token` for the next token. The mode should not be a mutable value; if part of the stream is re-tokenized, the mode saved from the immediately preceding token is given again to the `get-token` function. The backup distance returned by `get-token` indicates the maximum number of characters to back up (counting from the start of the token) and for re-parsing after a change to the editor within the token's region.

The `get-token` function is usually implemented with a lexer using the `parser-tools/lex` library. The `get-token` function must obey the following invariants:

- Every position in the buffer must be accounted for in exactly one token, and every token must have a non-zero width.
- The token returned by `get-token` must rely only on the contents of the input port argument plus the mode argument. This constraint means that the tokenization of some part of the input cannot depend on earlier parts of the input except through the mode (and implicitly through the starting positions for tokens).
- A change to the stream must not change the tokenization of the stream prior to the token immediately preceding the change plus the backup distance. In the following example, this invariant does not hold for a zero backup distance: If the buffer contains

```
" 1 2 3
```

and the tokenizer treats the unmatched `"` as its own token (a string error token), and separately tokenizes the `1 2` and `3`, an edit to make the buffer look like

```
" 1 2 3"
```

would result in a single string token modifying previous tokens. To handle these situations, `get-token` can treat the first line as a single token, or it can precisely track backup distances.

The *pairs* argument is a list of different kinds of matching parens. The second value returned by *get-token* is compared to this list to see how the paren matcher should treat the token. An example: Suppose *pairs* is '(*(* (*|* *)* *|*) (*|* [*|* *]* *|*) (*begin* *end*))'. This means that there are three kinds of parens. Any token which has '*begin*' as its second return value will act as an open for matching tokens with '*end*'. Similarly any token with '*|* [*|* *]* *|*' will act as a closing match for tokens with '*|* [*|*'. When trying to correct a mismatched closing parenthesis, each closing symbol in *pairs* will be converted to a string and tried as a closing parenthesis.

---

```
(send a-color:text stop-colorer [clear-colors]) → void
clear-colors : boolean = #t
```

Stops coloring and paren matching the buffer.

If *clear-colors* is true all the text in the buffer will have its style set to Standard.

---

```
(send a-color:text force-stop-colorer stop?) → void
stop? : boolean?
```

Causes the entire tokenizing/coloring system to become inactive. Intended for debugging purposes only.

*stop?* determines whether the system is being forced to stop or allowed to wake back up.

---

```
(send a-color:text is-stopped?) → boolean?
```

Indicates if the colorer for this editor has been stopped, or not.

---

```
(send a-color:text is-frozen?) → boolean?
```

Indicates if this editor's colorer is frozen. See also *freeze-colorer* and *thaw-colorer*.

---

```
(send a-color:text freeze-colorer) → void
```

Keep the text tokenized and paren matched, but stop altering the colors.

*freeze-colorer* will not return until the coloring/tokenization of the entire text is brought up-to-date. It must not be called on a locked text.

---

```
(send a-color:text thaw-colorer [recolor
retokenize]) → void
```

```
recolor : boolean = #t
retokenize : boolean = #f
```

Start coloring a frozen buffer again.

If *recolor?* is *#t*, the text is re-colored. If it is *#f* the text is not re-colored. When *recolor?* is *#t*, *retokenize?* controls how the text is re-colored. *#f*



causes the text to be entirely re-colored before `thaw-colorer` returns using the existing tokenization. `#t` causes the entire text to be retokenized and re-colored from scratch. This will happen in the background after the call to `thaw-colorer` returns.

---

```
(send a-color:text reset-region start end) → void
start : natural-number?
end : (union 'end natural-number?)
```

Set the region of the text that is tokenized.

---

```
(send a-color:text reset-regions regions) → void
regions : (listof (list number (union 'end number)))
```

Sets the currently active regions to be *regions*.

---

```
(send a-color:text get-regions)
→ (listof (list number (union 'end number)))
```

This returns the list of regions that are currently being colored in the editor.

---

```
(send a-color:text skip-whitespace position
                                direction
                                comments?) → natural-number?
position : natural-number?
direction : (symbols 'forward 'backward)
comments? : boolean?
```

Returns the next non-whitespace character.

Starts from *position* and skips whitespace in the direction indicated by *direction*. If *comments?* is true, comments are skipped as well as whitespace. `skip-whitespace` determines whitespaces and comments by comparing the token type to `'white-space` and `'comment`.

Must only be called while the tokenizer is started.

---

```
(send a-color:text backward-match position
                                cutoff)
→ (union natural-number? false?)
position : natural-number?
cutoff : natural-number?
```

Skip all consecutive whitespaces and comments (using `skip-whitespace`) immediately preceding the position. If the token at this position is a close, return the position of the matching open, or `#f` if there is none. If the token was an open, return `#f`. For any other token, return the start of that token.

Must only be called while the tokenizer is started.

---

```
(send a-color:text backward-containing-sexp position
                                     cutoff)
```

```
→ (union natural-number? false?)
   position : natural-number?
   cutoff   : natural-number?
```

Return the starting position of the interior of the (non-atomic) s-expression containing position, or #f if there is none.

Must only be called while the tokenizer is started.

---

```
(send a-color:text forward-match position
                                     cutoff)
```

```
→ (union natural-number? false?)
   position : natural-number?
   cutoff   : natural-number?
```

Skip all consecutive whitespaces and comments (using `skip-whitespace`) immediately following position. If the token at this position is an open, return the position of the matching close, or #f if there is none. For any other token, return the end of that token.

Must only be called while the tokenizer is started.

---

```
(send a-color:text insert-close-paren position
                                     char
                                     flash?
                                     fixup?) → void
```

```
position : natural-number?
char      : char?
flash?   : boolean?
fixup?   : boolean?
```

The `position` is the place to put the parenthesis, and `char` is the parenthesis to be added (e.g., that the user typed). If `fixup?` is true, the right kind of closing parenthesis will be chosen from the set previously passed to `start-colorer`—but only if an inserted `char` would be colored as a parenthesis (i.e., with the `'parenthesis` classification). Otherwise, `char` will be inserted, even if it is not the right kind. If `flash?` is true, the matching open parenthesis will be flashed.

---

```
(send a-color:text classify-position position) → symbol?
position : exact-nonnegative-integer?
```

Return a symbol for the lexer-determined token type for the token that contains the item after `position`.

Must only be called while the tokenizer is started.

---

```
(send a-color:text get-token-range position)
→ (or/c #f exact-nonnegative-integer?)
   (or/c #f exact-nonnegative-integer?)
   position : exact-nonnegative-integer?
```

Returns the range of the token surrounding *position*, if there is a token there.

This method must be called only when the tokenizer is started.

---

```
(send a-color:text on-lexer-valid valid?) → any
valid? : boolean?
```

Augments <method not found>.

This method is an observer for when the lexer is working. It is called when the lexer's state changes from valid to invalid (and back). The *valid?* argument indicates if the lexer has finished running over the editor (or not).

The default method just returns (*void*).

---

```
(send a-color:text is-lexer-valid?) → boolean?
```

Indicates if the lexer is currently valid for this editor.

---

```
color:text-mixin : (class? . -> . class?)
argument extends/implements: text:basic<%>
result implements: color:text<%>
```

Adds the functionality needed for on-the-fly coloring and parenthesis matching based on incremental tokenization of the text.

---

```
(send a-color:text lock) → void
```

Overrides *lock* in *editor*<%>.

---

```
(send a-color:text on-focus) → void
```

Overrides *on-focus* in *editor*<%>.

---

```
(send a-color:text after-edit-sequence) → void
```

Augments *after-edit-sequence* in *editor*<%>.

---

```
(send a-color:text after-set-position) → void
```

Augments *after-set-position* in *text*%.

---

```
(send a-color:text after-change-style) → void
```

---

Augments `after-change-style` in `text%`.

---

```
(send a-color:text on-set-size-constraint) → void
```

Augments `on-set-size-constraint` in `text%`.

---

```
(send a-color:text after-insert) → void
```

Augments `after-insert` in `text%`.

---

```
(send a-color:text after-delete) → void
```

Augments `after-delete` in `text%`.

---

```
color:text% : class?
```

```
superclass: (color:text-mixin text:keymap%)
```

---

```
color:text-mode<%> : interface?
```

---

```
color:text-mode-mixin : (class? . -> . class?)
```

```
argument extends/implements: mode:surrogate-text<%>
```

```
result implements: color:text-mode<%>
```

This mixin adds coloring functionality to the mode.

---

```
(new color:text-mode-mixin
  [[get-token get-token]
   [token-sym->style token-sym->style]
   [matches matches]])
→ (is-a?/c color:text-mode-mixin)
get-token : lexer = default-lexer
token-sym->style : (symbol? . -> . string?)
                  = (λ (x) "Standard")
matches : (listof (list/c symbol? symbol?)) = null
```

The arguments are passed to `start-colorer`.

---

```
(send a-color:text-mode on-disable-surrogate) → void
```

Overrides `on-disable-surrogate` in `mode:surrogate-text<%>`.

---

`(send a-color:text-mode on-enable-surrogate) → void`

Overrides `on-enable-surrogate` in `mode:surrogate-text<%>`.

---

`color:text-mode% : class?`

superclass: `(color:text-mode-mixin mode:surrogate-text%)`

## 7 Comment Box

---

```
comment-box:snip% : class?  
  superclass: editor-snip:decorated%  
  extends: readable-snip<%>
```

This snippet implements the comment boxes that you see in DrRacket.

---

```
(send a-comment-box:snip make-editor) → (is-a?/c text%)
```

Overrides `make-editor` in `editor-snip:decorated%`.

Makes an instance of

```
(scheme:text-mixin text:keymap%)
```

---

```
(send a-comment-box:snip make-snip) → (is-a?/c comment-snip%)
```

Overrides `make-snip` in `editor-snip:decorated%`.

Returns an instance of the `comment-snip%` class.

---

```
(send a-comment-box:snip get-corner-bitmap)
```

```
→ (is-a?/c bitmap%)
```

Overrides `get-corner-bitmap` in `editor-snip:decorated-mixin`.

Returns the semicolon bitmap from the file

```
(build-path (collection-path "icons") "semicolon.gif")
```

---

```
(send a-comment-box:snip get-position)
```

```
→ (symbols 'left-top 'top-right)
```

Overrides `get-position` in `editor-snip:decorated-mixin`.

Returns `'left-top`

---

```
(send a-comment-box:snip get-text) → string
```

Overrides `get-text` in `snip%`.

Returns the same string as the super method, but with newlines replaced by `newline-semicolon-space`.

---

```
(send a-comment-box:snip get-menu) → (is-a?/c popup-menu%)
```

Overrides `get-menu` in `editor-snip:decorated-mixin`.

Returns a menu with a single item to change the box into semicolon comments.

## 8 Editor Snip

---

`editor-snip:decorated<%>` : interface?  
implements: `editor-snip%`

---

`(send an-editor-snip:decorated get-corner-bitmap)`  
→ `(or/c false/c (is-a?/c bitmap%))`  
Returns a bitmap that is drawn in the upper-right corner of this snip.

---

`(send an-editor-snip:decorated get-color)`  
→ `(or/c string? (is-a?/c color%))`  
Returns the color used to draw the background part of the snip.

---

`(send an-editor-snip:decorated get-menu)`  
→ `(or/c false/c (is-a?/c popup-menu%))`  
Returns a popup menu that is used when clicking on the top part of the snip.

---

`(send an-editor-snip:decorated get-position)`  
→ `(symbols 'top-right 'left-top)`  
Returns the location of the image and the clickable region. The symbol `'top-right` indicates top portion is clickable and icon on right. The symbol `'left-top` means left portion is clickable and icon on top.

---

`(send an-editor-snip:decorated reset-min-sizes)` → `void?`  
Sets the minimum sizes based on the result of `get-corner-bitmap`.

---

`editor-snip:decorated-mixin` : `(class? . -> . class?)`  
argument extends/implements: `editor-snip%`  
result implements: `editor-snip:decorated<%>`

---

`(send an-editor-snip:decorated get-corner-bitmap)`  
→ `(or/c false/c (is-a?/c bitmap%))`  
Returns `#f`.

---

`(send an-editor-snip:decorated get-color)`  
→ `(or/c string? (is-a?/c color%))`  
Returns

```
(if (preferences:get 'framework:white-on-black?)
    "white"
    "black")
```

---

```
(send an-editor-snip:decorated get-menu)
→ (or/c false/c (is-a?/c popup-menu%))
```

Returns #f.

---

```
(send an-editor-snip:decorated get-position)
→ (symbols 'top-right 'left-top)
```

Returns 'top-right.

---

```
editor-snip:decorated% : class?
superclass: (editor-snip:decorated-mixin editor-snip%)
```

---

```
(new editor-snip:decorated% ...superclass-args...)
→ (is-a?/c editor-snip:decorated%)
```

Invokes the super constructor with the keyword `editor` as a call to `make-editor`.

---

```
(send an-editor-snip:decorated make-snip)
→ (is-a?/c editor-snip:decorated%)
```

This method should return an instance of the class it is invoked in. If you create a subclass of this class, be sure to override this method and have it create instances of the subclass.

---

```
(send an-editor-snip:decorated make-editor)
→ (is-a?/c editor<?>)
```

Creates an editor to be used in this snip.

---

```
(send an-editor-snip:decorated copy)
→ (is-a?/c editor-snip:decorated%)
```

Uses the `make-editor` and `make-snip` methods to create a copy of this snip, as follows:

```
#lang (let ([snip (make-snip)]) (send snip set-editor
(send (get-editor) copy-self)) (send snip set-style (get-
style)) snip)
```

---

```
editor-snip:decorated-snipclass% : class?
superclass: snip-class%
```



---

```
(send an-editor-snip:decorated-snipclass make-snip stream-in)
→ -editor-snip:decorated<%>
   stream-in : (is-a?/c editor-stream-in%)
```

Returns an instance of `editor-snip:decorated%`.

---

```
(send an-editor-snip:decorated-snipclass read stream-in)
→ editor-snip:decorated<%>
   stream-in : (is-a?/c editor-stream-in%)
```

Calls `make-snip` to get an object and then invokes its `editor<%>`'s `read-from-file` method in order to read a snip from `stream-in`, eg:

```
(let ([snip (make-snip stream-in)])
  (send (send snip get-editor) read-from-file stream-
in #f)
  snip)
```

## 9 Editor

---

```
editor:basic<%> : interface?  
  implements: editor<%>
```

Classes matching this interface support the basic `editor<%>` functionality required by the framework.

---

```
(send an-editor:basic has-focus?) → boolean?
```

This function returns `#t` when the editor has the keyboard focus. It is implemented using: `on-focus`

---

```
(send an-editor:basic local-edit-sequence?) → boolean?
```

Indicates if this editor is in an edit sequence. Enclosing buffer's edit-sequence status is not considered by this method.

See `begin-edit-sequence` and `end-edit-sequence` for more info about edit sequences.

---

```
(send an-editor:basic run-after-edit-sequence thunk  
                                     [tag]) → void
```

```
thunk : (-> void)
```

```
tag : (union symbol? |#f|) = |#f|
```

This method is used to install callbacks that will be run after any edit-sequence completes.

The procedure `thunk` will be called immediately if the edit is not in an edit-sequence. If the edit is in an edit-sequence, it will be called when the edit-sequence completes.

If `tag` is a symbol, the `thunk` is keyed on that symbol, and only one thunk per symbol will be called after the edit-sequence. Specifically, the last call to `run-after-edit-sequence`'s argument will be called.

---

```
(send an-editor:basic get-top-level-window)  
→ (union |#f| (is-a?/c top-level-window<%>))
```

Returns the `top-level-window<%>` currently associated with this buffer.

This does not work for embedded editors.

---

```
(send an-editor:basic save-file-out-of-date?) → boolean?
```

Returns `#t` if the file on disk has been modified, by some other program.

---

```
(send an-editor:basic save-file/gui-error [filename
                                          format
                                          show-errors?])

→ boolean?
filename : (union path |#f|) = |#f|
format : (union 'guess 'standard 'text 'text-force-cr same copy)
         = 'same
show-errors? : boolean = |#t|
```

This method is an alternative to `save-file`. Rather than showing errors via the original stdout, it opens a dialog with an error message showing the error.

The result indicates if an error happened (the error has already been shown to the user). It returns `#t` if no error occurred and `#f` if an error occurred.

---

```
(send an-editor:basic load-file/gui-error [filename
                                          format
                                          show-errors?])

→ boolean?
filename : (union string |#f|) = |#f|
format : (union 'guess 'standard 'text 'text-force-cr 'same 'copy)
         = 'guess
show-errors? : boolean = |#t|
```

This method is an alternative to `load-file`. Rather than showing errors via the original stdout, it opens a dialog with an error message showing the error.

The result indicates if an error happened (the error has already been shown to the user). It returns `#t` if no error occurred and `#f` if an error occurred.

---

```
(send an-editor:basic on-close) → void
```

This method is called when an editor is closed. Typically, this method is called when the frame containing the editor is closed, but in some cases an editor is considered “closed” before the frame it is in is closed (e.g., when a tab in DrRacket is closed), and thus `on-close` will be called at that point.

See also `can-close?` and `close`.

Does nothing.

---

```
(send an-editor:basic can-close?) → boolean?
```

This method is called to query the editor if is okay to close the editor. Although there is no visible effect associated with closing an editor, there may be some cleanup actions that need to be run when the user is finished with the editor (asking if it should be saved, for example).

See also `on-close` and `close`.

Returns `#t`.

---

```
(send an-editor:basic close) → boolean?
```

This method is merely

```
(if (can-close?)
    (begin (on-close) #t)
    #f)
```

It is intended as a shorthand, helper method for closing an editor. See also [can-close?](#) and [on-close](#).

---

```
(send an-editor:basic get-filename/untitled-name) → string
```

Returns the printed version of the filename for this editor. If the editor doesn't yet have a filename, it returns a symbolic name (something like "Untitled").

---

```
(send an-editor:basic get-pos/text event)
→ (or/c false/c (is-a?/c editor<%>))
   (or/c false/c number?)
event : (is-a?/c mouse-event%)
```

This method's first result is `#f` when the mouse event does not correspond to a location in the editor.

If the first result is an `text%` object, then the second result will be a position in the editor and otherwise the second result will be `#f`.

The `editor<%>` object will always be the nearest enclosing editor containing the mouse click.

---

```
editor:basic-mixin : (class? . -> . class?)
argument extends/implements: editor<%>
result implements: editor:basic<%>
```

This provides the basic editor services required by the rest of the framework.

The result of this mixin uses the same initialization arguments as the mixin's argument.

Each instance of a class created with this mixin contains a private `keymap%` that is chained to the global keymap via: `(send keymap chain-to-keymap (keymap:get-global) #f)`.

This installs the global keymap `keymap:get-global` to handle keyboard and mouse mappings not handled by `keymap`. The global keymap is created when the framework is invoked.

---

```
(send an-editor:basic can-save-file? filename
      format) → boolean?
```

`filename` : `string`  
`format` : `symbol?`

Augments `can-save-file?` in `editor<%>`.

Checks to see if the file on the disk has been modified out side of this editor, using `save-file-out-of-date?`. If it has, this method prompts the user to be sure they want to save.

---

`(send an-editor:basic after-save-file success?)` → `void`  
`success?` : `boolean?`

Augments `after-save-file` in `editor<%>`.

If the current filename is not a temporary filename, this method calls `handler:add-to-recent` with the current filename.

to add the new filename to the list of recently opened files.

Additionally, updates a private instance variable with the modification time of the file, for using in implementing `save-file-out-of-date?`.

---

`(send an-editor:basic after-load-file success?)` → `void`  
`success?` : `boolean?`

Augments `after-load-file` in `editor<%>`.

Updates a private instance variable with the modification time of the file, for using in implementing `save-file-out-of-date?`

---

`(send an-editor:basic on-focus on?)` → `void`  
`on?` : `boolean?`

Overrides `on-focus` in `editor<%>`.

Manages the state to implement `has-focus?`

---

`(send an-editor:basic on-edit-sequence)` → `boolean?`

Augments `on-edit-sequence` in `editor<%>`.

Always returns `#t`. Updates a flag for `local-edit-sequence?`

---

`(send an-editor:basic after-edit-sequence)` → `void`

Augments `after-edit-sequence` in `editor<%>`.

Helps to implement `run-after-edit-sequence`.

---

`(send an-editor:basic on-new-box type)`  
→ `(instance editor-snip%)`  
`type` : `(union 'pasteboard 'text)`

Overrides `on-new-box` in `editor<%>`.

Creates instances of `pasteboard:basic%` or `text:basic%` instead of the built in `pasteboard%` and `text%` classes.

---

```
(send an-editor:basic on-new-image-snip filename
                                   kind
                                   relative-path?
                                   inline?)

→ (is-a?/c image-snip%)
   filename : (or/c path? false/c)
   kind : (one-of/c 'unknown 'gif 'jpeg 'xbm 'xpm 'bmp 'pict)
   relative-path? : any/c
   inline? : any/c

   Overrides on-new-image-snip in editor<%>.
   (super on-new-image-snip
          (if (eq? kind 'unknown) 'unknown/mask kind)
          relative-path?
          inline?))
```

---

```
(send an-editor:basic get-file directory) → string
   directory : (or/c path-string? false/c)

   Overrides get-file in editor<%>.

   Uses finder:get-file to find a filename. Also, sets the parameter
   finder:dialog-parent-parameter to the result of get-top-level-window.
```

---

```
(send an-editor:basic put-file directory
                               default-name) → string
   directory : (or/c path? false/c)
   default-name : (or/c path? false/c)

   Overrides put-file in editor<%>.

   Uses finder:put-file to find a filename. Also, sets the parameter
   finder:dialog-parent-parameter to the result of get-top-level-window.
```

---

```
editor:standard-style-list<%> : interface?
  implements: editor<%>
```

This interface is implemented by the results of `editor:standard-style-list-mixin`.

---

```
editor:standard-style-list-mixin : (class? . -> . class?)
```

argument extends/implements: `editor<%>`  
result implements: `editor:standard-style-list<%>`

The mixin adds code to the initialization of the class that sets the editor's style list (via `set-style-list`) to the result of `editor:get-standard-style-list`.

In addition, it calls `set-load-overwrites-styles` with `#f`. This ensures that saved files with different settings for the style list do not clobber the shared style list.

---

`editor:keymap<%>` : interface?  
implements: `editor:basic<%>`

Classes matching this interface add support for mixing in multiple keymaps. They provides an extensible interface to chained keymaps, through the `get-keymaps` method.

This editor is initialized by calling `add-editor-keymap-functions`, `add-text-keymap-functions`, and `add-pasteboard-keymap-functions`.

---

(send *an-editor:keymap* `get-keymaps`)  
→ (list-of (instance *keymap%*))

The keymaps returned from this method are chained to this `editor<%>`'s keymap.

The result of this method should not change – that is, it should return the same list of keymaps each time it is called.

See also `editor:add-after-user-keymap`.

Defaultly returns (list (`keymap:get-user`) (`keymap:get-global`))

---

`editor:keymap-mixin` : (class? . -> . class?)  
argument extends/implements: `editor:basic<%>`  
result implements: `editor:keymap<%>`

This provides a mixin that implements the `editor:keymap<%>` interface.

---

`editor:autowrap<%>` : interface?  
implements: `editor:basic<%>`

Classes implementing this interface keep the `auto-wrap` state set based on the `'framework:auto-set-wrap?` preference (see `preferences:get` for more information about preferences).

They install a preferences callback with `preferences:add-callback` that sets the state when the preference changes and initialize the value of `auto-wrap` to the current value of `'framework:auto-set-wrap?` via `preferences:get`.

---

```
editor:autowrap-mixin : (class? . -> . class?)  
  argument extends/implements: editor:basic<%>  
  result implements: editor:autowrap<%>
```

See `editor:autowrap<%>`

---

```
editor:file<%> : interface?  
  implements: editor:keymap<%>
```

Objects supporting this interface are expected to support files.

---

```
(send an-editor:file get-can-close-parent)  
→ (union false (is-a/c? frame%) (is-a/c? dialog%))
```

The result of this method is used as the parent for the dialog that asks about closing.

Defaultly returns `#f`.

---

```
(send an-editor:file update-frame-filename) → void
```

Attempts to find a frame that displays this editor. If it does, it updates the frame's title based on a new filename in the editor.

---

```
(send an-editor:file allow-close-with-no-filename?) → boolean?
```

This method indicates if closing the file when it hasn't been saved is a reason to alert the user. See also `can-close?`.

Defaultly returns `#f`.

---

```
(send an-editor:file user-saves-or-not-modified? allow-cancel?)  
→ boolean?
```



`allow-cancel?` : #t

If the file has not been saved, this prompts the user about saving and, if the user says to save, then it saves the file.

The result is #t if the save file is up to date, or if the user says it is okay to continue without saving. Generally used when closing the file or quitting the app.

---

`editor:file-mixin` : (class? . -> . class?)  
argument extends/implements: `editor:keymap<%>`  
result implements: `editor:file<%>`

This editor locks itself when the file that is opened is read-only in the filesystem.

The class that this mixin produces uses the same initialization arguments as it's input.

---

(send `an-editor:file` `set-filename` `name`  
[`temp?`]) → void

`name` : string  
`temp?` : boolean = |#f|

Overrides `set-filename` in `editor<%>`.

Updates the filename on each frame displaying this editor, for each frame that matches `frame:editor<%>`.

---

(send `an-editor:file` `can-close?`) → boolean?

Augments `can-close?` in `editor:basic<%>`.

If the `allow-close-with-no-filename?` method returns #f, this method checks to see if the file has been saved at all yet. If not, it asks the user about saving (and saves if they ask).

If the `allow-close-with-no-filename?` method returns #t, this method does as before, except only asks if the editor's `get-filename` method returns a path.

Also calls inner.

---

(send `an-editor:file` `get-keymaps`)  
→ (list-of (instance `keymap%`))

Overrides `get-keymaps` in `editor:keymap<%>`.

This returns a list containing the super-class's keymaps, plus the result of `keymap:get-file`

---

```
editor:backup-autosave<%> : interface?  
  implements: editor:basic<%>
```

Classes matching this interface support backup files and autosaving.

---

```
(send an-editor:backup-autosave backup?) → boolean?
```

Indicates weather this `editor<%>` should be backed up.  
Returns the value of the `preferences:get` applied to `'framework:backup-files?`.

---

```
(send an-editor:backup-autosave autosave?) → boolean?
```

Indicates weather this `editor<%>` should be autosaved.  
Returns `#t`.

---

```
(send an-editor:backup-autosave do-autosave)  
→ (union |#f| string)
```

This method is called to perform the autosaving. See also `autosave:register`  
When the file has been modified since it was last saved and autosaving it turned on (via the `autosave?` method) an autosave file is created for this `editor<%>`.  
Returns the filename where the autosave took place, or `#f` if none did.

---

```
(send an-editor:backup-autosave remove-autosave) → void
```

This method removes the autosave file associated with this `editor<%>`.

---

```
editor:backup-autosave-mixin : (class? . -> . class?)  
  argument extends/implements: editor:basic<%>  
  result implements: editor:backup-autosave<%>  
                    autosave:autosavable<%>
```

This mixin adds backup and autosave functionality to an editor.

During initialization, this object is registered with `autosave:register`.

The result of this mixin uses the same initialization arguments as the mixin's argument.

---

```
(send an-editor:backup-autosave on-save-file filename  
                                         format) → bool  
  
filename : path?  
format : (one-of/c 'guess 'standard 'text 'text-force-cr 'same 'copy)
```

Augments `on-save-file` in `editor<%>`.

If a backup file has not been created this session for this file, deletes any existing backup file and copies the old save file into the backup file. For the backup file's name, see `path-utils:generate-backup-name`

---

```
(send an-editor:backup-autosave on-close) → void
```

Augments `on-close` in `editor:basic<%>`.

Deletes the autosave file and turns off autosaving.

---

```
(send an-editor:backup-autosave on-change) → void
```

Augments `on-change` in `editor<%>`.

Sets a flag indicating that this `editor<%>` needs to be autosaved.

---

```
(send an-editor:backup-autosave set-modified modified?) → void  
modified? : any/c
```

Overrides `set-modified` in `editor<%>`.

If the file is no longer modified, this method deletes the autosave file. If it is, it updates a flag to indicate that the autosave file is out of date.

---

```
editor:info<%> : interface?  
implements: editor:basic<%>
```

An `editor<%>` matching this interface provides information about its lock state to its `top-level-window<%>`.

---

```
editor:info-mixin : (class? . -> . class?)  
argument extends/implements: editor:basic<%>  
result implements: editor:info<%>
```

This editor tells the frame when it is locked and unlocked. See also `frame:text-info<%>`.

---

```
(send an-editor:info lock lock?) → void  
lock? : boolean?
```

Overrides `lock` in `editor<%>`.

Uses `run-after-edit-sequence` to call `lock-status-changed`.

---

```
(editor:set-default-font-color color) → void?  
  color : (is-a?/c color%)
```

Sets the color of the style named `editor:get-default-color-style-name`.

---

```
(editor:get-default-color-style-name) → string?
```

The name of the style (in the list returned by `editor:get-standard-style-list`) that holds the default color.

---

```
(editor:set-standard-style-list-delta name  
                                     delta) → void?  
  name : string?  
  delta : (is-a?/c style-delta%)
```

Finds (or creates) the style named by *name* in the result of `editor:get-standard-style-list` and sets its delta to *delta*.

If the style named by *name* is already in the style list, it must be a delta style.

---

```
(editor:set-standard-style-list-pref-callbacks) → any
```

Installs the font preference callbacks that update the style list returned by `editor:get-standard-style-list` based on the font preference symbols.

---

```
(editor:get-standard-style-list) → (is-a?/c style-list%)
```

Returns a style list that is used for all instances of `editor:standard-style-list`.

---

```
(editor:add-after-user-keymap keymap  
                             keymaps)  
→ (listof (is-a?/c keymap%)  
  keymap : (is-a?/c keymap%)  
  keymaps : (listof (is-a?/c keymap%)
```

Returns a list that contains all of the keymaps in *keymaps*, in the same relative order, but also with *keymap*, where *keymap* is now the first keymap after `keymap:get-user` (if that keymap is in the list.)

## 10 Exit

---

`(exit:exiting?) → boolean?`

Returns `#t` to indicate that an exit operation is taking place. Does not indicate that the app will actually exit, since the user may cancel the exit.

See also `exit:insert-on-callback` and `exit:insert-can?-callback`.

---

`(exit:set-exiting exiting?) → void?`  
`exiting? : boolean?`

Sets a flag that affects the result of `exit:exiting?`.

---

`(exit:insert-on-callback callback) → (-> void?)`  
`callback : (-> void?)`

Adds a callback to be called when exiting. This callback must not fail. If a callback should stop an exit from happening, use `exit:insert-can?-callback`.

---

`(exit:insert-can?-callback callback) → (-> void?)`  
`callback : (-> boolean?)`

Use this function to add a callback that determines if an attempted exit can proceed. This callback should not clean up any state, since another callback may veto the exit. Use `exit:insert-on-callback` for callbacks that clean up state.

---

`(exit:can-exit?) → boolean?`

Calls the “can-callbacks” and returns their results. See `exit:insert-can?-callback` for more information.

---

`(exit:on-exit) → void?`

Calls the “on-callbacks”. See `exit:insert-on-callback` for more information.

---

`(exit:exit) → any`

`exit:exit` performs four actions:

- sets the result of the `exit:exiting?` function to `#t`.

- invokes the exit-callbacks, with `exit:can-exit?` if none of the “can?” callbacks return `#f`,
- invokes `exit:on-exit` and then
- queues a callback that calls `exit` (a racket procedure) and (if `exit` returns) sets the result of `exit:exiting?` back to `#t`.

---

`(exit:user-oks-exit)` → `boolean?`

Opens a dialog that queries the user about exiting. Returns the user’s decision.

## 11 Finder

---

```
(finder:dialog-parent-parameter)
→ (or/c false/c (is-a?/c dialog%) (is-a?/c frame%))
(finder:dialog-parent-parameter parent) → void?
  parent : (or/c false/c (is-a?/c dialog%) (is-a?/c frame%))
```

This parameter determines the parent of the dialogs created by `finder:get-file`, `finder:put-file`, `finder:common-get-file`, `finder:common-put-file`, `finder:common-get-file-list`, `finder:std-get-file`, and `finder:std-put-file`.

---

```
(finder:default-extension) → string?
(finder:default-extension extension) → void?
  extension : string?
```

This parameter controls the default extension for the framework's `finder:put-file` dialog. Its value gets passed as the `default-extension` argument to `put-file`.

Its default value is "".

---

```
(finder:default-filters) → (listof (list/c string? string?))
(finder:default-filters filters) → void?
  filters : (listof (list/c string? string?))
```

This parameter controls the default filters for the framework's `finder:put-file` dialog. Its value gets passed as the `default-filters` argument to `put-file`.

Its default value is `'(("Any" "*.*"))`.

---

```
(finder:common-put-file [name
                        directory
                        replace?
                        prompt
                        filter
                        filter-msg
                        parent]) → (or/c false/c path?)
  name : string? = "Untitled"
  directory : (or/c false/c path?) = #f
  replace? : boolean? = #f
  prompt : string? = "Select File"
  filter : (or/c false/c byte-regexp?) = #f
```

```

filter-msg : string?
            = "That filename does not have the right form."
parent : (or/c (is-a?/c top-level-window<%>) false/c)
        = (finder:dialog-parent-parameter)

```

This procedure queries the user for a single filename, using a platform-independent dialog box. Consider using `finder:put-file` instead of this function.

---

```

(finder:common-get-file [directory
                        prompt
                        filter
                        filter-msg
                        parent]) → (or/c path? false/c)
directory : (or/c path? false/c) = #f
prompt : string? = "Select File"
filter : (or/c byte-regexp? false/c) = #f
filter-msg : string?
            = "That filename does not have the right form."
parent : (or/c false/c (is-a?/c top-level-window<%>)) = #f

```

This procedure queries the user for a single filename, using a platform-independent dialog box. Consider using `finder:get-file` instead of this function.

---

```

(finder:std-put-file [name
                    directory
                    replace?
                    prompt
                    filter
                    filter-msg
                    parent]) → (or/c false/c path?)
name : string? = "Untitled"
directory : (or/c false/c path?) = #f
replace? : boolean? = #f
prompt : string? = "Select File"
filter : (or/c false/c byte-regexp?) = #f
filter-msg : string?
            = "That filename does not have the right form."
parent : (or/c (is-a?/c top-level-window<%>) false/c)
        = (finder:dialog-parent-parameter)

```

This procedure queries the user for a single filename, using a platform-dependent dialog box. Consider using `finder:put-file` instead of this function.



---

```

(finder:std-get-file [directory
                    prompt
                    filter
                    filter-msg
                    parent]) → (or/c path? false/c)
directory : (or/c path? false/c) = #f
prompt : string? = "Select File"
filter : (or/c byte-regexp? false/c) = #f
filter-msg : string?
           = "That filename does not have the right form."
parent : (or/c false/c (is-a?/c top-level-window<%>)) = #f

```

This procedure queries the user for a single filename, using a platform-dependent dialog box. Consider using `finder:get-file` instead of this function.

---

```

(finder:put-file [name
                directory
                replace?
                prompt
                filter
                filter-msg
                parent]) → (or/c false/c path?)
name : string? = "Untitled"
directory : (or/c false/c path?) = #f
replace? : boolean? = #f
prompt : string? = "Select File"
filter : (or/c false/c byte-regexp?) = #f
filter-msg : string?
           = "That filename does not have the right form."
parent : (or/c (is-a?/c top-level-window<%>) false/c)
        = (finder:dialog-parent-parameter)

```

Queries the user for a filename.

If the result of `(preferences:get 'framework:file-dialogs)` is `'std` this calls `finder:std-put-file`, and if it is `'common`, `finder:common-put-file` is called.

---

```

(finder:get-file [directory
                prompt
                filter
                filter-msg
                parent]) → (or/c path? false/c)
directory : (or/c path? false/c) = #f
prompt : string? = "Select File"

```

```
filter : (or/c byte-regexp? string? false/c) = #f
filter-msg : string?
            = "That filename does not have the right form."
parent : (or/c false/c (is-a?/c top-level-window<%>)) = #f
```

Queries the user for a filename.

If the result of `(preferences:get 'framework:file-dialogs)` is `'std` this calls `finder:std-get-file`, and if it is `'common`, `finder:common-get-file` is called.

---

```
(finder:common-get-file-list [directory
                             prompt
                             filter
                             filter-msg
                             parent])
→ (or/c (listof path?) false/c)
directory : (or/c false/c path?) = #f
prompt : string? = "Select File"
filter : (or/c false/c byte-regexp?) = #f
filter-msg : string?
            = "That filename does not have the right form."
parent : (or/c false/c (is-a?/c top-level-window<%>)) = #f
```

This procedure queries the user for a list of filenames, using a platform-independent dialog box.

## 12 Frame

---

```
frame:basic<%> : interface?  
  implements: frame%
```

Classes matching this interface support the basic `frame%` functionality required by the framework.

---

```
(send a-frame:basic get-area-container%)  
→ (is-a?/c area-container<%>)
```

The class that this method returns is used to create the `area-container<%>` in this frame.

---

```
(send a-frame:basic get-area-container)  
→ (instance (is-a?/c area-container<%>))
```

This returns the main `area-container<%>` in the frame

---

```
(send a-frame:basic get-menu-bar%) → (subclass?/c menu-bar%)
```

The result of this method is used to create the initial menu bar for this frame.  
Return `menu-bar%`.

---

```
(send a-frame:basic make-root-area-container class  
                                     parent)  
→ (instance (is-a?/c area-container<%>))  
  class : (is-a?/c area-container<%>)  
  parent : (instance (is-a?/c area-container<%>))
```

Override this method to insert a panel in between the panel used by the clients of this frame and the frame itself. For example, to insert a status line panel override this method with something like this:

```
(class ...  
  ...  
  (define status-panel #f)  
  (define/override (make-root-area-container cls parent)  
    (set! status-panel  
      (super make-root-area-container vertical-  
panel% parent))  
    (let ([root (make-object cls status-panel)])  
      ; ... add other children to status-panel ...  
      root))  
  ...)
```

In this example, `status-panel` will contain a root panel for the other classes, and whatever panels are needed to display status information.

The searching frame is implemented using this method.

Calls `make-object` with `class` and `parent`.

---

```
(send a-frame:basic close) → void
```

This method closes the frame by calling the `can-close?`, `on-close`, and `show` methods.

It's implementation is:

```
(inherit can-close? on-close)
(public
  [show
    (lambda ()
      (when (can-close?)
        (on-close)
        (show #f)))]])
```

---

```
(send a-frame:basic editing-this-file? filename) → boolean?
filename : path
```

Indicates if this frame contains this buffer (and can edit that file).

Returns `#f`.

---

```
(send a-frame:basic get-filename [temp]) → (or/c #f path)
temp : (or/c #f (box boolean?)) = #f
```

This returns the filename that the frame is currently being saved as, or `#f` if there is no appropriate filename.

Defaultly returns `#f`.

If `temp` is a box, it is filled with `#t` or `#f`, depending if the filename is a temporary filename.

---

```
(send a-frame:basic make-visible filename) → void
filename : string
```

Makes the file named by `filename` visible (intended for use with tabbed editing).

---

```
frame:basic-mixin : (class? . -> . class?)
argument extends/implements: frame%
result implements: frame:basic<%>
```

This mixin provides the basic functionality that the framework expects. It helps manage the list of frames in the `group:%` object returned by `group:get-the-frame-group`.

Do not give `panel%` or `control<%>` objects this frame as parent. Instead, use the result of the `get-area-container` method.

This mixin also creates a menu bar for the frame, as the frame is initialized. It uses the class returned by `get-menu-bar%`. It only passes the frame as an initialization argument. In addition, it creates the windows menu in the menu bar.

This mixin calls its `accept-drop-files` with `#t`.

It also calls its `set-icon` method according to the current value of `frame:current-icon`.

See also `frame:reorder-menus`.

---

```
(send a-frame:basic show on?) → void
on? : boolean?
```

Overrides `show` in `top-level-window<%>`.

Calls the super method.

When `on?` is `#t`, inserts the frame into the frame group and when it is `#f`, removes the frame from the group.

---

```
(send a-frame:basic can-exit?) → boolean?
```

Overrides `can-exit?` in `top-level-window<%>`.

This, together with `on-exit` mimics `exit:exit`.

First, it calls `exit:set-exiting` with `#t`. Then, it calls `exit:can-exit?`. If it returns `#t`, so does this method. If it returns `#f`, this method calls `exit:set-exiting` with `#f`.

---

```
(send a-frame:basic on-exit) → void
```

Overrides `on-exit` in `top-level-window<%>`.

Together with `can-exit?` this mimics the behavior of `exit:exit`.

Calls `exit:on-exit` and then queues a callback to call Racket's `exit` function.

If that returns, it calls `exit:set-exiting` to reset that flag to `#f`.

---

```
(send a-frame:basic on-superwindow-show shown?) → void
shown? : any/c
```

Overrides `on-superwindow-show` in `window<%>`.

Notifies the result of `(group:get-the-frame-group)` that a frame has been shown, by calling the `frame-shown/hidden` method.

---

```
(send a-frame:basic on-drop-file pathname) → void
pathname : string
```

Overrides `on-drop-file` in `window<%>`.

Calls `handler:edit-file` with `pathname` as an argument.

---

```
(send a-frame:basic after-new-child) → void
```

Overrides `after-new-child` in `area-container<%>`.

Raises an exception if attempting to add a child to this frame (except if using the `make-root-area-container` method).

---

```
frame:size-pref<%> : interface?  
implements: frame:basic<%>
```

---

```
frame:size-pref-mixin : (class? . -> . class?)  
argument extends/implements: frame:basic<%>  
result implements: frame:size-pref<%>
```

---

```
(new frame:size-pref-mixin  
 [size-preferences-key size-preferences-key]  
 [label label]  
 [[parent parent]  
 [x x]  
 [y y]  
 [style style]  
 [enabled enabled]  
 [border border]  
 [spacing spacing]  
 [alignment alignment]  
 [min-width min-width]  
 [min-height min-height]  
 [stretchable-width stretchable-width]  
 [stretchable-height stretchable-height]])  
→ (is-a?/c frame:size-pref-mixin)  
size-preferences-key : symbol?  
label : label-string?  
parent : (or/c (is-a?/c frame%) false/c) = #f  
x : (or/c (integer-in -10000 10000) false/c) = #f  
y : (or/c (integer-in -10000 10000) false/c) = #f  
style : (listof (or/c 'no-resize-border 'no-caption 'no-system-menu 'hide-menu-bar 'mdi.  
 = null
```

```
enabled : any/c = #t
border : (integer-in 0 1000) = 0
spacing : (integer-in 0 1000) = 0
alignment : (list/c (or/c 'left 'center 'right) (or/c 'top 'center 'bottom))
           = '(center top)
min-width : (integer-in 0 10000) = graphical-minimum-width
min-height : (integer-in 0 10000) = graphical-minimum-height
stretchable-width : any/c = #t
stretchable-height : any/c = #t
```

The size `size-preferences-key` symbol is used with `preferences:get` and `preferences:set` to track the current size.

Passes the `width` and `height` initialization arguments to the superclass based on the current value of the preference.

See also `frame:setup-size-pref`.

---

```
(send a-frame:size-pref on-size width
                                height) → void
```

```
width : number
height : number
```

Overrides `on-size` in `window<%>`.

Updates the preferences, according to the width and height. The preferences key is the one passed to the initialization argument of the class.

---

```
frame:register-group<%> : interface?
```

Frames that implement this interface are registered with the group. See `group:get-the-frame-group` and `frame:register-group-mixin`.

---

```
frame:register-group-mixin : (class? . -> . class?)
argument extends/implements: frame:basic<%>
result implements: frame:register-group<%>
```

During initialization, calls `insert-frame` with this.

---

```
(send a-frame:register-group can-close?) → bool
```

Augments `can-close?` in `top-level-window<%>`.

Calls the inner method, with a default of `#t`. If that returns `#t`, it checks for one of the these three conditions:

- `exit:exiting?` returns `#t`
- there is more than one frame in the group returned by `group:get-the-frame-group`, or
- the procedure `exit:user-oks-exit` returns `#t`.

If any of those conditions hold, the method returns `#t`.

---

```
(send a-frame:register-group on-close) → void
```

Augments `on-close` in `top-level-window<%>`.

First calls the inner method. Next, calls the `remove-frame` method of the result of `group:get-the-frame-group` with `this` as an argument. Finally, unless `exit:exiting?` returns `#t`, and if there are no more frames open, it calls `exit:exit`.

---

```
(send a-frame:register-group on-activate on?) → void
on? : boolean?
```

Overrides `on-activate` in `top-level-window<%>`.

Calls `set-active-frame` with `this` when `on?` is true.

---

```
frame:status-line<%> : interface?
implements: frame:basic<%>
```

The mixin that implements this interface provides an interface to a set of status lines at the bottom of this frame.

Each status line must be opened with `open-status-line` before any messages are shown in the status line and once `close-status-line` is called, no more messages may be displayed, unless the status line is re-opened.

The screen space for status lines is not created until `update-status-line` is called with a string. Additionally, the screen space for one status line is re-used when by another status line when the first passes `#f` to `update-status-line`. In this manner, the status line frame avoids opening too many status lines and avoids flashing the status lines open and closed too often.

---

```
(send a-frame:status-line open-status-line id) → void
id : symbol?
```

Creates a new status line identified by the symbol argument. The line will not appear in the frame until a message is put into it, via `update-status-line`.

---

```
(send a-frame:status-line close-status-line id) → void
id : symbol?
```



Closes the status line *id*.

---

```
(send a-frame:status-line update-status-line id
                                     status) → void

id : symbol?
status : (or/c #f string)
```

Updates the status line named by *id* with *status*. If *status* is *#f*, the status line becomes blank (and may be used by other ids).

---

```
frame:status-line-mixin : (class? . -> . class?)
argument extends/implements: frame:basic<%>
result implements: frame:status-line<%>
```

---

```
(send a-frame:status-line make-root-area-container class
                                     parent)

→ (is-a?/c panel%)
class : (subclass?/c panel%)
parent : (instanceof (subclass?/c panel%))
```

Overrides `make-root-area-container` in `frame:basic<%>`.  
Adds a panel at the bottom of the frame to hold the status lines.

---

```
frame:info<%> : interface?
implements: frame:basic<%>
```

Frames matching this interface support a status line.

The preference `'framework:show-status-line` controls the visibility of the status line. If it is *#t*, the status line is visible and if it is *#f*, the status line is not visible (see `preferences:get` for more info about preferences)

---

```
(send a-frame:info determine-width str
                                     canvas
                                     text) → integer

str : string
canvas : (instance editor-canvas%)
text : (instance text%)
```

This method is used to calculate the size of an `editor-canvas%` with a particular set of characters in it. It is used to calculate the sizes of the edits in the status line.

---

`(send a-frame:info lock-status-changed)` → `void`

This method is called when the lock status of the `editor<*>` changes.  
Updates the lock icon in the status line panel.

---

`(send a-frame:info update-info)` → `void`

This method updates all of the information in the panel.

---

`(send a-frame:info set-info-canvas canvas)` → `void`

`canvas` : (instance `canvas:basic%`)

Sets this canvas to be the canvas that the info frame shows info about. The on-focus and set-editor methods call this method to ensure that the info canvas is set correctly.

---

`(send a-frame:info get-info-canvas)` → (instance `canvas:basic%`)

Returns the canvas that the `frame:info<*>` currently shows info about. See also `set-info-canvas`

---

`(send a-frame:info get-info-editor)`

→ (or/c #f (is-a?/c editor<\*>))

Override this method to specify the editor that the status line contains information about.

Returns the result of `get-editor`.

---

`(send a-frame:info get-info-panel)`

→ (instance `horizontal-panel%`)

This method returns the panel where the information about this editor is displayed.

---

`(send a-frame:info show-info)` → `void`

Shows the info panel.

See also `is-info-hidden?`.

---

`(send a-frame:info hide-info)` → `void`

Hides the info panel.

See also `is-info-hidden?`.

---

`(send a-frame:info is-info-hidden?)` → `boolean?`

Result indicates if the show info panel has been explicitly hidden with `hide-info`.

If this method returns `#t` and `(preferences:get 'framework:show-status-line)` is `#f`, then the info panel will not be visible. Otherwise, it is visible.

---

```
frame:info-mixin : (class? . -> . class?)
  argument extends/implements: frame:basic<%>
  result implements: frame:info<%>
```

This mixin provides support for displaying various info in the status line of the frame.

The result of this mixin uses the same initialization arguments as the mixin's argument.

---

```
(send a-frame:info make-root-area-container class
                                     parent)
→ (instance area-container<%>)
  class : (subclass?/c area-container<%>)
  parent : (is-a?/c area-container<%>)

  Overrides make-root-area-container in frame:basic<%>.
  Builds an extra panel for displaying various information.
```

---

```
(send a-frame:info on-close) → void

  Augments on-close in top-level-window<%>.
  Removes the GC icon with unregister-collecting-blit and cleans up
  other callbacks.
```

---

```
frame:text-info<%> : interface?
  implements: frame:info<%>
```

Objects matching this interface receive information from editors constructed with `editor:info-mixin` and display it.

---

```
(send a-frame:text-info set-macro-recording on?) → void
  on? : boolean?

  Shows/hides the icon in the info bar that indicates if a macro recording is in
  progress.
```

---

```
(send a-frame:text-info overwrite-status-changed) → void

  This method is called when the overwrite mode is turned either on or off in the
  editor<%> in this frame.
```

---

`(send a-frame:text-info anchor-status-changed) → void`

This method is called when the anchor is turned either on or off in the `editor<%>` in this frame.

---

`(send a-frame:text-info editor-position-changed) → void`

This method is called when the position in the `editor<%>` changes.

---

`frame:text-info-mixin : (class? . -> . class?)`  
argument extends/implements: `frame:info<%>`  
result implements: `frame:text-info<%>`

This mixin adds status information to the info panel relating to an edit.

---

`(send a-frame:text-info on-close) → void`

Augments `on-close` in `top-level-window<%>`.

removes a preferences callback for `'framework:line-offsets`. See `preferences:add-callback` for more information.

---

`(send a-frame:text-info update-info) → void`

Overrides `update-info` in `frame:info<%>`.

Calls `overwrite-status-changed`, `anchor-status-changed`, and `editor-position-changed`.

---

`frame:pasteboard-info<%> : interface?`  
implements: `frame:info<%>`

---

`frame:pasteboard-info-mixin : (class? . -> . class?)`  
argument extends/implements: `frame:basic<%>`  
result implements: `frame:pasteboard-info<%>`

---

`frame:standard-menus<%> : interface?`  
implements: `frame:basic<%>`

---

`(send a-frame:standard-menus on-close) → void?`

Removes the preferences callbacks for the menu items

---

`(send a-frame:standard-menus get-menu%)`

→ `(is-a?/c menu:can-restore-underscore-menu%)`

The result of this method is used as the class for creating the result of these methods: `get-file-menu`, `get-edit-menu`, and `get-help-menu`.

---

`(send a-frame:standard-menus get-menu-item%)`

→ `(is-a?/c menu:can-restore-menu-item%)`

The result of this method is used as the class for creating the menu items in this frame.

Defaults to `menu:can-restore-menu-item`.

---

`(send a-frame:standard-menus get-checkable-menu-item%)`

→ `(is-a?/c menu:can-restore-checkable-menu-item%)`

The result of this method is used as the class for creating checkable menu items in this class.

Defaults to `menu:can-restore-checkable-menu-item`.

---

`(send a-frame:standard-menus get-file-menu) → (is-a?/c menu%)`

Returns the file menu. See also `get-menu%`.

---

`(send a-frame:standard-menus get-edit-menu) → (is-a?/c menu%)`

Returns the edit menu. See also `get-menu%`.

---

`(send a-frame:standard-menus get-help-menu) → (is-a?/c menu%)`

Returns the help menu. See also `get-menu%`.

---

`(send a-frame:standard-menus file-menu:get-new-item)`

→ `(or/c false/c (is-a?/c menu-item%))`

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `file-menu:create-new?`).

---

`(send a-frame:standard-menus file-menu:create-new?) → boolean?`

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus file-menu:new-callback item
                                          control)
```

```
→ void?
  item : (is-a?/c menu-item%)
  control : (is-a?/c control-event%)
```

Defaults to

```
(begin (handler:edit-file #f) #t)
```

---

```
(send a-frame:standard-menus file-menu:new-on-demand menu-item)
```

```
→ void?
  menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus file-menu:new-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant new-menu-item)`.

---

```
(send a-frame:standard-menus file-menu:new-help-string)
```

```
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant new-info)`.

---

```
(send a-frame:standard-menus file-menu:between-new-and-open menu)
```

```
→ void?
  menu : (is-a?/c menu-item%)
```

This method is called between the addition of the new and the open menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus file-menu:get-open-item)
```

```
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `file-menu:create-open?`).

---

```
(send a-frame:standard-menus file-menu:create-open?)
```

```
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to #t.

---

```
(send a-frame:standard-menus file-menu:open-callback item
                                           control)
```

```
→ void?
item : (is-a?/c menu-item%)
control : (is-a?/c control-event%)
```

Defaults to

```
(begin (handler:open-file) #t)
```

---

```
(send a-frame:standard-menus file-menu:open-on-demand menu-item)
```

```
→ void?
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus file-menu:open-string) → string?
```

The result of this method is used as the name of the menu-item%.

Defaults to (string-constant open-menu-item).

---

```
(send a-frame:standard-menus file-menu:open-help-string)
```

```
→ string?
```

The result of this method is used as the help string when the menu-item% object is created.

Defaults to (string-constant open-info).

---

```
(send a-frame:standard-menus file-menu:get-open-recent-item)
```

```
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the menu-item% object corresponding to this menu item, if it has been created (as controlled by file-menu:create-open-recent?).

---

```
(send a-frame:standard-menus file-menu:create-open-recent?)
```

```
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to #t.

---

```
(send a-frame:standard-menus file-menu:open-recent-callback x
                                           y)
```

```
→ void?
```

```
x : (is-a?/c menu-item%)
y : (is-a?/c control-event%)
```

Defaults to  
(void)

---

```
(send a-frame:standard-menus file-menu:open-recent-on-demand menu)
→ void?
menu : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to  
(handler:install-recent-items menu)

---

```
(send a-frame:standard-menus file-menu:open-recent-string)
→ string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to (string-constant open-recent-menu-item).

---

```
(send a-frame:standard-menus file-menu:open-recent-help-string)
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to (string-constant open-recent-info).

---

```
(send a-frame:standard-menus file-menu:between-open-and-revert menu)
→ void?
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the open and the revert menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus file-menu:get-revert-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `file-menu:create-revert?`).

---

```
(send a-frame:standard-menus file-menu:create-revert?)
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.



---

```
(send a-frame:standard-menus file-menu:revert-callback
  item
  control)
→ void?
item : (is-a?/c menu-item%)
control : (is-a?/c control-event%)
```

Defaults to  
(void)

---

```
(send a-frame:standard-menus file-menu:revert-on-demand menu-item)
→ void?
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.  
Defaults to  
(void)

---

```
(send a-frame:standard-menus file-menu:revert-string)
→ string?
```

The result of this method is used as the name of the `menu-item%`.  
Defaults to `(string-constant revert-menu-item)`.

---

```
(send a-frame:standard-menus file-menu:revert-help-string)
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.  
Defaults to `(string-constant revert-info)`.

---

```
(send a-frame:standard-menus file-menu:between-revert-and-save menu)
→ void?
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the revert and the save menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus file-menu:get-save-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `file-menu:create-save?`).

---

```
(send a-frame:standard-menus file-menu:create-save?)
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

```
(send a-frame:standard-menus file-menu:save-callback item
                                           control)
```

```
→ void?
item : (is-a?/c menu-item%)
control : (is-a?/c control-event%)
```

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus file-menu:save-on-demand menu-item)
```

```
→ void?
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus file-menu:save-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant save-menu-item)`.

---

```
(send a-frame:standard-menus file-menu:save-help-string)
```

```
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant save-info)`.

---

```
(send a-frame:standard-menus file-menu:get-save-as-item)
```

```
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `file-menu:create-save-as?`).

---

```
(send a-frame:standard-menus file-menu:create-save-as?)
```

```
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

```
(send a-frame:standard-menus file-menu:save-as-callback
  item
  control)
→ void?
item : (is-a?/c menu-item%)
control : (is-a?/c control-event%)
```

Defaults to  
(void)

---

```
(send a-frame:standard-menus file-menu:save-as-on-demand menu-item)
→ void?
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.  
Defaults to  
(void)

---

```
(send a-frame:standard-menus file-menu:save-as-string)
→ string?
```

The result of this method is used as the name of the `menu-item%`.  
Defaults to `(string-constant save-as-menu-item)`.

---

```
(send a-frame:standard-menus file-menu:save-as-help-string)
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.  
Defaults to `(string-constant save-as-info)`.

---

```
(send a-frame:standard-menus file-menu:between-save-as-and-print menu)
→ void?
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the save-as and the print menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus file-menu:get-print-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `file-menu:create-print?`).

---

```
(send a-frame:standard-menus file-menu:create-print?)
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

```
(send a-frame:standard-menus file-menu:print-callback item
                                          control)
```

```
→ void?
item : (is-a?/c menu-item%)
control : (is-a?/c control-event%)
```

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus file-menu:print-on-demand menu-item)
```

```
→ void?
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus file-menu:print-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant print-menu-item)`.

---

```
(send a-frame:standard-menus file-menu:print-help-string)
```

```
→ string?
The result of this method is used as the help string when the menu-item% object
is created.
```

Defaults to `(string-constant print-info)`.

---

```
(send a-frame:standard-menus file-menu:between-print-and-close menu)
```

```
→ void?
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the print and the close menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus file-menu:get-close-item)
```

```
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `file-menu:create-close?`).

---

```
(send a-frame:standard-menus file-menu:create-close?)
```

→ `boolean?`

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus file-menu:close-callback item
                                           control)
```

→ `void?`

```
item : (is-a?/c menu-item%)
control : (is-a?/c control-event%)
```

Defaults to

```
(begin (when (can-close?) (on-close) (show #f)) #t)
```

---

```
(send a-frame:standard-menus file-menu:close-on-demand menu-item)
```

→ `void?`

```
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus file-menu:close-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant close-menu-item)`.

---

```
(send a-frame:standard-menus file-menu:close-help-string)
```

→ `string?`

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant close-info)`.

---

```
(send a-frame:standard-menus file-menu:between-close-and-quit menu)
```

→ `void?`

```
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the `close` and the `quit` menu item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus file-menu:get-quit-item)
```

→ `(or/c false/c (is-a?/c menu-item%))`

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `file-menu:create-quit?`).

---

```
(send a-frame:standard-menus file-menu:create-quit?)
```

```
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `(not (eq? (system-type) 'macosx))`.

---

```
(send a-frame:standard-menus file-menu:quit-callback item
                                           control)
```

```
→ void?
```

```
item : (is-a?/c menu-item%)
```

```
control : (is-a?/c control-event%)
```

Defaults to

```
(when (exit:user-oks-exit) (exit:exit))
```

---

```
(send a-frame:standard-menus file-menu:quit-on-demand menu-item)
```

```
→ void?
```

```
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus file-menu:quit-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(if (eq? (system-type) 'windows) (string-constant quit-menu-item-windows) (string-constant quit-menu-item-others))`.

---

```
(send a-frame:standard-menus file-menu:quit-help-string)
```

```
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant quit-info)`.

---

```
(send a-frame:standard-menus file-menu:after-quit menu) → void?
```

```
menu : (is-a?/c menu-item%)
```

This method is called after the addition of the quit menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus edit-menu:get-undo-item)
```

```
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-undo?`).

---

```
(send a-frame:standard-menus edit-menu:create-undo?)  
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus edit-menu:undo-callback menu  
                                          evt)  
→ void?  
menu : (is-a?/c menu-item%)  
evt : (is-a?/c control-event%)
```

Defaults to

```
(begin (let ((edit (get-edit-target-object))) (when (and edit (is-a? edit editor<%>)) (send edit do-edit-operation 'undo))) #t)
```

---

```
(send a-frame:standard-menus edit-menu:undo-on-demand item)  
→ void?  
item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(let* ((editor (get-edit-target-object)) (enable? (and editor (is-a? editor editor<%>) (send editor can-do-edit-operation? 'undo)))) (send item enable enable?))
```

---

```
(send a-frame:standard-menus edit-menu:undo-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant undo-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:undo-help-string)  
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant undo-info)`.

---

```
(send a-frame:standard-menus edit-menu:get-redo-item)  
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-redo?`).

---

```
(send a-frame:standard-menus edit-menu:create-redo?)  
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus edit-menu:redo-callback menu  
                                          evt)  
→ void?  
menu : (is-a?/c menu-item%)  
evt : (is-a?/c control-event%)
```

Defaults to

```
(begin (let ((edit (get-edit-target-object))) (when (and edit (is-a? edit editor<%>)) (send edit do-edit-operation 'redo))) #t)
```

---

```
(send a-frame:standard-menus edit-menu:redo-on-demand item)  
→ void?  
item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(let* ((editor (get-edit-target-object)) (enable? (and editor (is-a? editor editor<%>) (send editor can-do-edit-operation? 'redo)))) (send item enable enable?))
```

---

```
(send a-frame:standard-menus edit-menu:redo-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant redo-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:redo-help-string)  
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant redo-info)`.

---

```
(send a-frame:standard-menus edit-menu:between-redo-and-cut menu)  
→ void?  
menu : (is-a?/c menu-item%)
```



This method is called between the addition of the redo and the cut menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus edit-menu:get-cut-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-cut?`).

---

```
(send a-frame:standard-menus edit-menu:create-cut?) → boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus edit-menu:cut-callback menu
                                          evt)
```

```
→ void?
menu : (is-a?/c menu-item%)
evt : (is-a?/c control-event%)
```

Defaults to

```
(begin (let ((edit (get-edit-target-object))) (when (and edit (is-a? edit editor<%>)) (send edit do-edit-operation 'cut))) #t)
```

---

```
(send a-frame:standard-menus edit-menu:cut-on-demand item)
```

```
→ void?
item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(let* ((editor (get-edit-target-object)) (enable? (and editor (is-a? editor editor<%>) (send editor can-do-edit-operation? 'cut)))) (send item enable enable?))
```

---

```
(send a-frame:standard-menus edit-menu:cut-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant cut-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:cut-help-string)
```

```
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant cut-info)`.

---

```
(send a-frame:standard-menus edit-menu:between-cut-and-copy menu)
→ void?
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the cut and the copy menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus edit-menu:get-copy-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-copy?`).

---

```
(send a-frame:standard-menus edit-menu:create-copy?)
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus edit-menu:copy-callback menu
                                          evt)
→ void?
menu : (is-a?/c menu-item%)
evt : (is-a?/c control-event%)
```

Defaults to

```
(begin (let ((edit (get-edit-target-object))) (when (and edit (is-a? edit editor<%>)) (send edit do-edit-operation 'copy))) #t)
```

---

```
(send a-frame:standard-menus edit-menu:copy-on-demand item)
→ void?
item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(let* ((editor (get-edit-target-object)) (enable? (and editor (is-a? editor editor<%>) (send editor can-do-edit-operation? 'copy)))) (send item enable enable?))
```

---

```
(send a-frame:standard-menus edit-menu:copy-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant copy-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:copy-help-string)
```

```
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant copy-info)`.

---

```
(send a-frame:standard-menus edit-menu:between-copy-and-paste menu)
```

```
→ void?
```

```
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the copy and the paste menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus edit-menu:get-paste-item)
```

```
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-paste?`).

---

```
(send a-frame:standard-menus edit-menu:create-paste?)
```

```
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus edit-menu:paste-callback menu  
                                evt)
```

```
→ void?
```

```
menu : (is-a?/c menu-item%)
```

```
evt : (is-a?/c control-event%)
```

Defaults to

```
(begin (let ((edit (get-edit-target-object))) (when (and edit (is-a? editor<%>)) (send edit do-edit-operation 'paste))) #t)
```

---

```
(send a-frame:standard-menus edit-menu:paste-on-demand item)
```

```
→ void?
```

```
item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(let* ((editor (get-edit-target-object)) (enable? (and editor (is-a? editor editor<%>) (send editor can-do-edit-operation? 'paste)))) (send item enable enable?))
```

---

```
(send a-frame:standard-menus edit-menu:paste-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant paste-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:paste-help-string)
```

```
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant paste-info)`.

---

```
(send a-frame:standard-menus edit-menu:between-paste-and-clear menu)
```

```
→ void?
```

```
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the paste and the clear menu item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus edit-menu:get-clear-item)
```

```
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-clear?`).

---

```
(send a-frame:standard-menus edit-menu:create-clear?)
```

```
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus edit-menu:clear-callback menu  
evt)
```

```
→ void?
```

```
menu : (is-a?/c menu-item%)
```

```
evt : (is-a?/c control-event%)
```

Defaults to

```
(begin (let ((edit (get-edit-target-  
object))) (when (and edit (is-a? edit editor<%>)) (send edit do-  
edit-operation 'clear))) #t)
```

---

```
(send a-frame:standard-menus edit-menu:clear-on-demand item)
```

```
→ void?
```

```
item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(let* ((editor (get-edit-target-object)) (enable? (and editor (is-a? editor editor<%>) (send editor can-do-edit-operation? 'clear)))) (send item enable enable?))
```

---

```
(send a-frame:standard-menus edit-menu:clear-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(if (eq? (system-type) 'windows) (string-constant clear-menu-item-windows) (string-constant clear-menu-item-windows))`.

---

```
(send a-frame:standard-menus edit-menu:clear-help-string) → string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant clear-info)`.

---

```
(send a-frame:standard-menus edit-menu:between-clear-and-select-all menu) → void?
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the `clear` and the `select-all` menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus edit-menu:get-select-all-item) → (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-select-all?`).

---

```
(send a-frame:standard-menus edit-menu:create-select-all?) → boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#t`.

---

```
(send a-frame:standard-menus edit-menu:select-all-callback
menu
evt) → void?
menu : (is-a?/c menu-item%)
evt : (is-a?/c control-event%)
```

Defaults to

```
(begin (let ((edit (get-edit-target-object))) (when (and edit (is-a? edit editor<%>)) (send edit do-edit-operation 'select-all))) #t)
```

---

```
(send a-frame:standard-menus edit-menu:select-all-on-demand item)
→ void?
item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(let* ((editor (get-edit-target-object)) (enable? (and editor (is-a? editor editor<%>) (send editor can-do-edit-operation? 'select-all)))) (send item enable enable?))
```

---

```
(send a-frame:standard-menus edit-menu:select-all-string)
→ string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant select-all-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:select-all-help-string)
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant select-all-info)`.

---

```
(send a-frame:standard-menus edit-menu:between-select-all-and-find menu)
→ void?
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the `select-all` and the `find` menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus edit-menu:get-find-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-find?`).

---

```
(send a-frame:standard-menus edit-menu:create-find?)
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

```
(send a-frame:standard-menus edit-menu:find-callback item
                                           control)
```

→ `void?`  
`item` : (`is-a?/c menu-item%`)  
`control` : (`is-a?/c control-event%`)

Defaults to  
`(void)`

---

```
(send a-frame:standard-menus edit-menu:find-on-demand item)
```

→ `void?`  
`item` : (`is-a?/c menu-item%`)

The menu item's on-demand proc calls this method.

Defaults to  
`(send item enable (let ((target (get-edit-target-object))) (and target (is-a? target editor<%>))))`

---

```
(send a-frame:standard-menus edit-menu:find-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant find-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:find-help-string)
```

→ `string?`

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant find-info)`.

---

```
(send a-frame:standard-menus edit-menu:get-find-next-item)
```

→ (`or/c false/c (is-a?/c menu-item%)`)

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-find-next?`).

---

```
(send a-frame:standard-menus edit-menu:create-find-next?)
```

→ `boolean?`

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

```
(send a-frame:standard-menus edit-menu:find-next-callback
      item
      control)
```

→ `void?`  
`item` : (`is-a?/c menu-item%`)  
`control` : (`is-a?/c control-event%`)

Defaults to  
(`void`)

---

(`send a-frame:standard-menus edit-menu:find-next-on-demand item`)

→ `void?`  
`item` : (`is-a?/c menu-item%`)

The menu item's on-demand proc calls this method.

Defaults to

(`send item enable (let ((target (get-edit-target-object))) (and target (is-a? target editor<%>))))`)

---

(`send a-frame:standard-menus edit-menu:find-next-string`)

→ `string?`

The result of this method is used as the name of the `menu-item%`.

Defaults to (`string-constant find-next-menu-item`).

---

(`send a-frame:standard-menus edit-menu:find-next-help-string`)

→ `string?`

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to (`string-constant find-next-info`).

---

(`send a-frame:standard-menus edit-menu:get-find-previous-item`)

→ (`or/c false/c (is-a?/c menu-item%)`)

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-find-previous?`).

---

(`send a-frame:standard-menus edit-menu:create-find-previous?`)

→ `boolean?`

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

(`send a-frame:standard-menus edit-menu:find-previous-callback`  
`item`  
`control`)

→ `void?`  
`item` : (`is-a?/c menu-item%`)



`control` : (is-a?/c control-event%)

Defaults to

(void)

---

(send *a-frame:standard-menus* edit-menu:find-previous-on-demand *item*)

→ void?

*item* : (is-a?/c menu-item%)

The menu item's on-demand proc calls this method.

Defaults to

(send *item* enable (let ((target (get-edit-target-object))) (and target (is-a? target editor<%>))))

---

(send *a-frame:standard-menus* edit-menu:find-previous-string)

→ string?

The result of this method is used as the name of the `menu-item%`.

Defaults to (string-constant find-previous-menu-item).

---

(send *a-frame:standard-menus* edit-menu:find-previous-help-string)

→ string?

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to (string-constant find-previous-info).

---

(send *a-frame:standard-menus* edit-menu:get-show/hide-replace-item)

→ (or/c false/c (is-a?/c menu-item%))

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-show/hide-replace?`).

---

(send *a-frame:standard-menus* edit-menu:create-show/hide-replace?)

→ boolean?

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

(send *a-frame:standard-menus* edit-menu:show/hide-replace-callback

*item*

*control*)

→ void?

*item* : (is-a?/c menu-item%)

*control* : (is-a?/c control-event%)

Defaults to

(void)

---

```
(send a-frame:standard-menus edit-menu:show/hide-replace-on-demand menu-item)
→ void?
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

(void)

---

```
(send a-frame:standard-menus edit-menu:show/hide-replace-string)
→ string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to (string-constant show-replace-menu-item).

---

```
(send a-frame:standard-menus edit-menu:show/hide-replace-help-string)
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to (string-constant show/hide-replace-info).

---

```
(send a-frame:standard-menus edit-menu:get-replace-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-replace?`).

---

```
(send a-frame:standard-menus edit-menu:create-replace?)
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

```
(send a-frame:standard-menus edit-menu:replace-callback
item
control)
→ void?
item : (is-a?/c menu-item%)
control : (is-a?/c control-event%)
```

Defaults to

(void)

---

```
(send a-frame:standard-menus edit-menu:replace-on-demand menu-item)
→ void?
  menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus edit-menu:replace-string)
→ string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant replace-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:replace-help-string)
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant replace-info)`.

---

```
(send a-frame:standard-menus edit-menu:get-replace-all-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-replace-all?`).

---

```
(send a-frame:standard-menus edit-menu:create-replace-all?)
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

```
(send a-frame:standard-menus edit-menu:replace-all-callback
  item
  control)
→ void?
  item : (is-a?/c menu-item%)
  control : (is-a?/c control-event%)
```

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus edit-menu:replace-all-on-demand menu-item)
→ void?
```

`menu-item` : (is-a?/c menu-item%)

The menu item's on-demand proc calls this method.

Defaults to

(void)

---

(send *a-frame:standard-menus* edit-menu:replace-all-string)  
→ string?

The result of this method is used as the name of the `menu-item%`.

Defaults to (string-constant replace-all-menu-item).

---

(send *a-frame:standard-menus* edit-menu:replace-all-help-string)  
→ string?

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to (string-constant replace-all-info).

---

(send *a-frame:standard-menus* edit-menu:get-find-case-sensitive-item)  
→ (or/c false/c (is-a?/c menu-item%))

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-find-case-sensitive?`).

---

(send *a-frame:standard-menus* edit-menu:create-find-case-sensitive?)  
→ boolean?

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to #f.

---

(send *a-frame:standard-menus* edit-menu:find-case-sensitive-callback  
item  
control)  
→ void?  
item : (is-a?/c menu-item%)  
control : (is-a?/c control-event%)

Defaults to

(void)

---

(send *a-frame:standard-menus* edit-menu:find-case-sensitive-on-demand item)  
→ void?  
item : (is-a?/c menu-item%)

The menu item's on-demand proc calls this method.

Defaults to

```
(send item enable (let ((target (get-edit-target-object))) (and target (is-a? target editor<%>))))
```

---

```
(send a-frame:standard-menus edit-menu:find-case-sensitive-string)  
→ string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant find-case-sensitive-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:find-case-sensitive-help-string)  
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant find-case-sensitive-info)`.

---

```
(send a-frame:standard-menus edit-menu:between-find-and-preferences menu)  
→ void?  
menu : (is-a?/c menu-item%)
```

This method is called between the addition of the find and the preferences menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus edit-menu:get-preferences-item)  
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `edit-menu:create-preferences?`).

---

```
(send a-frame:standard-menus edit-menu:create-preferences?)  
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `(not (current-eventspace-has-standard-menus?))`.

---

```
(send a-frame:standard-menus edit-menu:preferences-callback  
item  
control)  
→ void?  
item : (is-a?/c menu-item%)  
control : (is-a?/c control-event%)
```

Defaults to

```
(begin (preferences:show-dialog) #t)
```

---

```
(send a-frame:standard-menus edit-menu:preferences-on-demand menu-item)
→ void?
  menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus edit-menu:preferences-string)
→ string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant preferences-menu-item)`.

---

```
(send a-frame:standard-menus edit-menu:preferences-help-string)
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant preferences-info)`.

---

```
(send a-frame:standard-menus edit-menu:after-preferences menu)
→ void?
  menu : (is-a?/c menu-item%)
```

This method is called after the addition of the preferences menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus help-menu:before-about menu)
→ void?
  menu : (is-a?/c menu-item%)
```

This method is called before the addition of the about menu-item. Override it to add additional menu items at that point.

---

```
(send a-frame:standard-menus help-menu:get-about-item)
→ (or/c false/c (is-a?/c menu-item%))
```

This method returns the `menu-item%` object corresponding to this menu item, if it has been created (as controlled by `help-menu:create-about?`).

---

```
(send a-frame:standard-menus help-menu:create-about?)
→ boolean?
```

The result of this method determines if the corresponding menu item is created. Override it to control the creation of the menu item.

Defaults to `#f`.

---

```
(send a-frame:standard-menus help-menu:about-callback item
                                           control)
```

```
→ void?
item : (is-a?/c menu-item%)
control : (is-a?/c control-event%)
```

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus help-menu:about-on-demand menu-item)
```

```
→ void?
menu-item : (is-a?/c menu-item%)
```

The menu item's on-demand proc calls this method.

Defaults to

```
(void)
```

---

```
(send a-frame:standard-menus help-menu:about-string) → string?
```

The result of this method is used as the name of the `menu-item%`.

Defaults to `(string-constant about-menu-item)`.

---

```
(send a-frame:standard-menus help-menu:about-help-string)
```

```
→ string?
```

The result of this method is used as the help string when the `menu-item%` object is created.

Defaults to `(string-constant about-info)`.

---

```
(send a-frame:standard-menus help-menu:after-about menu)
```

```
→ void?
menu : (is-a?/c menu-item%)
```

This method is called after the addition of the about menu-item. Override it to add additional menu items at that point.

---

```
frame:standard-menus-mixin : (class? . -> . class?)
argument extends/implements: frame:basic<%>
result implements: frame:standard-menus<%>
```

The result of this mixin implements `frame:standard-menus<%>`.

---

```
(send a-frame:standard-menus on-close) → void
```

Augments `on-close` in `top-level-window<%>`.

Removes the preferences callbacks for the menu items

---

`frame:editor<%>` : interface?  
implements: `frame:standard-menus<%>`

Frame classes matching this interface support embedded editors.

---

`(send a-frame:editor get-entire-label)` → string

This method returns the entire label for the frame. See also `set-label` and `set-label-prefix`.

---

`(send a-frame:editor get-label-prefix)` → string

This returns the prefix for the frame's label.

---

`(send a-frame:editor set-label-prefix prefix)` → void  
`prefix` : string

Sets the prefix for the label of the frame.

---

`(send a-frame:editor get-canvas%)`  
→ (subclass?/c editor-canvas%)

The result of this method is used to create the canvas for the `editor<%>` in this frame.

Returns `editor-canvas%`.

---

`(send a-frame:editor get-canvas<%>)` → (instance canvas:basic%)

The result of this method is used to guard the result of the `get-canvas%` method.

---

`(send a-frame:editor get-editor%)` → (is-a?/c editor<%>)

The result of this class is used to create the `editor<%>` in this frame.

Override this method to specify a different editor class.

Returns the value of the init-field `editor%`.

---

`(send a-frame:editor get-editor<%>)` → interface

The result of this method is used by `make-editor` to check that `get-editor%` is returning a reasonable editor.

Returns `editor<%>`.



---

```
(send a-frame:editor make-editor)
→ (instance (is-a?/c editor<%>))
```

This method is called to create the editor in this frame. It calls `get-editor<%>` and uses that interface to make sure the result of `get-editor%` is reasonable. Calls `(make-object get-editor%)`.

---

```
(send a-frame:editor revert) → void
```

Loads the most recently saved version of the file to the disk. If the `editor<%>` is a `text%`, the start and end positions are restored.

---

```
(send a-frame:editor save [format]) → boolean?
format : (or/c 'guess 'standard 'text 'text-force-cr 'same 'copy)
        = 'same
```

Saves the file being edited, possibly calling `save-as` if the editor has no filename yet.

Returns `#f` if the user cancels this operation (only possible when the file has not been saved before and the user is prompted for a new filename) and returns `#t` if not.

---

```
(send a-frame:editor save-as [format]) → boolean?
format : (or/c 'guess 'standard 'text 'text-force-cr 'same 'copy)
        = 'same
```

Queries the user for a file name and saves the file with that name.

Returns `#f` if the user cancels the file-choosing dialog and returns `#t` otherwise.

---

```
(send a-frame:editor get-canvas)
→ (instance (subclass?/c canvas%))
```

Returns the canvas used to display the `editor<%>` in this frame.

---

```
(send a-frame:editor get-editor)
→ (instance (is-a?/c editor<%>))
```

Returns the editor in this frame.

---

```
frame:editor-mixin : (class? . -> . class?)
argument extends/implements: frame:standard-menus<%>
result implements: frame:editor<%>
```

This mixin adds functionality to support an `editor<%>` in the frame. This includes management of the title, implementations of some of the menu items, a reasonable initial size, and access to the `editor<%>` itself.

The size of this frame will be either 600 by 650 or 65 less than the width and height of the screen, whichever is smaller.

---

```
(new frame:editor-mixin
  [filename filename]
  [editor% editor%]
  [[parent parent]
   [width width]
   [height height]
   [x x]
   [y y]
   [style style]
   [enabled enabled]
   [border border]
   [spacing spacing]
   [alignment alignment]
   [min-width min-width]
   [min-height min-height]
   [stretchable-width stretchable-width]
   [stretchable-height stretchable-height]])
→ (is-a?/c frame:editor-mixin)
filename : string?
editor% : (is-a?/c editor<%>)
parent : (or/c (is-a?/c frame%) false/c) = #f
width : (or/c (integer-in 0 10000) false/c) = #f
height : (or/c (integer-in 0 10000) false/c) = #f
x : (or/c (integer-in -10000 10000) false/c) = #f
y : (or/c (integer-in -10000 10000) false/c) = #f
style : (listof (or/c 'no-resize-border 'no-caption 'no-system-menu 'hide-menu-bar 'mdi
  = null
enabled : any/c = #t
border : (integer-in 0 1000) = 0
spacing : (integer-in 0 1000) = 0
alignment : (list/c (or/c 'left 'center 'right) (or/c 'top 'center 'bottom))
  = '(center top)
min-width : (integer-in 0 10000) = graphical-minimum-width
min-height : (integer-in 0 10000) = graphical-minimum-height
stretchable-width : any/c = #t
stretchable-height : any/c = #t
```

---

```
(send a-frame:editor get-filename) → (or/c #f path)
```

Overrides `get-filename` in `frame:basic<%>`.

Returns the filename in the editor returned by `get-editor`.

---

```
(send a-frame:editor editing-this-file? filename) → boolean?  
  filename : path
```

Overrides `editing-this-file?` in `frame:basic<%>`.

Returns `#t` if the filename is the file that this frame is editing.

---

```
(send a-frame:editor on-close) → void
```

Augments `on-close` in `frame:standard-menus<%>`.

Calls the `editor:basic<%>`'s method `on-close`.

---

```
(send a-frame:editor can-close?) → void
```

Augments `can-close?` in `top-level-window<%>`.

Calls the `editor:basic<%>`'s method `can-close?`.

---

```
(send a-frame:editor get-label) → string
```

Overrides `get-label` in `window<%>`.

Returns the portion of the label after the hyphen. See also `get-entire-label`.

---

```
(send a-frame:editor set-label label) → void
```

```
  label : string?
```

Overrides `set-label` in `window<%>`.

Sets the label, but preserves the label's prefix. See also `set-label-prefix`.

---

```
(send a-frame:editor file-menu:open-callback item  
                                     evt) → void
```

```
  item : any
```

```
  evt : mouse-event
```

Overrides `file-menu:open-callback` in `frame:standard-menus<%>`.

Calls `handler:open-file` with the directory of the saved file associated with this editor (if any).

---

```
(send a-frame:editor file-menu:revert-on-demand) → void
```

Overrides `file-menu:revert-on-demand` in `frame:standard-menus<%>`.

Disables the menu item when the editor is locked.

---

```
(send a-frame:editor file-menu:revert-callback item  
                                     evt) → void
```

```
  item : (is-a?/c menu-item%)
```

```
  evt : (is-a?/c control-event%)
```

Overrides `file-menu:revert-callback` in `frame:standard-menus<%>`.

---

Informs the user that this action is not undoable and, if they still want to continue, calls `revert`.

---

```
(send a-frame:editor file-menu:create-revert?) → boolean?
  Overrides file-menu:create-revert? in frame:standard-menus<%>.
  returns #t
```

---

```
(send a-frame:editor file-menu:save-callback item
                                     evt) → void
  item : (is-a?/c menu-item%)
  evt  : (is-a?/c control-event%)
  Overrides file-menu:save-callback in frame:standard-menus<%>.
  Saves the file in the editor.
```

---

```
(send a-frame:editor file-menu:create-save?) → boolean?
  Overrides file-menu:create-save? in frame:standard-menus<%>.
  returns #t
```

---

```
(send a-frame:editor file-menu:save-as-callback item
                                     evt) → void
  item : (is-a?/c menu-item%)
  evt  : (is-a?/c control-event%)
  Overrides file-menu:save-as-callback in frame:standard-menus<%>.
  Prompts the user for a file name and uses that filename to save the buffer. Calls
  save-as with no arguments.
```

---

```
(send a-frame:editor file-menu:create-save-as?) → boolean?
  Overrides file-menu:create-save-as? in frame:standard-menus<%>.
  returns #t
```

---

```
(send a-frame:editor file-menu:print-callback item
                                     evt) → void
  item : (is-a?/c menu-item%)
  evt  : (is-a?/c control-event%)
  Overrides file-menu:print-callback in frame:standard-menus<%>.
  Calls the print method of editor<%> with the default arguments, except that
  the output-mode argument is the result of calling preferences:get with
  'framework:print-output-mode.
```

---

```
(send a-frame:editor file-menu:create-print?) → boolean?
  Overrides file-menu:create-print? in frame:standard-menus<%>.
```

returns #t

---

```
(send a-frame:editor file-menu:between-save-as-and-print file-menu)
→ void
file-menu : (is-a?/c menu%)
```

Overrides `file-menu:between-save-as-and-print` in `frame:standard-menus<%>`.

Creates a Print Setup menu item.

---

```
(send a-frame:editor edit-menu:between-select-all-and-find edit-menu)
→ void
edit-menu : (instance menu%)
```

Overrides `edit-menu:between-select-all-and-find` in `frame:standard-menus<%>`.

Adds a menu item for toggling `auto-wrap` in the focused text.

---

```
(send a-frame:editor help-menu:about-callback item
                                           evt) → void
item : (is-a?/c menu-item%)
evt : (is-a?/c control-event%)
```

Overrides `help-menu:about-callback` in `frame:standard-menus<%>`.

Calls `message-box` with a message welcoming the user to the application named by `application:current-app-name`

---

```
(send a-frame:editor help-menu:about-string) → string
Overrides help-menu:about-string in frame:standard-menus<%>.
Returns the result of (application:current-app-name)
```

---

```
(send a-frame:editor help-menu:create-about?) → boolean?
Overrides help-menu:create-about? in frame:standard-menus<%>.
returns #t
```

---

```
frame:open-here<%> : interface?
implements: frame:editor<%>
```

Frames implementing this mixin can change the file they are displaying.

The frame is only re-used when the `'framework:open-here?` preference is set (see `preferences:get` and `preferences:set` for details on preferences).

The `frame:open-here-mixin` implements this interface.

---

```
(send a-frame:open-here get-open-here-editor)
→ (is-a?/c editor<%>)
```

When the user switches the visible file in this frame, the of this method is the editor that gets switched.

Defaultly returns the result of `get-editor`.

---

```
(send a-frame:open-here open-here filename) → void
filename : string
```

Opens `filename` in the current frame, possibly prompting the user about saving a file (in which case the frame might not get switched).

---

```
frame:open-here-mixin : (class? . -> . class?)
argument extends/implements: frame:editor<%>
result implements: frame:open-here<%>
```

Provides an implementation of `frame:open-here<%>`

---

```
(send a-frame:open-here file-menu:new-on-demand item) → void
item : (is-a?/c menu-item%)
```

Overrides `file-menu:new-on-demand` in `frame:standard-menus<%>`.

Sets the label of `item` to "New..." if the preference `'framework:open-here?` is set.

---

```
(send a-frame:open-here file-menu:new-callback item
evt) → void
item : (instance (subclass?/c menu-item%))
evt : (instance control-event%)
```

Overrides `file-menu:new-callback` in `frame:standard-menus<%>`.

When the preference `'framework:open-here?` preference is set, this method prompts the user, asking if they would like to create a new frame, or just clear out this one. If they clear it out and the file hasn't been saved, they are asked about saving.

---

```
(send a-frame:open-here file-menu:open-on-demand item) → void
item : (is-a?/c menu-item%)
```

Overrides `file-menu:open-on-demand` in `frame:standard-menus<%>`.

Sets the label of `item` to "Open Here..." if the preference `'framework:open-here?` is set.

---

`(send a-frame:open-here on-close) → void`  
Augments `on-close` in `frame:standard-menus<%>`.  
Calls `set-open-here-frame` with `#f` if the result of `get-open-here-frame` is `eq?` to this.

---

`(send a-frame:open-here on-activate on?) → void`  
`on? : boolean?`  
Overrides `on-activate` in `top-level-window<%>`.  
When `on?` is `#t`, calls `set-open-here-frame` with this.

---

`frame:text<%> : interface?`  
implements: `frame:editor<%>`

Frames matching this interface provide support for `text%`s.

---

`frame:text-mixin : (class? . -> . class?)`  
argument extends/implements: `frame:editor<%>`  
result implements: `frame:text<%>`

This mixins adds support for `text%`s in the frame.

---

`(new frame:text-mixin [editor% editor%])`  
`→ (is-a?/c frame:text-mixin)`  
`editor% : (extends text%)`  
Calls the super initialization with either the value of the `editor%` init or, if none was supplied, it passes `text%`.

---

`(send a-frame:text get-editor<%>) → interface`  
Overrides `get-editor<%>` in `frame:editor<%>`.  
Returns `(class->interface text%)`.

---

`frame:pasteboard<%> : interface?`  
implements: `frame:editor<%>`

Frames matching this interface provide support for `pasteboard%`s.

---

```
frame:pasteboard-mixin : (class? . -> . class?)
  argument extends/implements: frame:editor<%>
  result implements: frame:pasteboard<%>
```

This mixin provides support for pasteboards in a frame.

---

```
(new frame:pasteboard-mixin [editor% editor%])
→ (is-a?/c frame:pasteboard-mixin
  editor% : (extends pasteboard%))

  Calls the super initialization with either the value of the editor% init or, if none
  was supplied, it passes pasteboard%.
```

---

```
(send a-frame:pasteboard get-editor<%>) → interface
  Overrides get-editor<%> in frame:editor<%>.
  Returns (class->interface pasteboard%).
```

---

```
frame:delegate<%> : interface?
  implements: frame:status-line<%>
             frame:text<%>
```

Frames that implement this interface provide a 20,000 feet overview of the text in the main editor. The term **delegate** in these method descriptions refers to the original editor and the term **delegatee** refers to the editor showing the 20,000 feet overview.

---

```
(send a-frame:delegate get-delegated-text)
→ (instanceof (is-a?/c text:delegate<%>))

  Returns the delegate text.
```

---

```
(send a-frame:delegate delegated-text-shown?) → boolean?
  Returns #t if the delegate is visible, and #f if it isn't.
```

---

```
(send a-frame:delegate hide-delegated-text) → void
  Hides the delegated text.

  When the delegated text is hidden, it is not being updated. This is accomplished
  by calling the set-delegate method of get-editor with #f.

  See also show-delegated-text
```



---

`(send a-frame:delegate show-delegated-text) → void`

Makes the delegated text visible.

When the delegated text is shown, the `set-delegate` method of `get-delegated-text` is called with the text to delegate messages to.

See also `hide-delegated-text`.

---

`(send a-frame:delegate delegate-moved) → void`

This method is called when the visible region of the delegate editor changes, so that the blue region in the delegatee is updated.

---

`frame:delegate-mixin : (class? . -> . class?)`  
argument extends/implements: `frame:status-line<%>`  
`frame:text<%>`  
result implements: `frame:delegate<%>`

Adds support for a 20,000-feet view via `text:delegate<%>` and `text:delegate-mixin`

---

`(send a-frame:delegate make-root-area-container class  
parent)`

→ `(is-a?/c panel%)`

`class : (subclass?/c panel%)`

`parent : (instanceof (subclass?/c panel%))`

Overrides `make-root-area-container` in `frame:basic<%>`.

adds a panel outside to hold the delegate `editor-canvas%` and `text%`.

---

`(send a-frame:delegate get-editor<%>) → interface`

Overrides `get-editor<%>` in `frame:editor<%>`.

Returns `text:delegate`.

---

`(send a-frame:delegate get-editor%)`

→ `(is-a?/c text:delegate<%>)`

Overrides `get-editor%` in `frame:editor<%>`.

returns the super result, with the `text:delegate-mixin` mixed in.

---

`frame:searchable<%> : interface?`  
implements: `frame:basic<%>`

Frames that implement this interface support searching.

---

```
(send a-frame:searchable search direction) → void?  
direction : (symbols 'forward 'backward)
```

Searches for the text in the search edit in the result of `get-text-to-search`.  
If the text is found and it sets the selection to the found text.

---

```
(send a-frame:searchable search-replace) → boolean?
```

If there is a dark purple bubble (ie, if the replace portion of the search bar is visible and there is a search hit after the insertion point), then this will replace it with the contents of the replace editor and move the insertion point to just after that, or to the end of the editor (if there are no more search hits after the insertion point, but there are search hits before it).

---

```
(send a-frame:searchable replace-all) → void?
```

Loops through the text from the beginning to the end, replacing all occurrences of the search string with the contents of the replace edit.

---

```
(send a-frame:searchable get-text-to-search) → (is-a?/c text%)
```

Returns the last value passed to `set-text-to-search`.

---

```
(send a-frame:searchable set-text-to-search txt) → void?  
txt : (or/c false/c (is-a?/c (subclass?/c text%)))
```

Sets the current text to be searched.

---

```
(send a-frame:searchable search-hidden?) → boolean?
```

Returns `#t` if the search subwindow is visible and `#f` otherwise.

---

```
(send a-frame:searchable hide-search) → void?
```

This method hides the searching information on the bottom of the frame.

---

```
(send a-frame:searchable unhide-search move-focus?) → void?  
move-focus? : boolean?
```

When the searching sub window is hidden, makes it visible. If `move-focus?` is `#f`, the focus is not moved, but if it is any other value, the focus is moved to the find window.

---

```
(send a-frame:searchable get-case-sensitive-search?)  
→ boolean?
```

Returns `#t` if the search is currently case-sensitive. (This method's value depends on the preference `'framework:case-sensitive-search?`, but the preference is only consulted when the frame is created.)

---

```
(send a-frame:searchable search-hits-changed) → void?
```

This method is called when the number of search matches changes and it updates the GUI.

---

```
frame:searchable-mixin : (class? . -> . class?)  
argument extends/implements: frame:standard-menus<%>  
result implements: frame:searchable<%>
```

This mixin adds support for searching in the `editor<%>` in this frame.

---

```
(send a-frame:searchable edit-menu:find-callback) → boolean?
```

Overrides `edit-menu:find-callback` in `frame:standard-menus<%>`.

Toggles the focus between the find window and the window being searched. When moving to the window with the search string, selects the entire range in the buffer.

---

```
(send a-frame:searchable edit-menu:create-find?) → boolean?
```

Overrides `edit-menu:create-find?` in `frame:standard-menus<%>`.

returns `#t`.

---

```
(send a-frame:searchable edit-menu:find-again-callback item  
evt)
```

→ `void?`

`item` : (`is-a?/c menu-item%`)

`evt` : (`is-a?/c control-event%`)

Overrides `<method not found>`.

Calls `unhide-search` and then `search`.

---

```
(send a-frame:searchable edit-menu:create-find-again?)
```

→ `boolean?`

Overrides `<method not found>`.

returns `#t`.

---

```
(send a-frame:searchable edit-menu:find-again-backwards-callback  
item  
evt)
```

→ void?  
item : (is-a?/c menu-item%)  
evt : (is-a?/c control-event%)  
Overrides <method not found>.  
Calls unhide-search and then search.

---

(send a-frame:searchable edit-menu:create-find-again-backwards?)  
→ boolean?  
Overrides <method not found>.  
returns #t.

---

(send a-frame:searchable edit-menu:replace-all-callback)  
→ boolean?  
Overrides edit-menu:replace-all-callback in frame:standard-menus<%>.  
Calls replace-all.

---

(send a-frame:searchable edit-menu:replace-all-on-demand item)  
→ void  
item : menu-item%  
Overrides edit-menu:replace-all-on-demand in frame:standard-menus<%>.  
Disables item when search-hidden? returns #t and enables it when that method returns #f.

---

(send a-frame:searchable edit-menu:create-replace-all?)  
→ boolean?  
Overrides edit-menu:create-replace-all? in frame:standard-menus<%>.  
returns #t.

---

(send a-frame:searchable edit-menu:find-case-sensitive-callback)  
→ boolean?  
Overrides edit-menu:find-case-sensitive-callback in frame:standard-menus<%>.  
Updates the state of the case-sensitive searching for this frame, and sets the 'framework:case-sensitive-search? preference for later frames.

---

(send a-frame:searchable edit-menu:find-case-sensitive-on-demand item)  
→ void  
item : menu-item%

Overrides `edit-menu:find-case-sensitive-on-demand` in `frame:standard-menus<%>`.

Checks *item* when searching is case-sensitive and unchecks it otherwise.

---

```
(send a-frame:searchable edit-menu:create-find-case-sensitive?)  
→ boolean?
```

Overrides `edit-menu:create-find-case-sensitive?` in `frame:standard-menus<%>`.

returns `#t`.

---

```
(send a-frame:searchable make-root-area-container)  
→ (is-a?/c area-container<%>)
```

Overrides `make-root-area-container` in `frame:basic<%>`.

Builds a panel for the searching information.

---

```
(send a-frame:searchable on-close) → void
```

Augments `on-close` in `frame:standard-menus<%>`.

Cleans up after the searching frame.

---

```
frame:searchable-text<%> : interface?  
implements: frame:searchable<%>  
            frame:text<%>
```

---

```
frame:searchable-text-mixin : (class? . -> . class?)  
argument extends/implements: frame:text<%>  
                             frame:searchable<%>  
result implements: frame:searchable-text<%>
```

---

```
(send a-frame:searchable-text get-text-to-search)  
→ (instanceof text%)
```

Overrides `get-text-to-search` in `frame:searchable<%>`. This method is final, so it cannot be overridden.

Returns the result of `get-editor`.

---

```
(send a-frame:searchable-text get-editor<%>)  
→ (is-a?/c editor<%>)
```

Overrides `get-editor<%>` in `frame:editor<%>`.  
Returns `text:searching<%>`.

---

```
(send a-frame:searchable-text get-editor%)  
→ (is-a?/c editor<%>)  
  Overrides get-editor% in frame:editor<%>.  
  Returns (text:searching-mixin (super get-editor%)).
```

---

```
frame:basic% : class?  
  superclass: (frame:register-group-mixin (frame:basic-mixin frame%))
```

---

```
frame:size-pref% : class?  
  superclass: (frame:size-pref-mixin frame:basic%)
```

---

```
frame:info% : class?  
  superclass: (frame:info-mixin frame:basic%)
```

---

```
frame:text-info% : class?  
  superclass: (frame:text-info-mixin frame:info%)
```

---

```
frame:pasteboard-info% : class?  
  superclass: (frame:pasteboard-info-mixin frame:text-info%)
```

---

```
frame:status-line% : class?  
  superclass: (frame:status-line-mixin frame:text-info%)
```

---

```
frame:standard-menus% : class?  
  superclass: (frame:standard-menus-mixin frame:status-line%)
```

---

```
frame:editor% : class?  
  superclass: (frame:editor-mixin frame:standard-menus%)
```

---

```
frame:open-here% : class?  
  superclass: (frame:open-here-mixin frame:editor%)
```

---

```
frame:text% : class?  
  superclass: (frame:text-mixin frame:open-here%)
```

---

```
frame:searchable% : class?  
  superclass: (frame:searchable-text-mixin (frame:searchable-mixin frame:text%))
```

---

```
frame:delegate% : class?  
  superclass: (frame:delegate-mixin frame:searchable%)
```

---

```
frame:pasteboard% : class?  
  superclass: (frame:pasteboard-mixin frame:open-here%)
```

---

```
(frame:setup-size-pref size-pref-sym
                      width
                      height) → void
size-pref-sym : symbol?
width : number?
height : number?
```

Initializes a preference for the `frame:size-pref` mixin.

The first argument should be the preferences symbol, and the second and third should be the default width and height, respectively.

---

```
(frame:add-snip-menu-items menu
                          menu-item%
                          [func]) → void?
menu : (is-a?/c menu%)
menu-item% : (subclass?/c menu-item%)
func : (-> (is-a?/c menu-item%) void?) = void
```

Inserts three menu items into `menu`, one that inserts a text box, one that inserts a pasteboard box, and one that inserts an image into the currently focused editor (if there is one). Uses `menu-item%` as the class for the menu items.

Calls `func` right after inserting each menu item.

---

```
(frame:reorder-menus frame) → void?
frame : (is-a?/c frame%)
```

Re-orders the menus in a frame. It moves the “File” and “Edit” menus to the front of the menubar and moves the “Windows” and “Help” menus to the end of the menubar.

This is useful in conjunction with the frame classes. After instantiating the class and adding ones own menus, the menus will be mis-ordered. This function fixes them up.

---

```
(frame:remove-empty-menus frame) → void?
frame : (is-a?/c frame%)
```

Removes empty menus in a frame.



---

```
(frame:current-icon) → (or/c #f
                        (is-a?/c bitmap%)
                        (cons/c (is-a?/c bitmap%)
                               (is-a?/c bitmap%)))

(frame:current-icon icon-spec) → void?
  icon-spec : (or/c #f
                (is-a?/c bitmap%)
                (cons/c (is-a?/c bitmap%)
                       (is-a?/c bitmap%)))
```

The value of this parameter is used by the initialization code of `frame:basic-mixin`.

- If it is `#f`, then its value is ignored.
- If it is a `bitmap%`, then the `set-icon` is called with the bitmap, the result of invoking the `bitmap% get-loaded-mask` method, and `'both`.
- If it is a pair of bitmaps, then the `set-icon` method is invoked twice, once with each bitmap in the pair. The first bitmap is passed (along with the result of its `bitmap% get-loaded-mask`) and `'small`, and then the second bitmap is passed (also along with the result of its `bitmap% get-loaded-mask`) and `'large`.

Defaults to `#f`.

## 13 Group

---

```
group:% : class?  
  superclass: object%
```

This class manages a group of frames matching the `frame:basic<%>` interface. There is one instance created by the framework, returned by the function `group:get-the-frame-group` and every frame that was constructed with `frame:basic-mixin` adds itself to the result of `group:get-the-frame-group`.

---

```
(send a-group: set-open-here-frame frame) → void  
  frame : (is-a?/c frame:editor%)
```

Sets the frame to load new files into. See also `frame:open-here<%>`.

---

```
(send a-group: get-open-here-frame)  
→ (or/c false/c (is-a?/c frame:editor<%>))
```

Returns the currently saved frame to load new files into.

---

```
(send a-group: get-mdi-parent)  
→ (or/c false/c (instance frame%))
```

The result of this method must be used as the parent frame for each frame in the group.

---

```
(send a-group: get-frames)  
→ (list-of (instance frame:basic<%>))
```

Returns the frames in the group.

---

```
(send a-group: frame-label-changed frame) → void  
  frame : (is-a?/c frame:basic<%>)
```

This method is called by frames constructed with `frame:basic-mixin` when their titles change.

Updates the windows menu of each frame in the group.

---

```
(send a-group: frame-shown/hidden) → void
```

This method is called by instances of `frame:basic%` to notify the frame group that a frame's visibility is changed.

Updates the Windows menus of all of the frames in the frame group.

---

```
(send a-group: for-each-frame f) → void
```

`f : ((instance frame:basic<?>) -> void)`

This method applies a function to each frame in the group. It also remembers the function and applies it to any new frames that are added to the group when they are added.

See also [get-frames](#).

Applies *f* to each frame in the group

---

`(send a-group: get-active-frame) → (is-a?/c frame:basic<?>)`

Returns the frame with the keyboard focus or the first frame in the group.

---

`(send a-group: set-active-frame frame) → void`  
`frame : (is-a?/c frame:basic<?>)`

Sets the active frame in the group. This method is called by [on-activate](#).

---

`(send a-group: insert-frame frame) → void`  
`frame : (is-a?/c frame:basic<?>)`

Inserts a frame into the group.

---

`(send a-group: remove-frame frame) → void`  
`frame : (is-a?/c frame:basic<?>)`

Removes a frame from the group.

---

`(send a-group: clear) → boolean?`

This removes all of the frames in the group. It does not close the frames. See also [on-close-all](#) and [can-close-all?](#).

---

`(send a-group: on-close-all) → void`

Call this method to close all of the frames in the group. The function [can-close-all?](#) must have been called just before this function and it must have returned `#t`.

Calls the [on-close](#) method and the [show](#) method (with `#f` as argument) on each frame in the group.

---

`(send a-group: can-close-all?) → void`

Call this method to make sure that closing all of the frames in the frame groups is permitted by the user. The function [on-close-all](#) is expected to be called just after this method is called.

Calls the [can-close?](#) method of each frame in the group.

---

`(send a-group: locate-file name)`

→ (or/c false/c (is-a?/c frame:basic<%>))  
name : path?

Returns the frame that is editing or viewing the file *name*.

---

(group:get-the-frame-group) → (is-a?/c group:%)

This returns the frame group.

---

(group:on-close-action) → void?

See also [group:can-close-check](#).

Call this function from the [can-close?](#) callback of a frame in order for the group to properly close the application.

---

(group:can-close-check) → boolean?

See also [group:on-close-action](#).

Call this function from the [can-close?](#) callback of a frame in order for the group to properly close the application.

---

(group:add-to-windows-menu proc) → any  
proc : (-> (is-a?/c menu%) any)

Procedures passed to this function are called when the Windows menu is created. Use it to add additional menu items.

## 14 GUI Utilities

```
(require framework/gui-utils)
```

---

```
(gui-utils:trim-string str size)
→ (and/c string?
    (λ (str)
      ((string-length str) . <= . size)))
str : string?
size : (and/c number? positive?)
```

Constructs a string whose size is less than *size* by trimming the *str* and inserting an ellipses into it.

---

```
(gui-utils:quote-literal-label str)
→ (and/c string?
    (lambda (str)
      ((string-length str) . <= . 200)))
str : string?
```

Constructs a string whose ampersand characters are escaped; the label is also trimmed to <= 200 characters.

---

```
(gui-utils:format-literal-label str
                                rest ...)
→ (and/c string?
    (lambda (str)
      ((string-length str) . <= . 200)))
str : string?
rest : (listof any/c)
```

Formats a string whose ampersand characters are mk-escaped; the label is also trimmed to <= 200 mk-characters.

---

```
(gui-utils:cancel-on-right?) → boolean?
```

Returns *#t* if cancel should be on the right-hand side (or below) in a dialog and *#f* otherwise.

Just returns what `system-position-ok-before-cancel?` does.

See also `gui-utils:ok/cancel-buttons`.

---

```

(gui-utils:ok/cancel-buttons parent
  confirm-callback
  cancel-callback
  [confirm-label
   cancel-label
   #:confirm-style confirm-style])
→ (is-a?/c button%) (is-a?/c button%)
parent : (is-a?/c area-container<%>)
confirm-callback : ((is-a?/c button%) (is-a?/c event%) . -> . any)
cancel-callback : ((is-a?/c button%) (is-a?/c event%) . -> . any)
confirm-label : string? = (string-constant ok)
cancel-label : string? = (string-constant cancel)
confirm-style : (listof symbol?) = '(border)

```

Adds an Ok and a cancel button to a panel, changing the order to suit the platform. Under Mac OS X and unix, the confirmation action is on the right (or bottom) and under Windows, the canceling action is on the right (or bottom). The buttons are also sized to be the same width.

The first result is be the OK button and the second is the cancel button.

By default, the confirmation action button has the `'(border)` style, meaning that hitting return in the dialog will trigger the confirmation action. The `confirm-style` argument can override this behavior, tho. See `button%` for the precise list of allowed styles.

See also `gui-utils:cancel-on-right?`.

---

```

(gui-utils:next-untitled-name) → string?

```

Returns a name for the next opened untitled frame. The first name is “Untitled”, the second is “Untitled 2”, the third is “Untitled 3”, and so forth.

---

```

(gui-utils:cursor-delay) → real?
(gui-utils:cursor-delay new-delay) → void?
  new-delay : real?

```

This function is *not* a parameter. Instead, the state is just stored in the closure.

The first case in the case lambda returns the current delay in seconds before a watch cursor is shown, when either `gui-utils:local-busy-cursor` or `gui-utils:show-busy-cursor` is called.

The second case in the case lambda Sets the delay, in seconds, before a watch cursor is shown, when either `gui-utils:local-busy-cursor` or `gui-utils:show-busy-`

`cursor` is called.

---

```
(gui-utils:show-busy-cursor thunk [delay]) → any/c
  thunk : (-> any/c)
  delay : integer? = (gui-utils:cursor-delay)
```

Evaluates (*thunk*) with a watch cursor. The argument *delay* specifies the amount of time before the watch cursor is opened. Use `gui-utils:cursor-delay` to set this value to all calls.

This function returns the result of *thunk*.

---

```
(gui-utils:delay-action delay-time
                        open
                        close) → (-> void?)

delay-time : real?
open       : (-> void?)
close      : (-> void?)
```

Use this function to delay an action for some period of time. It also supports cancelling the action before the time period elapses. For example, if you want to display a watch cursor, but you only want it to appear after 2 seconds and the action may or may not take more than two seconds, use this pattern:

```
(let ([close-down
      (gui-utils:delay-action
       2
       (λ () .. init watch cursor ...)
       (λ () .. close watch cursor ...))])
      (close-down))
```

Creates a thread that waits *delay-time*. After *delay-time* has elapsed, if the result *thunk* has *not* been called, call *open*. Then, when the result *thunk* is called, call *close*. The function *close* will only be called if *open* has been called.

---

```
(gui-utils:local-busy-cursor window
                             thunk
                             [delay]) → any/c

window : (is-a?/c window<%>)
thunk  : (-> any/c)
delay  : integer? = (gui-utils:cursor-delay)
```

Evaluates (*thunk*) with a watch cursor in *window*. If *window* is `#f`, the watch cursor is turned on globally. The argument *delay* specifies the amount of time before the watch cur-

sor is opened. Use `gui-utils:cursor-delay` to set this value for all uses of this function.

The result of this function is the result of `thunk`.

---

```
(gui-utils:unsaved-warning filename
                          action
                          [can-save-now?
                          parent
                          cancel?])
→ (symbols 'continue 'save 'cancel)
filename : string?
action : string?
can-save-now? : boolean? = #f
parent : (or/c false/c      = #f
          (is-a?/c frame%)
          (is-a?/c dialog%))
cancel? : boolean? = #t
```

This displays a dialog that warns the user of a unsaved file.

The string, `action`, indicates what action is about to take place, without saving. For example, if the application is about to close a file, a good action is "Close" "Anyway". The result symbol indicates the user's choice. If `can-save-now?` is `#f`, this function does not give the user the "Save" option and thus will not return `'save`.

If `cancel?` is `#t` there is a cancel button in the dialog and the result may be `'cancel`. If it is `#f`, then there is no cancel button, and `'cancel` will not be the result of the function.

---

```
(gui-utils:get-choice message
                      true-choice
                      false-choice
                      [title
                      default-result
                      parent
                      style
                      checkbox-proc
                      checkbox-label]) → any/c
message : string?
true-choice : string?
false-choice : string?
title : string? = (string-constant warning)
default-result : any/c = 'disallow-close
parent : (or/c false/c (is-a?/c frame%) (is-a?/c dialog%))
        = #f
style : (symbols 'app 'caution 'stop) = 'app
```



```
checkbox-proc : (or/c false/c (case-> (boolean? . -> . void?)
                                   (-> boolean?)))
           = #f
checkbox-label : string? = (string-constant dont-ask-again)
```

Opens a dialog that presents a binary choice to the user. The user is forced to choose between these two options, ie cancelling or closing the dialog opens a message box asking the user to actually choose one of the two options.

The dialog will contain the string *message* and two buttons, labeled with the *true-choice* and the *false-choice*. If the user clicks on *true-choice* *#t* is returned. If the user clicks on *false-choice*, *#f* is returned.

The argument *default-result* determines how closing the window is treated. If the argument is 'disallow-close, closing the window is not allowed. If it is anything else, that value is returned when the user closes the window.

If `gui-utils:cancel-on-right?` returns *#t*, the false choice is on the right. Otherwise, the true choice is on the right.

The *style* parameter is (eventually) passed to *message* as an icon in the dialog.

If *checkbox-proc* is given, it should be a procedure that behaves like a parameter for getting/setting a boolean value. The intention for this value is that it can be used to disable the dialog. When it is given, a checkbox will appear with a *checkbox-label* label (defaults to the *dont-ask-again* string constant), and that checkbox value will be sent to the *checkbox-proc* when the dialog is closed. Note that the dialog will always pop-up — it is the caller's responsibility to avoid the dialog if not needed.

---

```
(gui-utils:get-clicked-clickback-delta [white-on-black?])
→ (is-a?/c style-delta%)
white-on-black? : boolean? = #f
```

This delta is designed for use with `set-clickback`. Use it as one of the *style-delta%* argument to `set-clickback`.

If *white-on-black?* is true, the function returns a delta suitable for use on a black background.

See also `gui-utils:get-clickback-delta`.

---

```
(gui-utils:get-clickback-delta [white-on-black?])
→ (is-a?/c style-delta%)
white-on-black? : boolean? = #f
```

This delta is designed for use with `set-clickback`. Use the result of this function as the

style for the region text where the clickback is set.

If *white-on-black?* is true, the function returns a delta suitable for use on a black background.

See also [gui-utils:get-clicked-clickback-delta](#).

## 15 Handler

---

```
(handler:handler? obj) → boolean?  
  obj : any/c
```

This predicate determines if its input is a handler.

---

```
(handler:handler-name handler) → string?  
  handler : handler:handler?
```

Extracts the name from a handler.

---

```
(handler:handler-extension handler)  
→ (or/c (path? . -> . boolean?) (listof string?))  
  handler : handler:handler?
```

Extracts the extension from a handler.

---

```
(handler:handler-handler handler)  
→ (path? . -> . (is-a?/c frame:editor<%>))  
  handler : handler:handler?
```

Extracts the handler's handling function.

---

```
(handler:insert-format-handler name  
                                pred  
                                handler) → void?  
  
  name : string?  
  pred : (or/c string? (listof string?) (path? . -> . boolean?))  
  handler : (path? . -> . (or/c false/c (is-a?/c frame:editor<%>)))
```

This function inserts a format handler.

The string, *name* names the format handler for use with `handler:find-named-format-handler`. If *pred* is a string, it is matched with the extension of a filename by `handler:find-format-handler`. If *pred* is a list of strings, they are each matched with the extension of a filename by `handler:find-format-handler`. If it is a function, the filename is applied to the function and the functions result determines if this is the handler to use.

The most recently added format handler takes precedence over all other format handlers.

---

```
(handler:find-named-format-handler name)
→ (path? . -> . (is-a?/c frame:editor<%>))
   name : string?
```

This function selects a format handler. See also [handler:insert-format-handler](#).

It finds a handler based on *name*.

---

```
(handler:find-format-handler filename)
→ (path? . -> . (is-a?/c frame:editor<%>))
   filename : path?
```

This function selects a format handler. See also [handler:insert-format-handler](#).

It finds a handler based on *filename*.

---

```
(handler:edit-file filename [make-default])
→ (or/c false/c (is-a?/c frame:editor<%>))
   filename : (or/c path? false/c)
   make-default : (-> (is-a?/c frame:editor<%>))
                  = (λ () ((handler:current-create-new-window) filename))
```

This function creates a frame or re-uses an existing frame to edit a file.

If the preference `'framework:open-here` is set to `#t`, and `(send (group:get-the-frame-group) get-open-here-frame)` returns a frame, the `open-here` method of that frame is used to load the file in the existing frame.

Otherwise, it invokes the appropriate format handler to open the file (see [handler:insert-format-handler](#)).

- If *filename* is a string, this function checks the result of [group:get-the-frame-group](#) to see if the *filename* is already open by a frame in the group.
  - If so, it returns the frame.
  - If not, this function calls [handler:find-format-handler](#) with *filename*.
    - \* If a handler is found, it is applied to *filename* and it's result is the final result.
    - \* If not, *make-default* is used.
- If *filename* is `#f`, *make-default* is used.

---

```
(handler:current-create-new-window)
```

```
→ (-> (or/c false/c path?) (is-a?/c frame%))
(handler:current-create-new-window proc) → void?
proc : (-> (or/c false/c path?) (is-a?/c frame%))
```

This is a parameter that controls how the framework creates new application windows.

The default setting is this:

```
(λ (filename)
  (let ([frame (make-object frame:text-info-file% filename)])
    (send frame show #t)
    frame))
```

---

```
(handler:open-file [dir])
→ (or/c false/c (is-a?/c frame:basic<%>))
dir : (or/c false/c path? string?) = #f
```

This function queries the user for a filename and opens the file for editing. It uses `handler:edit-file` to open the file, once the user has chosen it.

Calls `finder:get-file` and `handler:edit-file`, passing along `dir`.

---

```
(handler:install-recent-items menu) → void?
menu : (is-a?/c menu%)
```

This function deletes all of the items in the given menu and adds one menu item for each recently opened file. These menu items, when selected, call `handler:edit-file` with the filename of the recently opened file.

The menu's size is limited to 10.

---

```
(handler:set-recent-items-frame-superclass frame) → void?
frame : (implementation?/c frame:standard-menus<%>)
```

Sets the superclass for the recently opened files frame. It must be derived from `frame:standard-menus`.

---

```
(handler:add-to-recent filename) → void?
filename : path?
```

Adds a filename to the list of recently opened files.

---

```
(handler:set-recent-position filename
                             start
                             end) → void?

filename : path?
start : number?
end : number?
```

Sets the selection of the recently opened file to *start* and *end*.

---

```
(handler:size-recently-opened-files num) → void?
num : number?
```

Sizes the '`framework:recently-opened-files/pos`' preference list length to *num*.

## 16 Icon

---

`(icon:get-paren-highlight-bitmap)` → `(is-a?/c bitmap%)`

This returns the parenthesis highlight `bitmap%`. It is only used on black and white screens.

---

`(icon:get-eof-bitmap)` → `(is-a?/c bitmap%)`

This returns the `bitmap%` used for the clickable “eof” icon from `text:ports`.

---

`(icon:get-autowrap-bitmap)` → `(is-a?/c bitmap%)`

This returns the autowrap’s `bitmap%`.

The bitmap may not respond `#t` to the `ok?` method.

---

`(icon:get-lock-bitmap)` → `(is-a?/c bitmap%)`

This returns the lock’s `bitmap%`.

The bitmap may not respond `#t` to the `ok?` method.

---

`(icon:get-unlock-bitmap)` → `(is-a?/c bitmap%)`

This returns the reset unlocked `bitmap%`.

The bitmap may not respond `#t` to the `ok?` method.

---

`(icon:get-anchor-bitmap)` → `(is-a?/c bitmap%)`

This returns the anchor’s `bitmap%`.

The bitmap may not respond `#t` to the `ok?` method.

---

`(icon:get-left/right-cursor)` → `(is-a?/c cursor%)`

This function returns a `cursor%` object that indicates left/right sizing is possible, for use with columns inside a window.

The cursor may not respond `#t` to the `ok?` method.

---

`(icon:get-up/down-cursor)` → `(is-a?/c cursor%)`

This function returns a `cursor%` object that indicates up/down sizing is possible, for use with columns inside a window.

The cursor may not respond `#t` to the `ok?` method.

---

`(icon:get-gc-on-bitmap)` → `(is-a?/c bitmap%)`

This returns a bitmap to be displayed in an `frame:info<%>` frame when garbage collection is taking place.

The bitmap may not respond `#t` to the `ok?` method.

---

`(icon:get-gc-off-bitmap)` → `(is-a?/c bitmap%)`

This returns a bitmap to be displayed in an `frame:info<%>` frame when garbage collection is not taking place.

The bitmap may not respond `#t` to the `ok?` method.



## 17 Keymap

---

```
keymap:aug-keymap<%> : interface?  
  implements: keymap%
```

This keymap overrides some of the built in `keymap%` methods to be able to extract the key-bindings from the keymap.

---

```
(send a-keymap:aug-keymap get-chained-keymaps)  
→ (listof (instance keymap%))
```

Returns the list of keymaps that are chained to this one.

---

```
(send a-keymap:aug-keymap get-map-function-table) → hash-table
```

Returns a hash-table that maps symbols naming key sequences to the names of the keymap functions the are bound to.

---

```
(send a-keymap:aug-keymap get-map-function-table/ht ht)  
→ hash-table  
ht : hash-table
```

This is a helper function for `get-map-function-table` that returns the same result, except it accepts a hash-table that it inserts the bindings into. It does not replace any bindings already in `ht`.

---

```
keymap:aug-keymap-mixin : (class? . -> . class?)  
  argument extends/implements: keymap%  
  result implements: keymap:aug-keymap<%>
```

---

```
(send a-keymap:aug-keymap chain-to-keymap next  
                                     prefix?) → void  
next : (instance keymap%)  
prefix? : boolean?
```

Overrides `chain-to-keymap` in `keymap%`.

Keeps a list of the keymaps chained to this one.

---

```
(send a-keymap:aug-keymap remove-chained-keymap keymap) → void  
keymap : (is-a?/c keymap)
```

Overrides `remove-chained-keymap` in `keymap%`.

Keeps the list of the keymaps chained to this one up to date.

---

```
(send a-keymap:aug-keymap map-function key-name
                                     function-name) → void
key-name : string
function-name : string
```

Overrides `map-function` in `keymap%`.

Keeps a separate record of the key names and functions that they are bound to in this keymap.

---

```
keymap:aug-keymap% : class?
superclass: (keymap:aug-keymap-mixin keymap%)
```

---

```
(keymap:remove-user-keybindings-file user-keybindings-path)
→ any
user-keybindings-path : any/c
```

Removes the keymap previously added by `keymap:add-user-keybindings-file`.

---

```
(keymap:add-user-keybindings-file user-keybindings-path-or-require-spec)
→ any
user-keybindings-path-or-require-spec : any/c
```

Chains the keymap defined by `user-keybindings-path-or-require-spec` to the global keymap, returned by `keymap:get-global`.

If `user-keybindings-path-or-require-spec` is a path, the module is loaded directly from that path. Otherwise, `user-keybindings-path-or-require-spec` is treated like an argument to `require`.

---

```
(keymap:add-to-right-button-menu) → (-> (is-a?/c popup-menu%)
                                         (is-a?/c editor<%>)
                                         (is-a?/c event%)
                                         void?)
(keymap:add-to-right-button-menu proc) → void?
proc : (-> (is-a?/c popup-menu%)
          (is-a?/c editor<%>)
          (is-a?/c event%)
          void?)
```

When the keymap that `keymap:get-global` returns is installed into an editor, this parameter's value is used for right button clicks.

Before calling this procedure, the function `append-editor-operation-menu-items` is called.

See also `keymap:add-to-right-button-menu/before`.

---

```
(keymap:add-to-right-button-menu/before)
→ (-> (is-a?/c popup-menu%) (is-a?/c editor<%>) (is-a?/c event%) void?)
(keymap:add-to-right-button-menu/before proc) → void?
proc : (-> (is-a?/c popup-menu%) (is-a?/c editor<%>) (is-a?/c event%) void?)
```

When the keymap that `keymap:get-global` returns is installed into an editor, this function is called for right button clicks.

After calling this procedure, the function `append-editor-operation-menu-items` is called.

See also `keymap:add-to-right-button-menu`.

---

```
(keymap:call/text-keymap-initializer thunk-proc) → any/c
thunk-proc : (-> any/c)
```

This function parameterizes the call to `thunk-proc` by setting the keymap-initialization procedure (see `current-text-keymap-initializer`) to install the framework's standard text bindings.

---

```
(keymap:canonicalize-keybinding-string keybinding-string)
→ string?
keybinding-string : string?
```

Returns a string that denotes the same keybindings as the input string, except that it is in canonical form; two canonical keybinding strings can be compared with `string=?`.

---

```
(keymap:get-editor) → (is-a?/c keymap%)
```

This returns a keymap for handling standard editing operations. It binds these keys:

- "z": undo
- "y": redo
- "x": cut

- "c": copy
- "v": paste
- "a": select all

where each key is prefixed with the menu-shortcut key, based on the platform. Under Unix, the shortcut is "a: "; under windows the shortcut key is "c: " and under MacOS, the shortcut key is "d: ".

---

```
(keymap:get-file) → (is-a?/c keymap%)
```

This returns a keymap for handling file operations.

---

```
(keymap:get-user) → (is-a?/c keymap%)
```

This returns a keymap that contains all of the keybindings in the keymaps loaded via [keymap:add-user-keybindings-file](#)

---

```
(keymap:get-global) → (is-a?/c keymap%)
```

This returns a keymap for general operations. See [keymap:setup-global](#) for a list of the bindings this keymap contains.

---

```
(keymap:get-search) → (is-a?/c keymap%)
```

This returns a keymap for searching operations.

---

```
(keymap:make-meta-prefix-list key) → (listof string?)
  key : string?
```

This prefixes a key with all of the different meta prefixes and returns a list of the prefixed strings.

Takes a keymap, a base key specification, and a function name; it prefixes the base key with all “meta” combination prefixes, and installs the new combinations into the keymap. For example, [\(keymap:send-map-function-meta keymap "a" func\)](#) maps "m:a" and "ESC;a" to func.

---

```
(keymap:send-map-function-meta keymap
                               key
                               func) → void?
  keymap : (is-a?/c keymap%)
```

```
key : string?  
func : string?
```

Most keyboard and mouse mappings are inserted into a keymap by calling the keymap's `map-function` method. However, “meta” combinations require special attention. The “m:” prefix recognized by `map-function` applies only to the Meta key that exists on some keyboards. By convention, however, “meta” combinations can also be accessed by using “ESC” as a prefix.

This procedure binds all of the key-bindings obtained by prefixing `key` with a meta-prefix to `func` in `keymap`.

---

```
(keymap:setup-editor keymap) → void?  
keymap : (is-a?/c keymap%)
```

This sets up the input keymap with the bindings described in `keymap:get-editor`.

---

```
(keymap:setup-file keymap) → void?  
keymap : (is-a?/c keymap%)
```

This extends a `keymap%` with the bindings for files.

---

```
(keymap:setup-global keymap) → void?  
keymap : (is-a?/c keymap%)
```

This function extends a `keymap%` with the following functions:

- ring-bell (any events) — Rings the bell (using `bell`) and removes the search panel from the frame, if there.
- save-file (key events) — Saves the buffer. If the buffer has no name, then `finder:put-file` is invoked.
- save-file-as (key events) — Calls `finder:put-file` to save the buffer.
- load-file (key events) — Invokes `finder:open-file`.
- find-string (key events) — Opens the search buffer at the bottom of the frame, unless it is already open, in which case it searches for the text in the search buffer.
- find-string-reverse (key events) — Same as “find-string”, but in the reverse direction.
- find-string-replace (key events) — Opens a replace string dialog box.
- toggle-anchor (key events) — Turns selection-anchoring on or off.

- center-view-on-line (key events) — Centers the buffer in its display using the currently selected line.
- collapse-space (key events) — Collapses all non-return whitespace around the caret into a single space.
- remove-space (key events) — Removes all non-return whitespace around the caret.
- collapse-newline (key events) — Collapses all empty lines around the caret into a single empty line. If there is only one empty line, it is removed.
- open-line (key events) — Inserts a new line.
- transpose-chars (key events) — Transposes the characters before and after the caret and moves forward one position.
- transpose-words (key events) — Transposes words before and after the caret and moves forward one word.
- capitalize-word (key events) — Changes the first character of the next word to a capital letter and moves to the end of the word.
- upcase-word (key events) — Changes all characters of the next word to capital letters and moves to the end of the word.
- downcase-word (key events) — Changes all characters of the next word to lowercase letters and moves to the end of the word.
- kill-word (key events) — Kills the next word.
- backward-kill-word (key events) — Kills the previous word.
- goto-line (any events) — Queries the user for a line number and moves the caret there.
- goto-position (any events) — Queries the user for a position number and moves the caret there.
- copy-clipboard (mouse events) — Copies the current selection to the clipboard.
- cut-clipboard (mouse events) — Cuts the current selection to the clipboard.
- paste-clipboard (mouse events) — Pastes the clipboard to the current selection.
- copy-click-region (mouse events) — Copies the region between the caret and the input mouse event.
- cut-click-region (mouse events) — Cuts the region between the caret and the input mouse event.
- paste-click-region (mouse events) — Pastes the clipboard into the position of the input mouse event.
- select-click-word (mouse events) — Selects the word under the input mouse event.

- select-click-line (mouse events) — Selects the line under the input mouse event.
- start-macro (key events) – Starts recording a keyboard macro
- end-macro (key events) — Stops recording a keyboard macro
- do-macro (key events) — Executes the last keyboard macro
- toggle-overwrite (key events) — Toggles overwriting mode

These functions are bound to the following keys (C = control, S = shift, A = alt, M = “meta”, D = command):

- C-g : “ring-bell”
- M-C-g : “ring-bell”
- C-c C-g : “ring-bell”
- C-x C-g : “ring-bell”
- C-p : “previous-line”
- S-C-p : “select-previous-line”
- C-n : “next-line”
- S-C-n : “select-next-line”
- C-e : “end-of-line”
- S-C-e : “select-to-end-of-line”
- D-RIGHT : “end-of-line”
- S-D-RIGHT : “select-to-end-of-line”
- M-RIGHT : “end-of-line”
- S-M-RIGHT : “select-to-end-of-line”
- C-a : “beginning-of-line”
- S-C-a : “select-to-beginning-of-line”
- D-LEFT : “beginning-of-line”
- D-S-LEFT : “select-to-beginning-of-line”
- M-LEFT : “beginning-of-line”
- M-S-LEFT : “select-to-beginning-of-line”

- C-h : “delete-previous-character”
- C-d : “delete-next-character”
- C-f : “forward-character”
- S-C-f : “select-forward-character”
- C-b : “backward-character”
- S-C-b : “select-backward-character”
- M-f : “forward-word”
- S-M-f : “select-forward-word”
- A-RIGHT : “forward-word”
- A-S-RIGHT : “forward-select-word”
- M-b : “backward-word”
- S-M-b : “select-backward-word”
- A-LEFT : “backward-word”
- A-S-LEFT : “backward-select-word”
- M-d : “kill-word”
- M-DELETE : “backward-kill-word”
- M-c : “capitalize-word”
- M-u : “upcase-word”
- M-l : “downcase-word”
- M-< : “beginning-of-file”
- S-M-< : “select-to-beginning-of-file”
- M-> : “end-of-file”
- S-M-> : “select-to-end-of-file”
- C-v : “next-page”
- S-C-v : “select-next-page”
- M-v : “previous-page”
- S-M-v : “select-previous-page”
- C-l : “center-view-on-line”



- C-k : “delete-to-end-of-line”
- C-y : “paste-clipboard” (Except Windows)
- A-v : “paste-clipboard”
- D-v : “paste-clipboard”
- C-\_ : “undo”
- C-x u : “undo”
- C-+ : “redo”
- C-w : “cut-clipboard”
- M-w : “copy-clipboard”
- C-x C-s : “save-file”
- C-x C-w : “save-file-as”
- C-x C-f : “load-file”
- C-s : “find-string”
- C-r : “find-string-reverse”
- M-% : “find-string-replace”
- SPACE : “collapse-space”
- M-Backslash : “remove-space”
- C-x C-o : “collapse-newline”
- C-o : “open-line”
- C-t : “transpose-chars”
- M-t : “transpose-words”
- C-SPACE : “toggle-anchor”
- M-g : “goto-line”
- M-p : “goto-position”
- LEFTBUTTONTRIPLE : “select-click-line”
- LEFTBUTTONDOUBLE : “select-click-word”
- RIGHTBUTTON : “copy-click-region”
- RIGHTBUTTONDOUBLE : “cut-click-region”

- MIDDLEBUTTON : “paste-click-region”
- C-RIGHTBUTTON : “copy-clipboard”
- INSERT : “toggle-overwrite”
- M-o : “toggle-overwrite”

---

```
(keymap:setup-search keymap) → void?
  keymap : (is-a?/c keymap%)
```

This extends a `keymap%` with the bindings for searching.

---

```
(keymap:set-chained-keymaps keymap
  children-keymaps) → void?
  keymap : (is-a?/c keymap:aug-keymap<%>)
  children-keymaps : (listof (is-a?/c keymap%))
```

Sets `keymap`'s chained keymaps to `children-keymaps`, unchaining any keymaps that are currently chained to `keymap`.

---

```
(keymap:remove-chained-keymap editor
  keymap) → void?
  editor : (is-a?/c editor<%>)
  keymap : (is-a?/c keymap:aug-keymap<%>)
```

Removes `keymap` from the keymaps chained to `editor`. Also (indirectly) removes all keymaps chained to `keymap` from `editor`, since they are removed when unchaining `keymap` itself.

Each of the keymaps chained to `editor` must be an `keymap:aug-keymap%` and `keymap` cannot be the result of `(send editor get-keymap)`. That is, `keymap` must be chained to some keymap attached to the editor.

## 18 Menu

---

```
menu:can-restore<%> : interface?  
  implements: selectable-menu-item<%>
```

Classes created with this mixin remember their keybindings so the keybindings can be removed and then restored.

---

```
(send a-menu:can-restore restore-keybinding) → void
```

Sets the keyboard shortcut to the setting it had when the class was created.

---

```
menu:can-restore-mixin : (class? . -> . class?)  
  argument extends/implements: selectable-menu-item<%>  
  result implements: menu:can-restore<%>
```

---

```
menu:can-restore-underscore<%> : interface?  
  implements: labelled-menu-item<%>
```

These menus can save and restore the underscores (indicated via the `&` characters in the original labels) in their labels.

If the preference `'framework:menu-bindings` is `#f`, calls `erase-underscores` during initialization.

---

```
(send a-menu:can-restore-underscore erase-underscores) → void
```

Erases the underscores in the label of this menu, but remembers them so they can be restored with `restore-underscores`.

---

```
(send a-menu:can-restore-underscore restore-underscores)  
→ void
```

Restores underscores in the menu's label to their original state.

---

```
menu:can-restore-underscore-mixin : (class? . -> . class?)  
  argument extends/implements: labelled-menu-item<%>  
  result implements: menu:can-restore-underscore<%>
```

---

```
menu:can-restore-menu-item% : class?  
  superclass: (menu:can-restore-mixin menu-item%)
```

---

```
menu:can-restore-checkable-menu-item% : class?  
  superclass: (menu:can-restore-mixin checkable-menu-item%)
```

---

```
menu:can-restore-underscore-menu% : class?  
  superclass: (menu:can-restore-underscore-mixin menu%)
```



```
orig : (is-a?/ctext%)
call-super : (->any)
event : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-display-size orig
                                     call-inner) → any
```

```
orig : (is-a?/ctext%)
call-inner : (->any)
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-edit-sequence orig
                                     call-inner) → any
```

```
orig : (is-a?/ctext%)
call-inner : (->any)
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-event orig
                                     call-super
                                     event) → any
```

```
orig : (is-a?/ctext%)
call-super : (->any)
event : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-focus orig
                                     call-super
                                     on?) → any
```

```
orig : (is-a?/ctext%)
call-super : (->any)
on? : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-load-file orig
                                     call-inner
                                     filename
                                     format) → any
```

```
orig : (is-a?/ctext%)
call-inner : (->any)
filename : any/c
format : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-local-char orig
                                     call-super
                                     event) → any

orig : (is-a?/ctext%)
call-super : (->any)
event : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-local-event orig
                                     call-super
                                     event) → any

orig : (is-a?/ctext%)
call-super : (->any)
event : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-new-box orig
                                     call-super
                                     type) → any

orig : (is-a?/ctext%)
call-super : (->any)
type : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-new-image-snip orig
                                     call-super
                                     filename
                                     kind
                                     relative-path?
                                     inline?)

→ any
orig : (is-a?/ctext%)
call-super : (->any)
filename : any/c
kind : any/c
relative-path? : any/c
inline? : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-paint orig
      call-super
      before?
      dc
      left
      top
      right
      bottom
      dx
      dy
      draw-caret) → any
```

```
orig : (is-a?/ctext%)
call-super : (->any)
before? : any/c
dc : any/c
left : any/c
top : any/c
right : any/c
bottom : any/c
dx : any/c
dy : any/c
draw-caret : any/c
```

Returns the result of invoking `call-super`.

---

```
(send a-mode:surrogate-text on-save-file orig
      call-inner
      filename
      format) → any
```

```
orig : (is-a?/ctext%)
call-inner : (->any)
filename : any/c
format : any/c
```

Returns the result of invoking `call-super`.

---

```
(send a-mode:surrogate-text on-snip-modified orig
      call-inner
      snip
      modified?) → any
```

```
orig : (is-a?/ctext%)
call-inner : (->any)
snip : any/c
modified? : any/c
```

Returns the result of invoking `call-super`.



---

```
(send a-mode:surrogate-text on-change-style orig
                                     call-inner
                                     start
                                     len)      → any
```

```
orig : (is-a?/ctext%)
call-inner : (->any)
start : any/c
len : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-delete orig
                                     call-inner
                                     start
                                     len)      → any
```

```
orig : (is-a?/ctext%)
call-inner : (->any)
start : any/c
len : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-insert orig
                                     call-inner
                                     start
                                     len)      → any
```

```
orig : (is-a?/ctext%)
call-inner : (->any)
start : any/c
len : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-new-string-snip orig
                                               call-super)
```

```
→ any
orig : (is-a?/ctext%)
call-super : (->any)
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-new-tab-snip orig
                                               call-super) → any
```

```
orig : (is-a?/ctext%)
call-super : (->any)
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text on-set-size-constraint orig
                                     call-inner)
```

→ any

*orig* : (is-a?/ctext%)

*call-inner* : (->any)

Returns the result of invoking call-super.

---

```
(send a-mode:surrogate-text after-change-style orig
                                     call-inner
                                     start
                                     len)
```

→ any

*orig* : (is-a?/ctext%)

*call-inner* : (->any)

*start* : any/c

*len* : any/c

Returns the result of invoking call-super.

---

```
(send a-mode:surrogate-text after-delete orig
                                     call-inner
                                     start
                                     len) → any
```

*orig* : (is-a?/ctext%)

*call-inner* : (->any)

*start* : any/c

*len* : any/c

Returns the result of invoking call-super.

---

```
(send a-mode:surrogate-text after-insert orig
                                     call-inner
                                     start
                                     len) → any
```

*orig* : (is-a?/ctext%)

*call-inner* : (->any)

*start* : any/c

*len* : any/c

Returns the result of invoking call-super.

---

```
(send a-mode:surrogate-text after-set-position orig
                                     call-inner)
```

→ any

*orig* : (is-a?/ctext%)

*call-inner* : (->any)

Returns the result of invoking `call-super`.

---

```
(send a-mode:surrogate-text after-set-size-constraint
      orig
      call-inner)
→ any
orig : (is-a?/ctext%)
call-inner : (->any)
```

Returns the result of invoking `call-super`.

---

```
(send a-mode:surrogate-text after-edit-sequence orig
                                          call-inner)
→ any
orig : (is-a?/ctext%)
call-inner : (->any)
```

Returns the result of invoking `call-super`.

---

```
(send a-mode:surrogate-text after-load-file orig
                                          call-inner
                                          success?) → any
orig : (is-a?/ctext%)
call-inner : (->any)
success? : any/c
```

Returns the result of invoking `call-super`.

---

```
(send a-mode:surrogate-text after-save-file orig
                                          call-inner
                                          success?) → any
orig : (is-a?/ctext%)
call-inner : (->any)
success? : any/c
```

Returns the result of invoking `call-super`.

---

```
(send a-mode:surrogate-text can-change-style? orig
                                          call-inner
                                          start
                                          len) → any
orig : (is-a?/ctext%)
call-inner : (->any)
start : any/c
len : any/c
```

Returns the result of invoking `call-super`.

---

```
(send a-mode:surrogate-text can-delete? orig
                                         call-inner
                                         start
                                         len)      → any

orig : (is-a?/ctext%)
call-inner : (->any)
start : any/c
len : any/c
```

Returns the result of invoking call-super.

---

```
(send a-mode:surrogate-text can-insert? orig
                                         call-inner
                                         start
                                         len)      → any

orig : (is-a?/ctext%)
call-inner : (->any)
start : any/c
len : any/c
```

Returns the result of invoking call-super.

---

```
(send a-mode:surrogate-text can-set-size-constraint?
orig
call-inner)
→ any
orig : (is-a?/ctext%)
call-inner : (->any)
```

Returns the result of invoking call-super.

---

```
(send a-mode:surrogate-text can-do-edit-operation? orig
                                                    call-super
                                                    op)

→ any
orig : (is-a?/ctext%)
call-super : (->any)
op : any/c

(send a-mode:surrogate-text can-do-edit-operation? orig
                                                    call-super
                                                    op
                                                    recursive?)

→ any
orig : (is-a?/ctext%)
call-super : (->any)
op : any/c
```

*recursive?* : any/c

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text can-load-file? orig
                                           call-inner
                                           filename
                                           format) → any
```

```
orig : (is-a?/c text%)
call-inner : (->any)
filename : any/c
format : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text can-save-file? orig
                                           call-inner
                                           filename
                                           format) → any
```

```
orig : (is-a?/c text%)
call-inner : (->any)
filename : any/c
format : any/c
```

Returns the result of invoking *call-super*.

---

```
(send a-mode:surrogate-text put-file orig
                                       call-super
                                       directory
                                       default-name) → any
```

```
orig : (is-a?/c text%)
call-super : (->any)
directory : any/c
default-name : any/c
```

Returns the result of invoking *call-super*.

---

*mode:host-text<%>* : interface?

---

```
(send a-mode:host-text get-surrogate)
→ (or/c false/c (is-a?/c mode:surrogate-text<%>))
```

Returns the currently active surrogate.

---

```
(send a-mode:host-text set-surrogate surrogate) → void?
surrogate : (or/c false/c (is-a?/c mode:surrogate-text<%>))
```

Sets the current surrogate to *surrogate*.

---

```
mode:host-text-mixin : (class? . -> . class?)  
  result implements: mode:host-text<%/>
```

---

```
(send a-mode:host-text on-change) → any  
  Delegates to the result of get-surrogate if it is not #f.
```

---

```
(send a-mode:host-text on-char event) → any  
  event : any/c  
  Delegates to the result of get-surrogate if it is not #f.
```

---

```
(send a-mode:host-text on-default-char event) → any  
  event : any/c  
  Delegates to the result of get-surrogate if it is not #f.
```

---

```
(send a-mode:host-text on-default-event event) → any  
  event : any/c  
  Delegates to the result of get-surrogate if it is not #f.
```

---

```
(send a-mode:host-text on-display-size) → any  
  Delegates to the result of get-surrogate if it is not #f.
```

---

```
(send a-mode:host-text on-edit-sequence) → any  
  Delegates to the result of get-surrogate if it is not #f.
```

---

```
(send a-mode:host-text on-event event) → any  
  event : any/c  
  Delegates to the result of get-surrogate if it is not #f.
```

---

```
(send a-mode:host-text on-focus on?) → any  
  on? : any/c  
  Delegates to the result of get-surrogate if it is not #f.
```

---

```
(send a-mode:host-text on-load-file filename  
                                     format) → any  
  filename : any/c  
  format : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-local-char event) → any
event : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-local-event event) → any
event : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-new-box type) → any
type : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-new-image-snip filename
                                         kind
                                         relative-path?
                                         inline?) → any
```

```
filename : any/c
kind : any/c
relative-path? : any/c
inline? : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-paint before?
                                dc
                                left
                                top
                                right
                                bottom
                                dx
                                dy
                                draw-caret) → any
```

```
before? : any/c
dc : any/c
left : any/c
top : any/c
right : any/c
bottom : any/c
dx : any/c
dy : any/c
draw-caret : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-save-file filename
                                     format) → any
  filename : any/c
  format   : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-snip-modified snip
                                     modified?) → any
  snip       : any/c
  modified?  : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-change-style start
                                     len) → any
  start : any/c
  len   : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-delete start len) → any
  start : any/c
  len   : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-insert start len) → any
  start : any/c
  len   : any/c
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-new-string-snip) → any
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-new-tab-snip) → any
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text on-set-size-constraint) → any
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text after-change-style start
                                     len) → any
  start : any/c
```



*len* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `after-delete` *start*  
*len*) → any

*start* : any/c

*len* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `after-insert` *start*  
*len*) → any

*start* : any/c

*len* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `after-set-position`) → any

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `after-set-size-constraint`) → any

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `after-edit-sequence`) → any

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `after-load-file` *success?*) → any

*success?* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `after-save-file` *success?*) → any

*success?* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `can-change-style?` *start*  
*len*) → any

*start* : any/c

*len* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

(send *a-mode:host-text* `can-delete?` *start*  
*len*) → any

*start* : any/c

*len* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text can-insert? start
                                     len) → any
```

*start* : any/c

*len* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text can-set-size-constraint?) → any
```

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text can-do-edit-operation? op) → any
  op : any/c
```

```
(send a-mode:host-text can-do-edit-operation? op
                                     recursive?) → any
```

*op* : any/c

*recursive?* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text can-load-file? filename
                                     format) → any
```

*filename* : any/c

*format* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text can-save-file? filename
                                     format) → any
```

*filename* : any/c

*format* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

---

```
(send a-mode:host-text put-file directory
                                     default-name) → any
```

*directory* : any/c

*default-name* : any/c

Delegates to the result of `get-surrogate` if it is not `#f`.

## 20 Number Snip

---

```
number-snip:snip-class% : class?  
  superclass: snip-class%
```

---

```
(send a-number-snip:snip-class read f) → snip  
  f : stream-in  
  Overrides read in snip-class%.  
  Constructs a number snip from its input.
```

---

```
(number-snip:make-repeating-decimal-snip num  
                                         show-prefix?)  
→ (is-a?/c snip%)  
  num : number?  
  show-prefix? : boolean?
```

Makes a number snip that shows the decimal expansion for `number`. The boolean indicates if a `#e` prefix appears on the number.

See also [number-snip:make-fraction-snip](#).

---

```
(number-snip:make-fraction-snip num  
                                show-prefix-in-decimal-view?)  
→ (is-a?/c snip%)  
  num : number?  
  show-prefix-in-decimal-view? : boolean?
```

Makes a number snip that shows a fractional view of `number`. The boolean indicates if a `#e` prefix appears on the number, when shown in the decimal state.

See also [number-snip:make-repeating-decimal-snip](#).

## 21 Panel

---

```
panel:single<%> : interface?  
  implements: area-container<%>
```

See `panel:single-mixin%`.

---

```
(send a-panel:single active-child child) → void  
  child : (is-a?/c area<%>)  
(send a-panel:single active-child) → (is-a?/c area<%>)  
  Sets the active child to be child  
  Returns the current active child.
```

---

```
panel:single-mixin : (class? . -> . class?)  
  argument extends/implements: area-container<%>  
  result implements: panel:single<%>
```

This mixin adds single panel functionality to an implementation of the `area-container<%>` interface.

Single panels place all of the children in the center of the panel, and allow make one child to be visible at a time. The `active-child` method controls which panel is currently active.

The `show` method is used to hide and show the children of a single panel.

---

```
(send a-panel:single after-new-child child) → void  
  child : subarea<%>  
  Overrides after-new-child in area-container<%>.  
  Hides this child by calling (send child show #f), unless this is the first  
  child in which case it does nothing.
```

---

```
(send a-panel:single container-size)  
→ exact-integer exact-integer  
  Overrides container-size in area-container<%>.  
  Returns the maximum width of all the children and the maximum height of all  
  of the children.
```

---

```
(send a-panel:single place-children)  
→ (listof (list exact-integer exact-integer exact-integer exact-integer))
```

Overrides `place-children` in `area-container<%>`.

Returns the positions for single panels and panes.

---

```
panel:single-window<%> : interface?  
  implements: panel:single<%>  
              window<%>
```

---

```
panel:single-window-mixin : (class? . -> . class?)  
  argument extends/implements: panel:single<%>  
                               window<%>  
  result implements: panel:single-window<%>
```

---

```
(send a-panel:single-window container-size info)  
→ exact-integer exact-integer  
  info : (list-of (list exact-integer exact-integer boolean boolean?))
```

Overrides `container-size` in `area-container<%>`.

Factors the border width into the size calculation.

---

```
panel:single% : class?  
  superclass: (panel:single-window-mixin (panel:single-mixin panel%))
```

---

```
panel:single-pane% : class?  
  superclass: (panel:single-mixin pane%)
```

---

```
panel:draggable<%> : interface?  
  implements: window<%>  
             area-container<%>
```

Classes matching this interface implement a panel where the user can adjust the percentage of the space that each takes up. The user adjusts the size by clicking and dragging the empty space between the children.

---

`(send a-panel:dragable after-percentage-change) → void`

This method is called when the user changes the percentage by dragging the bar between the children, or when a new child is added to the frame, but not when `set-percentages` is called.

Use `get-percentages` to find the current percentages.

---

`(send a-panel:dragable set-percentages new-percentages) → void`  
`new-percentages : (listof number)`

Call this method to set the percentages that each window takes up of the panel.

The argument, `new-percentages` must be a list of numbers that sums to 1. It's length must be equal to the number of children of the panel (see `get-children`) and each percentage must correspond to a number of pixels that is equal to or larger than the minimum width of the child, as reported by `min-width`.

---

`(send a-panel:dragable get-percentages) → (listof numbers)`

Return the current percentages of the children.

---

`(send a-panel:dragable get-vertical?) → boolean?`

This method controls the behavior of the other overridden methods in mixins that implement this interface.

If it returns `#t`, the panel will be vertically aligned and if it returns `#f`, they will be horizontally aligned.

---

`(send a-panel:dragable set-orientation horizontal?) → void?`  
`horizontal? : boolean?`

Sets the orientation of the panel, switching it from behaving like a `panel:horizontal-dragable<?>` and `panel:vertical-dragable<?>`.

---

`panel:vertical-dragable<?> : interface?`  
implements: `panel:dragable<?>`

A panel that implements `panel:vertical-dragable<?>`. It aligns its children vertically.

---

`panel:horizontal-dragable<?> : interface?`  
implements: `panel:dragable<?>`

A panel that implements `panel:horizontal-dragable<%>`. It aligns its children horizontally.

---

```
panel:dragable-mixin : (class? . -> . class?)
  argument extends/implements: window<%>
                               area-container<%>
  result implements: panel:dragable<%>
```

This mixin adds the `panel:dragable<%>` functionality to a `panel%`.

It is not useful unless the `get-vertical?` method is overridden.

---

```
(send a-panel:dragable after-new-child child) → void
  child : (instance-of (is-a?/c area<%>))
```

Overrides `after-new-child` in `area-container<%>`.

Updates the number of percentages to make sure that it matches the number of children and calls `after-percentage-change`.

---

```
(send a-panel:dragable on-subwindow-event receiver
                               event) → boolean?
  receiver : (instanceof window<%>)
  event : (instanceof mouse-event%)
```

Overrides `on-subwindow-event` in `window<%>`.

When the cursor is dragging the middle bar around, this method handles the resizing of the two panes.

---

```
(send a-panel:dragable place-children info
                               w
                               h)
→ (list-of (list exact-int exact-int exact-int exact-int))
  info : (list-of (list exact-int exact-int))
  w : exact-int
  h : exact-int
```

Overrides `place-children` in `area-container<%>`.

Places the children vertically in the panel, based on the percentages returned from `get-percentages`. Also leaves a little gap between each pair of children.

---

```
(send a-panel:dragable container-size info) → two
  info : list
```

Overrides `container-size` in `area-container<%>`.

Computes the minimum size the panel would have to be in order to have the current percentages (see `get-percentages`).

---

```
panel:vertical-dragable-mixin : (class? . -> . class?)  
  argument extends/implements: panel:dragable<%>  
  result implements: panel:vertical-dragable<%>
```

This mixin merely overrides the `get-vertical?` method of the `panel:dragable-mixin` to return `#t`.

---

```
(send a-panel:vertical-dragable get-vertical?) → boolean?  
  Overrides get-vertical? in panel:dragable<%>.  
  Returns #t.
```

---

```
panel:horizontal-dragable-mixin : (class? . -> . class?)  
  argument extends/implements: panel:dragable<%>  
  result implements: panel:vertical-dragable<%>
```

This mixin merely overrides the `get-vertical?` method of the `panel:dragable-mixin` to return `#f`.

---

```
(send a-panel:horizontal-dragable get-vertical?) → boolean?  
  Overrides get-vertical? in panel:dragable<%>.  
  Returns #f.
```

---

```
panel:vertical-dragable% : class?  
  superclass: (panel:vertical-dragable-mixin (panel:dragable-mixin vertical-panel%))
```

---

```
panel:horizontal-dragable% : class?  
  superclass: (panel:horizontal-dragable-mixin (panel:dragable-mixin horizontal-panel%))
```



---

```

(panel:dragable-container-size container-info
                               bar-thickness
                               vertical?) → real? real?
  container-info : (listof (list/c real? real? boolean? boolean?))
  bar-thickness  : real?
  vertical?      : boolean?

```

Returns the minimum width and height for a `panel:dragable<%/>` object where `container-info` (see `container-size` for more details on that argument) is the children's info, and `bar-thickness` and `vertical?` indicate the properties of the panel.

This function is exported mostly for the test suite.

---

```

(panel:dragable-place-children container-info
                               width
                               height
                               percentages
                               bar-thickness
                               vertical?)
→ (listof (list/c (integer-in 0 10000)
                 (integer-in 0 10000)
                 (integer-in 0 10000)
                 (integer-in 0 10000)))
   (listof (list/c (integer-in 0 10000)
                 (integer-in 0 10000)))
  container-info : (listof (list/c real? real? boolean? boolean?))
  width          : real?
  height         : real?
  percentages    : (listof (between/c 0 1))
  bar-thickness  : real?
  vertical?      : boolean?

```

Returns the geometry information for a draggable panel. The inputs are the `container-info` (see `place-children` for more info), the `width` and `height` of the window, the `percentages` for the spacing of the children, and a real and a boolean indicating the thickness of the bar between the child panels and whether or not this is a vertical panel, respectively.

This function is exported mostly for the test suite.

## 22 Pasteboard

---

```
pasteboard:basic% : class?  
  superclass: (editor:basic-mixin pasteboard%)
```

---

```
pasteboard:standard-style-list% : class?  
  superclass: (editor:standard-style-list-mixin pasteboard:basic%)
```

---

```
pasteboard:keymap% : class?  
  superclass: (editor:keymap-mixin pasteboard:standard-style-list%)
```

---

```
pasteboard:file% : class?  
  superclass: (editor:file-mixin pasteboard:keymap%)
```

---

```
pasteboard:backup-autosave% : class?  
  superclass: (editor:backup-autosave-mixin pasteboard:file%)
```

---

```
pasteboard:info% : class?  
  superclass: (editor:info-mixin pasteboard:backup-autosave%)
```

## 23 Path Utils

---

```
(path-utils:generate-autosave-name filename) → string?  
  filename : string?
```

Generates a name for an autosave file from *filename*.

---

```
(path-utils:generate-backup-name filename) → path?  
  filename : path?
```

Generates a name for an backup file from *filename*.

## 24 Preferences

---

```
(preferences:put-preferences/gui name-list
                               val-list) → any
  name-list : (listof symbol?)
  val-list  : (listof any/c)
```

Like `put-preferences`, but has more sophisticated error handling. In particular, it

- waits for three consecutive failures before informing the user
- gives the user the opportunity to “steal” the lockfile after the third failure, and
- when failures occur, it remembers what its arguments were and if any preference save eventually succeeds, all of the past failures are also written at that point.

---

```
(preferences:get-preference/gui sym
                               [default]) → any/c
  sym : symbol?
  default : (-> void?)
           = (λ () (error 'get-preference/gui "unknown pref ~s" sym))
```

Like `get-preference`, but has more sophisticated error handling. In particular, it passes a `#:timeout-lock-there` argument that informs the user that the preferences file is locked (and offers the alternative of not showing the message again).

---

```
(preferences:add-panel labels f) → void?
  labels : (or/c string? (cons/c string? (listof string?)))
  f : (->i ([parent (is-a?/c area-container-window<%>)])
        ()
        [_ (parent)
            (let ([old-children (send parent get-children)])
              (and/c (is-a?/c area-container-window<%>)
                    (λ (child)
                     (andmap eq?
                              (append old-children (list child))
                              (send parent get-children))))))])
```

`preferences:add-preference-panel` adds the result of `f` with name `labels` to the preferences dialog box.

The labels determine where this preference panel is placed in the dialog. If the list is just one string, the preferences panel is placed at the top level of the dialog. If there are more

strings, a hierarchy of nested panels is created and the new panel is added at the end. If multiple calls to `preferences:add-preference-panel` pass the same prefix of strings, those panels are placed in the same children.

When the preference dialog is opened for the first time, the function  $f$  is called with a panel, and  $f$  is expected to add a new child panel to it and add whatever preferences configuration controls it wants to that panel. Then,  $f$ 's should return the panel it added.

---

```
(preferences:add-editor-checkbox-panel) → void?
```

Adds a preferences panel for configuring options related to editing.

---

```
(preferences:add-general-checkbox-panel) → void?
```

Adds a catch-all preferences panel for options.

---

```
(preferences:add-warnings-checkbox-panel) → void?
```

Adds a preferences panel for configuring options relating to warnings.

---

```
(preferences:add-scheme-checkbox-panel) → void?
```

Adds a preferences panel for configuring options related to Racket.

---

```
(preferences:add-to-warnings-checkbox-panel proc) → void?  
proc : ((is-a?/c vertical-panel%) . -> . void?)
```

Saves *proc* until the preferences panel is created, when it is called with the Misc. panel to add new children to the panel.

---

```
(preferences:add-to-scheme-checkbox-panel proc) → void?  
proc : ((is-a?/c vertical-panel%) . -> . void?)
```

Saves *proc* until the preferences panel is created, when it is called with the Racket preferences panel to add new children to the panel.

---

```
(preferences:add-to-editor-checkbox-panel proc) → void?  
proc : ((is-a?/c vertical-panel%) . -> . void?)
```

Saves *proc* until the preferences panel is created, when it is called with the editor preferences panel to add new children to the panel.

---

```
(preferences:add-to-general-checkbox-panel proc) → void?  
  proc : ((is-a?/c vertical-panel%) . -> . void?)
```

Saves *proc* until the preferences panel is created, when it is called with the general preferences panel to add new children to the panel.

---

```
(preferences:add-font-panel) → void?
```

Adds a font selection preferences panel to the preferences dialog.

---

```
(preferences:show-dialog) → void?
```

Shows the preferences dialog.

---

```
(preferences:hide-dialog) → void?
```

Hides the preferences dialog.

---

```
(preferences:add-on-close-dialog-callback cb) → void?  
  cb : (-> void?)
```

Registers *cb*. Next time the user clicks the OK button the preferences dialog, all of the *cb* functions are called, assuming that each of the callbacks passed to [preferences:add-can-close-dialog-callback](#) succeed.

---

```
(preferences:add-can-close-dialog-callback cb) → void?  
  cb : (-> boolean?)
```

Registers *cb*. Next time the user clicks the OK button the preferences dialog, all of the *cb* functions are called. If any of them return `#f`, the dialog is not closed.

See also [preferences:add-on-close-dialog-callback](#).

## 25 Preferences, Textual

(require framework/preferences)

---

```
(preferences:get symbol) → any/c  
symbol : symbol?
```

See also `preferences:set-default`.

`preferences:get` returns the value for the preference `symbol`. It raises `exn:unknown-preference` if the preference's default has not been set.

---

```
(preferences:set symbol value) → void?  
symbol : symbol?  
value : any/c
```

See also `preferences:set-default`.

`preferences:set-preference` sets the preference `symbol` to `value`. This should be called when the users requests a change to a preference.

This function immediately writes the preference value to disk.

It raises `exn:unknown-preference` if the preference's default has not been set.

---

```
(preferences:add-callback p f [weak?]) → (-> void?)  
p : symbol?  
f : (λ (x) (and (procedure? x) (procedure-arity-includes? x 2)))  
weak? : boolean? = #f
```

This function adds a callback which is called with a symbol naming a preference and its value, when the preference changes. `preferences:add-callback` returns a thunk, which when invoked, removes the callback from this preference.

If `weak?` is true, the preferences system will only hold on to the callback weakly.

The callbacks will be called in the order in which they were added.

If you are adding a callback for a preference that requires marshalling and unmarshalling, you must set the marshalling and unmarshalling functions by calling `preferences:set-un/marshall` before adding a callback.

This function raises `exn:unknown-preference` if the preference has not been set.

---

```


```
(preferences:set-default symbol
                          value
                          test
                          [#:aliases aliases
                           #:rewrite-aliases rewrite-aliases])

→ void?
symbol : symbol?
value  : any/c
test   : (any/c . -> . any)
aliases : (listof symbol?) = '()
rewrite-aliases : (listof (-> any/c any))
                  = (map (lambda (x) values) aliases)
```


```

This function must be called every time your application starts up, before any call to `preferences:get` or `preferences:set` (for any given preference).

If you use `preferences:set-un/marshall`, you must call this function before calling it.

This sets the default value of the preference `symbol` to `value`. If the user has chosen a different setting, the user's setting will take precedence over the default value.

The `test` argument is used as a safeguard. That function is called to determine if a preference read in from a file is a valid preference. If `test` returns `#t`, then the preference is treated as valid. If `test` returns `#f` then the default is used.

The `aliases` and `rewrite-aliases` arguments aids in renaming preferences. If `aliases` is present, it is expected to be a list of symbols that correspond to old versions of the preferences. It defaults to `'()`. If `rewrite-aliases` is present, it is used to adjust the old values of the preferences when they are present in the saved file.

---

```


```
(preferences:set-un/marshall symbol
                             marshall
                             unmarshall) → void?

symbol : symbol?
marshall : (any/c . -> . printable/c)
unmarshall : (printable/c . -> . any/c)
```


```

`preferences:set-un/marshall` is used to specify marshalling and unmarshalling functions for the preference `symbol`. `marshall` will be called when the users saves their preferences to turn the preference value for `symbol` into a printable value. `unmarshall` will be called when the user's preferences are read from the file to transform the printable value into its internal representation. If `preferences:set-un/marshall` is never called for a particular preference, the values of that preference are assumed to be printable.

If the unmarshalling function returns a value that does not meet the guard passed to



`preferences:set-default` for this preference, the default value is used.

The `marshall` function might be called with any value returned from `read` and it must not raise an error (although it can return arbitrary results if it gets bad input). This might happen when the preferences file becomes corrupted, or is edited by hand.

`preferences:set-un/marshall` must be called before calling `preferences:get,preferences:set`.

See also `serialize` and `deserialize`.

---

`(preferences:restore-defaults)` → `void?`

`(preferences:restore-defaults)` restores the users' configuration to the default preferences.

---

`(preferences:register-save-callback callback)` → `symbol?`  
`callback` : `(-> boolean? any)`

Registers `callback` to run twice for each call to `preferences:set`—once before the preferences file is written, with `#t`, and once after it is written, with `#f`. Registration returns a key for use with `preferences:unregister-save-callback`. Caveats:

- The callback occurs on whichever thread happened to call `preferences:set`.
- Pre- and post-write notifications are not necessarily paired; unregistration may cancel the post-write notification before it occurs.

---

`(preferences:unregister-save-callback key)` → `void?`  
`key` : `symbol?`

Unregisters the save callback associated with `key`.

---

`(exn:make-unknown-preference message continuation-marks)`  
→ `exn:unknown-preference?`  
`message` : `string?`  
`continuation-marks` : `continuation-mark-set?`

Creates an unknown preference exception.

---

`(exn:unknown-preference? exn)` → `boolean?`  
`exn` : `any/c`

Determines if a value is an unknown preference exn.

---

```
(preferences:low-level-put-preferences)
→ ((listof symbol?) (listof any/c) . -> . any)
(preferences:low-level-put-preferences put-preferences) → void?
  put-preferences : ((listof symbol?) (listof any/c) . -> . any)
```

This parameter's value is called to save preference the preferences file. Its interface should be just like mzlib's *put-preferences*.

---

```
(preferences:low-level-get-preference)
→ (->* (symbol?) [(-> any)] any)
(preferences:low-level-get-preference get-preference) → void?
  get-preference : (->* (symbol?) [(-> any)] any)
```

This parameter's value is called to get a preference from the preferences file. Its interface should be just like *get-preference*.

---

```
(preferences:snapshot? arg) → boolean?
  arg : any/c
```

Determines if its argument is a preferences snapshot.

See also [preferences:get-prefs-snapshot](#) and [preferences:restore-prefs-snapshot](#).

---

```
(preferences:restore-prefs-snapshot snapshot) → void?
  snapshot : preferences:snapshot?
```

Restores the preferences saved in *snapshot*.

See also [preferences:get-prefs-snapshot](#).

---

```
(preferences:get-prefs-snapshot) → preferences:snapshot?
```

Caches all of the current values of the preferences and returns them. For any preference that has marshalling and unmarshalling set (see [preferences:set-un/marshall](#)), the preference value is copied by passing it through the marshalling and unmarshalling process. Other values are not copied, but references to them are instead saved.

See also [preferences:restore-prefs-snapshot](#).

## 26 Racket

---

`scheme:sexp-snip<%>` : interface?

---

`(send a-scheme:sexp-snip get-saved-snips)` → `(listof snip%)`

This returns the list of snips hidden by the sexp snip.

---

`scheme:sexp-snip%` : class?  
superclass: `snip%`  
extends: `scheme:sexp-snip<%>`  
`readable-snip<%>`

---

`(send a-scheme:sexp-snip get-text offset`  
`num`  
`[flattened?])` → `string`

`offset` : number  
`num` : number  
`flattened?` : boolean = `|#f|`

Overrides `get-text` in `snip%`.

Returns the concatenation of the text for all of the hidden snips.

---

`(send a-scheme:sexp-snip copy)` → `(is-a?/c scheme:sexp-snip%)`

Overrides `copy` in `snip%`.

Returns a copy of this snip that includes the hidden snips.

---

`(send a-scheme:sexp-snip write stream-out)` → `void`  
`stream-out` : `editor-stream-out%`

Overrides `write` in `snip%`.

Saves the embedded snips

---

```
(send a-scheme:sexp-snip draw dc
      x
      y
      left
      top
      right
      bottom
      dx
      dy
      draw-caret) → void
```

```
dc : dc<%>
x : real
y : real
left : real
top : real
right : real
bottom : real
dx : real
dy : real
draw-caret : symbol?
```

Overrides `draw` in `snip%`.

Draws brackets with a centered ellipses between them.

---

```
(send a-scheme:sexp-snip get-extent dc
      x
      y
      [w
      h
      descent
      space
      lspace
      rspace]) → void
```

```
dc : (is-a?/c dc<%>)
x : real
y : real
w : boxed = |#f|
h : boxed = |#f|
descent : boxed = |#f|
space : boxed = |#f|
lspace : boxed = |#f|
rspace : boxed = |#f|
```

Overrides `get-extent` in `snip%`.

Returns a size corresponding to what this snip draws.

---

```
scheme:text<%> : interface?
  implements: text:basic<%>
              mode:host-text<%>
              color:text<%>
```

Texts matching this interface support Racket mode operations.

---

```
(send a-scheme:text get-limit start) → int
  start : exact-integer
```

Returns a limit for backward-matching parenthesis starting at position *start*.

---

```
(send a-scheme:text balance-parens key-event) → void
  key-event : (instance key-event%)
```

This function is called when the user types a close parenthesis in the *text%*. If the close parenthesis that the user inserted does not match the corresponding open parenthesis and the `'framework:fixup-parens` preference is `#t` (see `preferences:get`) the correct closing parenthesis is inserted. If the `'framework:paren-match` preference is `#t` (see `preferences:get`) the matching open parenthesis is flashed.

---

```
(send a-scheme:text tabify-on-return?) → boolean?
```

The result of this method is used to determine if the return key automatically tabs over to the correct position.

Override it to change its behavior.

---

```
(send a-scheme:text tabify [start-pos]) → void
  start-pos : exact-integer
             = (send this text get-start-position)
```

Tabs the line containing by *start-pos*

---

```
(send a-scheme:text tabify-selection start
                                     end) → void
  start : exact-integer
  end   : exact-integer
```

Sets the tabbing for the lines containing positions *start* through *end*.

---

```
(send a-scheme:text tabify-all) → void
```

Tabs all lines.

---

```
(send a-scheme:text insert-return) → void
```

Inserts a newline into the buffer. If `tabify-on-return?` returns `#t`, this will tabify the new line.

---

```
(send a-scheme:text box-comment-out-selection start-pos
                                             end-pos) → void
start-pos : (or/c (symbols 'start) exact-integer?)
end-pos   : (or/c (symbols 'end) exact-integer?)
```

This method comments out a selection in the text by putting it into a comment box.

Removes the region from `start-pos` to `end-pos` from the editor and inserts a comment box with that region of text inserted into the box.

If `start-pos` is `'start`, the starting point of the selection is used. If `end-pos` is `'end`, the ending point of the selection is used.

---

```
(send a-scheme:text comment-out-selection start
                                             end) → void
start : exact-integer
end   : exact-integer
```

Comments the lines containing positions `start` through `end` by inserting a semi-colon at the front of each line.

---

```
(send a-scheme:text uncomment-selection start
                                             end) → void
start : int
end   : int
```

Uncomments the lines containing positions `start` through `end`.

---

```
(send a-scheme:text get-forward-sexp start)
→ (union |#f| exact-integer)
start : exact-integer
```

Returns the position of the end of next S-expression after position `start`, or `#f` if there is no appropriate answer.

---

```
(send a-scheme:text remove-sexp start) → void
start : exact-integer
```

Forward-deletes the S-expression starting after the position `start`.

---

```
(send a-scheme:text forward-sexp start) → exact-integer
start : |#t|
```

Moves forward over the S-expression starting at position `start`.

---

```
(send a-scheme:text flash-forward-sexp start-pos) → void
```

`start-pos` : exact-integer

Flashes the parenthesis that closes the sexpression at `start-pos`.

---

```
(send a-scheme:text get-backward-sexp start)
→ (union exact-integer |#f|)
start : exact-integer
```

Returns the position of the start of the S-expression before or containing `start`, or `#f` if there is no appropriate answer.

---

```
(send a-scheme:text flash-backward-sexp start-pos) → void
start-pos : exact-integer
```

Flashes the parenthesis that opens the sexpression at `start-pos`.

---

```
(send a-scheme:text backward-sexp start-pos) → void
start-pos : exact-integer
```

Move the caret backwards one sexpression

Moves the caret to the beginning of the sexpression that ends at `start-pos`.

---

```
(send a-scheme:text find-up-sexp start-pos)
→ (union |#f| exact-integer)
start-pos : exact-integer
```

Returns the position of the beginning of the next sexpression outside the sexpression that contains `start-pos`. If there is no such sexpression, it returns `#f`.

---

```
(send a-scheme:text up-sexp start) → void
start : exact-integer
```

Moves backward out of the S-expression containing the position `start`.

---

```
(send a-scheme:text find-down-sexp start-pos)
→ (union |#f| exact-integer)
start-pos : exact-integer
```

Returns the position of the beginning of the next sexpression inside the sexpression that contains `start-pos`. If there is no such sexpression, it returns `#f`.

---

```
(send a-scheme:text down-sexp start) → void
start : exact-integer
```

Moves forward into the next S-expression after the position `start`.

---

```
(send a-scheme:text remove-parens-forward start) → void
```

`start` : `exact-integer`

Removes the parentheses from the S-expression starting after the position `start`.

---

`(send a-scheme:text select-forward-sexp start)` → `|#t|`  
`start` : `exact-integer`

Selects the next S-expression, starting at position `start`.

---

`(send a-scheme:text select-backward-sexp start)` → `|#t|`  
`start` : `exact-integer`

Selects the previous S-expression, starting at position `start`.

---

`(send a-scheme:text select-up-sexp start)` → `|#t|`  
`start` : `exact-integer`

Selects the region to the enclosing S-expression, starting at position `start`.

---

`(send a-scheme:text select-down-sexp start)` → `|#t|`  
`start` : `exact-integer`

Selects the region to the next contained S-expression, starting at position `start`.

---

`(send a-scheme:text transpose-sexp start)` → `void`  
`start` : `exact-integer`

Swaps the S-expression beginning before the position `start` with the next S-expression following `start`.

---

`(send a-scheme:text mark-matching-parenthesis pos)` → `void`  
`pos` : `exact-positive-integer`

If the paren after `pos` is matched, this method highlights it and its matching counterpart in dark green.

---

`(send a-scheme:text get-tab-size)` → `exact-integer`

This method returns the current size of the tabs for scheme mode. See also `set-tab-size`.

---

`(send a-scheme:text set-tab-size new-size)` → `void`  
`new-size` : `exact-integer`

This method sets the tab size for this text.

---

`(send a-scheme:text introduce-let-ans)` → `void`

Adds a let around the current s-expression and a printf into the body of the let.



---

```
(send a-scheme:text move-sexp-out) → void
```

Replaces the sexpression surrounding the insertion point with the sexpression following the insertion point.

---

```
scheme:text-mixin : (class? . -> . class?)  
argument extends/implements: text:basic<%>  
                             mode:host-text<%>  
                             color:text<%>  
                             text:autocomplete<%>  
result implements: scheme:text<%>
```

This mixin adds functionality for editing Racket files.

The result of this mixin uses the same initialization arguments as the mixin's argument.

---

```
(send a-scheme:text get-word-at pos) → string  
pos : positive-exact-integer
```

Overrides `get-word-at` in `text:autocomplete<%>`.

Returns the word just before `pos`, which is then used as the prefix for auto-completion.

---

```
(send a-scheme:text get-start-of-line pos)  
→ exact-nonnegative-integer?  
pos : exact-nonnegative-integer?
```

Overrides `get-start-of-line` in `text:basic<%>`.

Returns the first non-whitespace character in the paragraph containing `pos`, unless the position is already there, in which case it returns the first position of the paragraph.

---

```
scheme:text-mode<%> : interface?
```

The result of `scheme:text-mode-mixin` implements this interface.

---

```
scheme:text-mode-mixin : (class? . -> . class?)  
argument extends/implements: color:text-mode<%>  
                             mode:surrogate-text<%>
```

result implements: `scheme:text-mode<%>`

This mixin adds Racket mode functionality to the mode that it is mixed into. The resulting mode assumes that it is only set to an editor that is the result of `scheme:text-mixin`.

---

```
(send a-scheme:text-mode on-disable-surrogate) → void
```

Overrides `on-disable-surrogate` in `mode:surrogate-text<%>`.

Removes the scheme keymap (see also `scheme:get-keymap`) and disables any parenthesis highlighting in the host editor.

---

```
(send a-scheme:text-mode on-enable-surrogate) → void
```

Overrides `on-enable-surrogate` in `mode:surrogate-text<%>`.

Adds the scheme keymap (see also `scheme:get-keymap`) and enables a parenthesis highlighting in the host editor.

---

```
scheme:set-mode-mixin : (class? . -> . class?)
```

argument extends/implements: `scheme:text<%>`  
`mode:host-text<%>`

This mixin creates a new instance of `scheme:text-mode%` and installs it, by calling its own `set-surrogate` method with the object.

---

```
scheme:text% : class?
```

superclass: `(scheme:set-mode-mixin (scheme:text-mixin (text:autocomplete-mixin (mode:host-text`

---

```
scheme:text-mode% : class?
```

superclass: `(scheme:text-mode-mixin color:text-mode%)`

---

```
(scheme:text-balanced? text [start end]) → boolean?
```

`text` : `(is-a?/c text%)`

`start` : `number? = 0`

```
end : (or/c false/c number?) = #f
```

Determines if the range in the editor from *start* to *end* in *text* has at least one complete s-expression and there are no incomplete s-expressions. If *end* is *#f*, it defaults to the last position of the *text*. The designation “complete” is defined to be something that does not cause `read` to raise a `exn:fail:read:eof?` exception, so there may be all kinds of strange read-level (not to speak of parse level) errors in the expressions.

The implementation of this function creates a port with `open-input-text-editor` and then uses `read` to parse the range of the buffer.

---

```
(scheme:add-preferences-panel) → void?
```

Adds a tabbing preferences panel to the preferences dialog.

---

```
(scheme:get-keymap) → (is-a?/c keymap%)
```

Returns a keymap with binding suitable for Racket.

---

```
(scheme:add-coloring-preferences-panel) → any
```

Installs the “Racket” preferences panel in the “Syntax Coloring” section.

---

```
(scheme:get-color-prefs-table)  
→ (listof (list/c symbol? (is-a?/c color%)))
```

Returns a table mapping from symbols (naming the categories that the online colorer uses for Racket mode coloring) to their colors.

These symbols are suitable for input to `scheme:short-sym->pref-name` and `scheme:short-sym->style-name`.

See also `scheme:get-white-on-black-color-prefs-table`.

---

```
(scheme:get-white-on-black-color-prefs-table)  
→ (listof (list/c symbol? (is-a?/c color%)))
```

Returns a table mapping from symbols (naming the categories that the online colorer uses for Racket mode coloring) to their colors when the user chooses the white-on-black mode in the preferences dialog.

See also `scheme:get-color-prefs-table`.

---

```
(scheme:short-sym->pref-name short-sym) → symbol?  
  short-sym : symbol?
```

Builds the symbol naming the preference from one of the symbols in the table returned by `scheme:get-color-prefs-table`.

---

```
(scheme:short-sym->style-name short-sym) → string?  
  short-sym : symbol?
```

Builds the symbol naming the editor style from one of the symbols in the table returned by `scheme:get-color-prefs-table`. This style is a named style in the style list returned by `editor:get-standard-style-list`.

---

```
(scheme:get-wordbreak-map) → (is-a?/c editor-wordbreak-map%)
```

This method returns a `editor-wordbreak-map%` that is suitable for Racket.

---

```
(scheme:init-wordbreak-map key) → void?  
  key : (is-a?/c keymap%)
```

Initializes the workdbreak map for `keymap`.

---

```
(scheme:setup-keymap keymap) → void?  
  keymap : (is-a?/c keymap%)
```

Initializes `keymap` with Racket-mode keybindings.

## 27 Text

---

```
text:basic<%> : interface?  
  implements: editor:basic<%>  
             text%
```

Classes matching this interface are expected to implement the basic functionality needed by the framework.

---

```
(send a-text:basic highlight-range start  
                                     end  
                                     color  
                                     [caret-space  
                                     priority  
                                     style]) → (-> void)  
  
start : exact-nonnegative-integer?  
end : exact-nonnegative-integer?  
color : (or/c string? (is-a?/c color%))  
caret-space : boolean? = #f  
priority : (symbols 'high 'low) = 'low  
style : (symbols 'rectangle 'ellipse 'hollow-ellipse 'dot)  
       = 'rectangle
```

This function highlights a region of text in the buffer.

The range between *start* and *end* will be highlighted with the color in *color*, if the style is *'rectangle* (the default). If the style is *'ellipse*, then an ellipse is drawn around the range in the editor, using the color. If the style is *'hollow-ellipse*, then the outline of an ellipse is drawn around the range in the editor, using the color.

If the style is *'dot*, then *start* and *end* must be the same, and a dot is drawn at the bottom of that position in the editor.

If *caret-space?* is not *#f*, the left edge of the range will be one pixel short, to leave space for the caret. The caret does not interfere with the right hand side of the range. Note that under some platforms, the caret is drawn with XOR, which means almost anything can happen. So if the caret is in the middle of the range it may be hard to see, or if it is on the left of the range and *caret-space?* is *#f* it may also be hard to see.

The *priority* argument indicates the relative priority for drawing overlapping regions. If two regions overlap and have different priorities, the region with *'high* priority will be drawn second and only it will be visible in the overlapping region.

This method returns a thunk, which, when invoked, will turn off the highlighting from this range.

See also [unhighlight-range](#).

---

```
(send a-text:basic unhighlight-range start
                                     end
                                     color
                                     [caret-space
                                     style]) → void?

start : exact-nonnegative-integer?
end : exact-nonnegative-integer?
color : (or/c string? (is-a?/c color%))
caret-space : boolean? = #f
style : (symbols 'rectangle 'ellipse 'hollow-ellipse)
        = 'rectangle
```

This method removes the highlight from a region of text in the buffer.

The region must match up to a region specified from an earlier call to [highlight-range](#).

---

```
(send a-text:basic get-highlighted-ranges) → (listof range)

Returns a list of (opaque) values representing the active ranges in the editor.
```

---

```
(send a-text:basic get-styles-fixed) → boolean?
```

If the result of this function is #t, the styles in this `text:basic<%>` will be fixed. This means that any text inserted to this editor has its style set to this editor's `style-list%'s "Standard"` style.

See also [set-styles-fixed](#).

---

```
(send a-text:basic get-fixed-style) → (is-a?/c style<%>)

Returns the style used by set-styles-fixed when setting the styles.
```

---

```
(send a-text:basic set-styles-fixed fixed?) → void
fixed? : boolean?
```

Sets the styles fixed parameter of this `text%`. See also [get-styles-fixed](#) and [get-fixed-style](#).

---

```
(send a-text:basic move/copy-to-edit dest-text
                                     start
                                     end
                                     dest-pos) → void

dest-text : (instance text%)
start : exact-integer
end : exact-integer
dest-pos : exact-integer
```

This moves or copies text and snips to another edit.

Moves or copies from the edit starting at *start* and ending at *end*. It puts the copied text and snips in *dest-text* starting at location *dest-pos*.

If a snip refused to be moved, it will be copied, otherwise it will be moved. A snip may refuse to be moved by returning *#f* from `release-from-owner`.

---

```
(send a-text:basic initial-autowrap-bitmap)
→ (union |#f| (instance bitmap%))
```

The result of this method is used as the initial autowrap bitmap. Override this method to change the initial `bitmap%`. See also `set-autowrap-bitmap`

Defaultly returns the result of `icon:get-autowrap-bitmap`

---

```
(send a-text:basic get-port-name) → symbol?
```

The result of this method is a symbol that identifies this editor and that is used as the port-name of a port that is read from this editor if this editor is used in DrRacket. See also `port-name-matches?`.

---

```
(send a-text:basic port-name-matches? id) → boolean?
id : (or/c path? symbol?)
```

Indicates if *id* matches the port name of this file. If the file is saved, the port name matches when the save file is the path as *id*. If the file has not been saved, the port name matches if the symbol is the same as the result of `port-name-matches?`.

---

```
(send a-text:basic get-edition-number)
→ exact-nonnegative-integer?
```

Returns a number that increments everytime something in the editor changes.

The number is updated in `after-insert` in `text%` and `after-delete` in `text%`.

---

```
(send a-text:basic get-start-of-line pos)
→ exact-nonnegative-integer?
pos : exact-nonnegative-integer?
```

This method is used by `keymap:setup-global` to implement a keybinding for the "home" key and for "c:a".

Its default implementation is `(line-start-position (position-line pos))`.

---

```
text:basic-mixin : (class? . -> . class?)
argument extends/implements: editor:basic<%>
text%
```

result implements: `text:basic<%>`

This mixin implements the basic functionality needed for `text%` objects in the framework.

The class that this mixin produces uses the same initialization arguments as it's input.

---

```
(send a-text:basic on-paint before?
      dc
      left
      top
      right
      bottom
      dx
      dy
      draw-caret) → void

before? : any/c
dc      : (is-a?/c dc<%>)
left   : real?
top    : real?
right  : real?
bottom : real?
dx     : real?
dy     : real?
draw-caret : (one-of/c 'no-caret 'show-inactive-caret 'show-caret)
```

Overrides `on-paint` in `editor<%>`.  
Draws the rectangles installed by `highlight-range`.

---

```
(send a-text:basic on-insert start end) → void
start : exact-int
end   : exact-int
```

Augments `on-insert` in `text%`.  
See `set-styles-fixed`.

---

```
(send a-text:basic after-insert start len) → void
start : exact-nonnegative-integer?
len   : exact-nonnegative-integer?
```

Augments `after-insert` in `text%`.  
See `set-styles-fixed`.

---

```
(send a-text:basic put-file directory
      default-name) → void
directory : path
```



`default-name` : path

Overrides `put-file` in `editor<%>`.

Like `put-file` but uses `finder:put-file` instead of `put-file`.

---

`text:first-line<%>` : interface?

implements: `text%`

Objects implementing this interface, when `highlight-first-line` is invoked with `#t`, always show their first line, even with scrolled (as long as `first-line-currently-drawn-specially?` returns `#t`).

---

`(send a-text:first-line highlight-first-line on?)` → void?  
`on?` : boolean?

Call this method to enable special treatment of the first line in the editor.

---

`(send a-text:first-line first-line-currently-drawn-specially?)`  
→ boolean?

Returns `#t` if `is-special-first-line?` returned `#t` for the current first line and if the buffer is scrolled down so that the first line would not (ordinarily) be visible.

---

`(send a-text:first-line get-first-line-height)` → number?

Returns the height, in pixels, of the first line.

---

`(send a-text:first-line is-special-first-line? line)` → boolean?  
`line` : string?

Override this method to control when the first line is always visible. The argument is the first line, as a string.

---

`text:first-line-mixin` : (class? . -> . class?)

argument extends/implements: `text%`

result implements: `text:first-line<%>`

Provides the implementation of `text:first-line<%>`. Does so by just painting the text of the first line over top of what is already there and overriding `scroll-editor-to` to patch up scrolling and `on-event` to patch up mouse handling.

---

```

(send a-text:first-line on-paint before?
      dc
      left
      top
      right
      bottom
      dx
      dy
      draw-caret) → void?

before? : any/c
dc : (is-a?/c dc<%>)
left : real?
top : real?
right : real?
bottom : real?
dx : real?
dy : real?
draw-caret : (one-of/c 'no-caret 'show-inactive-caret 'show-caret)

```

Overrides `on-paint` in `editor<%>`.

Based on the various return values of the methods in `text:first-line`, draws the first actual line of the editor over top of the first visible line in the editor.

---

```

(send a-text:first-line on-event event) → void?
event : (is-a?/c mouse-event%)

```

Overrides `on-event` in `editor<%>`.

Clicks in the first line cause the editor to scroll to the actual first line.

---

```

(send a-text:first-line scroll-editor-to localx
      locally
      width
      height
      refresh?
      bias) → void?

```

```

localx : real?
locally : real?
width : (and/c real? (not/c negative?))
height : (and/c real? (not/c negative?))
refresh? : any/c
bias : (one-of/c 'start 'end 'none)

```

Overrides `scroll-editor-to` in `editor<%>`.

Scrolls a little bit more, when a scroll would be requested that scrolls something so that it is line underneath the first line.

---

```
text:foreground-color<%> : interface?
  implements: text:basic<%>
             editor:standard-style-list<%>
```

---

```
text:foreground-color-mixin : (class? . -> . class?)
  argument extends/implements: text:basic<%>
                              editor:standard-style-list<%>
  result implements: text:foreground-color<%>
```

This mixin changes the default text style to have the foreground color controlled by `editor:set-default-font-color`.

---

```
(send a-text:foreground-color default-style-name) → string
  Overrides default-style-name in editor<%>.
  Returns the result of editor:get-default-color-style-name.
```

---

```
(send a-text:foreground-color get-fixed-style)
→ (is-a?/c style<%>)
  Overrides get-fixed-style in text:basic<%>.
  Returns the style named by editor:get-default-color-style-name.
```

---

```
text:hide-caret/selection<%> : interface?
  implements: text:basic<%>
```

This class hides the caret, except when the selection is active.

Instances of this class are useful for editors that used for displaying purposes, but still allow users to copy their text.

---

```
text:hide-caret/selection-mixin : (class? . -> . class?)
  argument extends/implements: text:basic<%>
  result implements: text:hide-caret/selection<%>
```

---

```
(send a-text:hide-caret/selection after-set-position) → void
```

Augments `after-set-position` in `text%`.

Calls `hide-caret` to hide the caret when there is only a caret and no selection.

---

```
text:nbsp->space<%> : interface?
```

implements: `text%`

Classes that implement this interface silently change non-breaking spaces, ie the character (`integer->char 160`), to regular spaces when inserted into the editor.

---

```
text:nbsp->space-mixin : (class? . -> . class?)
```

argument extends/implements: `text%`

result implements: `text:nbsp->space<%>`

---

```
(send a-text:nbsp->space on-insert start  
                                end) → void
```

`start` : `exact-int`

`end` : `exact-int`

Augments `on-insert` in `text%`.

Starts an edit-sequence by calling `begin-edit-sequence`.

---

```
(send a-text:nbsp->space after-insert start  
                                len) → void
```

`start` : `exact-nonnegative-integer?`

`len` : `exact-nonnegative-integer?`

Augments `after-insert` in `text%`.

Replaces all non-breaking space characters (`integer->char 160`) by `#\space` characters.

Ends the edit sequence (by calling `end-edit-sequence`) started in `on-insert`.

---

```
text:normalize-paste<%> : interface?
```

implements: `text:basic<%>`

---

`(send a-text:normalize-paste ask-normalize?) → boolean?`

Prompts the user if the pasted text should be normalized (and updates various preferences based on the response).

Override this method in the mixin to avoid all GUI and preferences interactions.

---

`(send a-text:normalize-paste string-normalize s) → string?`  
`s : string?`

Normalizes `s`. Defaults to `string-normalize-nfkc`.

---

`text:normalize-paste-mixin : (class? . -> . class?)`  
argument extends/implements: `text:basic<%>`  
result implements: `text:normalize-paste<%>`

---

`(send a-text:normalize-paste do-paste start  
time) → void?`  
`start : exact-nonnegative-integer?`  
`time : (and/c exact? integer?)`

Overrides `do-paste` in `text%`.

Overridden to detect when insertions are due to pasting. Sets some internal state and calls the super.

---

`(send a-text:normalize-paste on-insert start  
len) → void?`  
`start : exact-nonnegative-integer?`  
`len : exact-nonnegative-integer?`

Augments `on-insert` in `text%`.

Calls `begin-edit-sequence`.

---

`(send a-text:normalize-paste after-insert start  
len) → void?`  
`start : exact-nonnegative-integer?`  
`len : exact-nonnegative-integer?`

Augments `after-insert` in `text%`.

Normalizes any next text and calls `end-edit-sequence`.

---

`text:searching<%> : interface?`

implements: `editor:keymap<%>`  
`text:basic<%>`

Any object matching this interface can be searched.

Searches using this class has a non-traditional feature for performance reasons. Specifically, multiple adjacent hits are coalesced into a single search results when bubbles are drawn. This means, for example, that searching for a space in a file with 80,000 spaces (as one file in the Racket code base has) is still tractable, since many of those spaces will be next to each other and thus there will be far fewer bubbles (the file in question has only 20,000 such bubbles).

---

```
(send a-text:searching set-searching-state str
                                cs?
                                replace-start)
```

```
→ void?
str : (or/c false/c string?)
cs? : boolean?
replace-start : (or/c false/c number?)
```

If `str` is not `#f`, then this method highlights every occurrence of `str` in the editor. If `str` is `#f`, then it clears all of the highlighting in the buffer.

If `cs?` is `#f`, the search is case-insensitive, and otherwise it is case-sensitive.

If the `replace-start` argument is `#f`, then the search is not in replacement mode. If it is a number, then the first search hit after that position in the editor is where the next replacement will take place.

---

```
(send a-text:searching set-search-anchor position) → void?
position : (or/c false/c number?)
```

Sets the anchor's position in the editor. Only takes effect if the `'framework:anchored-search` preference is on.

---

```
(send a-text:searching get-search-hit-count) → number?
```

Returns the number of hits for the search in the buffer, based on the count found last time that a search happened.

---

```
(send a-text:searching set-replace-start pos) → void?
pos : (or/c false/c number?)
```

Sets the position where replacement next occurs. This is equivalent to calling `set-searching-state` with a new `replace-start` argument, but the other arguments the same as the last call to `set-searching-state`, but is more efficient (since `set-searching-state` will search the entire buffer and rebuild all of the bubbles).

---

```
(send a-text:searching get-search-bubbles)
→ (listof (list/c (cons/c number number)
                 (list/c number number number)))
```

Returns information about the search bubbles in the editor. Each item in the outermost list corresponds to a single bubble. The pair of numbers is the range of the bubble and the triple of numbers is the color of the bubble, in RGB coordinates.

If `replace-start` has been set (via `set-replace-start`) and the closest search hit following `replace-start` does not collapse with an adjacent bubble, the result will include that bubble. If the closest search hit after `replace-start` is collapsed with another bubble, then the search hit is not reflected in the result.

This method is intended for use in test suites.

---

```
text:searching-mixin : (class? . -> . class?)
argument extends/implements: editor:keymap<%>
                             text:basic<%>
result implements: text:searching<%>
```

This `text%` can be searched.

The result of this mixin uses the same initialization arguments as the mixin's argument.

---

```
(send a-text:searching get-keymaps)
→ (list-of (instance keymap%))

Overrides get-keymaps in editor:keymap<%>.
```

This returns a list containing the super-class's keymaps, plus the result of `keymap:get-search`

---

```
(send a-text:searching after-insert start
                             len) → void?

start : exact-nonnegative-integer?
len : exact-nonnegative-integer?
```

Augments `after-insert` in `text%`.

Re-does any search now that the contents of the window have changed.

---

```
(send a-text:searching after-delete start
                             len) → void?

start : exact-nonnegative-integer?
len : exact-nonnegative-integer?
```

Augments `after-delete` in `text%`.

Re-does any search now that the contents of the window have changed.

---

```
(send a-text:searching on-focus on?) → void?  
on? : boolean?
```

Overrides `on-focus` in `editor<%>`.

Tells the frame containing the editor to search based on this editor via the `set-text-to-search` method.

---

```
text:return<%> : interface?  
implements: text%
```

Objects supporting this interface were created by `text:return-mixin`.

---

```
text:return-mixin : (class? . -> . class?)  
argument extends/implements: text%  
result implements: text:return<%>
```

Use this buffer to perform some special action when return is typed.

---

```
(new text:return-mixin [return return])  
→ (is-a?/c text:return-mixin)  
return : (-> boolean?)
```

---

```
(send a-text:return on-local-char event) → void  
event : (is-a?/c key-event%)
```

Overrides `on-local-char` in `editor<%>`.

If `key` is either return or newline, only invoke the `return` thunk (initialization argument) and do nothing else.

---

```
text:wide-snip<%> : interface?  
implements: text:basic<%>
```

---

```
(send a-text:wide-snip add-wide-snip snip) → void  
snip : (instance snip%)
```



Registers a snip in this editor to be resized when its viewing area changes. Ensures the snip is as wide as the viewing area.

This method should only be called by `add-wide-snip` in `canvas:wide-snip<%>`.

---

```
(send a-text:wide-snip add-tall-snip snip) → void
snip : (is-a?/c snip%)
```

Registers a snip in this editor. It is resized when the viewing area of the editor changes.

This method should only be called by `add-tall-snip` in `canvas:wide-snip<%>`.

---

```
text:wide-snip-mixin : (class? . -> . class?)
argument extends/implements: text:basic<%>
result implements: text:wide-snip<%>
```

---

```
text:delegate<%> : interface?
implements: text:basic<%>
```

Implementations of this interface copy all of the changes to this editor to the result of `get-delegate` except instead of regular string and tab snips, instead instances of `text:1-pixel-string-snip%` and `text:1-pixel-tab-snip%` are created.

The contents of the two editor are kept in sync, as modifications to this object happen.

---

```
(send a-text:delegate get-delegate)
→ (union |#f| (instanceof text%))
```

The result of this method is the `text%` object that the contents of this editor are being delegated to, or `#f`, if there is none.

---

```
(send a-text:delegate set-delegate delegate) → void
delegate : (union |#f| (instanceof text%))
```

This method sets the current delegate.

When it is set, all of the snips are copied from this object to `delegate`. Additionally, if this object implements `scheme:text<%>` the tab settings of `delegate` are updated to match this objects.

---

```
text:1-pixel-string-snip% : class?  
  superclass: string-snip%
```

This class re-uses the implementation of `string-snip%` to implement a string snip that just draws a single pixel for each character in the string.

See also `text:1-pixel-tab-snip%` for a similar extension to the `tab-snip%` class.

This snip is used in conjunction with the `frame:delegate<%>` and `text:delegate<%>` interfaces.

---

```
(send a-text:1-pixel-string-snip split position  
                                     first  
                                     second) → void  
  
position : exact  
first : (box (instanceof snip%))  
second : (box (instanceof snip%))
```

Overrides `split` in `snip%`.

Fills the boxes with instance of `text:1-pixel-string-snip%`.

---

```
(send a-text:1-pixel-string-snip copy) → (instanceof snip%)
```

Overrides `copy` in `snip%`.

Creates and returns an instance of `text:1-pixel-string-snip%`.

---

```
(send a-text:1-pixel-string-snip get-extent dc  
                                     x  
                                     y  
                                     [w  
                                     h  
                                     descent  
                                     space  
                                     lspace  
                                     rspace]) → void
```

```
dc : (instanceof dc<%>)  
x : real  
y : real  
w : (box (union non-negative-real-number |#f|)) = |#f|  
h : (box (union non-negative-real-number |#f|)) = |#f|  
descent : (box (union non-negative-real-number |#f|)) = |#f|  
space : (box (union non-negative-real-number |#f|)) = |#f|  
lspace : (box (union non-negative-real-number |#f|)) = |#f|  
rspace : (box (union non-negative-real-number |#f|)) = |#f|
```

Overrides `get-extent` in `snip%`.

Sets the descent, space, lspace, and rspace to zero. Sets the height to 1. Sets the width to the number of characters in the string.

---

```
(send a-text:1-pixel-string-snip insert s
                                     len
                                     [pos]) → void

s : string
len : exact
pos : exact = 0
```

Overrides `insert` in `string-snip%`.

---

```
(send a-text:1-pixel-string-snip draw dc
                                     x
                                     y
                                     left
                                     top
                                     right
                                     bottom
                                     dx
                                     dy
                                     draw-caret) → void

dc : (instanceof dc<%>)
x : real
y : real
left : real
top : real
right : real
bottom : real
dx : real
dy : real
draw-caret : (union 'no-caret 'show-inactive-caret 'show-caret)
```

Overrides `draw` in `snip%`.

Draws black pixels for non-whitespace characters and draws nothing for whitespace characters.

---

```
text:1-pixel-tab-snip% : class?
  superclass: tab-snip%
```

This class re-uses the implementation of `tab-snip%` to implement a string snip that is always one pixel high.

See also `text:1-pixel-string-snip%` for a similar extension to the `string-snip%` class.

This snip is used in conjunction with the `frame:delegate<%>` and `text:delegate<%>` interfaces.

---

```
(send a-text:1-pixel-tab-snip split position
                                first
                                second) → void
```

```
position : exact
first : (box (instanceof snip%))
second : (box (instanceof snip%))
```

Overrides `split` in `snip%`.

Fills the boxes with instance of `text:1-pixel-tab-snip%`.

---

```
(send a-text:1-pixel-tab-snip copy) → (instanceof snip%)
```

Overrides `copy` in `snip%`.

Creates and returns an instance of `text:1-pixel-tab-snip%`.

---

```
(send a-text:1-pixel-tab-snip get-extent dc
                                x
                                y
                                [w
                                h
                                descent
                                space
                                lspace
                                rspace]) → void
```

```
dc : (instanceof dc<%>)
x : real
y : real
w : (box (union non-negative-real-number |#f|)) = |#f|
h : (box (union non-negative-real-number |#f|)) = |#f|
descent : (box (union non-negative-real-number |#f|)) = |#f|
space : (box (union non-negative-real-number |#f|)) = |#f|
lspace : (box (union non-negative-real-number |#f|)) = |#f|
rspace : (box (union non-negative-real-number |#f|)) = |#f|
```

Overrides `get-extent` in `snip%`.

Sets the descent, space, lspace, and rspace to zero. Sets the height to 1. Sets the width to the width of tabs as returned in the `tab-width` parameter of the `get-tabs` method.

---

```
(send a-text:1-pixel-tab-snip draw dc
      x
      y
      left
      top
      right
      bottom
      dx
      dy
      draw-caret) → void

dc : (instanceof dc<%>)
x : real
y : real
left : real
top : real
right : real
bottom : real
dx : real
dy : real
draw-caret : (union 'no-caret 'show-inactive-caret 'show-caret)
  Overrides draw in snip%.
  Draws nothing.
```

---

```
text:delegate-mixin : (class? . -> . class?)
argument extends/implements: text:basic<%>
result implements: text:delegate<%>
```

This mixin provides an implementation of the `text:delegate<%>` interface.

---

```
(send a-text:delegate highlight-range start
      end
      color
      [caret-space
      priority
      style]) → (-> void)

start : exact-integer
end : exact-nonnegative-integer?
color : (or/c string? (is-a?/c color%))
caret-space : boolean? = #f
priority : (symbols 'high 'low) = 'low
style : (symbols 'rectangle 'ellipse 'hollow-ellipse 'dot)
       = 'rectangle
```

Overrides `highlight-range` in `text:basic<%>`.

In addition to calling the super method, `highlight-range`, this method forwards the highlighting to the delegatee.

---

```
(send a-text:delegate unhighlight-range start
                                     end
                                     color
                                     [caret-space
                                     style]) → void?

start : exact-nonnegative-integer?
end   : exact-nonnegative-integer?
color : (or/c string? (is-a?/c color%))
caret-space : boolean? = #f
style : (symbols 'rectangle 'ellipse 'hollow-ellipse)
       = 'rectangle
```

Overrides `unhighlight-range` in `text:basic<%>`.

This method propagates the call to the delegate and calls the super method.

---

```
(send a-text:delegate on-paint before?
                             dc
                             left
                             top
                             right
                             bottom
                             dx
                             dy
                             draw-caret) → void

before? : any/c
dc      : (is-a?/c dc<%>)
left    : real?
top     : real?
right   : real?
bottom  : real?
dx      : real?
dy      : real?
draw-caret : (one-of/c 'no-caret 'show-inactive-caret 'show-caret)
```

Overrides `on-paint` in `editor<%>`.

Draws a blue region in the delegatee editor that shows where the visible region of the delegate editor is.

---

```
(send a-text:delegate on-edit-sequence) → void
```

Augments `on-edit-sequence` in `editor<%>`.

starts an edit sequence in the delegate.

---

`(send a-text:delegate after-edit-sequence) → void`

Augments `after-edit-sequence` in `editor<%>`.

ends an edit sequence in the delegate.

---

`(send a-text:delegate resized snip  
redraw-now?) → void`

`snip : (is-a?/c snip%)`

`redraw-now? : boolean?`

Overrides `resized` in `editor<%>`.

Sends a message to the delegate to update the size of the copied snip, if there is one.

---

`(send a-text:delegate after-insert start  
len) → void`

`start : number`

`len : number`

Augments `after-insert` in `text%`.

forwards the change to the delegate

---

`(send a-text:delegate after-delete start  
len) → void`

`start : number`

`len : number`

Augments `after-delete` in `text%`.

forwards the change to the delegate.

---

`(send a-text:delegate after-change-style start  
len) → void`

`start : number`

`len : number`

Augments `after-change-style` in `text%`.

forwards the changed style to the delegate.

---

`(send a-text:delegate on-load-file filename  
format) → void`

`filename : string`

`format : symbol?`

Augments `on-load-file` in `editor<%>`.

remembers the filename, for use in `after-load-file`.

---

---

```
(send a-text:delegate after-load-file success?) → void
  success? : boolean?
```

Augments `after-load-file` in `editor<%>`.

updates the delegate with the new contents of the text.

---

```
text:info<%> : interface?
  implements: text:basic<%>
```

Objects supporting this interface are expected to send information about themselves to the frame that is displaying them.

---

```
text:info-mixin : (class? . -> . class?)
  argument extends/implements: editor:keymap<%>
                               text:basic<%>
  result implements: text:info<%>
```

This mixin adds support for supplying information to objects created with `frame:info-mixin`. When this `editor:basic<%>` is displayed in a frame, that frame must have been created with `frame:info-mixin`.

---

```
(send a-text:info set-anchor on?) → void
  on? : any/c
```

Overrides `set-anchor` in `text%`.

Calls the `anchor-status-changed` method of the frame that is viewing this object. It uses `get-canvas` to get the canvas for this frame, and uses that canvas's `top-level-window<%>` as the frame.

---

```
(send a-text:info set-overwrite-mode on?) → void
  on? : any/c
```

Overrides `set-overwrite-mode` in `text%`.

Calls the `overwrite-status-changed` method of the frame that is viewing this object. It uses `get-canvas` to get the canvas for this frame, and uses that canvas's `top-level-window<%>` as the frame.

---

```
(send a-text:info after-set-position) → void
```

Augments `after-set-position` in `text%`.



Calls the `editor-position-changed` method of the frame that is viewing this object. It uses `get-canvas` to get the canvas for this frame, and uses that canvas's `top-level-window<%>` as the frame.

---

```
(send a-text:info after-insert start len) → void
start : exact-nonnegative-integer?
len : exact-nonnegative-integer?
```

Augments `after-insert` in `text%`.

Calls the `editor-position-changed` method of the frame that is viewing this object. It uses `get-canvas` to get the canvas for this frame, and uses that canvas's `top-level-window<%>` as the frame.

---

```
(send a-text:info after-delete start len) → void
start : exact-nonnegative-integer?
len : exact-nonnegative-integer?
```

Augments `after-delete` in `text%`.

Calls the `editor-position-changed` method of the frame that is viewing this object. It uses `get-canvas` to get the canvas for this frame, and uses that canvas's `top-level-window<%>` as the frame.

---

```
text:clever-file-format<%> : interface?
implements: text%
```

Objects supporting this interface are expected to support a clever file format when saving.

---

```
text:clever-file-format-mixin : (class? . -> . class?)
argument extends/implements: text%
result implements: text:clever-file-format<%>
```

The result of this mixin uses the same initialization arguments as the mixin's argument.

When files are saved from this `text%`, a check is made to see if there are any non-`string-snip%` objects in the `text%`. If so, it is saved using the file format `'std`. (see `set-file-format` for more information. If not, the file format passed to `save-file` is used.

---

```
(send a-text:clever-file-format on-save-file filename
                                     format) → void
filename : path?
```

```
format : (one-of/c 'guess 'standard 'text 'text-force-cr 'same 'copy)
```

Augments `on-save-file` in `editor`<%>.

If the method `get-file-format` returns `'standard` and the text has only `string-snip`%s, the file format is set to `'text`.

If the method `get-file-format` returns `'text` and the text has some non `string-snip`%s, the file format is set to `'standard`.

Depending on the user's preferences, the user may also be queried.

Also, the changes to the file format only happen if the argument `file-format` is `'copy` or `'same`.

---

```
text:file<%> : interface?  
  implements: editor:file<%>  
              text:basic<%>
```

Mixins that implement this interface lock themselves when the file they are editing is read only.

---

```
(send a-text:file get-read-write?) → boolean?
```

Indicates whether or not this editor is in read-write mode.

---

```
(send a-text:file while-unlocked thunk) → any/c  
  thunk : (-> any/c)
```

Unlocks the editor, calls the `thunk`, and then relocks the editor, all using a `dynamic-wind`.

---

```
text:file-mixin : (class? . -> . class?)  
  argument extends/implements: editor:file<%>  
                               text:basic<%>  
  result implements: text:file<%>
```

---

```
(send a-text:file can-insert? start len) → boolean?  
  start : number  
  len : number
```

Augments `can-insert?` in `text`%.

Returns false if the result of `get-read-write?` is true, otherwise returns the result of calling `inner`.

---

```
(send a-text:file can-delete? start len) → boolean?
```

```
start : number
len : number
```

Augments `can-delete?` in `text%`.

Returns false if the result of `get-read-write?` is true, otherwise returns the result of calling `inner`.

---

```
(send a-text:file after-save-file) → void
```

Augments `after-save-file` in `editor<%>`.

Checks if the newly saved file is write-only in the filesystem. If so, locks the editor with the `lock` method. Otherwise unlocks the buffer

For each canvas returned from `get-canvases` it checks to see if the `canvas%`'s `get-top-level-window` matches the `frame:editor<%>` interface. If so, it calls `set-label` with the last part of the filename (ie, the name of the file, not the directory the file is in).

---

```
(send a-text:file after-load-file) → void
```

Augments `after-load-file` in `editor<%>`.

Checks if the newly loaded file is write-only in the filesystem. If so, locks the editor with the `lock` method. Otherwise unlocks the buffer

For each canvas returned from `get-canvases` it checks to see if the `canvas%`'s `get-top-level-window` matches the `frame:editor<%>` interface. If so, it calls `set-label` with the last part of the filename (ie, the name of the file, not the directory the file is in).

---

```
text:ports<%> : interface?
```

Classes implementing this interface (via the associated mixin) support input and output ports that read from the editor.

There are two input ports: the normal input port just reads from the editor's contents directly and the box input port inserts an editor snip into this text and uses input typed into the box as input into the port.

They create three threads to mediate access to the input and output ports (one for each input port and one for all of the output ports).

---

```
(send a-text:ports delete/io start end) → void
```

```
start : exact-integer
```

```
end : exact-integer
```

Deletes the text between `start` and `end` without changing the behavior of the ports (otherwise, deleting the text would break internal invariants of the port).

Both *start* and *end* must be less than [get-insertion-point](#) (or else it is safe to delete them so you don't need this method).

---

`(send a-text:ports get-insertion-point)` → `exact-integer`  
Returns the position where characters put into the output port will appear.

---

`(send a-text:ports set-insertion-point ip)` → `void`  
*ip* : `exact-integer`  
Sets the position where the output port will insert characters. See also [get-insertion-point](#).

---

`(send a-text:ports get-unread-start-point)` → `exact-integer`  
Returns the position where input will be taken into the input port (after the next time return is typed).

---

`(send a-text:ports set-unread-start-point usp)` → `void`  
*usp* : `exact-integer`  
Sets the position where input will be taken into the input port (after the next time return is typed).  
See also [get-unread-start-point](#).

---

`(send a-text:ports set-allow-edits allow-edits?)` → `void`  
*allow-edits?* : `boolean?`  
Enables or disables editing in the buffer. Be sure to update the unread start point (via [set-unread-start-point](#)) and the insertion point (via [set-insertion-point](#)) after making changes to the buffer.

---

`(send a-text:ports get-allow-edits)` → `boolean?`  
Indicates if editing is allowed in the buffer at this point.

---

`(send a-text:ports insert-between str)` → `void`  
*str* : `(union snip% string)`  
Inserts some text between the unread start point and the insertion point (and updates them properly). To insert before the two points, see [insert-before](#).  
See also [set-unread-start-point](#) and [set-insertion-point](#).

---

`(send a-text:ports insert-before str)` → `void`  
*str* : `(union snip% string)`  
Inserts some text before the unread start point and updates it and the insertion point properly. To insert between the two points, see [insert-between](#).  
See also [set-unread-start-point](#) and [set-insertion-point](#).

---

`(send a-text:ports submit-to-port? key) → boolean?`  
`key : char`

Augment this method to help control when characters should be submitted to the input port.

Return `#t` or the result of calling `inner`.

---

`(send a-text:ports on-submit) → void`

This method is called when text is sent into the input port.

Does nothing.

---

`(send a-text:ports send-eof-to-in-port) → void`

This method puts an eof into the input port.

---

`(send a-text:ports send-eof-to-box-in-port) → void`

This method puts an eof into the box input port.

---

`(send a-text:ports reset-input-box) → void`

This method removes the current input box from the editor (and all input in it is lost).

---

`(send a-text:ports clear-output-ports) → void`

Flushes all of the data in all of the output ports that hasn't appeared in the editor yet.

---

`(send a-text:ports clear-input-port) → void`

Flushes all of the data in the input port that hasn't yet been read. Reading will now block.

---

`(send a-text:ports clear-box-input-port) → void`

Flushes all of the data in the box input port that hasn't yet been read. Reading will now block.

---

`(send a-text:ports get-out-style-delta)`  
`→ (or/c (is-a?/c style-delta%) string?)`

The result of this method is the style that is used to color text submitted to the result of `get-out-port`.

If the result is a string that is not mapped in the editor's style list, the style named `"Standard"` is used and if that isn't mapped, the style named `"Basic"` is used.

This method is called during the initialization of the class.

Defaultly returns `"text:ports out"` which is mapped to a blue style in the style list returned by `editor:get-standard-style-list`.

---

```
(send a-text:ports get-err-style-delta)
→ (or/c (is-a?/c style-delta%) string?)
```

The result of this method is the style that is used to color text submitted to the result of `get-err-port`.

If the result is a string that is not mapped in the editor's style list, the style named `"Standard"` is used and if that isn't mapped, the style named `"Basic"` is used.

This method is called during the initialization of the class.

Defaultly returns `"text:ports err"` which is mapped to a red italic style in the style list returned by `editor:get-standard-style-list`.

---

```
(send a-text:ports get-value-style-delta)
→ (or/c (is-a?/c style-delta%) string?)
```

The result of this method is the style (or the name of the style) that is used to color text submitted to the result of `get-value-port`.

If the result is a string that is not mapped in the editor's style list, the style named `"Standard"` is used and if that isn't mapped, the style named `"Basic"` is used.

This method is called during the initialization of the class.

Defaultly returns `"text:ports value"` which is mapped to a blue style in the style list returned by `editor:get-standard-style-list`.

---

```
(send a-text:ports get-in-port) → input-port
```

Returns the input port that data in this editor is sent to.

---

```
(send a-text:ports get-in-box-port) → input-port
```

Returns the box input port that data in this editor is sent to.

---

```
(send a-text:ports get-out-port) → output-port
```

Returns an output port that writes into this editor. The only difference between this port and the ports returned by `get-err-port` and `get-value-port` is the font style and color.

---

```
(send a-text:ports get-err-port) → output-port
```

Returns an output port that writes into this editor. The only difference between this port and the ports returned by `get-err-port` and `get-out-port` is the font style and color.

---

`(send a-text:ports get-value-port)` → output-port

Returns an output port that writes into this editor. The only difference between this port and the ports returned by `get-err-port` and `get-out-port` is the font style and color.

---

`(send a-text:ports after-io-insertion)` → void

This method is called after an insertion due to IO occurs.

---

`(send a-text:ports get-box-input-editor-snip%)`

→ (subclass editor-snip%)

The result of this method is used as the class of editor snips that is inserted by the box port in this editor.

---

`(send a-text:ports get-box-input-text%)`

→ (is-a?/c text:input-box)

The result of this method is instantiated and placed inside the result of `get-box-input-editor-snip%`.

---

`text:ports-mixin` : (class? . -> . class?)  
argument extends/implements: `text:wide-snip<%>`  
result implements: `text:ports<%>`

---

`(send a-text:ports can-insert? start len)` → boolean?

`start` : exact-integer

`len` : exact-integer

Augments `can-insert?` in `text%`.

Returns the results of the inner call, unless `get-allow-edits` returns `#f`.

---

`(send a-text:ports can-delete? start len)` → boolean?

`start` : exact-integer

`len` : exact-integer

Augments `can-delete?` in `text%`.

Returns the results of the inner call, unless `get-allow-edits` returns `#f`.

---

`(send a-text:ports on-local-char event)` → void

`event` : (is-a?/c key-event%)

Overrides `on-local-char` in `editor<%>`.

Sends the data between the last position and the result of `get-unread-start-point` to the input port, unless `submit-to-port?` returns `#f`.

Also calls `on-submit`.

---

```
(send a-text:ports on-display-size) → void
```

Augments `on-display-size` in `editor<%>`.

Adjusts the embedded editor-snip (used for reading input to the `get-in-box-port`) to match the width of the editor.

---

```
text:input-box<%> : interface?
```

implements: `text%`

Classes that implement this interface are used as the editors for the box input port in `text:ports%`.

---

```
text:input-box-mixin : (class? . -> . class?)
```

argument extends/implements: `text%`

result implements: `text:input-box<%>`

This mixin provides an implementation of `text:input-box<%>` for use with `text:ports<%>`.

---

```
(send a-text:input-box on-default-char event) → void
```

`event` : `key-event%`

Overrides `on-default-char` in `text%`.

Notifies the `text:ports<%>` enclosing this editor that a new line of input has been provided.

---

```
text:autocomplete<%> : interface?
```

implements: `text%`

The mixin implementing this interface provides an unintrusive autocompletion menu when a particular (configurable) keystroke is pressed.

---

```
(send a-text:autocomplete auto-complete) → void
```



Starts a completion.

---

```
(send a-text:autocomplete get-autocomplete-border-color)
→ (or/c string? (is-a?/c color%))
```

The border color for the autocomplete menu. Defaults to "black".

---

```
(send a-text:autocomplete get-autocomplete-background-color)
→ (or/c string? (is-a?/c color%))
```

The background color for the non-selected menu items. Defaults to "lavender".

---

```
(send a-text:autocomplete get-autocomplete-selected-color)
→ (or/c string? (is-a?/c color%))
```

The background color for the selected menu item. Defaults to (make-object color% 204 153 255).

---

```
(send a-text:autocomplete completion-mode-key-event? key-event)
→ boolean?
key-event : key-event%
```

Returns true when the key event passed to it should initiate the completions menu.

---

```
(send a-text:autocomplete get-all-words) → (listof string)
```

Returns the list of the words that autocomplete should choose from.

---

```
(send a-text:autocomplete get-word-at pos) → string
pos : positive-exact-integer
```

Given an editor location, returns the prefix ending at that location that autocomplete should try to complete.

---

```
text:autocomplete-mixin : (class? . -> . class?)
argument extends/implements: text%
result implements: text:autocomplete<%>
```

---

```
(send a-text:autocomplete on-paint) → void
```

Overrides on-paint in editor<%>.

Draws the completion menu (when it is popped up).

---

```
(send a-text:autocomplete on-char) → void
```

Overrides `on-char` in `editor<%>`.

Takes over the handling of key events when the completions menu is visible. Also, when the completions menu is not visible, it calls the `completion-mode-key-event?` method to see if it should start completing.

---

`(send a-text:autocomplete on-event) → void`

Overrides `on-event` in `editor<%>`.

This method is overridden to allow mouse access of the completions menu. It only handles events when there is a menu open and the mouse is in the menu, in which case it makes the menu trace the mouse.

The only time it does not call the super method is when the mouse is button is pushed.

---

`text:basic% : class?`  
superclass: `(text:basic-mixin (editor:basic-mixin text%))`

---

`text:hide-caret/selection% : class?`  
superclass: `(text:hide-caret/selection-mixin text:basic%)`

---

`text:nbsp->space% : class?`  
superclass: `(text:nbsp->space-mixin text:basic%)`

---

`text:delegate% : class?`  
superclass: `(text:delegate-mixin text:basic%)`

---

`text:wide-snip% : class?`  
superclass: `(text:wide-snip-mixin text:basic%)`

---

`text:standard-style-list% : class?`  
  `superclass: (editor:standard-style-list-mixin text:wide-snip%)`

---

`text:input-box% : class?`  
  `superclass: (text:input-box-mixin text:standard-style-list%)`

---

`text:keymap% : class?`  
  `superclass: (editor:keymap-mixin text:standard-style-list%)`

---

`text:return% : class?`  
  `superclass: (text:return-mixin text:keymap%)`

---

`text:autowrap% : class?`  
  `superclass: (editor:autowrap-mixin text:keymap%)`

---

`text:file% : class?`  
  `superclass: (text:file-mixin (editor:file-mixin text:autowrap%))`

---

`text:clever-file-format% : class?`  
  `superclass: (text:clever-file-format-mixin text:file%)`

---

```
text:backup-autosave% : class?  
  superclass: (editor:backup-autosave-mixin text:clever-file-format%)
```

---

```
text:searching% : class?  
  superclass: (text:searching-mixin text:backup-autosave%)
```

---

```
text:info% : class?  
  superclass: (text:info-mixin (editor:info-mixin text:searching%))
```

---

```
text:line-numbers<%> : interface?
```

---

```
(send a-text:line-numbers show-line-numbers! show) → void  
  show : boolean?
```

Enables or disables line number drawing.

---

```
(send a-text:line-numbers show-line-numbers?) → boolean?
```

Returns whether or not line drawing is enabled.

---

```
(send a-text:line-numbers set-line-numbers-color color) → void?  
  color : string?
```

Sets the color of the line numbers.

---

```
text:line-numbers-mixin : (class? . -> . class?)  
  argument extends/implements: text%  
  result implements: text:line-numbers<%>
```

---

```
(send a-text:line-numbers on-paint) → void
```

Overrides `on-paint` in `editor<%>`.

Draws the line numbers.

---

```
(send a-text:line-numbers show-line-numbers! show) → void  
show : boolean?
```

Enables or disables line number drawing.

---

```
(send a-text:line-numbers show-line-numbers?) → boolean?
```

Returns whether or not line drawing is enabled.

---

```
(send a-text:line-numbers set-line-numbers-color color) → void?  
color : string?
```

Sets the color of the line numbers.

---

```
(text:range? arg) → boolean?  
arg : any/c
```

Determines if *arg* is an instance of the range struct.

---

```
(text:range-start range) → exact-nonnegative-integer?  
range : text:range?
```

Returns the start position of the range.

---

```
(text:range-end range) → exact-nonnegative-integer?  
range : text:range?
```

Returns the end position of the range.

---

```
(text:range-caret-space? range) → boolean?  
range : text:range?
```

Returns a boolean indicating where the caret-space in the range goes. See also [highlight-range](#).

---

```
(text:range-style range) → exact-nonnegative-integer?  
range : text:range?
```

Returns the style of the range. See also [highlight-range](#).

---

```
(text:range-color range) → (or/c string? (is-a?/c color%))
```

`range` : `text:range?`

Returns the color of the highlighted range.

---

```
(text:autocomplete-append-after) → string?  
(text:autocomplete-append-after suffix) → void?  
  suffix : string?
```

A string that is inserted after a completion is inserted by a `text:autocomplete` instance.

Defaults to `""`.

---

```
(text:autocomplete-limit) → (and/c integer? exact? positive?)  
(text:autocomplete-limit count) → void?  
  count : (and/c integer? exact? positive?)
```

Controls the number of completions visible at a time in the menu produced by `text:autocomplete` instances.

Defaults to 15.

---

```
(text:get-completions/manuals manuals) → (listof string?)  
  manuals : (or/c false/c (listof symbol?))
```

Returns the list of keywords for the manuals from `manuals` by extracting all of the documented exports of the manuals. The symbols are meant to be module paths, e.g., the quoted form of the argument to `require`.

If `manuals` is false, then all of the documented names are used.

---

```
(text:lookup-port-name manuals)  
→ (or/c (is-a?/c editor:basic<?>) false/c)  
  manuals : symbol?
```

Returns the editor instance whose port-name matches the given symbol. If no editor can be found, then returns `false`.

## 28 Splash

```
(require framework/splash)
```

This module helps support applications with splash screens like the one in DrRacket.

When this module is invoked, it sets the `current-load` parameter to a procedure that counts how many files are loaded (until `shutdown-splash` is called) and uses that number to control the gauge along the bottom of the splash screen.

---

```
(start-splash draw-spec
              splash-title
              width-default
              [#:allow-funny? allow-funny?]) → void?
draw-spec : (or/c path-string?
                (vector/c (or/c (-> (is-a?/c dc<%/>) void?)
                                   (-> (is-a?/c dc<%/>)
                                       exact-nonnegative-integer?
                                       exact-nonnegative-integer?
                                       exact-nonnegative-integer?
                                       exact-nonnegative-integer?
                                       void?))
                          exact-nonnegative-integer?
                          exact-nonnegative-integer?))
splash-title : string?
width-default : exact-nonnegative-integer?
allow-funny? : boolean? = #f
```

Starts a new splash screen. The splash screen is created in its own, new eventspace. The progress gauge at the bottom of the window advances as files are loaded (monitored via the `current-load` parameter).

The `draw-spec` determines what the splash window contains. The `splash-title` is used as the title of the window and the `width-default` determines how many progress steps the gauge in the splash screen should contain if there is no preference saved for the splash screen width. The splash library uses `get-preference` and `put-preferences` to store preferences, using

```
(string->symbol (format "plt:~a-splash-max-width" splash-title))
```

as the key for the preference. Each time the app starts up, the maximum width is reset based on the number of files that were loaded that time.

If the `draw-spec` is a `path-string?`, then the path is expected to be a file that contains a bitmap that is drawn as the contents of the splash screen. If `draw-spec` is a vector, then the

vector's first element is a procedure that is called to draw the splash screen and the other two integers are the size of the splash screen, width followed by height. If the procedure accepts only one argument, then it is called with a `dc< %>` object where the drawing should occur. If it accepts 5 arguments, it is called with the `dc< %>`, as well as (in order) the current value of the gauge, the maximum value of the gauge, and the width and the height of the area to draw.

The `allow-funny?` argument determines if a special gauge is used on Christmas day.

---

```
(shutdown-splash) → void?
```

Stops the splash window's gauge from advancing. Call this after all of the files have been loaded.

---

```
(close-splash) → void?
```

Closes the splash window. Call `shutdown-splash` first. You can leave some time between these two if there is more initialization work to be done where you do not want to count loaded files.

---

```
(add-splash-icon bmp x y) → void?  
  bmp : (is-a?/c bitmap%)  
  x : exact-nonnegative-integer?  
  y : exact-nonnegative-integer?
```

Adds an icon to the splash screen. (DrRacket uses this function to show the tools as they are loaded.)

---

```
(get-splash-bitmap) → (or/c #f (is-a?/c bitmap%))
```

Returns the splash bitmap unless one has not been set.

---

```
(set-splash-bitmap bmp) → void?  
  bmp : (is-a?/c bitmap%)
```

Sets the splash bitmap to `bmp` and triggers a redrawing of the splash screen. Don't use this to set the initial bitmap, use `start-splash` instead.

---

```
(get-splash-canvas) → (is-a?/c canvas%)
```

Returns the canvas where the splash screen bitmap is drawn (if there is a bitmap; see `start-splash` for how the splash is drawn).



---

```
(get-splash-eventspace) → eventspace?
```

Returns the splash screen's eventspace.

---

```
(get-splash-paint-callback) → (-> (is-a?/c dc<%>)
                                     exact-nonnegative-integer?
                                     exact-nonnegative-integer?
                                     exact-nonnegative-integer?
                                     exact-nonnegative-integer?
                                     void?)
```

Returns the callback that is invoked when redrawing the splash screen.

---

```
(set-splash-paint-callback cb) → void?
  cb : (-> (is-a?/c dc<%>)
           exact-nonnegative-integer?
           exact-nonnegative-integer?
           exact-nonnegative-integer?
           exact-nonnegative-integer?
           void?)
```

Sets the callback that is invoked when redrawing the splash screen. See `start-splash` for what the arguments are.

---

```
(set-splash-progress-bar?! b) → void?
  b : boolean?
```

Calling this procedure with `#f` removes the progress bar from the splash screen. Useful in conjunction with setting your own paint callback for the splash screen that measures progress in its own way, during drawing. DrRacket uses this on King Kamehameha and Prince Kuhio day.

---

```
(set-splash-char-observer obs) → void?
  obs : (-> (is-a?/c key-event%) any)
```

Sets a procedure that is called whenever a user types a key with the splash screen as the focus.

---

```
(set-splash-event-callback obj) → void?
  obj : (-> (is-?/c mouse-event%) any)
```

Sets a procedure that is called whenever a mouse event happens in the splash canvas.

---

```
(get-splash-event-callback) → (-> (is-?/c mouse-event%) any)
```

Returns the last procedure passed to `set-splash-event-callback` or `void`, if `set-splash-event-callback` has not been called.

---

```
(set-refresh-splash-on-gauge-change?! proc) → void?  
  proc : (-> exact-nonnegative-integer?  
          exact-nonnegative-integer?  
          any)
```

Sets a procedure that is called each time the splash gauge changes. If the procedure returns a true value (i.e., not `#f`), then the splash screen is redrawn. The procedure is called with the current value of the gauge and the maximum value.

The default function is `(lambda (curr tot) #f)`.

---

```
(get-splash-width) → exact-nonnegative-integer?
```

Returns the width of the splash drawing area / bitmap. See `start-splash` for the details of the size and how things are drawn.

---

```
(get-splash-height) → exact-nonnegative-integer?
```

Returns the width of the splash drawing area / bitmap. See `start-splash` for the details of the size and how things are drawn.

---

```
(refresh-splash) → void?
```

Triggers a refresh of the splash, handling the details of double buffering and doing the drawing on the splash's eventspace's main thread.

## 29 Test

```
(require framework/test)
```

The framework provides several new primitive functions that simulate user actions, which may be used to test applications. You use these primitives and combine them just as regular Racket functions. For example,

```
(test:keystroke #\A)
(test:menu-select "File" "Save")
```

sends a keystroke event to the window with the keyboard focus and invokes the callback function for the “Save” menu item from the “File” menu. This has the same effect as if the user typed the key “A”, pulled down the “File” menu and selected “Save”.

It is possible to load this portion of the framework without loading the rest of the framework. Use `(require framework/test)`.

Currently, the test engine has primitives for pushing buttons, setting check-boxes and choices, sending keystrokes, selecting menu items and clicking the mouse. Many functions that are also useful in application testing, such as traversing a tree of panels, getting the text from a canvas, determining if a window is shown, and so on, exist in GRacket.

### 29.1 Actions and completeness

The actions associated with a testing primitive may not have finished when the primitive returns to its caller. Some actions may yield control before they can complete. For example, selecting “Save As...” from the “File” menu opens a dialog box and will not complete until the “OK” or “Cancel” button is pushed.

However, all testing functions wait at least a minimum interval before returning to give the action a chance to finish. This interval controls the speed at which the test suite runs, and gives some slack time for events to complete. The default interval is 100 milliseconds. The interval can be queried or set with `test:run-interval`.

A primitive action will not return until the run-interval has expired and the action has finished, raised an error, or yielded. The number of incomplete actions is given by `test:number-pending-actions`.

*Note:* Once a primitive action is started, it is not possible to undo it or kill its remaining effect. Thus, it is not possible to write a utility that flushes the incomplete actions and resets `number-pending-actions` to zero.

However, actions which do not complete right away often provide a way to cancel themselves. For example, many dialog boxes have a “Cancel” button which will terminate the

action with no further effect. But this is accomplished by sending an additional action (the button push), not by undoing the original action.

## 29.2 Errors

Errors in the primitive actions (which necessarily run in the handler thread) are caught and reraised in the calling thread.

However, the primitive actions can only guarantee that the action has started, and they may return before the action has completed. As a consequence, an action may raise an error long after the function that started it has returned. In this case, the error is saved and reraised at the first opportunity (the next primitive action).

The test engine keeps a buffer for one error, saving only the first error. Any subsequent errors are discarded. Reraising an error empties the buffer, allowing the next error to be saved.

The function `test:reraise-error` reraises any pending errors.

## 29.3 Technical Issues

### 29.3.1 Active Frame

The Self Test primitive actions all implicitly apply to the top-most (active) frame.

### 29.3.2 Thread Issues

The code started by the primitive actions must run in the handler thread of the eventspace where the event takes place. As a result, the test suite that invokes the primitive actions must *not* run in that handler thread (or else some actions will deadlock). See `make-eventspace` for more info.

### 29.3.3 Window Manager (Unix only)

In order for the Self Tester to work correctly, the window manager must set the keyboard focus to follow the active frame. This is the default behavior in Microsoft Windows and MacOS, but not in X windows.

In X windows, you must explicitly tell your window manager to set the keyboard focus to the top-most frame, regardless of the position of the actual mouse.

## 29.4 Test Functions

---

```
(test:button-push button) → void?
  button : (or/c (λ (str)
    (and (string? str)
      (test:top-level-focus-window-has?
        (λ (c)
          (and (is-a? c button%)
            (string=? (send c get-label) str)
            (send c is-enabled?)
            (send c is-shown?)))))))
    (and/c (is-a?/c button%)
      (λ (btn)
        (and (send btn is-enabled?)
          (send btn is-shown?)))
      (λ (btn)
        (test:top-level-focus-window-has?
          (λ (c) (eq? c btn)))))))
```

Simulates pushing *button*. If a string is supplied, the primitive searches for a button labelled with that string in the active frame. Otherwise, it pushes the button argument.

---

```
(test:set-radio-box! radio-box state) → void?
  radio-box : (or/c string? regexp? (is-a?/c radio-box%))
  state : (or/c string? number?)
```

Sets the radio-box to the label matching *state*. If *state* is a string, this function finds the choice with that label. If it is a regexp, this function finds the first choice whose label matches the regexp. If it is a number, it uses the number as an index into the state. If the number is out of range or if the label isn't in the radio box, an exception is raised.

If *radio-box* is a string, this function searches for a `radio-box%` object with a label matching that string, otherwise it uses *radio-box* itself.

---

```
(test:set-radio-box-item! entry) → void?
  entry : (or/c string? regexp?)
```

Finds a `radio-box%` that has a label matching *entry* and sets the radio-box to *entry*.

---

```
(test:set-check-box! check-box state) → void?
  check-box : (or/c string? (is-a?/c check-box%))
  state : boolean?
```

Clears the `check-box%` item if `state` is `#f`, and sets it otherwise.

If `check-box` is a string, this function searches for a `check-box%` with a label matching that string, otherwise it uses `check-box` itself.

---

```
(test:set-choice! choice str) → void?
  choice : (or/c string? (is-a?/c choice%))
  str : (or/c string? (and/c number? exact? integer? positive?))
```

Selects `choice`'s item `str`. If `choice` is a string, this function searches for a `choice%` with a label matching that string, otherwise it uses `choice` itself.

---

```
(test:set-list-box! choice str) → void?
  choice : (or/c string? (is-a?/c list-box%))
  str : (or/c string? (and/c number? exact? integer? positive?))
```

Selects `list-box`'s item `str`. If `list-box` is a string, this function searches for a `list-box%` with a label matching that string, otherwise it uses `list-box` itself.

---

```
(test:keystroke key [modifier-list]) → void?
  key : (or/c char? symbol?)
  modifier-list : (listof (symbols 'alt 'control 'meta 'shift 'noalt 'nocontrol 'nometa 'nosl
                             = null
```

This function simulates a user pressing a key. The argument, `key`, is just like the argument to the `get-key-code` method of the `key-event%` class.

*Note:* To send the “Enter” key, use `#\return`, not `#\newline`.

The `'shift` or `'noshift` modifier is implicitly set from `key`, but is overridden by the argument list. The `'shift` modifier is set for any capital alpha-numeric letters and any of the following characters:

```
#\? #\: #\~ #\\ #\|
#\< #\> #\{ #\} #\[ #\] #\< ( #\ )
#\! #\@ #\# #\$ #\% #\^ #\& #\* #\_ #\+
```

If conflicting modifiers are provided, the ones later in the list are used.

---

```
(test:menu-select menu item) → void?
  menu : string?
  item : string?
```

Selects the menu-item named `item` in the menu named `menu`.

*Note:* The string for the menu item does not include its keyboard equivalent. For example, to select “New” from the “File” menu, use “New”, not “New Ctrl+m n”.

---

```
(test:mouse-click button x y [modifiers]) → void?  
  button : (symbols 'left 'middle 'right)  
  x : (and/c exact? integer?)  
  y : (and/c exact? integer?)  
  modifiers : (listof (symbols 'alt 'control 'meta 'shift 'noalt 'nocontrol 'nometa 'noshift))  
              = null
```

Simulates a mouse click at the coordinate (x,y) in the currently focused `window`, assuming that it supports the `on-event` method. Use `test:button-push` to click on a button.

On the Macintosh, `'right` corresponds to holding down the command modifier key while clicking and `'middle` cannot be generated.

Under Windows, `'middle` can only be generated if the user has a three button mouse.

The modifiers later in the list `modifiers` take precedence over ones that appear earlier.

---

```
(test:run-interval msec) → void?  
  msec : number?  
(test:run-interval) → number?
```

See also §29.1 “Actions and completeness”. The first case in the case-lambda sets the run interval to `msec` milliseconds and the second returns the current setting.

---

```
(test:current-get-eventspaces) → (-> (listof eventspace?))  
(test:current-get-eventspaces func) → void?  
  func : (-> (listof eventspace?))
```

This parameter that specifies which eventspaces (see also §1.6 “Event Dispatching and Eventspaces”) are considered when finding the frontmost frame. The first case sets the parameter to `func`. The procedure `func` will be invoked with no arguments to determine the eventspaces to consider when finding the frontmost frame for simulated user events. The second case returns the current value of the parameter. This will be a procedure which, when invoked, returns a list of eventspaces.

---

```
(test:new-window window) → void?  
  window : (is-a?/c window<?>)
```

Moves the keyboard focus to a new window within the currently active frame. Unfortunately, neither this function nor any other function in the test engine can cause the focus to move from the top-most (active) frame.

---

```
(test:close-top-level-window tlw) → void?  
  tlw : (is-a?/c top-level-window<%>)
```

Use this function to simulate clicking on the close box of a frame. Closes *tlw* with this expression:

```
(when (send tlw can-close?)  
      (send tlw on-close)  
      (send tlw show #f))
```

---

```
(test:top-level-focus-window-has? test) → boolean?  
  test : (-> (is-a?/c area<%>) boolean?)
```

Calls *test* for each child of the top-level-focus-frame and returns #t if *test* ever does, otherwise returns #f. If there is no top-level-focus-window, returns #f.

---

```
(test:number-pending-actions) → number?
```

Returns the number of pending events (those that haven't completed yet)

---

```
(test:reraise-error) → void?
```

See also §29.2 “Errors”.

---

```
(test:run-one f) → void?  
  f : (-> void?)
```

Runs the function *f* as if it was a simulated event.



## 30 Version

---

```
(version:add-spec spec revision) → void?  
  spec : any/c  
  revision : any/c
```

The two values are appended to the version string. `write` is used to transform them to strings. For example:

```
(version:add-spec 's 1)
```

in version 205 will make the version string be `205s1`. The symbols `'f` and `'d` were used internally for framework and drscheme revisions in the past.

---

```
(version:version) → string?
```

This function returns a string describing the version of this application. See also `version:add-spec`.

## Index

'framework:backup-files?', 34  
'framework:basic-canvas-background, 5  
Actions and completeness, 203  
Active Frame, 204  
active-child, 140  
add-splash-icon, 200  
add-tall-snip, 7  
add-tall-snip, 177  
add-wide-snip, 7  
add-wide-snip, 176  
after-change-style, 19  
after-change-style, 136  
after-change-style, 183  
after-change-style, 130  
after-delete, 175  
after-delete, 185  
after-delete, 130  
after-delete, 137  
after-delete, 20  
after-delete, 183  
after-edit-sequence, 131  
after-edit-sequence, 183  
after-edit-sequence, 19  
after-edit-sequence, 137  
after-edit-sequence, 29  
after-insert, 172  
after-insert, 175  
after-insert, 185  
after-insert, 173  
after-insert, 130  
after-insert, 168  
after-insert, 183  
after-insert, 137  
after-insert, 20  
after-io-insertion, 191  
after-load-file, 184  
after-load-file, 187  
after-load-file, 131  
after-load-file, 137  
after-load-file, 29  
after-new-child, 140  
after-new-child, 46  
after-new-child, 143  
after-percentage-change, 142  
after-save-file, 187  
after-save-file, 131  
after-save-file, 137  
after-save-file, 29  
after-set-position, 184  
after-set-position, 137  
after-set-position, 130  
after-set-position, 19  
after-set-position, 172  
after-set-size-constraint, 131  
after-set-size-constraint, 137  
allow-close-with-no-filename?, 32  
anchor-status-changed, 52  
Application, 3  
application:current-app-name, 3  
ask-normalize?, 173  
auto-complete, 192  
Autosave, 4  
autosave:autosavable<%>, 4  
autosave:register, 4  
autosave:restore-autosave-  
files/gui, 4  
autosave?, 34  
background color, 5  
backup?, 34  
backward-containing-sexp, 18  
backward-kill-word, 118  
backward-match, 17  
backward-sexp, 159  
balance-parens, 157  
box-comment-out-selection, 158  
can-change-style?, 131  
can-change-style?, 137  
can-close-all?, 99  
can-close?, 47  
can-close?, 33  
can-close?, 27  
can-close?, 83

- can-delete?, 186
- can-delete?, 132
- can-delete?, 191
- can-delete?, 137
- can-do-edit-operation?, 132
- can-do-edit-operation?, 138
- can-exit?, 45
- can-insert?, 191
- can-insert?, 186
- can-insert?, 138
- can-insert?, 132
- can-load-file?, 133
- can-load-file?, 138
- can-save-file?, 28
- can-save-file?, 138
- can-save-file?, 133
- can-set-size-constraint?, 132
- can-set-size-constraint?, 138
- Canvas, 5
  - canvas:basic%, 7
  - canvas:basic-mixin, 5
  - canvas:basic<%>, 5
  - canvas:color%, 7
  - canvas:color-mixin, 5
  - canvas:color<%>, 5
  - canvas:delegate%, 8
  - canvas:delegate-mixin, 5
  - canvas:delegate<%>, 5
  - canvas:info%, 8
  - canvas:info-mixin, 6
  - canvas:info<%>, 6
  - canvas:wide-snip%, 8
  - canvas:wide-snip-mixin, 7
  - canvas:wide-snip<%>, 6
- capitalize-word, 118
- center-view-on-line, 118
- chain-to-keymap, 113
- classify-position, 18
- clear, 99
- clear-box-input-port, 189
- clear-input-port, 189
- clear-output-ports, 189
- close, 28
- close, 44
- close-splash, 200
- close-status-line, 48
- collapse-newline, 118
- collapse-space, 118
- Color, 14
- Color Model, 9
- Color Prefs, 11
  - color-model:rgb->xyz, 9
  - color-model:rgb-color-distance, 9
  - color-model:xyz->rgb, 9
  - color-model:xyz-x, 10
  - color-model:xyz-y, 10
  - color-model:xyz-z, 10
  - color-model:xyz?, 9
  - color-prefs:add-background-preferences-panel, 11
  - color-prefs:add-to-preferences-panel, 12
  - color-prefs:black-on-white, 13
  - color-prefs:build-color-selection-panel, 12
  - color-prefs:marshall-style-delta, 12
  - color-prefs:register-color-preference, 11
  - color-prefs:set-default/color-scheme, 11
  - color-prefs:unmarshall-style-delta, 12
  - color-prefs:white-on-black, 12
  - color:text%, 20
  - color:text-mixin, 19
  - color:text-mode%, 21
  - color:text-mode-mixin, 20
  - color:text-mode<%>, 20
  - color:text<%>, 14
- Comment Box, 22
- comment-box:snip%, 22
- comment-out-selection, 158
- completion-mode-key-event?, 193
- container-size, 141

[container-size](#), 143  
[container-size](#), 140  
[copy](#), 180  
[copy](#), 155  
[copy](#), 24  
[copy](#), 178  
[copy-click-region](#), 118  
[copy-clipboard](#), 118  
[cut-click-region](#), 118  
[cut-clipboard](#), 118  
[default-style-name](#), 171  
[delegate-moved](#), 89  
[delegated-text-shown?](#), 88  
[delete/io](#), 187  
[determine-width](#), 49  
[do-autosave](#), 4  
[do-autosave](#), 34  
[do-macro](#), 119  
[do-paste](#), 173  
[down-sexp](#), 159  
[downcase-word](#), 118  
[draw](#), 179  
[draw](#), 181  
[draw](#), 156  
[edit-menu:after-preferences](#), 78  
[edit-menu:between-clear-and-select-all](#), 69  
[edit-menu:between-copy-and-paste](#), 67  
[edit-menu:between-cut-and-copy](#), 66  
[edit-menu:between-find-and-preferences](#), 77  
[edit-menu:between-paste-and-clear](#), 68  
[edit-menu:between-redo-and-cut](#), 64  
[edit-menu:between-select-all-and-find](#), 70  
[edit-menu:between-select-all-and-find](#), 85  
[edit-menu:clear-callback](#), 68  
[edit-menu:clear-help-string](#), 69  
[edit-menu:clear-on-demand](#), 68  
[edit-menu:clear-string](#), 69  
[edit-menu:copy-callback](#), 66  
[edit-menu:copy-help-string](#), 67  
[edit-menu:copy-on-demand](#), 66  
[edit-menu:copy-string](#), 66  
[edit-menu:create-clear?](#), 68  
[edit-menu:create-copy?](#), 66  
[edit-menu:create-cut?](#), 65  
[edit-menu:create-find-again-backwards?](#), 92  
[edit-menu:create-find-again?](#), 91  
[edit-menu:create-find-case-sensitive?](#), 76  
[edit-menu:create-find-case-sensitive?](#), 93  
[edit-menu:create-find-next?](#), 71  
[edit-menu:create-find-previous?](#), 72  
[edit-menu:create-find?](#), 91  
[edit-menu:create-find?](#), 70  
[edit-menu:create-paste?](#), 67  
[edit-menu:create-preferences?](#), 77  
[edit-menu:create-redo?](#), 64  
[edit-menu:create-replace-all?](#), 92  
[edit-menu:create-replace-all?](#), 75  
[edit-menu:create-replace?](#), 74  
[edit-menu:create-select-all?](#), 69  
[edit-menu:create-show/hide-replace?](#), 73  
[edit-menu:create-undo?](#), 63  
[edit-menu:cut-callback](#), 65  
[edit-menu:cut-help-string](#), 65  
[edit-menu:cut-on-demand](#), 65  
[edit-menu:cut-string](#), 65  
[edit-menu:find-again-backwards-callback](#), 91  
[edit-menu:find-again-callback](#), 91  
[edit-menu:find-callback](#), 91  
[edit-menu:find-callback](#), 71  
[edit-menu:find-case-sensitive-callback](#), 92  
[edit-menu:find-case-sensitive-callback](#), 76  
[edit-menu:find-case-sensitive-help-string](#), 77

edit-menu:find-case-sensitive-on-demand, 76  
 edit-menu:find-case-sensitive-on-demand, 92  
 edit-menu:find-case-sensitive-string, 77  
 edit-menu:find-help-string, 71  
 edit-menu:find-next-callback, 71  
 edit-menu:find-next-help-string, 72  
 edit-menu:find-next-on-demand, 72  
 edit-menu:find-next-string, 72  
 edit-menu:find-on-demand, 71  
 edit-menu:find-previous-callback, 72  
 edit-menu:find-previous-help-string, 73  
 edit-menu:find-previous-on-demand, 73  
 edit-menu:find-previous-string, 73  
 edit-menu:find-string, 71  
 edit-menu:get-clear-item, 68  
 edit-menu:get-copy-item, 66  
 edit-menu:get-cut-item, 65  
 edit-menu:get-find-case-sensitive-item, 76  
 edit-menu:get-find-item, 70  
 edit-menu:get-find-next-item, 71  
 edit-menu:get-find-previous-item, 72  
 edit-menu:get-paste-item, 67  
 edit-menu:get-preferences-item, 77  
 edit-menu:get-redo-item, 63  
 edit-menu:get-replace-all-item, 75  
 edit-menu:get-replace-item, 74  
 edit-menu:get-select-all-item, 69  
 edit-menu:get-show/hide-replace-item, 73  
 edit-menu:get-undo-item, 62  
 edit-menu:paste-callback, 67  
 edit-menu:paste-help-string, 68  
 edit-menu:paste-on-demand, 67  
 edit-menu:paste-string, 68  
 edit-menu:preferences-callback, 77  
 edit-menu:preferences-help-string, 78  
 edit-menu:preferences-on-demand, 78  
 edit-menu:preferences-string, 78  
 edit-menu:redo-callback, 64  
 edit-menu:redo-help-string, 64  
 edit-menu:redo-on-demand, 64  
 edit-menu:redo-string, 64  
 edit-menu:replace-all-callback, 92  
 edit-menu:replace-all-callback, 75  
 edit-menu:replace-all-help-string, 76  
 edit-menu:replace-all-on-demand, 75  
 edit-menu:replace-all-on-demand, 92  
 edit-menu:replace-all-string, 76  
 edit-menu:replace-callback, 74  
 edit-menu:replace-help-string, 75  
 edit-menu:replace-on-demand, 75  
 edit-menu:replace-string, 75  
 edit-menu:select-all-callback, 69  
 edit-menu:select-all-help-string, 70  
 edit-menu:select-all-on-demand, 70  
 edit-menu:select-all-string, 70  
 edit-menu:show/hide-replace-callback, 73  
 edit-menu:show/hide-replace-help-string, 74  
 edit-menu:show/hide-replace-on-demand, 74  
 edit-menu:show/hide-replace-string, 74  
 edit-menu:undo-callback, 63  
 edit-menu:undo-help-string, 63  
 edit-menu:undo-on-demand, 63  
 edit-menu:undo-string, 63  
 editing-this-file?, 83  
 editing-this-file?, 44  
 Editor, 26  
 Editor Snip, 23  
 editor-position-changed, 52  
 editor-snip:decorated%, 24  
 editor-snip:decorated-mixin, 23

[editor-snip:decorated-snipclass%](#), 24  
[editor-snip:decorated<%>](#), 23  
[editor:add-after-user-keymap](#), 36  
[editor:autowrap-mixin](#), 32  
[editor:autowrap<%>](#), 31  
[editor:backup-autosave-mixin](#), 34  
[editor:backup-autosave<%>](#), 34  
[editor:basic-mixin](#), 28  
[editor:basic<%>](#), 26  
[editor:file-mixin](#), 33  
[editor:file<%>](#), 32  
[editor:get-default-color-style-name](#), 36  
[editor:get-standard-style-list](#), 36  
[editor:info-mixin](#), 35  
[editor:info<%>](#), 35  
[editor:keymap-mixin](#), 31  
[editor:keymap<%>](#), 31  
[editor:set-default-font-color](#), 36  
[editor:set-standard-style-list-delta](#), 36  
[editor:set-standard-style-list-pref-callbacks](#), 36  
[editor:standard-style-list-mixin](#), 30  
[editor:standard-style-list<%>](#), 30  
[end-macro](#), 119  
[erase-underscores](#), 123  
[Errors](#), 204  
[Exit](#), 37  
[exit:can-exit?](#), 37  
[exit:exit](#), 37  
[exit:exiting?](#), 37  
[exit:insert-can?-callback](#), 37  
[exit:insert-on-callback](#), 37  
[exit:on-exit](#), 37  
[exit:set-exiting](#), 37  
[exit:user-oks-exit](#), 38  
[exn:make-unknown-preference](#), 153  
[exn:unknown-preference](#), 151  
[exn:unknown-preference](#), 151  
[exn:unknown-preference](#), 151  
[exn:unknown-preference?](#), 153  
[file-menu:after-quit](#), 62  
[file-menu:between-close-and-quit](#), 61  
[file-menu:between-new-and-open](#), 54  
[file-menu:between-open-and-revert](#), 56  
[file-menu:between-print-and-close](#), 60  
[file-menu:between-revert-and-save](#), 57  
[file-menu:between-save-as-and-print](#), 85  
[file-menu:between-save-as-and-print](#), 59  
[file-menu:close-callback](#), 61  
[file-menu:close-help-string](#), 61  
[file-menu:close-on-demand](#), 61  
[file-menu:close-string](#), 61  
[file-menu:create-close?](#), 60  
[file-menu:create-new?](#), 53  
[file-menu:create-open-recent?](#), 55  
[file-menu:create-open?](#), 54  
[file-menu:create-print?](#), 84  
[file-menu:create-print?](#), 59  
[file-menu:create-quit?](#), 62  
[file-menu:create-revert?](#), 56  
[file-menu:create-revert?](#), 84  
[file-menu:create-save-as?](#), 58  
[file-menu:create-save-as?](#), 84  
[file-menu:create-save?](#), 57  
[file-menu:create-save?](#), 84  
[file-menu:get-close-item](#), 60  
[file-menu:get-new-item](#), 53  
[file-menu:get-open-item](#), 54  
[file-menu:get-open-recent-item](#), 55  
[file-menu:get-print-item](#), 59  
[file-menu:get-quit-item](#), 61  
[file-menu:get-revert-item](#), 56  
[file-menu:get-save-as-item](#), 58  
[file-menu:get-save-item](#), 57  
[file-menu:new-callback](#), 54

- file-menu:new-callback, 86
- file-menu:new-help-string, 54
- file-menu:new-on-demand, 54
- file-menu:new-on-demand, 86
- file-menu:new-string, 54
- file-menu:open-callback, 55
- file-menu:open-callback, 83
- file-menu:open-help-string, 55
- file-menu:open-on-demand, 86
- file-menu:open-on-demand, 55
- file-menu:open-recent-callback, 55
- file-menu:open-recent-help-string, 56
- file-menu:open-recent-on-demand, 56
- file-menu:open-recent-string, 56
- file-menu:open-string, 55
- file-menu:print-callback, 84
- file-menu:print-callback, 60
- file-menu:print-help-string, 60
- file-menu:print-on-demand, 60
- file-menu:print-string, 60
- file-menu:quit-callback, 62
- file-menu:quit-help-string, 62
- file-menu:quit-on-demand, 62
- file-menu:quit-string, 62
- file-menu:revert-callback, 57
- file-menu:revert-callback, 83
- file-menu:revert-help-string, 57
- file-menu:revert-on-demand, 83
- file-menu:revert-on-demand, 57
- file-menu:revert-string, 57
- file-menu:save-as-callback, 84
- file-menu:save-as-callback, 59
- file-menu:save-as-help-string, 59
- file-menu:save-as-on-demand, 59
- file-menu:save-as-string, 59
- file-menu:save-callback, 84
- file-menu:save-callback, 58
- file-menu:save-help-string, 58
- file-menu:save-on-demand, 58
- file-menu:save-string, 58
- find-down-sexp, 159
- find-string, 117
- find-string-replace, 117
- find-string-reverse, 117
- find-up-sexp, 159
- Finder, 39
- finder:common-get-file, 40
- finder:common-get-file-list, 42
- finder:common-put-file, 39
- finder:default-extension, 39
- finder:default-filters, 39
- finder:dialog-parent-parameter, 39
- finder:get-file, 41
- finder:open-file, 117
- finder:put-file, 41
- finder:put-file, 117
- finder:put-file, 117
- finder:std-get-file, 41
- finder:std-put-file, 40
- first-line-currently-drawn-specially?, 169
- flash-backward-sexp, 159
- flash-forward-sexp, 158
- for-each-frame, 98
- force-stop-colorer, 16
- forward-match, 18
- forward-sexp, 158
- Frame, 43
- frame-label-changed, 98
- frame-shown/hidden, 98
- frame:add-snip-menu-items, 96
- frame:basic%, 94
- frame:basic-mixin, 44
- frame:basic< %>, 43
- frame:current-icon, 97
- frame:delegate%, 95
- frame:delegate-mixin, 89
- frame:delegate< %>, 88
- frame:editor%, 95
- frame:editor-mixin, 81
- frame:editor< %>, 80
- frame:info%, 94
- frame:info-mixin, 51

[frame:info< %>](#), 49  
[frame:open-here%](#), 95  
[frame:open-here-mixin](#), 86  
[frame:open-here< %>](#), 85  
[frame:pasteboard%](#), 95  
[frame:pasteboard-info%](#), 94  
[frame:pasteboard-info-mixin](#), 52  
[frame:pasteboard-info< %>](#), 52  
[frame:pasteboard-mixin](#), 88  
[frame:pasteboard< %>](#), 87  
[frame:register-group-mixin](#), 47  
[frame:register-group< %>](#), 47  
[frame:remove-empty-menus](#), 96  
[frame:reorder-menus](#), 96  
[frame:searchable%](#), 95  
[frame:searchable-mixin](#), 91  
[frame:searchable-text-mixin](#), 93  
[frame:searchable-text< %>](#), 93  
[frame:searchable< %>](#), 89  
[frame:setup-size-pref](#), 96  
[frame:size-pref%](#), 94  
[frame:size-pref-mixin](#), 46  
[frame:size-pref< %>](#), 46  
[frame:standard-menus%](#), 95  
[frame:standard-menus-mixin](#), 79  
[frame:standard-menus< %>](#), 52  
[frame:status-line%](#), 94  
[frame:status-line-mixin](#), 49  
[frame:status-line< %>](#), 48  
[frame:text%](#), 95  
[frame:text-info%](#), 94  
[frame:text-info-mixin](#), 52  
[frame:text-info< %>](#), 51  
[frame:text-mixin](#), 87  
[frame:text< %>](#), 87  
[framework](#), 1  
[framework/gui-utils](#), 101  
[framework/preferences](#), 151  
[framework/splash](#), 199  
[framework/test](#), 203  
**Framework:** Racket GUI Application  
     Framework, 1  
[freeze-colorer](#), 16  
[get-active-frame](#), 99  
[get-all-words](#), 193  
[get-allow-edits](#), 188  
[get-area-container](#), 43  
[get-area-container%](#), 43  
[get-autocomplete-background-color](#), 193  
[get-autocomplete-border-color](#), 193  
[get-autocomplete-selected-color](#), 193  
[get-backward-sexp](#), 159  
[get-box-input-editor-snip%](#), 191  
[get-box-input-text%](#), 191  
[get-can-close-parent](#), 32  
[get-canvas](#), 81  
[get-canvas%](#), 80  
[get-canvas< %>](#), 80  
[get-case-sensitive-search?](#), 90  
[get-chained-keymaps](#), 113  
[get-checkable-menu-item%](#), 53  
[get-color](#), 23  
[get-color](#), 23  
[get-corner-bitmap](#), 23  
[get-corner-bitmap](#), 23  
[get-corner-bitmap](#), 22  
[get-delegate](#), 177  
[get-delegated-text](#), 88  
[get-edit-menu](#), 53  
[get-edition-number](#), 167  
[get-editor](#), 81  
[get-editor%](#), 94  
[get-editor%](#), 89  
[get-editor%](#), 80  
[get-editor< %>](#), 89  
[get-editor< %>](#), 80  
[get-editor< %>](#), 87  
[get-editor< %>](#), 88  
[get-editor< %>](#), 93  
[get-entire-label](#), 80  
[get-err-port](#), 190  
[get-err-style-delta](#), 190



[get-extent](#), 180  
[get-extent](#), 156  
[get-extent](#), 178  
[get-file](#), 30  
[get-file-menu](#), 53  
[get-filename](#), 82  
[get-filename](#), 44  
[get-filename/untitled-name](#), 28  
[get-first-line-height](#), 169  
[get-fixed-style](#), 166  
[get-fixed-style](#), 171  
[get-forward-sexp](#), 158  
[get-frames](#), 98  
[get-help-menu](#), 53  
[get-highlighted-ranges](#), 166  
[get-in-box-port](#), 190  
[get-in-port](#), 190  
[get-info-canvas](#), 50  
[get-info-editor](#), 50  
[get-info-panel](#), 50  
[get-insertion-point](#), 188  
[get-keymaps](#), 175  
[get-keymaps](#), 33  
[get-keymaps](#), 31  
[get-label](#), 83  
[get-label-prefix](#), 80  
[get-limit](#), 157  
[get-map-function-table](#), 113  
[get-map-function-table/ht](#), 113  
[get-mdi-parent](#), 98  
[get-menu](#), 22  
[get-menu](#), 24  
[get-menu](#), 23  
[get-menu%](#), 53  
[get-menu-bar%](#), 43  
[get-menu-item%](#), 53  
[get-open-here-editor](#), 86  
[get-open-here-frame](#), 98  
[get-out-port](#), 190  
[get-out-style-delta](#), 189  
[get-percentages](#), 142  
[get-port-name](#), 167  
[get-pos/text](#), 28  
[get-position](#), 24  
[get-position](#), 23  
[get-position](#), 22  
[get-read-write?](#), 186  
[get-regions](#), 17  
[get-saved-snips](#), 155  
[get-search-bubbles](#), 175  
[get-search-hit-count](#), 174  
[get-splash-bitmap](#), 200  
[get-splash-canvas](#), 200  
[get-splash-event-callback](#), 202  
[get-splash-eventspace](#), 201  
[get-splash-height](#), 202  
[get-splash-paint-callback](#), 201  
[get-splash-width](#), 202  
[get-start-of-line](#), 161  
[get-start-of-line](#), 167  
[get-styles-fixed](#), 166  
[get-surrogate](#), 133  
[get-tab-size](#), 160  
[get-text](#), 155  
[get-text](#), 22  
[get-text-to-search](#), 90  
[get-text-to-search](#), 93  
[get-token-range](#), 19  
[get-top-level-window](#), 26  
[get-unread-start-point](#), 188  
[get-value-port](#), 191  
[get-value-style-delta](#), 190  
[get-vertical?](#), 144  
[get-vertical?](#), 144  
[get-vertical?](#), 142  
[get-word-at](#), 161  
[get-word-at](#), 193  
[goto-line](#), 118  
[goto-position](#), 118  
[Group](#), 98  
[group: %](#), 98  
[group: add-to-windows-menu](#), 100  
[group: can-close-check](#), 100  
[group: get-the-frame-group](#), 100

group:on-close-action, 100  
 GUI Utilities, 101  
 gui-utils:cancel-on-right?, 101  
 gui-utils:cursor-delay, 102  
 gui-utils:delay-action, 103  
 gui-utils:format-literal-label, 101  
 gui-utils:get-choice, 104  
 gui-utils:get-clickback-delta, 105  
 gui-utils:get-clicked-clickback-delta, 105  
 gui-utils:local-busy-cursor, 103  
 gui-utils:next-untitled-name, 102  
 gui-utils:ok/cancel-buttons, 102  
 gui-utils:quote-literal-label, 101  
 gui-utils:show-busy-cursor, 103  
 gui-utils:trim-string, 101  
 gui-utils:unsaved-warning, 104  
 Handler, 107  
 handler:add-to-recent, 109  
 handler:current-create-new-window, 108  
 handler:edit-file, 108  
 handler:find-format-handler, 108  
 handler:find-named-format-handler, 108  
 handler:handler-extension, 107  
 handler:handler-handler, 107  
 handler:handler-name, 107  
 handler:handler?, 107  
 handler:insert-format-handler, 107  
 handler:install-recent-items, 109  
 handler:open-file, 109  
 handler:set-recent-items-frame-superclass, 109  
 handler:set-recent-position, 110  
 handler:size-recently-opened-files, 110  
 has-focus?, 26  
 help-menu:about-callback, 79  
 help-menu:about-callback, 85  
 help-menu:about-help-string, 79  
 help-menu:about-on-demand, 79  
 help-menu:about-string, 79  
 help-menu:about-string, 85  
 help-menu:after-about, 79  
 help-menu:before-about, 78  
 help-menu:create-about?, 85  
 help-menu:create-about?, 78  
 help-menu:get-about-item, 78  
 hide-delegated-text, 88  
 hide-info, 50  
 hide-search, 90  
 highlight-first-line, 169  
 highlight-range, 165  
 highlight-range, 181  
 Icon, 111  
 icon:get-anchor-bitmap, 111  
 icon:get-autowrap-bitmap, 111  
 icon:get-eof-bitmap, 111  
 icon:get-gc-off-bitmap, 112  
 icon:get-gc-on-bitmap, 112  
 icon:get-left/right-cursor, 111  
 icon:get-lock-bitmap, 111  
 icon:get-paren-highlight-bitmap, 111  
 icon:get-unlock-bitmap, 111  
 icon:get-up/down-cursor, 112  
 initial-autowrap-bitmap, 167  
 insert, 179  
 insert-before, 188  
 insert-between, 188  
 insert-close-paren, 18  
 insert-frame, 99  
 insert-return, 157  
 introduce-let-ans, 160  
 is-frozen?, 16  
 is-info-hidden?, 50  
 is-lexer-valid?, 19  
 is-special-first-line?, 169  
 is-stopped?, 16  
 Keymap, 113  
 keymap:add-to-right-button-menu, 114  
 keymap:add-to-right-button-

- menu/before, 115
- keymap:add-user-keybindings-file, 114
- keymap:aug-keymap%, 114
- keymap:aug-keymap-mixin, 113
- keymap:aug-keymap<%>, 113
- keymap:call/text-keymap-initializer, 115
- keymap:canonicalize-keybinding-string, 115
- keymap:get-editor, 115
- keymap:get-file, 116
- keymap:get-global, 116
- keymap:get-search, 116
- keymap:get-user, 116
- keymap:make-meta-prefix-list, 116
- keymap:remove-chained-keymap, 122
- keymap:remove-user-keybindings-file, 114
- keymap:send-map-function-meta, 116
- keymap:set-chained-keymaps, 122
- keymap:setup-editor, 117
- keymap:setup-file, 117
- keymap:setup-global, 117
- keymap:setup-search, 122
- kill-word, 118
- load-file, 117
- load-file/gui-error, 27
- local-edit-sequence?, 26
- locate-file, 99
- lock, 19
- lock, 35
- lock-status-changed, 50
- make-editor, 22
- make-editor, 24
- make-editor, 81
- make-root-area-container, 43
- make-root-area-container, 89
- make-root-area-container, 93
- make-root-area-container, 51
- make-root-area-container, 49
- make-snip, 25
- make-snip, 24
- make-snip, 22
- make-visible, 44
- map-function, 114
- mark-matching-parenthesis, 160
- Menu, 123
- menu:can-restore-checkable-menu-item%, 124
- menu:can-restore-menu-item%, 124
- menu:can-restore-mixin, 123
- menu:can-restore-underscore-menu%, 124
- menu:can-restore-underscore-mixin, 123
- menu:can-restore-underscore<%>, 123
- menu:can-restore<%>, 123
- Meta, 117
- Mode, 125
- mode:host-text-mixin, 134
- mode:host-text<%>, 133
- mode:surrogate-text%, 125
- mode:surrogate-text<%>, 125
- move-sexp-out, 161
- move/copy-to-edit, 166
- Number Snip, 139
- number-snip:make-fraction-snip, 139
- number-snip:make-repeating-decimal-snip, 139
- number-snip:snip-class%, 139
- on-activate, 87
- on-activate, 48
- on-change, 125
- on-change, 134
- on-change, 35
- on-change-style, 136
- on-change-style, 129
- on-char, 193
- on-char, 134
- on-char, 125
- on-close, 79
- on-close, 48
- on-close, 87

[on-close](#), 53  
[on-close](#), 27  
[on-close](#), 83  
[on-close](#), 52  
[on-close](#), 93  
[on-close](#), 35  
[on-close](#), 51  
[on-close-all](#), 99  
[on-default-char](#), 192  
[on-default-char](#), 134  
[on-default-char](#), 125  
[on-default-event](#), 134  
[on-default-event](#), 125  
[on-delete](#), 129  
[on-delete](#), 136  
[on-disable-surrogate](#), 162  
[on-disable-surrogate](#), 20  
[on-disable-surrogate](#), 125  
[on-display-size](#), 126  
[on-display-size](#), 192  
[on-display-size](#), 134  
[on-drop-file](#), 45  
[on-edit-sequence](#), 182  
[on-edit-sequence](#), 29  
[on-edit-sequence](#), 134  
[on-edit-sequence](#), 126  
[on-enable-surrogate](#), 162  
[on-enable-surrogate](#), 125  
[on-enable-surrogate](#), 21  
[on-event](#), 126  
[on-event](#), 134  
[on-event](#), 170  
[on-event](#), 194  
[on-exit](#), 45  
[on-focus](#), 29  
[on-focus](#), 19  
[on-focus](#), 176  
[on-focus](#), 6  
[on-focus](#), 134  
[on-focus](#), 126  
[on-insert](#), 168  
[on-insert](#), 173  
[on-insert](#), 136  
[on-insert](#), 129  
[on-insert](#), 172  
[on-lexer-valid](#), 19  
[on-load-file](#), 126  
[on-load-file](#), 183  
[on-load-file](#), 134  
[on-local-char](#), 176  
[on-local-char](#), 191  
[on-local-char](#), 127  
[on-local-char](#), 135  
[on-local-event](#), 127  
[on-local-event](#), 135  
[on-new-box](#), 127  
[on-new-box](#), 29  
[on-new-box](#), 135  
[on-new-image-snip](#), 135  
[on-new-image-snip](#), 127  
[on-new-image-snip](#), 30  
[on-new-string-snip](#), 129  
[on-new-string-snip](#), 136  
[on-new-tab-snip](#), 136  
[on-new-tab-snip](#), 129  
[on-paint](#), 135  
[on-paint](#), 168  
[on-paint](#), 170  
[on-paint](#), 196  
[on-paint](#), 182  
[on-paint](#), 128  
[on-paint](#), 193  
[on-save-file](#), 128  
[on-save-file](#), 34  
[on-save-file](#), 185  
[on-save-file](#), 136  
[on-set-size-constraint](#), 130  
[on-set-size-constraint](#), 136  
[on-set-size-constraint](#), 20  
[on-size](#), 7  
[on-size](#), 47  
[on-snip-modified](#), 128  
[on-snip-modified](#), 136  
[on-submit](#), 189

- [on-subwindow-event](#), 143
- [on-superwindow-show](#), 6
- [on-superwindow-show](#), 45
- [open-here](#), 86
- [open-line](#), 118
- [open-status-line](#), 48
- [overwrite-status-changed](#), 51
- [Panel](#), 140
- [panel:draggable-container-size](#), 145
- [panel:draggable-mixin](#), 143
- [panel:draggable-place-children](#), 145
- [panel:draggable<%>](#), 141
- [panel:horizontal-draggable%](#), 144
- [panel:horizontal-draggable-mixin](#), 144
- [panel:horizontal-draggable<%>](#), 142
- [panel:single%](#), 141
- [panel:single-mixin](#), 140
- [panel:single-pane%](#), 141
- [panel:single-window-mixin](#), 141
- [panel:single-window<%>](#), 141
- [panel:single<%>](#), 140
- [panel:vertical-draggable%](#), 144
- [panel:vertical-draggable-mixin](#), 144
- [panel:vertical-draggable<%>](#), 142
- [paste-click-region](#), 118
- [paste-clipboard](#), 118
- [Pasteboard](#), 146
- [pasteboard:backup-autosave%](#), 146
- [pasteboard:basic%](#), 146
- [pasteboard:file%](#), 146
- [pasteboard:info%](#), 146
- [pasteboard:keymap%](#), 146
- [pasteboard:standard-style-list%](#), 146
- [Path Utils](#), 147
- [path-utils:generate-autosave-name](#), 147
- [path-utils:generate-backup-name](#), 147
- [place-children](#), 143
- [place-children](#), 140
- [port-name-matches?](#), 167
- [Preferences](#), 148
- [Preferences, Textual](#), 151
- [preferences:add-callback](#), 151
- [preferences:add-can-close-dialog-callback](#), 150
- [preferences:add-editor-checkbox-panel](#), 149
- [preferences:add-font-panel](#), 150
- [preferences:add-general-checkbox-panel](#), 149
- [preferences:add-on-close-dialog-callback](#), 150
- [preferences:add-panel](#), 148
- [preferences:add-scheme-checkbox-panel](#), 149
- [preferences:add-to-editor-checkbox-panel](#), 149
- [preferences:add-to-general-checkbox-panel](#), 150
- [preferences:add-to-scheme-checkbox-panel](#), 149
- [preferences:add-to-warnings-checkbox-panel](#), 149
- [preferences:add-warnings-checkbox-panel](#), 149
- [preferences:get](#), 151
- [preferences:get-preference/gui](#), 148
- [preferences:get-prefs-snapshot](#), 154
- [preferences:hide-dialog](#), 150
- [preferences:low-level-get-preference](#), 154
- [preferences:low-level-put-preferences](#), 154
- [preferences:put-preferences/gui](#), 148
- [preferences:register-save-callback](#), 153
- [preferences:restore-defaults](#), 153
- [preferences:restore-prefs-snapshot](#), 154
- [preferences:set](#), 151
- [preferences:set-default](#), 152

[preferences:set-un/marshall](#), 152  
[preferences:show-dialog](#), 150  
[preferences:snapshot?](#), 154  
[preferences:unregister-save-callback](#), 153  
[put-file](#), 138  
[put-file](#), 168  
[put-file](#), 133  
[put-file](#), 30  
[Racket](#), 155  
[read](#), 25  
[read](#), 139  
[recalc-snips](#), 6  
[refresh-splash](#), 202  
[remove-autosave](#), 34  
[remove-chained-keymap](#), 113  
[remove-frame](#), 99  
[remove-parens-forward](#), 159  
[remove-sexp](#), 158  
[remove-space](#), 118  
[replace-all](#), 90  
[reset-input-box](#), 189  
[reset-min-sizes](#), 23  
[reset-region](#), 17  
[reset-regions](#), 17  
[resized](#), 183  
[restore-keybinding](#), 123  
[restore-underscores](#), 123  
[revert](#), 81  
[ring-bell](#), 117  
[run-after-edit-sequence](#), 26  
[save](#), 81  
[save-as](#), 81  
[save-file](#), 117  
[save-file-as](#), 117  
[save-file-out-of-date?](#), 26  
[save-file/gui-error](#), 27  
[scheme:add-coloring-preferences-panel](#), 163  
[scheme:add-preferences-panel](#), 163  
[scheme:get-color-prefs-table](#), 163  
[scheme:get-keymap](#), 163  
[scheme:get-white-on-black-color-prefs-table](#), 163  
[scheme:get-wordbreak-map](#), 164  
[scheme:init-wordbreak-map](#), 164  
[scheme:set-mode-mixin](#), 162  
[scheme:setup-keymap](#), 164  
[scheme:sexp-snip%](#), 155  
[scheme:sexp-snip<%>](#), 155  
[scheme:short-sym->pref-name](#), 164  
[scheme:short-sym->style-name](#), 164  
[scheme:text%](#), 162  
[scheme:text-balanced?](#), 162  
[scheme:text-mixin](#), 161  
[scheme:text-mode%](#), 162  
[scheme:text-mode-mixin](#), 161  
[scheme:text-mode<%>](#), 161  
[scheme:text<%>](#), 157  
[scroll-editor-to](#), 170  
[search](#), 90  
[search-hidden?](#), 90  
[search-hits-changed](#), 91  
[search-replace](#), 90  
[select-backward-sexp](#), 160  
[select-click-line](#), 119  
[select-click-word](#), 118  
[select-down-sexp](#), 160  
[select-forward-sexp](#), 160  
[select-up-sexp](#), 160  
[send-eof-to-box-in-port](#), 189  
[send-eof-to-in-port](#), 189  
[set-active-frame](#), 99  
[set-allow-edits](#), 188  
[set-anchor](#), 184  
[set-delegate](#), 177  
[set-editor](#), 6  
[set-filename](#), 33  
[set-info-canvas](#), 50  
[set-insertion-point](#), 188  
[set-label](#), 83  
[set-label-prefix](#), 80  
[set-line-numbers-color](#), 197  
[set-line-numbers-color](#), 196

- set-macro-recording, 51
- set-modified, 35
- set-open-here-frame, 98
- set-orientation, 142
- set-override-mode, 184
- set-percentages, 142
- set-refresh-splash-on-gauge-change?!, 202
- set-replace-start, 174
- set-search-anchor, 174
- set-searching-state, 174
- set-splash-bitmap, 200
- set-splash-char-observer, 201
- set-splash-event-callback, 201
- set-splash-paint-callback, 201
- set-splash-progress-bar?!, 201
- set-styles-fixed, 166
- set-surrogate, 133
- set-tab-size, 160
- set-text-to-search, 90
- set-unread-start-point, 188
- show, 45
- show-delegated-text, 89
- show-info, 50
- show-line-numbers!, 196
- show-line-numbers!, 197
- show-line-numbers?, 197
- show-line-numbers?, 196
- shutdown-splash, 200
- skip-whitespace, 17
- Splash, 199
- split, 180
- split, 178
- start-colorer, 14
- start-macro, 119
- start-splash, 199
- stop-colorer, 16
- string-normalize, 173
- submit-to-port?, 189
- tabify, 157
- tabify-all, 157
- tabify-on-return?, 157
- tabify-selection, 157
- Technical Issues, 204
- Test, 203
- Test Functions, 205
- test:button-push, 205
- test:close-top-level-window, 208
- test:current-get-eventspaces, 207
- test:keystroke, 206
- test:menu-select, 206
- test:mouse-click, 207
- test:new-window, 207
- test:number-pending-actions, 208
- test:reraise-error, 208
- test:run-interval, 207
- test:run-one, 208
- test:set-check-box!, 205
- test:set-choice!, 206
- test:set-list-box!, 206
- test:set-radio-box!, 205
- test:set-radio-box-item!, 205
- test:top-level-focus-window-has?, 208
- Text, 165
- text:1-pixel-string-snip%, 178
- text:1-pixel-tab-snip%, 179
- text:autocomplete-append-after, 198
- text:autocomplete-limit, 198
- text:autocomplete-mixin, 193
- text:autocomplete<%>, 192
- text:autowrap%, 195
- text:backup-autosave%, 196
- text:basic%, 194
- text:basic-mixin, 167
- text:basic<%>, 165
- text:clever-file-format%, 195
- text:clever-file-format-mixin, 185
- text:clever-file-format<%>, 185
- text:delegate%, 194
- text:delegate-mixin, 181
- text:delegate<%>, 177
- text:file%, 195
- text:file-mixin, 186

[text:file<%>](#), 186  
[text:first-line-mixin](#), 169  
[text:first-line<%>](#), 169  
[text:foreground-color-mixin](#), 171  
[text:foreground-color<%>](#), 171  
[text:get-completions/manuals](#), 198  
[text:hide-caret/selection%](#), 194  
[text:hide-caret/selection-mixin](#), 171  
[text:hide-caret/selection<%>](#), 171  
[text:info%](#), 196  
[text:info-mixin](#), 184  
[text:info<%>](#), 184  
[text:input-box%](#), 195  
[text:input-box-mixin](#), 192  
[text:input-box<%>](#), 192  
[text:keymap%](#), 195  
[text:line-numbers-mixin](#), 196  
[text:line-numbers<%>](#), 196  
[text:lookup-port-name](#), 198  
[text:nbsp->space%](#), 194  
[text:nbsp->space-mixin](#), 172  
[text:nbsp->space<%>](#), 172  
[text:normalize-paste-mixin](#), 173  
[text:normalize-paste<%>](#), 172  
[text:ports-mixin](#), 191  
[text:ports<%>](#), 187  
[text:range-caret-space?](#), 197  
[text:range-color](#), 197  
[text:range-end](#), 197  
[text:range-start](#), 197  
[text:range-style](#), 197  
[text:range?](#), 197  
[text:return%](#), 195  
[text:return-mixin](#), 176  
[text:return<%>](#), 176  
[text:searching%](#), 196  
[text:searching-mixin](#), 175  
[text:searching<%>](#), 173  
[text:standard-style-list%](#), 195  
[text:wide-snip%](#), 194  
[text:wide-snip-mixin](#), 177  
[text:wide-snip<%>](#), 176  
[thaw-colorer](#), 16  
 Thread Issues, 204  
[toggle-anchor](#), 117  
[toggle-overwrite](#), 119  
[transpose-chars](#), 118  
[transpose-sexp](#), 160  
[transpose-words](#), 118  
[uncomment-selection](#), 158  
[unhide-search](#), 90  
[unhighlight-range](#), 166  
[unhighlight-range](#), 182  
[up-sexp](#), 159  
[upcase-word](#), 118  
[update-frame-filename](#), 32  
[update-info](#), 52  
[update-info](#), 50  
[update-status-line](#), 49  
[user-saves-or-not-modified?](#), 32  
 Version, 209  
[version:add-spec](#), 209  
[version:version](#), 209  
[while-unlocked](#), 186  
 Window Manager (Unix only), 204  
 Windows menu, 45  
[write](#), 155