

Windows Native SSL: Secure Communication

Version 6.2.1

August 10, 2015

```
(require net/win32-ssl)    package: base
```

The `net/win32-ssl` module offers a fraction of the functionality of `openssl` and works only on Windows, but it has the advantage that it works before OpenSSL libraries are installed.

```
(win32-ssl-connect hostname
                  port-no
                  [client-protocol])
→ (and/c input-port? win32-ssl-port?)
   (and/c output-port? win32-ssl-port?)
hostname : string?
port-no  : (integer-in 1 65535)
client-protocol : (or/c 'ssl2-or-v3 = 'ssl2-or-v3
                       'ssl2
                       'ssl3
                       'tls)
```

Like `ssl-connect`, but without support for client contexts (which could enable certificate checking, for example).

```
(win32-ssl-abandon-port in) → void?
in : (and/c win32-ssl-port? output-port?)
```

Analogous to `ssl-abandon-port`.

```
(ports->win32-ssl-ports input-port
                       output-port
                       [#:encrypt protocol])
→ (and/c input-port? win32-ssl-port?)
   (and/c output-port? win32-ssl-port?)
```

```
input-port : input-port?  
output-port : output-port?  
protocol : (or/c 'sslv2-or-v3 'sslv2 'sslv3 'tls)  
           = 'sslv2-or-v3
```

Analogous to `ports->ssl-ports`.

```
(win32-ssl-port? v) → boolean?  
v : any/c
```

Returns `#t` if `v` is an SSL port produced by `win32-ssl-connect` or `ports->win32-ssl-ports`.

```
win32-ssl-available? : boolean?
```

A boolean value that reports whether the Windows native SSL library was successfully loaded. Calling `win32-ssl-connect`, etc. when this value is `#f` will raise an exception.