

# Test Support

Version 6.3

Kathryn Gray

November 20, 2015

## **Contents**

<b>1</b>	<b>Using Check Forms</b>	<b>3</b>
<b>2</b>	<b>GUI Interface</b>	<b>7</b>

# 1 Using Check Forms

```
(require test-engine/racket-tests)    package: htdp-lib
```

This module provides test forms for use in Racket programs, as well as parameters to configure the behavior of test reports.

Each check form may only occur at the top-level; results are collected and reported by the test function. Note that the check forms only register checks to be performed. The checks are actually run by the `test` function.

```
| (check-expect expr expected-expr)
```

Checks whether the value of the *expr* expression is `equal?` to the value produced by the *expected-expr*.

It is an error for *expr* or *expected-expr* to produce a function value or an inexact number.

```
| (check-random expr expected-expr)
```

Checks whether the value of the *expr* expression is `equal?` to the value produced by the *expected-expr*.

The form supplies the same random-number generator to both parts. If both parts request `random` numbers from the same interval in the same order, they receive the same random numbers.

Examples:

```
> (check-random (random 10) (random 10))

> (check-random
  (begin (random 100) (random 200))
  (begin (random 100) (random 200)))

> (test)
Both tests passed!
```

If the two parts call `random` for different intervals, they are likely to fail:

Examples:

```
> (check-random
  (begin (random 100) (random 200))
  (begin (random 200) (random 100)))
```

```

> (test)
Ran 1 check.
0 checks passed.
  Actual value differs from the expected value.
    Actual value: 49
    Expected value: 74

  At line 2 column 0

```

It is an error for *expr* or *expected-expr* to produce a function value or an inexact number.

```
(check-satisfied expr property?)
```

Checks whether the value of the *expr* expression satisfies the *property?* predicate (which must evaluate to a function of one argument).

Examples:

```

> (check-satisfied 1 odd?)

> (check-satisfied 1 even?)

> (test)
Ran 2 checks.
1 of the 2 checks failed.

  Actual value 1 does not satisfy "even?".

  At line 3 column 0

```

Changed in version 1.1 of package `htdp-lib`: allow the above examples to run in BSL and BSL+

```
(check-within expr expected-expr delta-expr)

  delta-expr : number?
```

Checks whether the value of the test expression is structurally equal to the value produced by the *expected* expression; every number in the first expression must be within *delta* of the corresponding number in the second expression.

It is an error for *expr* or *expected* to produce a function value.

```
(check-error expr)
(check-error expr msg-expr)

  msg-expr : string?
```

Checks that evaluating *expr* signals an error, where the error message matches the string (if any).

```
(check-member-of expr expected-expr ...)
```

Checks whether the value of the *expr* expression is `equal?` to any of the values produced by the *expected-exprs*.

It is an error for *expr* or any of the *expected-exprs* to produce a function value or an inexact number.

```
(check-range expr min-expr max-expr)  
  
  expr : number?  
  min-expr : number?  
  max-expr : number?
```

Checks whether value of *expr* is between the values of *min-expr* and *max-expr* inclusive.

```
(test)
```

Runs all of the tests specified by check forms in the current module and reports the results. When using the `gui` module, the results are provided in a separate window, otherwise the results are printed to the current output port.

```
(test-format)  
  → (or/c (-> any/c (or/c (is-a?/c snip%) string?))  
      (-> any/c output-port? void?))  
(test-format format) → void?  
  format : (or/c (-> any/c (or/c (is-a?/c snip%) string?))  
            (-> any/c output-port? void?))
```

A parameter that stores the formatting function for the values tested by the check forms.

If the parameter is a function of two arguments, then it is supplied the value and an output port to render the value to. Otherwise, if it is a function of one argument, then the resulting string is used to render the value.

The default value accepts two arguments and `prints` the `any/c` argument to the given port.

```
(test-silence) → boolean?  
(test-silence silence?) → void?  
  silence? : any/c
```

A parameter that stores a boolean, defaults to `#f`, that can be used to suppress the printed summary from test.

```
(test-execute) → boolean?  
(test-execute execute?) → void?  
  execute? : any/c
```

A parameter that stores a boolean, defaults to #t, that can be used to suppress evaluation of test expressions.

## 2 GUI Interface

```
(require test-engine/racket-gui)    package: htdp-lib
```

This module requires produces an independent window when displaying test results. It provides the same bindings as `test-engine/racket-tests`.