

Simple Tree Text Markup: Simple Markup for Display as Text or in GUI

Version 8.0

Mike Sperber

February 4, 2021

This is a tree-based combinator library for simple markup, mainly for displaying messages in a REPL. It features horizontal and vertical composition as well as framed markup. Its main distinguishing feature is its ability to embed source locations, which can be rendered as links.

This package comes with separate modules for *inspecting* and *constructing* markup - `simple-tree-text-markup/data` and `simple-tree-text-markup/construct`, respectively.

There's also a module `simple-tree-text-markup/text` that renders markup to text. Rendering markup to GUI is quite context-specific. Hence, the code for rendering to GUIs is implemented with specific applications, such as DrRacket or the test engine.

1 Markup Representation

```
(require simple-tree-text-markup/data)
package: simple-tree-text-markup-lib
```

This module defines the representation for markup as a set of struct definitions. It should be required when inspecting markup, For constructing markup, see [simple-tree-text-markup/construct](#).

A markup object can be one of the following:

- a string
- an [empty-markup](#)
- a [horizontal-markup](#)
- a [vertical-markup](#)
- a [srcloc-markup](#)
- a [framed-markup](#)

```
(markup? object) → boolean?
object : any
```

Returns `#t` if `object` is a markup object, `#f` otherwise.

```
(struct empty-markup ())
```

This is an empty markup object, which consumes no space.

```
(struct horizontal-markup (markups))
markups : (listof markup?)
```

This markup object contains several sub-markups, which will be arranged horizontally when rendered.

```
(struct vertical-markup (markups))
markups : (listof markup?)
```

This markup object contains several sub-markups, which will be arranged vertically when rendered.

```
(struct srcloc-markup (srcloc markup))
srcloc : srcloc?
markup : markup?
```

This markup object represents a link to a source location, represented by `srcloc`, where the link visualization is represented by `markup`.

```
(struct framed-markup (markup))  
  markup : markup?
```

This markup object puts a frame around `markup`.

2 Markup Construction

```
(require simple-tree-text-markup/construct)
package: simple-tree-text-markup-lib
```

While the struct definitions in `simple-tree-text-markup/data` can also be used for constructing markup, the procedures exported here are somewhat more convenient to use, and do a fair amount of normalization upon constructions.

```
(srcloc-markup srcloc markup) → markup?
  srcloc : srcloc?
  markup : markup?
```

This constructs a markup object that will represent a link to a source location, represented by `srcloc`, where the link visualization is represented by `markup`.

```
(framed-markup markup) → markup?
  markup : markup?
```

This markup constructor puts a frame around `markup`.

```
empty-markup : markup?
```

This is the empty markup object.

```
empty-line : markup?
```

This is a markup object representing an empty line, i.e. empty vertical space.

```
(horizontal markup ...) → markup?
  markup : markup?
```

This procedure arranges the `markup` arguments horizontally.

```
(vertical markup ...) → markup?
  markup : markup?
```

This procedure arranges the `markup` arguments vertically.

3 Rendering Markup to Text

```
(require simple-tree-text-markup/text)
package: simple-tree-text-markup-lib
```

This module renders markup to text by printing to a port.

```
(display-markup markup [output-port]) → any
markup : markup?
output-port : output-port? = (current-output-port)
```

Renders a textual version of *markup* to *output-port*. It uses Unicode lines and corners to display framed markup.